

RAVIN CABLES LTD

Production BOM Report | GTP Ref: SM/121124/0 | Type: None | Date: 05-May-2026

Customer: Antelec Limited | Project: Hansalpur, Gujarat Line - D for Suzuki Motor Gujar

Item 1 — 1C x 400mm² A2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	997.618
XLPE Insulation	Xlpe Insulation	25.22	1.785	120.904
Outer Sheath	Frish Sheath	29.84	2.31	299.681
	TOTAL			1,418.203

Item 2 — 2C x 50mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	796.084
XLPE Insulation	Xlpe Insulation	8.47	0.84	37.049
Inner Sheath	Pvc Armoured Sheath	9.1	0.315	14.007
Outer Sheath	Frish Sheath	13.1	2.0	104.615
	TOTAL			951.755

Item 3 — 3.5C x 25mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	847.552
XLPE Insulation	Xlpe Insulation	6.44	0.745	49.088
Inner Sheath	Pvc Armoured Sheath	7.07	0.315	10.772
Outer Sheath	Frish Sheath	11.07	2.0	85.492
	TOTAL			992.904

Item 4 — 3.5C x 70mm² A2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	700.812
XLPE Insulation	Xlpe Insulation	10.04	0.935	98.363
Inner Sheath	Pvc Armoured Sheath	10.88	0.42	22.235
Outer Sheath	Frish Sheath	15.28	2.2	135.593
	TOTAL			957.003

Item 5 — 3.5C x 185mm² A2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	1,893.040
XLPE Insulation	Xlpe Insulation	16.23	1.407	241.182
Inner Sheath	Pvc Armoured Sheath	17.28	0.525	44.536
Outer Sheath	Frish Sheath	22.48	2.6	243.623
	TOTAL			2,422.381

Item 6 — 3.5C x 240mm² A2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	2,483.672
XLPE Insulation	Xlpe Insulation	18.38	1.502	293.045
Inner Sheath	Pvc Armoured Sheath	19.64	0.63	60.630
Outer Sheath	Frish Sheath	25.24	2.8	296.128

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
	TOTAL			3,133.475

Item 7 — 3.5C x 300mm² A2XY-FRLSH | 1.1 kV | Delivery: 500 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	3,104.588
XLPE Insulation	Xlpe Insulation	20.38	1.596	346.629
Inner Sheath	Pvc Armoured Sheath	21.64	0.63	67.005
Outer Sheath	Frish Sheath	27.64	3.0	348.368
	TOTAL			3,866.590

Item 8 — 3C x 50mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	1,194.126
XLPE Insulation	Xlpe Insulation	8.47	0.84	55.573
Inner Sheath	Pvc Armoured Sheath	9.1	0.315	14.007
Outer Sheath	Frish Sheath	13.1	2.0	104.615
	TOTAL			1,368.321

Item 9 — 3C x 70mm² A2XIFY-FRLSH | 11/11 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	525.609
Conductor Screen	Semicon Screen	9.67	0.3	10.597
XLPE Insulation	Xlpe Insulation	19.86	5.093	651.853
Insulation Screen	Semicon Screen	20.45	0.3	22.795
Copper Tape Screen	Copper Tape Screen	-	-	59.214
Inner Sheath	Pvc Armoured Sheath	21.77	0.63	67.429
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	354.142
Outer Sheath	Frish Sheath	28.0	2.31	279.597
	TOTAL			1,971.236

Item 10 — 3C x 185mm² A2XIFY-FRLSH | 11/11 kV | Delivery: 500 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	1,419.780
Conductor Screen	Semicon Screen	15.51	0.3	17.202
XLPE Insulation	Xlpe Insulation	25.7	5.093	909.725
Insulation Screen	Semicon Screen	26.3	0.3	29.400
Copper Tape Screen	Copper Tape Screen	-	-	76.096
Inner Sheath	Pvc Armoured Sheath	27.82	0.735	100.785
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	455.325
Outer Sheath	Frish Sheath	35.05	2.814	427.511
	TOTAL			3,435.824

Item 11 — 3C x 300mm² A2XIFY-FRLSH | 11/11 kV | Delivery: 500 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	2,328.441
Conductor Screen	Semicon Screen	19.7	0.3	21.941
XLPE Insulation	Xlpe Insulation	29.89	5.093	1,094.738
Insulation Screen	Semicon Screen	30.48	0.3	34.138

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Copper Tape Screen	Copper Tape Screen	-	-	88.207
Inner Sheath	Pvc Armoured Sheath	32.02	0.735	116.373
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	531.213
Outer Sheath	Frish Sheath	39.91	3.15	545.741
	TOTAL			4,760.792

Item 12 — 3C x 400mm² A2XIFY-FRLSH | 11/11 kV | Delivery: 250 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Aluminium Conductor	-	-	2,992.854
Conductor Screen	Semicon Screen	22.25	0.3	24.825
XLPE Insulation	Xlpe Insulation	32.44	5.093	1,207.336
Insulation Screen	Semicon Screen	33.03	0.3	37.022
Copper Tape Screen	Copper Tape Screen	-	-	95.579
Inner Sheath	Pvc Armoured Sheath	34.56	0.735	125.860
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	556.508
Outer Sheath	Frish Sheath	42.47	3.15	583.593
	TOTAL			5,623.577

Item 13 — 4C x 2.5mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	83.152
XLPE Insulation	Xlpe Insulation	2.83	0.557	14.646
Inner Sheath	Pvc Armoured Sheath	3.46	0.315	5.019
Outer Sheath	Frish Sheath	7.06	1.8	44.642
	TOTAL			147.459

Item 14 — 4C x 4mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	133.660
XLPE Insulation	Xlpe Insulation	3.3	0.557	17.670
Inner Sheath	Pvc Armoured Sheath	3.93	0.315	5.769
Outer Sheath	Frish Sheath	7.53	1.8	48.629
	TOTAL			205.728

Item 15 — 4C x 6mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	200.056
XLPE Insulation	Xlpe Insulation	3.78	0.557	20.758
Inner Sheath	Pvc Armoured Sheath	4.41	0.315	6.534
Outer Sheath	Frish Sheath	8.01	1.8	52.701
	TOTAL			280.049

Item 16 — 4C x 10mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	336.704
XLPE Insulation	Xlpe Insulation	4.58	0.557	25.905
Inner Sheath	Pvc Armoured Sheath	5.21	0.315	7.810
Outer Sheath	Frish Sheath	8.81	1.8	59.486

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
	TOTAL			429.905

Item 17 — 4C x 16mm² 2XFY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	535.800
XLPE Insulation	Xlpe Insulation	5.05	0.557	28.929
Inner Sheath	Pvc Armoured Sheath	5.68	0.315	8.559
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	101.183
Outer Sheath	Frish Sheath	10.22	1.47	60.634
	TOTAL			735.105

Item 18 — 4C x 16mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	535.800
XLPE Insulation	Xlpe Insulation	5.05	0.557	28.929
Inner Sheath	Pvc Armoured Sheath	5.68	0.315	8.559
Outer Sheath	Frish Sheath	9.28	1.8	63.473
	TOTAL			636.761

Item 19 — 4C x 25mm² 2XFY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	847.552
XLPE Insulation	Xlpe Insulation	6.44	0.745	49.088
Inner Sheath	Pvc Armoured Sheath	7.07	0.315	10.772
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	126.479
Outer Sheath	Frish Sheath	11.61	1.47	70.249
	TOTAL			1,104.140

Item 20 — 4C x 25mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	847.552
XLPE Insulation	Xlpe Insulation	6.44	0.745	49.088
Inner Sheath	Pvc Armoured Sheath	7.07	0.315	10.772
Outer Sheath	Frish Sheath	11.07	2.0	85.492
	TOTAL			992.904

Item 21 — 4C x 35mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	1,175.896
XLPE Insulation	Xlpe Insulation	7.32	0.745	56.673
Inner Sheath	Pvc Armoured Sheath	7.95	0.315	12.175
Outer Sheath	Frish Sheath	11.95	2.0	93.786
	TOTAL			1,338.530

Item 22 — 4C x 50mm² 2XY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	1,592.168
XLPE Insulation	Xlpe Insulation	8.47	0.84	74.097

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Inner Sheath	Pvc Armoured Sheath	9.1	0.315	14.007
Outer Sheath	Frlsh Sheath	13.1	2.0	104.615
	TOTAL			1,784.887

Item 23 — 19C x 2.5mm² 2XFY-FRLSH | 1.1 kV | Delivery: 1000 m

Layer	Material	OD (mm)	Thickness (mm)	Weight (kg/km)
Conductor	Copper Conductor	-	-	394.972
XLPE Insulation	Xlpe Insulation	2.83	0.557	69.570
Inner Sheath	Pvc Armoured Sheath	3.46	0.315	5.019
GS Flat Strip Armour	Gs Flat Strip Armour	-	-	75.888
Outer Sheath	Frlsh Sheath	8.0	1.47	45.255
	TOTAL			590.704