

1244. Design A Leaderboard

Medium  293  60  Add to List  Share

Design a Leaderboard class, which has 3 functions:

1. `addScore(playerId, score)` : Update the leaderboard by adding `score` to the given player's score. in the leaderboard, add him to the leaderboard with the given `score` .
2. `top(K)` : Return the score sum of the top `K` players.
3. `reset(playerId)` : Reset the score of the player with the given id to 0 (in other words erase it from th that the player was added to the leaderboard before calling this function.

Initially, the leaderboard is empty.

Example 1:

Input:

```
["Leaderboard","addScore","addScore","addScore","addScore","addScore","top","reset","reset",
[[1,73],[2,56],[3,39],[4,51],[5,4],[1],[1],[2],[2,51],[3]]
```

Output:

```
[null,null,null,null,null,null,73,null,null,null,141]
```

Explanation:

```
Leaderboard leaderboard = new Leaderboard ();
leaderboard.addScore(1,73);    // leaderboard = [[1,73]];
leaderboard.addScore(2,56);    // leaderboard = [[1,73],[2,56]];
leaderboard.addScore(3,39);    // leaderboard = [[1,73],[2,56],[3,39]];
leaderboard.addScore(4,51);    // leaderboard = [[1,73],[2,56],[3,39],[4,51]];
leaderboard.addScore(5,4);     // leaderboard = [[1,73],[2,56],[3,39],[4,51],[5,4]];
leaderboard.top(1);            // returns 73;
leaderboard.reset(1);          // leaderboard = [[2,56],[3,39],[4,51],[5,4]];
leaderboard.reset(2);          // leaderboard = [[3,39],[4,51],[5,4]];
leaderboard.addScore(2,51);     // leaderboard = [[2,51],[3,39],[4,51],[5,4]];
leaderboard.top(3);            // returns 141 = 51 + 51 + 39;
```

Constraints:

- `1 <= playerId, K <= 10000`
- It's guaranteed that `K` is less than or equal to the current number of players.
- `1 <= score <= 100`
- There will be at most `1000` function calls.