

772. Basic Calculator III

Hard 615 229 Add to List Share

Implement a basic calculator to evaluate a simple expression string.

The expression string contains only non-negative integers, '+', '-', '*', '/' operators, and open '(' and closing parentheses ')'. The integer division should **truncate toward zero**.

You may assume that the given expression is always valid. All intermediate results will be in the range of $[-2^{31}, 2^{31} - 1]$.

Note: You are not allowed to use any built-in function which evaluates strings as mathematical expressions, such as `eval()`.

Example 1:

Input: s = "1+1"
Output: 2

Example 2:

Input: s = "6-4/2"
Output: 4

Example 3:

Input: s = "2*(5+5*2)/3+(6/2+8)"
Output: 21

Example 4:

Input: s = "(2+6*3+5-(3*14/7+2)*5)+3"
Output: -12

Example 5:

Input: s = "0"
Output: 0

Constraints:

- 1 <= s <= 10⁴
- s consists of digits, '+', '-', '*', '/', '(', and ')'.
- s is a **valid** expression.

Accepted 58,943 Submissions 131,775

Seen this question in a real interview before?

Yes

No

Companies

🔒

i

0 ~ 6 months 6 months ~ 1 year 1 year ~ 2 years

- Amazon | 4
- Facebook | 3
- Uber | 2
- ByteDance | 2

Related Topics

Similar Questions

```
1 class Solution:
2     # Function
3     # to find
4     # precedence
5     # of
6     # operators.
7     def
8     precedence(self
9     , op):
10         if op
11         == '+' or op ==
12         '-':
13
14         return 1
15
16         if op
17         == '*' or op ==
18         '/':
19
20         return 2
21
22         #
23         # brackets
24         return
25         0
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
```

Your previous code was restored from

Test... Run Code ... Deb... 🔒

> Watch Expressions

▶ 🔍

Local Variables

⬆️ ⬇️

i: 0
ops: []
tokens: ...
values: ...

stdout