

C:\Users\STUDENT\Desktop\1bm21cs220\banker.exe

```
Enter details for P3
Enter allocation      --      2 1 1
Enter Max             --      2 2 2
Enter details for P4
Enter allocation      --      0 0 2
Enter Max             --      4 3 3
```

```
Enter Available Resources      --      3 3 2
```

```
Enter New Request Details --
```

```
Enter pid              --      1
```

```
Enter Request for Resources    --      1 0 2
```

```
P1 is visited( 5 3 2)
```

```
P3 is visited( 7 4 3)
```

```
P4 is visited( 7 4 5)
```

```
P0 is visited( 7 5 5)
```

```
P2 is visited( 10 5 7)
```

```
SYSTEM IS IN SAFE STATE
```

```
The Safe Sequence is -- (P1 P3 P4 P0 P2 )
```

Process	Allocation			Max			Need		
P0	0	1	0	7	5	3	7	4	3
P1	3	0	2	3	2	2	0	2	0
P2	3	0	2	9	0	2	6	0	0
P3	2	1	1	2	2	2	0	1	1
P4	0	0	2	4	3	3	4	3	1

```
Process returned 5 (0x5)   execution time : 81.658 s
```

```
Press any key to continue.
```

```
#include<stdio.h>
```

```
struct file
```

```
{
```

```
int all[10];
```

```
int max[10];
```

```
int need[10];
```

```
int flag;
```

```
};
```

```
void main()
```

```
{
```

```
struct file f[10];
```

```
int fl;
```

```
int i, j, k, p, b, n, r, g, cnt=0, id, newr;
```

```
int avail[10],seq[10];
```

```
printf("Enter number of processes -- ");
```

```

scanf("%d",&n);

printf("Enter number of resources -- ");

scanf("%d",&r);

for(i=0;i<n;i++)
{
printf("Enter details for P%d",i);
printf("\nEnter allocation\t -- \t");
for(j=0;j<r;j++)
scanf("%d",&f[i].all[j]);
printf("Enter Max\t\t -- \t");
for(j=0;j<r;j++)
scanf("%d",&f[i].max[j]);
f[i].flag=0;
}

printf("\nEnter Available Resources\t -- \t");
for(i=0;i<r;i++)
scanf("%d",&avail[i]);

printf("\nEnter New Request Details -- ");
printf("\nEnter pid \t -- \t");
scanf("%d",&id);
printf("Enter Request for Resources \t -- \t");
for(i=0;i<r;i++)
{
scanf("%d",&newr);
f[id].all[i] += newr;
avail[i]=avail[i] - newr;
}

for(i=0;i<n;i++)
{
for(j=0;j<r;j++)
{

```

```

f[i].need[j]=f[i].max[j]-f[i].all[j];
if(f[i].need[j]<0)
f[i].need[j]=0;
}
}
cnt=0;
fl=0;
while(cnt!=n)
{
g=0;
for(j=0;j<n;j++)
{
if(f[j].flag==0)
{
b=0;
for(p=0;p<r;p++)
{
if(avail[p]>=f[j].need[p])
b=b+1;
else
b=b-1;
}
if(b==r)
{
printf("\nP%d is visited",j);
seq[fl++]=j;
f[j].flag=1;
for(k=0;k<r;k++)
avail[k]=avail[k]+f[j].all[k];
cnt=cnt+1;
printf("");

```

```

for(k=0;k<r;k++)
printf("%3d",avail[k]);
printf("");
g=1;
}
}
}
if(g==0)
{
printf("\n REQUEST NOT GRANTED -- DEADLOCK OCCURRED");
printf("\n SYSTEM IS IN UNSAFE STATE");
goto y;
}
}
printf("\nSYSTEM IS IN SAFE STATE");
printf("\nThe Safe Sequence is -- (");
for(i=0;i<f;i++)
printf("P%d ",seq[i]);
printf(")");
y: printf("\nProcess\t\tAllocation\t\tMax\t\t\tNeed\n");
for(i=0;i<n;i++)
{
printf("P%d\t",i);
for(j=0;j<r;j++)
printf("%6d",f[i].all[j]);
for(j=0;j<r;j++)
printf("%6d",f[i].max[j]);
for(j=0;j<r;j++)
printf("%6d",f[i].need[j]);
printf("\n");
}

```

}

```
C:\Users\STUDENT\Desktop\1bm21cs220\banker.exe
Enter details for P3
Enter allocation -- 2 1 1
Enter Max -- 2 2 2
Enter details for P4
Enter allocation -- 0 0 2
Enter Max -- 4 3 3

Enter Available Resources -- 3 3 2

Enter New Request Details --
Enter pid -- 0
Enter Request for Resources -- 0 0 0

P1 is visited( 5 3 2)
P3 is visited( 7 4 3)
P4 is visited( 7 4 5)
P0 is visited( 7 5 5)
P2 is visited( 10 5 7)
SYSTEM IS IN SAFE STATE
The Safe Sequence is -- (P1 P3 P4 P0 P2 )
Process Allocation Max Need
P0 0 1 0 7 5 3 7 4 3
P1 2 0 0 3 2 2 1 2 2
P2 3 0 2 9 0 2 6 0 0
P3 2 1 1 2 2 2 0 1 1
P4 0 0 2 4 3 3 4 3 1

Process returned 5 (0x5) execution time : 107.591 s
Press any key to continue.
```