



This kit is for integrating Aggrepaypayments Payment request API in your PHP application. This is intended to developers how need **quick PHP integration**. For a more detailed documentation see “Aggrepaypayments Api Integration Document v1.3” (Request Aggrepaypayments if you need detailed api documentation).

Content

The Zip file contains one file “paymentrequest.php”.

Requirement

You will need following for your api integration to work.

1. API Access: You need to be enabled by Aggrepaypayments to use api integration.
2. API Key: You will need an api_key, this will be provided by Aggrepaypayments
3. Salt: This is like a password for you api access. This will be provided by Aggrepaypayments.

Usage

Follow the steps below:

1. Place the paymentrequest.php in suitable location on your server.
2. Edit this file and update your api_key and salt.
3. Now submit a post request to this file from your application. Below is list of fields that are allowed to post.

Fields needed to post to paymentrequest.php:

Parameter	Description	Data type	Mandatory
order_id	This is your (merchant) reference number. It must be unique for every transaction. We do perform a validation at our end and do not allow duplicate order_ids for the same merchant.	Unsigned Integer	Yes
mode	This is the payment mode (TEST or LIVE are valid values)	Varchar(4)	Optional
amount	This is the payment amount.	Decimal(15,2)	Yes
currency	This is the 3digit currency code (This value should be INR)	Varchar(3)	Yes
description	Brief description of product or service that the customer is being charged for.	Varchar(500)	Yes
name	Name of customer.	Varchar(100)	Yes
email	Customer email address.	Varchar(100)	Yes
phone	Customer phone number	Varchar(50)	Yes
address_line_1	Customer address line 1	Varchar(100)	Optional
address_line_2	Customer address line 2	Varchar(100)	Optional
city	Customer city	Varchar(50)	Yes
state	Customer State	Varchar(50)	Optional
country	Customer country (This value should be IND)	Varchar(50)	Yes
zip_code	Customer zip code	Varchar(20)	Yes
return_url	Return URL – Aggrepaypayments will make a POST request to this URL after transaction is completed (success or failure), with a set of parameters, which you can process as you want to.	Varchar(300)	Yes
udf1	User defined field 1	Varchar(300)	Optional
udf2	User defined field 2	Varchar(300)	Optional
udf3	User defined field 3	Varchar(300)	Optional
udf4	User defined field 4	Varchar(300)	Optional

udf5	User defined field 5	Varchar(300)	Optional

Fields returned to return_url after success or failure response.

Parameter name	Description
transaction_id	A unique ID that can be used to trace the transaction uniquely within Aggrepaypayments. Transaction IDs are alphanumeric.
payment_method	This tells the payment method used by customer – example: “credit card”, “debit card”, “netbanking”, etc.
payment_datetime	Date and Time of this payment in “YYYY-MM-DD HH:MM:SS” format *
response_code	Status of the transaction (return code). 0 signifies successful transaction. Non-zero values signify error.
response_message	Can have a value of “success” or “failure”.
order_id	The same order_id that was originally posted by the merchant in the request.
amount	The same original amount that was sent by the merchant in the transaction request.
currency	This is the 3digit currency code (INR), it will be same value that was originally sent by merchant. *
description	The same description that was originally sent by the merchant in the transaction request.
name	The same value that was originally sent by merchant
email	The same value that was originally sent by merchant
phone	The same value that was originally sent by merchant
address_line_1	The same value that was originally sent by merchant
address_line_2	The same value that was originally sent by merchant
city	The same value that was originally sent by merchant
state	The same value that was originally sent by merchant
country	The same value that was originally sent by merchant
zip_code	The same value that was originally sent by merchant
udf1	The same value that was originally sent by merchant
udf2	The same value that was originally sent by merchant
udf3	The same value that was originally sent by merchant
udf4	The same value that was originally sent by merchant
udf5	The same value that was originally sent by merchant
hash	Aggrepaypayments calculates the hash using the same algorithm which was outlined earlier. Hence, the merchant needs to check whether this returned hash matches the hash that was originally passed. This is to make sure the response is not modified and you are seeing a legitimate response for current transaction. (If you need to know the hashing algorithm look at <code>function hashCalculate(\$salt, \$input)</code> in paymentrequest.php)
error_desc	Failure reason (if transaction is failed)