Modelisation of ExoMars 2020's network using SystemC

Anas Naïri

Julien Plante

December 21, 2018

1 Devices description

- 1.1 NavCam
- 1.2 PanCam
- **1.3 ISEM**
- 1.4 CLUPI
- 1.5 WISDOM
- 1.6 Adron

1.7 Ma MISS

Ma_MISS, for Mars Multispectral Imager for Subsurface Studies, is a spectrometer located in the drill of the rover, used to determine horizontal and vertical composition of the Martian soil. By illuminating the borehole and analysing the reflected light and its spectrum, it will be able to gather information about the distribution of minerals, especially of water-related ones, to search potential indicators of life.

It will work alongside the three other spectrometers (RLS, MicrOmega, MOMA), being specialised in studying unexposed material, and in collaboration with WISDOM and ADRON to choose interesting drilling location

1.8 MicrOmega

MicrOmega is an infra-red spectrometer made to identify composition of Martian soil samples at a grain scale, after their gathering by the drilling system. It is similar as RLS and MOMA in this way, since the three spectrometers will study samples collected by the drill. The infra-red study of the samples is adapted to find evidences of past or present carbon and water presence. 250x256 pixels + λ (max 320 wave length)

1.9 RLS

RLS uses the Raman effect to find life signatures in Martian soil samples in a non-destructive way. The measurements carried out by the RLS will be performed as described within the ExoMars

Rover Reference Surface Mission, which includes six experiment cycles (with two samples each, one extracted from a surface target and the other at depth) and two vertical surveys (with five samples each extracted at different depths).

1.10 **MOMA**

Before sample analysis by MOMA, the MicrOmega and RLS instruments will conduct contextual measurements of mineralogy and organic functional groups that may be present. In cases where uplink and downlink schedules permit a tactical response during the science operations cycle, quick look snapshots of these data may be used to select or tune the MOMA analytical approach.

References

- [1] PanCam team. The PanCam Instrument for the ExoMars Rover. *Astrobiology*, 17(6 and 7), 2017.
- [2] ISEM team. Infrared Spectrometer for ExoMars: A Mast-Mounted Instrument for the Rover. *Astrobiology*, 17(6 and 7), 2017.
- [3] CLUPI team. The Close-Up Imager Onboard the ESA ExoMars Rover: Objectives, Description, Operations, and Science Validation Activities. *Astrobiology*, 17(6 and 7), 2017.
- [4] WISDOM team. The WISDOM Radar: Unveiling the Subsurface Beneath the ExoMars Rover and Identifying the Best Locations for Drilling. *Astrobiology*, 17(6 and 7), 2017.
- [5] ADRON team. The ADRON-RM Instrument Onboard the ExoMars Rover. *Astrobiology*, 17(6 and 7), 2017.
- [6] Ma_MISS team. Ma_MISS on Exomars: Mineralogical Characterization of the Martian Subsurface. *Astrobiology*, 17(6 and 7), 2017.
- [7] MicrOmega team. The MicrOmega Investigation Onboard ExoMars. *Astrobiology*, 17(6 and 7), 2017.
- [8] MOMA team. The Mars Organic Molecule Analyzer (MOMA) Instrument: Characterization of Organic Material in Martian Sediments. *Astrobiology*, 17(6 and 7), 2017.
- [9] RLS team. The Raman Laser Spectrometer for the ExoMars Rover Mission to Mars. *Astro-biology*, 17(6 and 7), 2017.
- [10] Steve Parkes. SpaceWire User's Guide. STAR-Dundee, 2012.