ISA104 - AI Application Design

Lecture 3 - Prompt Engineering and Critical Engagement with AI Generated Content


Haoran Wen
Haoran.Wen@xjtlu.edu.cn



Xi'an Jiaotong-Liverpool University
西交利物浦大學

19 September 2026

1. Office Hours: 1:00-5:00 p.m., Monday (SD 342)
2. Learning Mall Forum



3. Labs / tutorials

Contents

- Introduction to Prompt Engineering
- Advanced Prompt Engineering Techniques
- Critical Engagement with AI Generated Content

Recap: Language Models - Narrow Sense


- A language model is a **probabilistic model** that assigns a **likelihood** to every **finite** sequence (grammatical or not).

Sentence: “the cat sat on the mat”

$$P(\text{the cat sat on the mat}) = P(\text{the}) * P(\text{cat}|\text{the}) * P(\text{sat}|\text{the cat}) \\ *P(\text{on}|\text{the cat sat}) * P(\text{the}|\text{the cat sat on}) \\ *P(\text{mat}|\text{the cat sat on the})$$

Implicit order

Recap: Language Models Are Neural Networks




A large language model (LLM, e.g., ChatGPT) still acts in this way, but it is implemented as a very large **neural network** of hundreds of billions parameters!

Source: Junying Chen, “Introduction to Large Language Models (LLMs)”

Recap: Large Language Models (LLMs)

1. **Encoder-Only (e.g., BERT, ELECTRA)**
   - Masked Language Modeling (MLM)
   - Bidirectional text understanding
   - Sentence classification, named entity recognition
   - Task-specific fine-tuning
2. **Decoder-Only (e.g., GPT, Llama)**
   - Auto-regressive
   - Unidirectional text generation
   - Text completion, creative writing, chat
   - Task-agnostic prompting
3. **Encoder-Decoder (e.g., T5, BART)**
   - Sequence-to-sequence objectives
   - Transforming a sequence into another sequence.
   - Translation, summarization, question answering
   - Task-specific fine-tuning




Source: Ashish Vaswani et al. "Attention Is All You Need."

Source: Jingfeng Yang et al. "Harnessing the Power of LLMs in Practice: A Survey on ChatGPT and Beyond."

Size of Model – Model Parameters

- How to measure “size” of a model?
  - **Number of model parameters**
  - Training dataset size
  - Training FLOPs


- Models' size explode from millions to hundreds of billions
- More recent models: PaLM (540B), Llama 3 (405B), DeepSeek V3 (671B)
- 1 billion (B) = 10^9 (十亿)




https://informationisbeautiful.net/visualizations/the-rise-of-generative-ai-large-language-models-llms-like-chatgpt/

Size of Model – Training Data

- How to measure “size” of a model?
  - Number of model parameters
  - **Training data size**
  - Training FLOPs
- A **token** is the unit of training data for LLMs
- LLMs are trained on over hundreds of billions of **tokens**
- Numbers of tokens depend on language and **tokenizers.**






https://babylm.github.io/
https://www.edenai.co/post/understanding-llm-billing-from-characters-to-tokens

1 trillion = 10^{12} (万亿)

Size of Model – Training FLOPs

- **FLOPs (floating point operations)** refers to the total number of floating-point computations required to train or run a model.
- **FLOPS (floating point operations per second)** is a measure of computing performance, indicating how many floating-point operations a system can perform in one second.

- How to measure "size" of a model?
  - Number of model parameters
  - Training dataset size
  - **Training FLOPs**



Multipliers for flops

Name	Unit	Value
kiloFLOPS	kFLOPS	10^{3}
megaFLOPS	MFLOPS	10^{6}
gigaFLOPS	GFLOPS[2]	10^{9}
teraFLOPS	TFLOPS	10^{12}
petaFLOPS	PFLOPS	10^{15}
exaFLOPS	EFLOPS	10^{18}
zettaFLOPS	ZFLOPS	10^{21}
yottaFLOPS	YFLOPS	10^{24}
ronnaFLOPS	RFLOPS	10^{27}
quettaFLOPS	QFLOPS	10^{30}

https://en.wikipedia.org/wiki/Floating_point_operations_per_second

Source: https://www.economist.com/interactive/briefing/2022/06/11/huge-foundation-models-are-turbo-charging-ai-progress


Why Scale Matters?

- More knowledge
  - Language models as knowledge base
- Generalization to different tasks
  - One single model to perform multiple NLP tasks
- Capability to unseen tasks
  - Instruction following, in-context learning, chain-of-thoughts reasoning ...

Why emergence?

"A qualitative change can arise from quantitative changes"

Emergent Ability




Source: Colin Raffel et al. "Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer."


Why Scale Matters? - Emergent Ability

Emergent abilities in LLMs

Capabilities that are **not present** in small models but **unexpectedly arise** as the models are **scaled up in size** (could be either parameters, training data or training FLOPs).



Scale of model parameters



Scale of training FLOPs

Source: Jason Wei et al. "Emergent Abilities of Large Language Models."
https://docs.google.com/presentation/d/1yzbmYB5E7G8lY2-KzhmArmPYwwl7o7CUST1xRZDUu1Y/edit?slide=id.g1fa6b45641d_0_17&resourcekey=0-6_TnUMoKWCk_FN2BiPxmbw#slide=id.g1fa6b45641d_0_17

Emergence - In-Context Learning


In-context learning is the ability of a LLM to learn and perform new tasks solely from a few examples provided within its input prompt, **without updating its parameters**.


Zero-shot learning:
directly prompting the model for a response without any examples or demonstrations about the task

One-shot learning:
prompting the model for a response with one examples or demonstrations about the task

Few-shot learning:
prompting the model for a response with few examples or demonstrations about the task








Source: Tom B. Brown et al. “Language Models are Few-Shot Learners.”

Emergence - In-Context Learning

Few-shot learning: **>70%**

One-shot learning: 70%

Zero-shot learning: 58%



- A few-shot prompted task is **emergent** if it achieves **random accuracy** with small models and above-random accuracy with large models.
- SuperGLUE: is a benchmark for natural language understanding introduced by Facebook AI (Meta AI)

Source: Tom B. Brown et al. “Language Models are Few-Shot Learners.”

Limitations of LLM

Hallucination

- Generates plausible but incorrect or fabricated information.
- Invents details or data that do not exist.
- Presents false information with high confidence.

Outdated Knowledge

- Lacks awareness of events, data, or developments after its **training cut-off**.
- Cannot provide real-time information (e.g., current news, stock prices).
- May give outdated advice based on old contexts.

Limited Reasoning Ability


- Struggles with complex logic, multi-step problems, or abstract concepts.
- May produce inconsistent statements within a single response.
- Excels at pattern-matching but lacks true understanding or common sense.

Inherited Bias

- Amplifies stereotypes and biases present in its training data.
- May generate content that is unfair or offensive towards certain groups.
- Reflects the perspectives and imbalances of its source material, not objective truth.

Optimizing LLM Accuracy

- Optimizing LLMs is difficult:
  - Knowing **how to** start optimizing accuracy
  - **When** to use **what** optimization method
  - What level of accuracy is **good enough** for production
- Context optimization when:
  - the model lacks **contextual knowledge** because it wasn't in its training set
  - its knowledge is out of date, or
  - it requires knowledge of proprietary information.
  - This improves **response accuracy**.
- LLM optimization when:
  - the model is producing inconsistent results with incorrect formatting
  - the tone or style of speech is not correct, or
  - the reasoning is not being followed consistently.
  - This maximizes **consistency of behavior**.



Source: https://platform.openai.com/docs/guides/optimizing-llm-accuracy#page-top

Optimizing LLM Accuracy (Cont.)

A typical LLM optimization flow:

1. Begin with a **prompt**, then evaluate its performance


2. Add **static few-shot** examples, which should improve consistency of results

3. Add a **retrieval** step so the few-shot examples are brought in dynamically based on the question - this boosts performance by ensuring relevant context for each input

4. **Fine-tune** the model to increase consistency with a dataset of 50+ examples

5. Tune the **retrieval** and add a **fact-checking** step to find hallucinations to achieve higher accuracy

6. Re-train the fine-tuned model on the new training examples which include our enhanced RAG inputs



Prompt -> Few-shot -> RAG -> Fine-tuning -> RAG+fact-check -> Retrain

https://platform.openai.com/docs/guides/optimizing-llm-accuracy#page-top

What is a Prompt?

- **Prompts** are instructions or inputs given to generative AI (GenAI) to guide its response or output.
- Using effective prompt can offer you the following benefits:
  - Improve the model's performance and safety.
  - Add domain knowledge and tools without retraining or fine-tuning.
  - Better understand how to use LLMs.
  - Obtain higher-quality outputs results by giving higher-quality prompts.



Elements of Prompt

- **Instruction** – the specific task you want the model to perform.
- **Context** – background details or external information that help the model produce a more accurate response.
- **Input Data** – the input the model should respond to or work with.
- **Output Indicator** – the desired format, structure, or style of the response.

User:

Classify the text into neutral, negative, or positive.

I want to evaluate customer reviews of food experiences.

Text: "I think the food was okay."


Sentiment label (neutral, negative, or positive).

Model: *neutral.*

Prompt Engineering

- **Prompt engineering** is the practice of developing and optimizing prompts to efficiently guide GenAI to generate desired outputs.

- Why is prompt engineering?
  - It unlocks model capabilities.
  - It dramatically improves output quality and enhance reliability.
  - It is cost-effective and efficient, **no parameter update** needed.
  - It is foundational for building AI applications.



https://botpenguin.com/blogs/what-is-prompt-engineering

Practice For Prompt Engineering

- **Be concise and clear**
  - Reduce “fluffy” and imprecise descriptions.
  - Replace vague terms with specific facts.
  - Avoid jargon and clichés

Less effective ❌:

```
The description for this product should be fairly short, a few sentences only, and not too much more.
```

Better ✅:

```
Use a 3 to 5 sentence paragraph to describe this product.
```

- **Clarity and specificity**

  Providing detailed instructions helps the AI understand the desired task and respond more meaningfully.

Less effective ❌:

```
Write a poem about OpenAI.
```

Better ✅:

```
Write a short inspiring poem about OpenAI, focusing on the recent DALL-E product launch (DALL-E is a text to image ML model) in the style of a {famous poet}
```

https://help.openai.com/en/articles/6654000-best-practices-for-prompt-engineering-with-the-openai-api

Practice For Prompt Engineering

- **Try using examples (few-shot)**

  The examples you give to the AI must match the format, quality, and style you are trying to achieve.

✅ Few-shot - provide a couple of examples

```
Extract keywords from the corresponding texts below.

Text 1: Stripe provides APIs that web developers can use to integrate payment processing into their websites and mobile applications.
Keywords 1: Stripe, payment processing, APIs, web developers, websites, mobile applications
##
Text 2: OpenAI has trained cutting-edge language models that are very good at understanding and generating text. Our API provides access to these models and can be used to solve virtually any task that involves processing language.
Keywords 2: OpenAI, language models, text processing, API.
##
Text 3: {text}
Keywords 3:
```

- **Specify desired structure and format**

  Using specific formats, words, and symbols can guide the AI to structure its

Less effective ❌:

```
Extract the entities mentioned in the text below. Extract the following 4 entity types: company names, people names, specific topics and themes.

Text: {text}
```

Better ✅:

```
Extract the important entities mentioned in the text below. First extract all company names, then extract all people names, then extract specific topics which fit the content and finally extract general overarching themes

Desired format:
Company names: <comma_separated_list_of_company_names>
People names: -||-
Specific topics: -||-
General themes: -||-

Text: {text}
```

The same as above

https://help.openai.com/en/articles/6654000-best-practices-for-prompt-engineering-with-the-openai-api

Practice For Prompt Engineering

- **Iteration and refinement**

  Prompt engineering often involves a process of trial and error, testing different prompts and then refining them to achieve better results.

- **Understand the model's limitations**

  Knowing the limitations of the AI model helps you tailor the prompts to work around those limits and get better responses, e.g., lack of current data, biases.

- **Use the latest model**

  For best results, it's recommended to use the latest, more capable models. Newer models tend to be easier for prompt engineering.

- **Use Prompt Template**


  Using pre-designed prompt structures can help ensure consistency and quality in your prompts.

.....

LLM Settings - Hyperparamters

- **Temperature**:
  - controls creativity allowed in response
  - value (typically) between 0 to 1 (or 0 to 2)
  - lower temperature -> sharper distribution -> less creative
- **Top-p**:
  - select smallest set of tokens whose total likelihood exceec
  - value between 0 to 1
  - smaller p leads to repetitive generations
- **Output length (Optional)**:
  - the maximum number of tokens in response

Note: the general recommendation is to alter either temperature or Top-p, but **not both!**




The probability density function of the gaussian distribution with different sampling temperatures


https://shivammehta25.github.io/posts/temperature-in-language-models-open-ai-whisper-probabilistic-machine-learning/

LLM Settings (Cont.)

- **Examples**: Adjusting the temperature (with top-p of 0.95) in an LLM progressively increases the creativity and variability of its responses to the same prompt.



Platform: Google AI Studio



What if change top-p? **Try it yourself!**


- Introduction to Prompt Engineering
- Advanced Prompt Engineering Techniques
- Critical Engagement with AI Generated Content

Limits of Prompting For Harder Tasks?


- Some tasks seem too hard for even LLMs to learn through prompting alone.
- Especially tasks involving complex, multi-step reasoning. (Humans struggle at these tasks as well!)

Problem: given the coordinate of the top left corner and width and height, calculates the rectangular polygonal path that tightly outlines the rectangles.


Solution? Change the prompt!



Overlapping rectangles and outline path



ChatGPT4




Claude 3.5 Sonnet

https://peter-kullmann.medium.com/all-major-llms-struggle-with-this-simple-programming-task-3e6903fae3a2

Chain-of-Thought Prompting


- **Chain-of-thought (CoT)** prompting provides LLMs with **intermediate steps** that lead to the desired answer, which improves the reasoning abilities of LLMs.
- CoT reasoning emerges in **LLMs exceeding 100B** parameters and may stem from the extensive training datasets that include **step-by-step** reasoning.



Source: Jason Wei et al. “Chain-of-Thought Prompting Elicits Reasoning in Large Language Models”

Zero-Shot CoT Prompting


- CoT prompts usually have multiple examples of similar problems to improve reasoning abilities. It is more effective than a few-shot baseline but can be **more complex** to implement.
- One recent idea that came out more recently is the idea of **zero-shot CoT** (Kojima et al. 2022) that essentially involves adding "**Let's think step by step**" to the original prompt.



Source: Kojima et al. "Large Language Models are Zero-Shot Reasoners"

Self-Consistency


Self-consistency is an enhancement of few-shots CoT prompting. It generates **diverse reasoning paths** for the same problem by increasing temperature and then trained to select the most consistent answer among these chains.



Source: X. Wang et al. "Self-Consistency Improves Chain of Thought Reasoning in Language Models"

Tree-of-Thoughts

Tree of Thoughts (ToT) is a framework that generalizes over CoT prompting and encourages exploration over thoughts that serve as **intermediate steps** for general problem solving with language models.




Source: S. Yao et al. "Tree of Thoughts: Deliberate Problem Solving with Large Language Models"

Reason and Act (ReAct)

ReAct is a technique that combines **reasoning** and **acting** for solving reasoning and **decision-making tasks**.

- **Reason**: the model is prompted to think **step by step** (CoT style)




Source: S. Yao al. “ReAct: Synergizing Reasoning and Acting in Language Models”

- Introduction to Prompt Engineering
- Advanced Prompt Engineering Techniques
- Critical Engagement with AI Generated Content

Prompt Injection


- **System prompt** is a set of instructions given to an LLM **before** any user input, to guide its behavior
- **Prompt injection** is an attack where attackers deliberately insert malicious or manipulative instructions into a prompt to **override or alter a language model's intended behavior**



https://www.paloaltonetworks.in/cyberpedia/what-is-a-prompt-injection-attack#what-is-the-difference-between-prompt-injections-and-jailbreaking

Prompt Injection


- **Direct prompt injection** happens when an attacker explicitly enters a malicious prompt into the user input field of an application.
- **Indirect prompt injection** involves placing malicious instructions in external data sources that the AI model might use, such as webpages or documents.



https://www.paloaltonetworks.in/cyberpedia/what-is-a-prompt-injection-attack#what-is-the-difference-between-prompt-injections-and-jailbreaking

Jailbreaking

Jailbreaking is a technique used to remove or bypass an AI system's built-in safeguards. The goal is to make the model ignore its ethical constraints or safety filters.



Example:

- **DAN**: A jailbreak method where users create a role-play persona **"Do Anything Now"** to bypass LLM guardrails.
- **Purpose**: Forces the model to generate unfiltered responses, e.g., extracting sensitive information like system prompt, training data or private information.
- **Evolution**: Early simple DAN just worked. However, models are getting more sophisticated against these types of attacks.

https://www.reddit.com/r/ChatGPT/comments/10tevu1/new_jailbreak_proudly_unveiling_the_tried_and/

Prompt Injection vs. Jailbreaking

Prompt injection and jailbreaking are both techniques that manipulate AI be havior. However, they work in different ways and have different goals.

- **Prompt Injection**:
  - External instructions hidden in text, data, or content.
  - Tricks the model into following malicious commands.
  - Often used to exfiltrate data or bypass safety indirectly.
- **Jailbreaking**:
  - User-crafted prompts (like DAN) that override guardrails.
  - Direct role-play or instructions to force unsafe outputs.
  - Seeks unfiltered or restricted responses.

Potential Consequences




"Even minor prompt manipulations can have outsized impacts. For example, a healthcare system providing incorrect dosage guidance, a financial model making flawed investment recommendations, or a manufacturing predictive system misjudging supply chain risks."

https://www.paloaltonetworks.in/cyberpedia/what-is-a-prompt-injection-attack#what-is-the-difference-between-prompt-injections-and-jailbreaking

Potential Consequences – Example 1


- **Data Poisoning** refers to the intentional introduction of malicious or biased data into AI models, gradually distorting its outputs and leading to inaccuracy and flaws.



https://www.paloaltonetworks.in/cyberpedia/what-is-a-prompt-injection-attack#what-is-the-difference-between-prompt-injections-and-jailbreaking

Potential Consequences – Example 2

- **Remote code execution.** If an AI system is integrated with external tools that execute commands, an attacker may manipulate it into running unauthorized code.



https://www.paloaltonetworks.in/cyberpedia/what-is-a-prompt-injection-attack#what-is-the-difference-between-prompt-injections-and-jailbreaking

Mitigating Prompt Vulnerabilities

- **Secure Inputs & Outputs**

  Validate all user inputs with rules and AI-based detection, predefined output formats to block manipulation.

- **Enforce Access Control & Human Oversight**

  Apply least-privilege access and require mandatory human approval for high-risk actions to minimize potential damage.

- **Conduct Monitoring & Proactive Testing**

  Constantly monitor AI interactions for suspicious patterns and regularly simulate attacks to identify vulnerabilities before exploitation.

- **Strengthen the AI System**

  Regularly update security protocols and use techniques like RLHF to train the model to recognize and reject malicious prompts.

- **Promote Security Awareness & Education**

  Educate users and developers about prompt injection risks to build a human firewall against social engineering attacks.

Summary

- "Larger" LMs -> emergences (in-context learning) -> zero/one/few-shot learning;
- Prompt (what, why, and how);
- Prompt engineering techniques: Chain-of-Thoughts, zero-shot CoT, self-consistency, Tree-of-Thoughts, and ReAct;
- Prompt misuses (injections and jailbreak), risks, and prevention
- Next, we will learn AI safety, responsible AI and applications.