



Subashini M 251801338-2025-AIDS ▾

S2

Started on	Thursday, 17 September 2026, 8:11 AM
State	Finished
Completed on	Thursday, 17 September 2026, 8:45 AM
Time taken	33 mins 49 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int compareAsc(const void *a, const void *b) {
5      return (*(int*)a - *(int*)b);
6  }
7
8  int compareDesc(const void *a, const void *b) {
9      return (*(int*)b - *(int*)a);
10 }
11
12 int main() {
13     int n;
14
15     if (scanf("%d", &n) != 1) {
16         return 1;
17     }
18
19     int *arr1 = (int*)malloc(n * sizeof(int));
20     int *arr2 = (int*)malloc(n * sizeof(int));
21
22     for (int i = 0; i < n; i++) {
23         scanf("%d", &arr1[i]);
24     }
25
26     for (int i = 0; i < n; i++) {
27         scanf("%d", &arr2[i]);
28     }
29
30     qsort(arr1, n, sizeof(int), compareAsc);
31
32     qsort(arr2, n, sizeof(int), compareDesc);
33
34     long long minSum = 0;
35     for(int i = 0; i < n; i++) {
36         minSum += (long long)arr1[i] * arr2[i];
37     }
38
39     printf("%lld\n", minSum);
40
41     free(arr1);
42     free(arr2);
43
44     return 0;
45 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)