

尼泊尔电动车型介绍

Introduction to Electric Vehicle Models for Nepal

纯电动微卡车型介绍Introduction to Battery Electric Mini Light Truck Models

1.5吨栏板车主要配置参数（右舵）Main configuration parameters of 1.5-ton pallet truck（right-hand drive

技术参数Technical parameters	车辆型号Vehicle model	M31栏板车尺寸
尺寸参数 Dimensional parameters	车辆长Vehicle length（mm）	5165
	车辆宽Vehicle width（mm）	1780
	车辆高（空载）Vehicle height（utetheisa kong load）（mm）	2030
	轴距Wheelbase（mm）	3400
	车厢尺寸Compartment dimensions（mm）	3200*1720*360
	前轮距（沿地面）Front track（along the ground）（mm）	1420
	后轮距（双轮中心）Rear wheel track（center of dual wheels）（mm）	1390
	前/后悬Front/rear overhang（mm）	580/1185
质量参数Quality parameters	整备质量Curb weight（kg）	1625
	额定载质量Rated load capacity（kg）	1225
	额定总质量Rated total mass（kg）	2980
	允许前轴轴载质量Permitted front axle load mass（kg）	1200
	允许后桥轴载质量Permitted rear axle load mass（kg）	1800
	乘员数（含驾驶员）Number of occupants（including the driver）	2



纯电动微卡车型介绍Introduction to Battery Electric Mini Light Truck Models

1.5吨栏板车主要配置参数（右舵）Main configuration parameters of 1.5-ton pallet truck（right-hand drive

技术参数Technical parameters	车辆型号Vehicle model	M31栏板车尺寸
性能参数Performance parameters	最高车速Maximum speed (Km/h)	90
	最大爬坡度Maximum Climbing Gradient (%)	20
	最小转弯直径Minimum turning diameter (m)	14.5
	最小离地间隙Minimum ground clearance (mm)	>200
	续驶里程Driving range (Km)	235
电机Electric motor	厂家及型号Manufacturer and model	深圳大地和
	额定功率/峰值功率Rated power/Peak power(Kw)	35/ 70
	额定扭矩/峰值扭矩Rated torque / Peak torque (Nm)	90/230
电机控制器Motor controller	厂家Manufacturer	深圳大地和
	额定输入电压 (V) /电流(A)Rated input voltage (V)/current (A)	336/115
	工作电压 (V) 范围Operating voltage (V) range	220~430
磷酸铁锂锂离子电池Lithium iron phosphate lithium-ion power battery	厂家Manufacturer	天津国轩Tianjin Gotion
	电池组标称电压/标称容量Nominal voltage / nominal capacity of battery pack	41.93kwh
	电池冷却系统Battery cooling system	风冷，带电加热Air-cooled, with electric heating



纯电动微卡车型介绍Introduction to Battery Electric Mini Light Truck Models

1.5吨栏板车主要配置参数（右舵）Main configuration parameters of 1.5-ton pallet truck（right-hand drive

技术参数 Technical parameters	车辆型号 Vehicle model	M31栏板车尺寸
底盘配置 Chassis configuration	前桥front axle	非驱动、管轴单拳式，自调臂，带ABS，带制动衬片磨损报警装置 Non-driven, tubular axle single-shoe type, self-adjusting arm, with ABS, with brake lining abrasion of tooth warning device
	后桥rear axle	冲压焊接式桥壳，单级减速器，自调臂，带ABS Stamped and welded axle housing, single-stage reducer, automatic slack adjuster, with ABS
	后桥总成主减速比 Rear axle assembly main reduction ratio	10.5
	车架总成Frame Assembly	槽形结构变截面梁Trough-shaped joint Broussonetia papyrifera variable cross-section beam
	前悬架Front suspension	前簧5片，筒式减震器 Front spring with 5 leaves, tubular shock absorber
	后悬架Rear Suspension	后簧5片，筒式减震器 Rear spring with 5 leaves, tubular shock absorber
	转向机总成Steering gear assembly	电子转向助力Electric Power Steering
	制动系统Braking system	液压制动，前盘后鼓制动器，带ABS+EBD，机械手刹 Hydraulic braking, front disc and rear drum brakes, with ABS+EBD, mechanical handbrake
	轮胎Tire	185R14LT 8PR，4条，不带备胎 185R14LT 8PR, 4 pieces, without spare tire



纯电动微卡车型介绍Introduction to Battery Electric Mini Light Truck Models

1.5吨栏板车主要配置参数（右舵）Main configuration parameters of 1.5-ton pallet truck（right-hand drive

技术参数Technical parameters	车辆型号Vehicle model	M31栏板车尺寸
驾驶室Driver's cab	驾驶室Driver's cab	1650mm宽 右舵平头型，不可翻转，不带导流罩 1650mm wide right-hand drive cab-over type, non-tilting, without wind deflector
	司机座椅Driver's seat	弹簧减震座椅，织物 Spring shock-absorbing seat, fabric
电器 Electrical appliance	空调系统air conditioning system	不带空调，暖风 no Air conditioning, warm air
	雾灯fog light	标配Standard configuration
	倒车雷达	标配
	中控门锁Central locking system	中控门锁Without central locking system
	电动车窗升降器Electric window regulator	电动升降器Without electric lifting device
	倒车镜Rearview mirror	手动后视镜Manual rearview mirror
	USB	点烟器，带USB接口 Cigarette lighter with USB port
	充电方式Charging method	慢充3.3kw，国标充电，快充 Slow charging 3.3kw, fast charging



纯电动16-19座客车

Battery Electric 16-19 Seater Passenger Bus

Vehicle size (mm): 5998*1885*2285

Wheelbase (mm): 3720

Power battery (kWh): 77.28

Rated power/peak power (kW): 50 / 90

Rated/Peak torque (N.m):160/350

Range (km): 350

Seating capacity: 18



纯电动16-19座客车

Battery Electric 16-19 Seater Passenger Bus



主要参数MAIN PARAMETERS	
Vehicle model车辆型号	SLK6540BEV (左/右舵LHD/RHD)
length*width*height 长宽高(mm)	5380*1880*2285
Wheelbase(mm)轴距(mm)	3110
Seats 座位数	4+4+4+4+2=18
Battery type 电池类型	'LFP (Lithium iron phosphate)磷酸铁锂
Battery Capacity(kWh)装载电量(kWh)	87kWh
Battery management system 电池管理系统	
Motor rated/peak power(kw)电机额定功率	50/100
Voyage course NEDCNEDC 续驶里程(km)	340
Charging equipment 充电配置	'Fast Charging and Slow Charging"
Tire 轮胎	195R15C radialtire 195R15C子午线轮胎
Brake system 制动系统	disc/ drum,ABS+EBD,vacuum booster system 前盘后鼓,ABS+EBD,真空助力系统
Suspension 悬挂	front double wishbone independent suspension/rear variable rate leaf spring (four pcs) 前双横臂式独立悬架/后变刚度板(四片)
Steering system 转向系统	Electric power steering power EPS