

Summary

- Language models (LMs) predict both text-evoked and speech-evoked brain activity to an impressive degree irrespective of choice of modality.
- Speech-based models (SMs), which would be expected to predict speech-evoked brain activity better, provided they model language processing in the brain well.
- These findings poses several questions:
 - Are speech models (SMs) outperform language models (LMs) during speech-evoked brain activity?
 - Do both LMs and SMs combine a new word representation with previous context?
 - What type of information is shared between LMs and SMs that results in improved brain predictivity?
- We investigate these questions using both LMs (GPT2) and SMs (Wav2vec2.0, HuBERT and Data2vec), and observe how these models predict MEG brain recordings acquired while participants listened to the naturalistic stories.
- Language models outperform speech models irrespective of speech-evoked brain activity.
- Both type of models still behind the estimated noise-ceiling performance.
- Like LMs, previous context is important in predicting MEG recordings for SMs

Language Models (LMs) / Speech Models (SMs) are trained to predict missing words/speech




Figure 1: Language Models (LMs) and Speech Models (SMs) have achieved impressive performance across many benchmarks

LMs/SMs also predict brain activity evoked by complex language (e.g. listening a story) to an impressive degree





Figure 2: Brain alignment of a LM/SM

With MEG we can analyze sub-word time course

- MEG recording data at very fast temporal resolution
- So, we can look at sub-word process
- fMRI recording data at very high-spatial resolution



Brain encoding schema






Figure 3: Approach to directly test for the alignment between a LM/SM and MEG brain recordings.

Encoding performance of LM and SMs



Brain alignment – 4-fold Cross-Validation + Ridge regression



Layer-wise Performance of SM: Data2vec





Figure 5: Topo map for Average Normalized predictivity by Data2Vec (across subjects) for MEG activity. Word onset is at 0ms. Layer 2 (top), Layer 7 (middle), and Layer 11 (bottom).

Encoding performance SMs: Contextual Embeddings



References

- Toneva et al. 2019. Interpreting and improving natural-language processing (in machines) with natural language-processing (in the brain).
- Gwilliams et al. 2022. Meg-masc: a high-quality magneto-encephalography dataset for evaluating natural speech processing.
- Oota et al. 2023. Meg encoding using word context semantics in listening stories.

Acknowledgements

① We thank Inria for the PhD funding and ANR DeepPool project.