1)su - user1

```
root@eltex-practice2-pg2-v7:~# su - user1
Warning: your password will expire in 5 days.
$
```

2) ps -eLo pid,nlwp,comm --no-headers | awk '$2 > 1' | wc -l

ps -eLo pid,nlwp,comm --no-headers | awk '$2 > 1'

```
$ ps -eLo pid,nlwp,comm --no-headers | awk '$2 > 1' | wc -l
41
$ ps -eLo pid,nlwp,comm --no-headers | awk '$2 > 1'
    725    2 unattended-upgr
    725    2 gmain
  19925    7 multipathd
  19925    7 multipathd
  19925    7 multipathd
  19925    7 multipathd
  19925    7 multipathd
  19925    7 multipathd
  19925    7 multipathd
  22431    2 qemu-ga
  22431    2 qemu-ga
  47918    6 fwupd
  47918    6 gmain
  47918    6 libusb_event
  47918    6 GUsbEventThread
  47918    6 pool-spawner
  47918    6 gdbus
  47926    4 upowerd
  47926    4 pool-spawner
  47926    4 gmain
  47926    4 gdbus
  47947    4 polkitd
  47947    4 gmain
  47947    4 pool-spawner
  47947    4 gdbus
  47954    2 systemd-timesyn
  47954    2 sd-resolve
  47956    6 udisksd
  47956    6 gmain
  47956    6 pool-spawner
  47956    6 gdbus
  47956    6 probing-thread
  47956    6 cleanup
  47974    4 ModemManager
  47974    4 gmain
  47974    4 pool-spawner
  47974    4 gdbus
  47987    4 rsyslogd
  47987    4 in:imuxsock
  47987    4 in:imklog
  47987    4 rs:main Q:Reg
$
```

3) взашли top и отключили процесы через d и вкл RUSER

```
root@eltex-practice2-pg2-v7:~# top

top - 11:43:38 up 5 days,  3:15,  1 user,  load average: 0.00, 0.00, 0.00
Tasks: 107 total,   1 running, 106 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.0 us,  0.0 sy,  0.0 ni,100.0 id,  0.0 wa,  0.0 hi,  0.0 si,  0
MiB Mem :   3916.0 total,   1170.3 free,    496.9 used,   2540.7 buff/cach
MiB Swap:   3185.0 total,   3185.0 free,      0.0 used.   3419.1 avail Mem
```

| PID | USER | PR | NI | VIRT | RES | SHR | S | %CPU | %MEM | TIME+ |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | root | 20 | 0 | 22472 | 13696 | 9600 | S | 0.0 | 0.3 | 0:13.18 |
| 2 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.05 |
| 3 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 4 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 5 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 6 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 7 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 10 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.74 |
| 12 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 13 | root | 20 | 0 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 14 | root | 20 | 0 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 15 | root | 20 | 0 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 16 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.22 |
| 17 | root | 20 | 0 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:03.66 |
| 18 | root | rt | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:01.68 |
| 19 | root | -51 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 20 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 21 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 22 | root | -51 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 23 | root | rt | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:02.03 |
| 24 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.20 |
| 26 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 27 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 28 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 30 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 31 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.10 |
| 32 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 33 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 34 | root | 20 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:10.35 |
| 36 | root | 25 | 5 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 37 | root | 39 | 19 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 38 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 39 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 40 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 41 | root | -51 | 0 | 0 | 0 | 0 | S | 0.0 | 0.0 | 0:00.00 |
| 42 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |
| 43 | root | 0 | -20 | 0 | 0 | 0 | I | 0.0 | 0.0 | 0:00.00 |

```
Fields Management for window 1:Def, whose current sort field is %CPU
   Navigate with Up/Dn, Right selects for move then <Enter> or Left commits
   'd' or <Space> toggles display, 's' sets sort.  Use 'q' or <Esc> to end!

* PID      = Process Id            nsIPC    = IPC namespace Inode
* USER     = Effective User Name   nsMNT    = MNT namespace Inode
* PR       = Priority              nsNET    = NET namespace Inode
* NI       = Nice Value            nsPID    = PID namespace Inode
  VIRT     = Virtual Image (KiB)   nsUSER   = USER namespace Inode
  RES      = Resident Size (KiB)   nsUTS    = UTS namespace Inode
  SHR      = Shared Memory (KiB)   LXC      = LXC container name
* S        = Process Status        RSan     = RES Anonymous (KiB)
* %CPU     = CPU Usage             RSfd     = RES File-based (KiB)
* %MEM     = Memory Usage (RES)    RSlk     = RES Locked (KiB)
* TIME+    = CPU Time, hundredths  RSsh     = RES Shared (KiB)
* COMMAND  = Command Name/Line     CGNAME   = Control Group name
  PPID     = Parent Process pid    NU       = Last Used NUMA node
  UID      = Effective User Id     LOGID    = Login User Id
  RUID     = Real User Id          EXE      = Executable Path
* RUSER    = Real User Name        RSS      = Res Mem (smaps), KiB
  SUID     = Saved User Id         PSS      = Proportion RSS,  KiB
  SUSER    = Saved User Name       PSan     = Proportion Anon, KiB
  GID      = Group Id              PSfd     = Proportion File, KiB
  GROUP    = Group Name            PSsh     = Proportion Shrd, KiB
  PGRP     = Process Group Id      USS      = Unique RSS, KiB
  TTY      = Controlling Tty       ioR      = I/O Bytes Read
  TPGID    = Tty Process Grp Id    ioRop    = I/O Read Operations
  SID      = Session Id            ioW      = I/O Bytes Written
  nTH      = Number of Threads     ioWop    = I/O Write Operations
  P        = Last Used Cpu (SMP)   AGID     = Autogroup Identifier
  TIME     = CPU Time              AGNI     = Autogroup Nice Value
  SWAP     = Swapped Size (KiB)    STARTED  = Start Time from boot
  CODE     = Code Size (KiB)       ELAPSED  = Elapsed Running Time
  DATA     = Data+Stack (KiB)      %CUU     = CPU Utilization
  nMaj     = Major Page Faults     %CUC     = Utilization + child
  nMin     = Minor Page Faults     nsCGROUP = CGRP namespace Inode
  nDRT     = Dirty Pages Count     nsTIME   = TIME namespace Inode
  WCHAN    = Sleeping in Function
  Flags    = Task Flags <sched.h>
  CGROUPS  = Control Groups
  SUPGIDS  = Supp Groups IDs
```

4)

```
MiB Swap:   3183.0 total,   3183.0 free,      0.0 used.   3409.3 avail Mem

    PID USER      PR  NI S  %CPU  %MEM     TIME+ COMMAND            RUSER
  64053 root      20   0 S   0.0   0.1   0:00.00 bash               root
  64070 root      20   0 I   0.0   0.0   0:00.00 kworker/0:1-events root
  64078 root      20   0 R   0.0   0.2   0:00.03 top                root
  64081 root      20   0 I   0.0   0.0   0:00.00 kworker/1:1        root
```

5)В новом терминале ввили команду passwd, и показался новый процесс

```
top - 14:42:21 up 5 days,  6:14,  2 users,  load average: 0.00, 0.00, 0.00
Tasks: 112 total,   1 running, 111 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.0 us,  0.0 sy,  0.0 ni,100.0 id,  0.0 wa,  0.0 hi,  0.0 si,  0.
MiB Mem :   3916.0 total,   1144.3 free,    511.9 used,   2551.8 buff/cache
MiB Swap:   3185.0 total,   3185.0 free,      0.0 used.   3404.2 avail Mem

    PID USER      PR  NI S  %CPU  %MEM     TIME+ COMMAND            RUSER
  64053 root      20   0 S   0.0   0.1   0:00.00 bash               root
  64070 root      20   0 I   0.0   0.0   0:00.00 kworker/0:1-cgrou+ root
  64081 root      20   0 I   0.0   0.0   0:00.00 kworker/1:1        root
  64082 root      20   0 S   0.0   0.3   0:00.01 sshd               root
  64139 root      20   0 S   0.0   0.1   0:00.00 bash               root
  64156 root      20   0 R   0.0   0.2   0:00.09 top                root
  64159 root      20   0 I   0.0   0.0   0:00.00 kworker/0:0-events root
  64160 root      20   0 I   0.0   0.0   0:00.00 kworker/u4:2-even+ root
  64161 root      20   0 S   0.0   0.1   0:00.00 su                 root
  64162 user1     20   0 S   0.0   0.0   0:00.00 dash               user1
  64167 root      20   0 S   0.0   0.1   0:00.00 passwd             user1
```

passwd были отправлены сигналы 15 (SIGTERM), 2 (SIGINT), 3 (SIGQUIT) и 9 (SIGKILL).
Практически завершение процесса было достигнуто только при отправке сигнала 9, что показывает его принудительный характер.
Сигналы 15, 2 и 3 не обеспечили такого же гарантированного завершения процесса.

```
    PID USER      PR  NI S  %CPU  %MEM     TIME+ COMMAND            RUSER
  64413 root      20   0 S   0.0   0.1   0:00.00 bash               root
  64424 root      20   0 S   0.0   0.1   0:00.00 su                 root
  64425 user1     20   0 S   0.0   0.0   0:00.00 dash               user1
```

```
*** System restart required ***
Thu Mar 12 04:40:01 PM UTC 2026
Last login: Tue Mar 17 14:52:09 2026 from 172.16.8.4
root@eltex-practice2-pg2-v7:~# su - user1
Warning: your password will expire in 5 days.
$ passwd
Changing password for user1.
Current password: Killed
$
```

6)открыли файл через vim и вышли через cntr+Z

```
/home/user1
$ vim ~/file_task3.txt
[1] + Stopped                 vim ~/file_task3.txt
$
```

7)600 сек спит, также остановили cntr+Z

```
$ sleep 600
^Z[2] + Stopped                 sleep 600
$ jobs
[2] + Stopped                 sleep 600
[1] - Stopped                 vim ~/file_task3.txt
$
```

8)возобновили работу

```
$ bg %2
[2] sleep 600
$ jobs
[1] + Stopped                 vim ~/file_task3.txt
[2] - Running                 sleep 600
$
```

9 и 10

renice уже успешно изменил nice у процесса sleep 600 на 10. Для проверки через ps нужно указывать список полей без пробелов: pid,ni,comm

```
$ jobs -l
[1] + 64592 Stopped                 vim ~/file_task3.txt
[2] - 64607 Running                 sleep 600
$ renice 10 -p 64607
64607 (process ID) old priority 0, new priority 10
```

```
$ ps -o pid,ni,comm -p 64607
    PID  NI COMMAND
  64607  10 sleep
$
```

11) jobs

fg %1

Возобновили файл

```
$ jobs
[1] + Stopped                 vim ~/file_task3.txt
[2] - Running                 sleep 600
$ fg %1
vim ~/file_task3.txt
$ jobs
[2] + Running                 sleep 600
$
```

12) Команда kill -15 64607 отправляет процессу сигнал SIGTERM. Для фонового задания sleep 600 этого обычно достаточно, чтобы завершить его. Проверка результата выполняется через jobs.

```
$ jobs
[2] + Running                 sleep 600
$ jobs -l
[2] + 64607 Running           sleep 600
$ kill -15 64607
[2] + Done                    sleep 600
$ jobs
$
```

13) trap позволяет оболочке Bash перехватывать сигналы и выполнять свою команду вместо стандартной реакции

```
$ trap 'echo "Меня голыми руками не возьмёшь!"' INT QUIT
$ ^C
Меня голыми руками не возьмёшь!
$ ^\
Меня голыми руками не возьмёшь!
$ echo $$
64587
$ kill -INT $$
Меня голыми руками не возьмёшь!
$ KILL _QUIT $$
-dash: 29: KILL: not found
$ KILL -QUIT $$
-dash: 30: KILL: not found
$ kill -QUIT $$
Меня голыми руками не возьмёшь!
$
```

# Раздел2

1)

был создан bash-скрипт cuckoo.sh. Скрипт создаёт каталог /tmp/run и именованные каналы /tmp/run/cuckoo.pid и /tmp/run/cuckoo.resp. При запуске скрипт записывает в файл cuckoo.log сообщение о старте в формате ДАТА ВРЕМЯ Startup!.

При получении запроса через именованный канал вида NAME[PID]: how much time do I have? скрипт генерирует случайное число N в диапазоне от 2 до 10, записывает обращение и ответ в лог и возвращает число клиенту через канал ответа. Проверка показала, что скрипт корректно принимает запросы и возвращает ответ, например значение 2.

```
#!/bin/bash

PIPE="/tmp/run/cuckoo.pid"
RESP="/tmp/run/cuckoo.resp"
LOGFILE="$HOME/cuckoo.log"

mkdir -p /tmp/run

if [ ! -p "$PIPE" ]; then
    mkfifo "$PIPE"
fi

if [ ! -p "$RESP" ]; then
    mkfifo "$RESP"
fi

trap 'echo "$(date "+%F %T") Shutdown!" >> "$LOGFILE"; rm -f "$PIPE" "$RESP";
 exit 0' TERM

echo "$(date "+%F %T") Startup!" >> "$LOGFILE"

while true; do
    if read line < "$PIPE"; then
        n=$((RANDOM % 9 + 2))
        echo "$(date "+%F %T") $line $n" >> "$LOGFILE"
        echo "$n" > "$RESP"
    fi
done
~
~
~
```

2) screen позволяет запустить cuckoo.sh как долгоживущий процесс, не привязанный к открытому терминалу.

```
root@eltex-practice2-pg2-v7:~# kill -TERM PID
-bash: kill: PID: arguments must be process or job IDs
root@eltex-practice2-pg2-v7:~# kill -TERM 65288
root@eltex-practice2-pg2-v7:~# screen -S cuckoo
[detached from 65303.cuckoo]
root@eltex-practice2-pg2-v7:~# screen -ls
There is a screen on:
        65303.cuckoo    (03/17/2026 05:11:52 PM)        (Detached)
1 Socket in /run/screen/S-root.
root@eltex-practice2-pg2-v7:~# pgrep -af cuckoo.sh
65288 /bin/bash /root/cuckoo.sh
65312 /bin/bash /root/cuckoo.sh
root@eltex-practice2-pg2-v7:~# echo 'testproc[1234]: how much time do I have
' > /tmp/run/cuckoo.pid
cat /tmp/run/cuckoo.resp
cat ~/cuckoo.log
7
2026-03-17 16:57:46 Startup!
2026-03-17 16:57:53 testproc[1234]: how much time do I have? 2
2026-03-17 17:06:42 Startup!
2026-03-17 17:12:21 Startup!
2026-03-17 17:13:32 testproc[1234]: how much time do I have? 7
root@eltex-practice2-pg2-v7:~#
```

3) Один и тот же скрипт template_task.sh может работать как шаблон и как реальная задача — в зависимости от имени запуска через символическую ссылку.

```
root@eltex-practice2-pg2-v7:~# ln -s ~/template_task.sh ~/worker_test
root@eltex-practice2-pg2-v7:~# ls -l ~/worker_test
lrwxrwxrwx 1 root root 22 Mar 17 17:20 /root/worker_test -> /root/template_ta
sk.sh
root@eltex-practice2-pg2-v7:~# ~/worker_test
root@eltex-practice2-pg2-v7:~# cat ~/report_worker_test.log
2026-03-17 17:20:29 [65338] Скрипт запущен
2026-03-17 17:20:37 [65338] Скрипт завершился, работал 8 секунд.
root@eltex-practice2-pg2-v7:~# cat ~/cuckoo.log
2026-03-17 16:57:46 Startup!
2026-03-17 16:57:53 testproc[1234]: how much time do I have? 2
2026-03-17 17:06:42 Startup!
2026-03-17 17:12:21 Startup!
2026-03-17 17:13:32 testproc[1234]: how much time do I have? 7
2026-03-17 17:20:29 worker_test[65338]: how much time do I have? 8
root@eltex-practice2-pg2-v7:~#
```

4)

```
root@eltex-practice2-pg2-v7:~# cat > ~/observer.sh <<'EOF'
#!/bin/bash

CONFIG="$HOME/observer.conf"
LOGFILE="$HOME/observer.log"

while read task; do
    [ -z "$task" ] && continue

    found=0

    for procdir in /proc/[0-9]*; do
        [ -f "$procdir/comm" ] || continue

        procname=$(cat "$procdir/comm" 2>/dev/null)

        if [ "$procname" = "$task" ]; then
            found=1
            break
        fi
    done

    if [ "$found" -eq 0 ]; then
        nohup "$HOME/$task" >/dev/null 2>&1 &
        echo "$(date '+%F %T') restarted $task" >> "$LOGFILE"
    fi

done < "$CONFIG"
EOF

chmod +x ~/observer.sh
root@eltex-practice2-pg2-v7:~# cat ~/observer.conf
cat ~/observer.sh
template_task.sh
worker1
worker2
#!/bin/bash

CONFIG="$HOME/observer.conf"
LOGFILE="$HOME/observer.log"

while read task; do
    [ -z "$task" ] && continue

    found=0

    for procdir in /proc/[0-9]*; do
```

```
    for procdir in /proc/[0-9]*; do
        [ -f "$procdir/comm" ] || continue

        procname=$(cat "$procdir/comm" 2>/dev/null)

        if [ "$procname" = "$task" ]; then
            found=1
            break
        fi
    done

    if [ "$found" -eq 0 ]; then
        nohup "$HOME/$task" >/dev/null 2>&1 &
        echo "$(date '+%F %T') restarted $task" >> "$LOGFILE"
    fi

done < "$CONFIG"
root@eltex-practice2-pg2-v7:~# cat ~/observer.conf
cat ~/observer.sh
template_task.sh
worker1
worker2
#!/bin/bash

CONFIG="$HOME/observer.conf"
LOGFILE="$HOME/observer.log"

while read task; do
    [ -z "$task" ] && continue

    found=0

    for procdir in /proc/[0-9]*; do
        [ -f "$procdir/comm" ] || continue

        procname=$(cat "$procdir/comm" 2>/dev/null)

        if [ "$procname" = "$task" ]; then
            found=1
            break
        fi
    done

    if [ "$found" -eq 0 ]; then
        nohup "$HOME/$task" >/dev/null 2>&1 &
        echo "$(date '+%F %T') restarted $task" >> "$LOGFILE"
    fi

done < "$CONFIG"
```

```
root@eltex-practice2-pg2-v7:~# rm -f ~/observer.log ~/report_worker1.log ~/re
port_worker2.log ~/report_template_task.sh.log
root@eltex-practice2-pg2-v7:~# pgrep -af cuckoo.sh
65288 /bin/bash /root/cuckoo.sh
65312 /bin/bash /root/cuckoo.sh
root@eltex-practice2-pg2-v7:~# ~/observer.sh
root@eltex-practice2-pg2-v7:~# cat ~/observer.log
2026-03-17 17:46:27 restarted template_task.sh
2026-03-17 17:46:27 restarted worker1
2026-03-17 17:46:27 restarted worker2
root@eltex-practice2-pg2-v7:~# ls -l ~/report_*.log
-rw-r--r-- 1 root root 150 Mar 17 17:46 /root/report_worker1.log
-rw-r--r-- 1 root root 150 Mar 17 17:46 /root/report_worker2.log
-rw-r--r-- 1 root root 150 Mar 17 17:20 /root/report_worker_test.log
root@eltex-practice2-pg2-v7:~#
```

5) был настроен запуск observer.sh через планировщик cron с периодичностью один раз в минуту. Это позволило автоматически выполнять проверку наличия задач

```
root@eltex-practice2-pg2-v7:~# crontab -e
no crontab for root - using an empty one
crontab: installing new crontab
root@eltex-practice2-pg2-v7:~# crontab -l
* * * * * /bin/bash /root/observer.sh
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h  dom mon dow   command
root@eltex-practice2-pg2-v7:~# crontab -l
* * * * * /bin/bash /root/observer.sh
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
```

6)

```
root@eltex-practice2-pg2-v7:~# pgrep -af cuckoo.sh
root@eltex-practice2-pg2-v7:~# tail -n 5 ~.cuckoo.log
tail: cannot open '~.cuckoo.log' for reading: No such file or direct
root@eltex-practice2-pg2-v7:~# tail -n 5 ~/cuckoo.log
2026-03-18 03:38:01 worker1[461425]: how much time do I have? 5
2026-03-18 03:38:01 worker2[461655]: how much time do I have? 9
2026-03-18 03:39:02 worker1[462113]: how much time do I have? 9
2026-03-18 03:39:02 worker2[462343]: how much time do I have? 2
2026-03-18 03:43:18 Shutdown!
```

7) Перед упаковкой был остановлен процесс cuckoo.sh, а автоматический запуск observer.sh через cron был отключён. После этого все необходимые файлы были упакованы в архив practice3_report.tar

```
root@eltex-practice2-pg2-v7:~# ls -l ~/cuckoo.sh ~/template_task.sh ~/observer.sh ~/ob
server.conf ~/cuckoo.log ~/observer.log ~/report_*.log
-rw-r--r-- 1 root root 74443 Mar 18 03:43 /root/cuckoo.log
-rwxr-xr-x 1 root root   526 Mar 17 17:08 /root/cuckoo.sh
-rw-r--r-- 1 root root    33 Mar 17 17:40 /root/observer.conf
-rw-r--r-- 1 root root 71340 Mar 18 03:39 /root/observer.log
-rwxr-xr-x 1 root root   537 Mar 17 17:41 /root/observer.sh
-rw-r--r-- 1 root root 88113 Mar 18 03:39 /root/report_worker1.log
-rw-r--r-- 1 root root 88126 Mar 18 03:39 /root/report_worker2.log
-rw-r--r-- 1 root root   150 Mar 17 17:20 /root/report_worker_test.log
-rwxr-xr-x 1 root root   503 Mar 17 17:18 /root/template_task.sh
root@eltex-practice2-pg2-v7:~# tar -cvf ~/practice3_report.tar \
~/cuckoo.sh \
~/template_task.sh \
~/observer.sh \
~/observer.conf \
~/cuckoo.log \
~/observer.log \
~/report_*.log
tar: Removing leading `/' from member names
/root/cuckoo.sh
tar: Removing leading `/' from hard link targets
/root/template_task.sh
/root/observer.sh
/root/observer.conf
/root/cuckoo.log
/root/observer.log
/root/report_worker1.log
/root/report_worker2.log
/root/report_worker_test.log
root@eltex-practice2-pg2-v7:~# tar -tvf ~/practice3_report.tar
-rwxr-xr-x root/root       526 2026-03-17 17:08 root/cuckoo.sh
-rwxr-xr-x root/root       503 2026-03-17 17:18 root/template_task.sh
-rwxr-xr-x root/root       537 2026-03-17 17:41 root/observer.sh
-rw-r--r-- root/root        33 2026-03-17 17:40 root/observer.conf
-rw-r--r-- root/root     74443 2026-03-18 03:43 root/cuckoo.log
-rw-r--r-- root/root     71340 2026-03-18 03:39 root/observer.log
-rw-r--r-- root/root     88113 2026-03-18 03:39 root/report_worker1.log
-rw-r--r-- root/root     88126 2026-03-18 03:39 root/report_worker2.log
-rw-r--r-- root/root       150 2026-03-17 17:20 root/report_worker_test.log
root@eltex-practice2-pg2-v7:~# ls -lh ~/practice3_report.tar
-rw-r--r-- 1 root root 330K Mar 18 03:49 /root/practice3_report.tar
root@eltex-practice2-pg2-v7:~# Connection to 217.71.138.1 closed by remote host.
```