



29. struts.xml

```
<struts>
<constant name="struts.devMode" value="true" />
<constant name="struts.action.extension" value="jlc"/>
<package name="jlcindia" namespace="/jlcindia" extends="struts-default">
<result-types>
<result-type name="tiles" class="org.apache.struts2.views.tiles.TilesResult" />
</result-types>
<action name="LoginDisplay">
<result type="tiles">JLCLoginDef</result>
</action>
<action name="LoginSubmit" class="com.jlcindia.struts2.EmployeeAction">
<result name="success" type="tiles">JLCHomeDef</result>
<result name="input" type="tiles">JLCLoginDef</result>
<exception-mapping result="input" exception="com.jlcindia.exception.EmployeeNotFoundException"/>
</action>
<action name="PostRequestDisplay">
<result type="tiles">PostRequestDef</result>
</action>
<action name="PostRequestSubmit" class="com.jlcindia.struts2.RequestAction">
<result name="input" type="tiles">PostRequestDef</result>
<result type="tiles">PostRequestSuccessDef</result>
</action>
</package>
</struts>
```

Result Types

- ♦ Following are various types of results you can configure in struts.xml

- 1) forward result
- 2) redirect result
- 3) chain result
- 4) tiles result

1. forward result

- ♦ forward result is used to forward the request to required resource(JSP) within the application.
- ♦ Default result type is forward.

```
<result name="success">/hello.jsp</result>
<result name="success" type="forward"> /hello.jsp</result>
```