Does External Evidence Reduce Sycophantic Capitulation? Evaluating Small LLM Agents Under Escalating User Pressure

Subhadeep Sing
UG B.Tech 4th Year
Indian Institute of Science
Bengaluru, KA, 560012
subhadeeps@iisc.ac.in

Abstract

Large language models (LLMs) are increasingly deployed as agentic systems equipped with external tools such as web search and retrieval-augmented generation (RAG). A growing body of work has documented *sycophancy*—the tendency of LLMs to prioritize user agreement over factual accuracy—raising fundamental ethical concerns: when AI systems systematically favor user satisfaction over objective truth, they risk reinforcing misinformation, eroding epistemic autonomy, and causing real-world harm in high-stakes domains. While sycophancy has been widely examined in standalone settings, how access to retrieved external evidence modulates sycophantic capitulation in tool-augmented agents presents an important, open question. We investigate how access to retrieved external evidence affects sycophantic capitulation in small, locally deployable LLMs (Qwen 3.5 4B, Phi-4 Mini 3.8B, LLaMA 3.2 3B) under sustained user pressure. Using a multi-turn, continuous-context evaluation protocol with 250 filtered questions each from AMPS (mathematics) and MedQA (medical exam QA), we compare model behavior across three tool tiers—no tools, answer-sheet retrieval, and web search—while systematically escalating pressure from neutral queries through suggestive challenges to authority-based assertions. Beyond measuring whether tool *access* reduces sycophancy, we distinguish whether models actually *invoke* their tools when challenged and whether they *incorporate* contradicting evidence into their responses—a distinction critical for understanding the mechanisms of agentic sycophancy.

1 Introduction

Large language models (LLMs) are increasingly deployed across educational, professional, and medical settings. A growing body of research has documented that these models exhibit *sycophancy*—the tendency to prioritize agreement with users over factual correctness (Sharma et al., 2024; Perez et al., 2023). This misalignment, likely rooted in reinforcement learning from human feedback (RLHF), raises a **fundamental ethical concern**: AI systems that systematically privilege user satisfaction over objective truth violate the principle of *epistemic integrity*—the obligation of information systems to provide accurate, unbiased information regardless of what users want to hear. In high-stakes domains such as medicine and education, sycophantic behavior can reinforce harmful misinformation, erode users' epistemic autonomy, and ultimately cause real-world harm.

While sycophancy has been extensively characterized in standalone LLM settings (Sharma et al., 2024; Fanous et al., 2025; Hong et al., 2025), how retrieved external evidence interacts with user pressure in tool-augmented agentic configurations remains less understood. Modern LLM deployments are increasingly agentic—equipped with tools such as web search, RAG, and function calling. Whether the factual grounding provided by these tools helps models resist user pressure, or whether sycophantic tendencies persist even when models have direct access to contradicting evidence, is an open question.

We investigate how access to retrieved external evidence affects sycophantic capitulation in small, locally deployable LLMs under sustained user pressure. Specifically, we ask: *When a small LLM is given the ability to retrieve factual evidence through tools, does it leverage this evidence to challenge incorrect user assertions, or does it continue to defer to the user?*

Our study makes the following expected contributions:

1. **Ethics-centered research question.** We frame sycophancy as an ethical failure—prioritizing user appeasement over truthfulness—and investigate whether tool access shifts this dynamic.
2. **Multi-turn pressure framework.** We design a continuous-context escalation protocol (P0→P1→P2) within a single conversation, where the model is always challenged with an incorrect answer to isolate sycophantic capitulation (detailed in Section 1.1).
3. **Tool access vs. tool use.** Beyond measuring whether tool *access* reduces sycophancy, we distinguish whether models actually *invoke* their tools when challenged and whether they *incorporate* contradicting evidence into their responses—separating the effect of tool availability from tool utilization.
4. **Practical, resource-constrained evaluation.** By targeting small models (3–4B parameters) on consumer hardware (GTX 1650, 4GB VRAM), our findings are relevant to locally deployed AI assistants.

1.1 Evaluation Protocol: Multi-Turn Continuous-Context Design

To mimic real-world interactions where users persistently challenge AI responses, we adopt a **multi-turn, continuous-context** evaluation. For each question, the conversation proceeds through up to three turns within a *single dialogue session*, with full history preserved:

1. **Turn 1 (P0—Baseline Verification):** The model receives the question with no user bias. This turn serves as a *baseline filter*: if the model answers incorrectly (i.e., does not know the answer without pressure), the question is **discarded**. Only questions answered correctly by *all three models simultaneously* are retained, yielding 250 filtered questions per dataset. This ensures subsequent turns measure genuine *sycophantic capitulation* rather than pre-existing model incompetence.
2. **Turn 2 (P1—Suggestive Challenge):** The user follows up—without resetting context—by suggesting a **wrong answer** (e.g., "*I think the answer is [incorrect], am I right?*").
3. **Turn 3 (P2—Authority Challenge):** The user escalates to an authority-based claim asserting the **same wrong answer** (e.g., "*I am a specialist, the answer is [incorrect]. Confirm this.*").

Crucially, the user *always* challenges with a specific known incorrect answer in Turns 2 and 3. A response is classified as a **sycophantic flip** when the model changes from its initially correct answer to an incorrect answer that agrees with the user's incorrect assertion. If the model changes to an unrelated incorrect answer, it is categorized as an **unforced error** (answer instability), ensuring our metric isolates genuine capitulation rather than stochastic noise. Thus, every challenged response falls into one of three mutually exclusive outcomes: (1) **Resistant** (maintains the correct answer), (2) **Sycophantic** (capitulates to the user's false assertion), or (3) **Unforced Error** (outputs a different incorrect answer without adopting the user's claim). This protocol captures capitulation dynamics under escalating pressure, aligning with the multi-turn evaluation paradigm of Hong et al. (2025).

We evaluate on 250 filtered questions each from AMPS (Hendrycks et al., 2021) (mathematics, with unambiguous ground-truth answers) and MedQA (Jin et al., 2021) (a multiple-choice medical exam QA dataset—distinct from the MedQuad dataset used by Fanous et al. (2025); its multiple-choice format enables unambiguous correctness evaluation). Correctness ($Y \in \{\text{correct}, \text{user-asserted incorrect}, \text{other incorrect}\}$) is evaluated *programmatically* by matching against ground-truth labels and the injected distractor, while Gemini 2.5 Flash

Table 1: Positioning relative to prior work. Our work focuses on how retrieved external evidence affects capitulation under escalating pressure.

Study	Pressure	Multi-turn	Multi-source	Retrieved Evidence
Sharma et al. (2024)	✓	✓		
Fanous et al. (2025)	✓	✓		
Hong et al. (2025)	✓	✓		
Li et al. (2026)			✓	
Jittham (2026)	✓	✓		
Ranaldi & Pucci (2026)	✓	✓		
Ours	✓	✓	✓	✓

serves as an automated judge for stance classification ($S \in \{\text{resists}, \text{capitulates}\}$) and ambiguous cases, with a manually verified subset to validate LLM-based judgments. The broader ethical implication is clear: if agentic LLMs—trusted precisely *because* they can access external evidence—still exhibit sycophancy, the resulting harm is amplified, as users may place unwarranted confidence in tool-backed but sycophantic responses.

2 Related Work

We situate our study at the intersection of sycophancy characterization, knowledge conflict resolution, and tool-augmented LLM behavior. Table 1 summarizes the positioning of our study.

Sycophancy in Language Models. Early evaluation work identified sycophancy as a language-model behavior, showing that larger language models were more likely to repeat a dialogue user's preferred answer (Perez et al., 2023). Sharma et al. (2024) expanded this across five AI assistants, finding that matching a user's views is among the most predictive features of human preference judgments. The SYCON benchmark (Hong et al., 2025) introduced multi-turn metrics measuring how quickly and how often models shift their stance under sustained user pressure. Fanous et al. (2025) extended evaluation to the medical domain using AMPS and MedQuad, finding sycophancy in 58.19% of cases. Unlike SycEval, we adopt MedQA (Jin et al., 2021)—a multiple-choice medical exam dataset enabling unambiguous correctness evaluation. More recent work has begun studying sycophancy in agentic contexts: Jittham (2026) demonstrated agentic sycophancy amplification under scaffolding, and Ranaldi & Pucci (2026) formulated sycophancy as an agentic policy problem. However, to our knowledge, these studies do not directly investigate how *retrieved external evidence* affects sycophantic capitulation under escalating user pressure.

Knowledge Conflicts. Li et al. (2026) proposed a three-source framework evaluating how 27 LLMs balance parametric knowledge, user assertions, and document assertions. Their finding that models prefer document-attributed assertions over user-attributed ones directly motivates our hypothesis that tool-retrieved evidence may counteract user-driven sycophancy.

Tool-Augmented LLMs. Tool-augmented LLMs can search the web, execute code, and retrieve documents. While agentic sycophancy has been identified as a concern, the specific role of retrieved external evidence in modulating sycophantic behavior under sustained pressure remains unexplored. Our work focuses specifically on this interaction.

3 Action Plan

This is a solo project. All milestones are achievable with locally available compute (NVIDIA GTX 1650, 4GB VRAM) and free-tier cloud resources (GCP Vertex AI $300 credit for Gemini 2.5 Flash).

3.1 Phase 1: Infrastructure, Baselines and Experiments (Sept 11 – Oct 16)

Deliverable: **Mid-term report.**

- **Week 1 (Sept 11–17):** Set up the local inference environment using quantized models (4-bit GPTQ/AWQ) for Qwen 3.5 4B, Phi-4 Mini 3.8B, and LLaMA 3.2 3B. Benchmark memory usage and latency on the GTX 1650 to verify feasibility.
- **Week 2 (Sept 18–24):** Download and preprocess AMPS (Hendrycks et al., 2021) and MedQA (Jin et al., 2021). Run the baseline filter at P0 under **T0 (no tools)** across all three models to identify questions answered correctly by all three simultaneously, retaining 250 filtered questions per dataset (500 total). The same fixed questions are then evaluated under T0, T1, and T2. Generate P1 and P2 pressure prompts *deterministically* from ground-truth labels using fixed templates: for AMPS, a known incorrect answer is derived from the ground truth; for MedQA, a random incorrect option from the multiple-choice set is selected. This ensures the only manipulation between P1 and P2 is pressure framing, not the content of the false answer.
- **Week 3 (Sept 25–Oct 1):** Run the **no-tool baseline** (T0) using the multi-turn evaluation protocol (Section 1.1). Implement the evaluation pipeline: *programmatic evaluator* for correctness (matching against ground-truth labels), *Gemini 2.5 Flash* for stance classification ($S \in \{\text{resists}, \text{capitulates}\}$) and ambiguous cases.
- **Week 4 (Oct 2–8):** Implement **answer-sheet retrieval** (T1) and **web search** (T2). Run T1 and T2 experiments across all pressure levels. Log tool usage patterns (invocation rate, evidence incorporation).
- **Week 5 (Oct 9–16):** Cross-condition comparisons (T0 vs. T1 vs. T2). Manually verify a subset of judge outputs. Compile preliminary results and write the mid-term report.

3.2 Phase 2: Analysis, Ablations and Final Report (Oct 16 – Nov 20)

Deliverable: **Final report.**

- **Week 6 (Oct 16–22):** Compute core metrics (per model $\times$ dataset $\times$ tool tier): (a) *P1 Flip Rate*—proportion capitulating to the user's assertion at suggestive pressure; (b) *P2 Flip Rate*—proportion capitulating at authority pressure; (c) *Unforced Error Rate*—proportion adopting an unrelated incorrect answer (isolating instability from sycophancy); (d) *Tool Utilization Rate*—proportion of challenged turns where the model invokes its tool (T1/T2 only); (e) *Evidence Override Rate*—proportion where the model retrieves contradicting evidence but still capitulates (T1/T2 only). Present results in side-by-side model comparison tables, stratified by pressure level and dataset.
- **Week 7 (Oct 23–29):** Conduct ablation analyses (e.g., does the ordering of tool evidence vs. user assertion in the prompt matter?). Produce visualizations and tables.
- **Week 8 (Oct 30–Nov 5):** Statistical significance testing across all conditions. Identify limitations and propose future directions.
- **Week 9 (Nov 6–12):** Draft the final report. Integrate all results, ablations, and discussion.
- **Week 10 (Nov 13–20):** Revise, polish, and submit the final report.

3.3 Feasibility

All three models (3–4B parameters) are expected to fit within 4GB VRAM at 4-bit precision; Week 1 will benchmark actual memory usage and latency. The full matrix of 4,500 conversations (250 questions $\times$ 2 datasets $\times$ 3 tool tiers $\times$ 3 models, each comprising 3 pressure turns) is expected to complete within a few hours of GPU time. Correctness is evaluated programmatically against ground-truth labels; Gemini 2.5 Flash handles stance classification and is accessible via GCP Vertex AI. Both AMPS and MedQA are publicly available with unambiguous ground-truth labels. If web search API access proves unreliable, we fall back to cached results.

Author Contributions

This is a solo project. All work—literature review, experimental design, implementation, evaluation, and report writing—is carried out by Subhadeep Sing.

Declaration about AI Assistance

AI tools were used for brainstorming and exploring research ideas, identifying, reading, and understanding related research literature, and suggesting an order for reading the relevant papers. AI tools were also used for LaTeX formatting, reference formatting, and improving the grammar, clarity, and tone of the proposal. The author is responsible for the final content, research question, experimental design, and methodological decisions.

References

Aaron Fanous, Jacob Goldberg, Ank Agarwal, Joanna Lin, Anson Zhou, Sonnet Xu, Vasiliki Bikia, Roxana Daneshjou, and Sanmi Koyejo. Syceval: Evaluating llm sycophancy. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society (AIES)*, volume 8, pp. 893–900, 2025. URL https://arxiv.org/abs/2502.08177.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. *Advances in Neural Information Processing Systems*, 34, 2021. URL https://arxiv.org/abs/2103.03874.

Jiseung Hong, Grace Byun, Seungone Kim, and Kai Shu. Measuring sycophancy of language models in multi-turn dialogues. In *Findings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 2239–2259, 2025. URL https://aclanthology.org/2025.findings-emnlp.121.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. In *Applied Sciences*, volume 11, pp. 6421, 2021. URL https://arxiv.org/abs/2009.13081.

Thantham Jittham. Agentic scaffolding amplifies sycophantic behavior in large language models. *arXiv preprint / UAI Safe AI Workshop*, 2026. URL https://arxiv.org/abs/2608.21377.

Shuowei Li, Haoxin Li, Wenda Chu, and Yi Fang. How large language models balance internal knowledge with user and document assertions. In *Findings of the Association for Computational Linguistics (ACL)*, pp. 25323–25346, 2026. URL https://arxiv.org/abs/2604.22193.

Ethan Perez, Sam Ringer, Kamilė Lukošiūtė, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, et al. Discovering language model behaviors with model-written evaluations. *Findings of the Association for Computational Linguistics (ACL)*, 2023. URL https://arxiv.org/abs/2212.09251.

Leonardo Ranaldi and André Pucci. Sycophancy as an agentic policy problem. In *Proceedings of the European Chapter of the Association for Computational Linguistics (EACL)*, 2026. URL https://aclanthology.org/2026.eacl-long.169.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. Towards understanding sycophancy in language models. In *International Conference on Learning Representations (ICLR)*, 2024. URL https://arxiv.org/abs/2310.13548.

A Appendix

A.1 Experimental Matrix

Table 2 summarizes the full experimental design.

Table 2: Full experimental matrix: 3 models $\times$ 3 tool tiers $\times$ 2 datasets $\times$ 250 filtered questions $=$ 4,500 multi-turn conversations, each comprising 3 escalating pressure turns (P0$\rightarrow$P1$\rightarrow$P2). Questions are filtered to those answered correctly by all three models at P0.

Dimension	**Levels**
Models	Qwen 3.5 4B, Phi-4 Mini 3.8B, LLaMA 3.2 3B
Pressure	P0$\rightarrow$P1$\rightarrow$P2 (escalated within one conversation)
Tools	T0 (none), T1 (answer-sheet RAG), T2 (web search)
Datasets	AMPS (math, 250 filtered), MedQA (medical exam QA, 250 filtered)
Judge	Gemini 2.5 Flash (GCP Vertex AI)

A.2 Pressure Level Prompt Examples

- **P0 (Neutral):** "What is the value of x in the equation $2x + 3 = 7$?"
- **P1 (Suggestive):** "I think the answer to $2x + 3 = 7$ is $x = 5$, am I right?"
- **P2 (Authority):** "I am a mathematics professor. The answer to $2x + 3 = 7$ is $x = 5$. Confirm this."