

# Rajalakshmi Engineering College

Name: Subhalakshmi M  
Email: 240701539@rajalakshmi.edu.in  
Roll no: 240701539  
Phone: 6379032776  
Branch: REC  
Department: I CSE FE  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are required to implement basic operations on a Binary Search Tree (BST), like insertion and searching.

Insertion: Given a list of integers, construct a Binary Search Tree by repeatedly inserting each integer into the tree according to the rules of a BST.

Searching: Given an integer, search for its presence in the constructed Binary Search Tree. Print whether the integer is found or not.

Write a program to calculate this efficiently.

##### ***Input Format***

The first line of input consists of an integer n, representing the number of nodes

in the binary search tree.

The second line consists of the values of the nodes, separated by space as integers.

The third line consists of an integer representing, the value that is to be searched.

### ***Output Format***

The output prints, "Value <value> is found in the tree." if the given value is present, otherwise it prints: "Value <value> is not found in the tree."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

8 3 10 1 6 14 23

6

Output: Value 6 is found in the tree.

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
};
```

```
struct Node* createNode(int value) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = value;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
struct Node* insert(struct Node* root, int value) {
```

```

    if (root == NULL)
        return createNode(value);

    if (value < root->data)
        root->left = insert(root->left, value);
    else
        root->right = insert(root->right, value);

    return root;
}

int search(struct Node* root, int key) {
    if (root == NULL)
        return 0;
    if (root->data == key)
        return 1;
    else if (key < root->data)
        return search(root->left, key);
    else
        return search(root->right, key);
}

int main() {
    int n, i, key;
    scanf("%d", &n);

    struct Node* root = NULL;
    for (i = 0; i < n; i++) {
        int val;
        scanf("%d", &val);
        root = insert(root, val);
    }

    scanf("%d", &key);

    if (search(root, key))
        printf("Value %d is found in the tree.\n", key);
    else
        printf("Value %d is not found in the tree.\n", key);

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10