Makers of finest quality paints since 1987





Rustblock Hammertone

SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Rustblock Hammertone

Manufacturing Product Code: Various (depending on colour)
Recommended Uses: Industrial Paint (Spraying)

Supplier: Omega International Coatings P/L

Street Address 111, Kurrajong Ave, Mount Druitt, NSW, 2770

Telephone Number: (02) 9832 0000 Fax: (02) 9832 8888

Emergency phone: **Poison Information Center**: 13 11 26

SECTION 2- HAZARDS IDENTIFICATION

Health Hazard Classification

This product is classified as hazardous under SafeWork Australia criteria.

Hazard Category

F: Flammable: Xn: Harmful: Xi: Irritant

Risk Phrases

R20/21/22: Harmful by inhalation, in contact with skin or swallowed

R36/37/38: Irritating to eyes, respiratory system and skin

R41: Risk of serious damage to eyes

R51/52: Toxic and harmful to aquatic organisms.

R53: May cause long-term adverse effects in the aquatic environment

R65: Harmful: May cause lung damage if swallowed

R66: Repeated exposure may cause skin dryness or cracking

R67: Vapors may cause drowsiness and dizziness

Safety Phrases

S16: Keep away from sources of ignition

S57: Use appropriate container to avoid environmental contamination

S60: This material and its container must be disposed of as hazardous waste.

Date of revision: 15th Mar 2014 Page 1 of 6

SECTION 3- COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Entity	CAS No.	Proportion (%w/w)
Xylene	133020-7	10-30%
Toluene	108-88-3	10-30%
Aromatic Hydrocarbon Mixture	64742-95-6	<10%
Aluminum Flake	7429-90-5	<10%
Lighting Kerosene	8008-20-6	<10%
Ingredients determined to be non-hazardous or below the hazardous threshold	TC) 100%

SECTION 4- FIRST AID MEASURES

Ingestion

If swallowed, do not induce vomiting. Give 250 ml water to rinse out mouth and drink. Seek immediate medical attention.

Eye contact

Immediately flush eyes with large amount of water for at least 15 minutes. Seek immediate medical attention.

Skin contact

Flush thoroughly with soap and water. Immediately remove contaminated clothing including footwear. Seek medical attention in event of persisting skin irritations.

Inhalation

Remove victim from exposure to fresh air. Keep at rest. If breathing is difficult, administer artificial respiration. Seek immediate medical attention

First aid facilities

Provide eye baths and safety showers.

Medical attention

Treat symptomatically.

SECTION 5- FIRE FIGHTING MEASURES

Suitable extinguishing equipment

Foam, Dry Powder, CO2, Water Fog. Do not use water except as fog to cool nearby containers.

Hazards arising from combustion of product

Oxides of Carbon.

Special protective equipment and precautions for fire fighters

Wear breathing apparatus when fighting fire.

Date of revision: 15th Mar 2014 Page 2 of 6

Hazchem Code: 3[Y]E

SECTION 6- ACCIDENTAL RELEASE MEASURES

Minor spill

Extinguish naked flames. And avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

Major spill

Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor, in accordance with local regulations.

SECTION 7- HANDLING AND STORAGE

Precaution for safe handling

This product is flammable. Avoid sources of heat, naked flames and sparks. Use in well-ventilated area. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity.

Conditions for safe storage

Store in a cool, well-ventilated area and place away from heat, naked flames and sparks. Store away from oxidizing agents, alkaline materials and strong acids. Keep container closed at all times. Keep away from food, and drink and clothing.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Entity	Cas No	Weight%	TWA ¹ (ppm)	STEL ² (ppm)
Xylene	1330-20-7	10-30%	50	150
Toluene	108-88-3	10-30%	50	100
Aromatic	64742-95-6	<10%	19	
Hydrocarbon				
Mixture				
Aluminum Flake	7429-90-5	<10%	10	15
Lighting Kerosene	8008-20-6	<10%	Not Specified	

¹ Time weighted average concentration

Engineering controls

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TWA. Ventilation equipment should be explosion proof.

Personal protective equipment

Wear chemical safety glasses/goggles or face shield. Wear half face respirator, with organic vapor cartridge. Wear PVC or Nitrile chemical handling gloves.

Date of revision: 15th Mar 2014 Page 3 of 6

² Short-term exposure limit

SECTION9- PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Coloured Liquid
Odour	-	Solvent Odour
Boiling Point	°C	118
Flash Point	°C	20
Density @ 25°C	g/ml	0.96
Flammability Limits	%(v/v)	1-8
Volatile content	%(w/w)	42.1
Solubility in water		Low

SECTION 10- STABILITY AND REACTIVITY

Chemical stability

Stable at room temperature and pressure.

Conditions to avoid

Source of heat and ignition, open flames.

Incompatible materials

Not specified.

Hazardous decomposition products

Carbon oxides and other organic complexes on incomplete burning or oxidation.

Hazardous reactions

Oxidizing agents, mineral acids, halogenated organic compounds and peroxides.

SECTION 11- TOXICOLOGICAL INFORMATION

Acute effects

Ingestion

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

Eye Contact

Irritating, causing redness and burning sensation.

Skin Contact

Irritating, causing redness and burning sensation.

Inhalation

Harmful by inhalation. The vapour is irritating to the upper respiratory tract. May cause nausea, dizziness and narcosis. Extreme exposure may result in unconsciousness, and possibly death.

Date of revision: 15th Mar 2014 Page 4 of 6

Chronic effects

Prolonged and repeated contact with the skin may irritate, and cause dermatitis. Prolonged overexposure to the solvents (inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems.

Toxicology information

Chemical Entity	Weight %	Oral LD ₅₀ (Rat) mg/kg	Dermal LD ₅₀ (Rat or rabbit) mg/kg	LC ₅₀ Inhalation (Rat) mgL ⁻¹ /4 hr
Xylene	10-30%	>2000	>2000	>5
Toluene	10-30%	>7000	>2000	>5
Aromatic	<10%	>2000	>2000	
Hydrocarbon Mixture				
Aluminum Flake	<10%	N/A		
Lighting Kerosene	<10%	>2000	>2000	>5

SECTION 12- ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SECTION 13- DISPOSAL CONSIDERATIONS

Do not let this product enter the environment. Dispose of this material and its container as hazardous waste. Do not pour unwanted paint or paint-related material down the drain. Keep unwanted material in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well-ventilated area to dry out. When dry recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities check with your local council first.

SECTION 14- TRANSPORT INFORMATION

For local transportation within New Zealand refer NZS 5433:1999: For Australia refers ADG code.

UN No.	1263
Proper Shipping Name	Paint
DG Class	3
Subsidiary Risk	Not Applicable
Packing Group	П
Hazchem Code	3[Y] E

SECTION 15-REGULATORY INFORMATION

HMIS Code: 230H

Date of revision: 15th Mar 2014 Page 5 of 6

SECTION 16- OTHER INFORMATION

Contact Apco Coatings **Person/Point** Technical Manager

Ph 02 98 32 0000 Mob 0422237710

Other Information Principal toxic properties of this product are due to the solvent composition and

vapour inhalation hazards.

Abbreviations: N/A - Not Applicable N/AV - Not Available

Abbreviations:

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number

Date of revision: 15th Mar 2014 Page 6 of 6