Makers of finest quality paints since 1987





# **Rustblock Heavy Duty Metal Primer**

## SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Rustblock Heavy Duty Metal Primer

Manufacturing Product Code: Various, depending on (White, Grey & Black)

Recommended Uses: For priming metal surface

Supplier: Omega International Coatings P/L

Street Address 111, Kurrajong Ave, Mount Druitt, NSW, 2770

Telephone Number: (02) 9832 0000 Fax: (02) 9832 8888

Emergency phone: **Poison Information Center**: 13 11 26

## **SECTION 2- HAZARDS IDENTIFICATION**

#### **Health Hazard Classification**

This product is classified as hazardous under Safe Work Australia criteria.

## **Hazard Category**

F: Flammable; Xn: Harmful; Xi: Irritant

#### **Risk Phrases**

R11: Highly flammable.

R66: Repeated exposure may cause skin dryness and cracking.

R20/22: Harmful by inhalation and if swallowed.

R36/38: Irritating to eyes and skin.

#### **Safety Phrases**

S7/9: Keep container tightly closed and in a well-ventilated place.

S16: Keep away from sources of ignition.

S23: Do not breathe vapours or mist.

S29: Do not empty into drains

S33: Take precautionary measures against static discharges.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible.)

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

Date of revision: 15<sup>th</sup> Mar 2014 Page 1 of 6

## **SECTION 3- COMPOSITION/ INFORMATION ON INGREDIENTS**

<b>Chemical Entity</b>	CAS No.	Proportion (%w/w)
Toluene	108-88-3	10-30%
Ethanol	64-17-5	10-30%
Butanol	71-36-3	<10%
Paint additives	N/A	<10%
Phosphoric acid 85%	7664-38-2	<1%

Ingredients determined to be non-hazardous	TO 100%	
Or below the hazardous threshold		

#### **SECTION4- FIRST AID MEASURES**

#### **Ingestion**

Thoroughly rinse mouth with clean water. If swallowed give a glass of water. Do NOT induce vomiting.

## Eye contact

Check for and remove any contact lenses. Irrigate copiously with clean fresh water for 15 minutes, holding the eyelids apart. Seek medical attention if irritation persists.

#### **Skin contact**

Wash affected areas with soap and water or an industrial skin cleanser. Remove contaminated clothing and flush skin and hair with running water. Seek medical attention if irritation persists.

#### Inhalation

No problems anticipated at normal temperatures. Remove to fresh air if any effects apparent. Seek medical attention if any effects persist.

#### First aid facilities

Water should be available to rinse eyes or skin. Provide eye baths and safety showers.

# **Medical attention**

Treat symptomatically.

## **SECTION 5- FIRE FIGHTING MEASURES**

#### Suitable extinguishing equipment

Use water fog (or if unavailable fine water spray), dry chemical, carbon dioxide or alcohol stable foam. Use water to cool exposed containers.

#### Hazards arising from combustion of product

Emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

#### Special protective equipment and precautions for fire fighters

Highly flammable liquid. Fire fighters should wear self-contained breathing apparatus (SCBA) and complete protective clothing.

Date of revision: 15<sup>th</sup> Mar 2014 Page 2 of 5

Hazchem Code: 3[Y]E

## **SECTION 6- ACCIDENTAL RELEASE MEASURES**

## Minor spill

Extinguish naked flames and avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

#### Major spill

Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor, in accordance with local regulations.

# **SECTION 7- HANDLING AND STORAGE**

## **Precaution for safe handling**

This product is highly flammable. Avoid sources of heat, naked flames and sparks. Use in well-ventilated area. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity.

#### **Conditions for safe storage**

Store in a cool, well-ventilated area and place away from heat, naked flames and sparks. Store away from oxidizing agents, alkaline materials and strong acids. Keep container closed at all times. Keep away from food, and drink and clothing.

#### SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Chemical Entity</b>	Cas No	Weight%	TWA <sup>1</sup> (ppm)	STEL <sup>2</sup> (ppm)
Ethanol	64-17-5	10-30%	1000	N/A
Toluene	108-88-3	10-30%	200	500
Butanol	71-36-3	<10%	100	N/A
Paint additives	N/A	<10 %	N/A	N/A

<sup>&</sup>lt;sup>1</sup> Time weighted average concentration

## **Engineering controls**

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TWA. Ventilation equipment should be explosion proof.

#### **Respiratory protection**

With good ventilation - none required. In confined spaces and/or limited ventilation or in areas where the exposure standards may be exceeded, wear a cartridge respirator fitted with a cartridge suitable for organic vapours and particulates.

Date of revision: 15<sup>th</sup> Mar 2014 Page 3 of 5

<sup>&</sup>lt;sup>2</sup> Short-term exposure limit

# **Eye protection**

Eye protection to prevent splashing in the eyes, e.g. safety glasses with side shields or chemical goggles.

## Personal protective equipment

Wear overalls to keep skin contact to a minimum. Wear PVC or rubber gloves.

## Hygiene measure

Wash hands thoroughly before eating or smoking.

## **SECTION9- PHYSICAL AND CHEMICAL PROPERTIES**

Property	Unit of measurement	Typical value	
Appearance	-	Coloured Liquid	
Odour	-	Characteristic Solvent	
		odour	
Vapor Pressue @ 25°C	kPa	1.6	
<b>Boiling Point</b>	°C	94	
Flash Point	°C	16	
Density @ 25°C	g/ml	0.93-0.99 (depends on	
		colour)	
Flammability Limits	%(v/v)	7.1	
Volatile content	%(w/w)	> 80	

#### **SECTION 10- STABILITY AND REACTIVITY**

#### **Chemical Stability**

Stable under normal handling conditions.

#### **Hazardous Reactions**

Source of heat and ignition, open flames.

# **SECTION 11- TOXICOLOGICAL INFORMATION**

#### **Acute effects**

#### Ingestion

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

#### Eye Contact

Irritating, causing redness and burning sensation.

#### Skin Contact

Irritating, causing redness and burning sensation.

#### Inhalation

Harmful by inhalation. The vapour is irritating to the upper respiratory tract. May cause nausea, dizziness and narcosis. Extreme exposure may result in unconsciousness, and possibly death.

Date of revision: 15<sup>th</sup> Mar 2014 Page 4 of 5

#### **Chronic effects**

Prolonged and repeated contact with the skin may irritate, and cause dermatitis. Prolonged overexposure to the solvents (inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems.

## **Toxicology information**

No LD data available for this product.

#### **SECTION 12- ECOLOGICAL INFORMATION**

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

#### **SECTION 13- DISPOSAL CONSIDERATIONS**

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Advise flammable nature. Product is normally suitable for incineration by an approved agent.

## **SECTION 14- TRANSPORT INFORMATION**

For local transportation within New Zealand refer NZS 5433:1999: For Australia refers ADG code.

UN No.	1263
Proper Shipping Name	Paint
DG Class	3
Subsidiary Risk	Not Applicable
Packing Group	II
Hazchem Code	3[Y] E

## **SECTION 15-REGULATORY INFORMATION**

Poisons Schedule Not Scheduled

AICS (Australia) All components are listed on AICS.

## **SECTION 16- OTHER INFORMATION**

**Contact** Apco Coatings **Person/Point** Technical Manager

Ph 02 98 32 0000 Mob 0422237710

Other Information Principal toxic properties of this product are due to the solvent composition and

vapour inhalation hazards.

Abbreviations: N/A - Not Applicable N/AV - Not Available

**Abbreviations:** 

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number

Date of revision: 15<sup>th</sup> Mar 2014 Page 5 of 5