

Multi Purpose Thinner

SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER

| | |
|-----------------------------|---|
| Product Name: | Multi Purpose Thinner |
| Manufacturing Product Code: | Z67705 |
| Recommended Uses: | Industrial Solvent |
| Supplier: | Omega International Coatings P/L |
| Street Address | 111, Kurrajong Ave, Mount Druitt, NSW, 2770 |
| Telephone Number: | (02) 9832 0000 |
| Fax: | (02) 9677 0566 |
| Emergency phone: | Poison Information Center: 13 11 26 |

SECTION 2- HAZARDS IDENTIFICATION

Health Hazard Classification

This product is classified as hazardous under SafeWork Australia criteria.

Hazard Category

F: Flammable; Xn: Harmful; Xi: Irritant

Risk Phrases

R11: Highly flammable.

R36/38: Irritating to eyes and skin.

R48/20: Danger of serious damage to health by prolonged exposure through inhalation.

R63: Possible risk of harm to the unborn child.

R65: May cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety Phrases

S2: Keep out of reach of children.

S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37: Wear suitable protective clothing and gloves.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

SECTION 3- COMPOSITION/ INFORMATION ON INGREDIENTS

| Chemical Entity | CAS No. | Proportion (%w/w) |
|---|----------|-------------------|
| Toluene | 108-88-3 | 30-60% |
| Butyl Acetate | 123-86-4 | 10-30% |
| Acetone | 67-64-1 | 10-30% |
| Ingredients determined to be non-hazardous or below the hazardous threshold | | TO 100% |

Ingestion

If swallowed, do not induce vomiting. Give 250 ml water to rinse out mouth and drink. Seek immediate medical attention.

Eye contact

Immediately flush eyes with large amount of water for at least 15 minutes. Seek immediate medical attention.

Skin contact

Flush thoroughly with soap and water. Immediately remove contaminated clothing including footwear. Seek medical attention in event of persisting skin irritations.

Inhalation

Remove victim from exposure to fresh air. Keep at rest. If breathing is difficult, administer artificial respiration. Seek immediate medical attention

First aid facilities

Provide eye baths and safety showers.

Medical attention

Treat symptomatically.

SECTION 5- FIRE FIGHTING MEASURES**Suitable extinguishing equipment**

Foam, Dry Powder, CO₂, Water Fog. Do not use water except as fog to cool nearby containers.

Hazards arising from combustion of product

Oxides of Carbon.

Special protective equipment and precautions for fire fighters

Wear breathing apparatus when fighting fire.

Hazchem Code: 3[Y]E

SECTION 6- ACCIDENTAL RELEASE MEASURES**Minor spill**

Extinguish naked flames. And avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

Major spill

Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor, in accordance with local regulations.

SECTION 7- HANDLING AND STORAGE**Precaution for safe handling**

This product is flammable. Avoid sources of heat, naked flames and sparks. Use in well ventilated area. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity.

Conditions for safe storage

Store in a cool, well-ventilated area and place away from heat, naked flames and sparks. Store away from oxidizing agents, alkaline materials and strong acids. Keep container closed at all times. Keep away from food, and drink and clothing.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

| Chemical Entity | Cas No | Weight% | TWA ¹ (ppm) | STEL ² (ppm) |
|-----------------|----------|---------|------------------------|-------------------------|
| Toluene | 108-88-3 | 30-60% | 50 | 150 |
| Butyl Acetate | 123-86-4 | 30-60% | 150 | 200 |
| Acetone | 67-64-1 | 10-30% | 500 | 1000 |

¹ Time weighted average concentration

² Short-term exposure limit

Engineering controls

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TWA. Ventilation equipment should be explosion proof.

Personal protective equipment

Wear chemical safety glasses/goggles or face shield. Wear half face respirator, with organic vapor cartridge. Wear PVC or Nitrile chemical handling gloves.

SECTION9- PHYSICAL AND CHEMICAL PROPERTIES

| Property | Unit of measurement | Typical value |
|---------------------|---------------------|--------------------------|
| Appearance | - | Clear Colourless, Liquid |
| Odour | - | Solvent Odour |
| Boiling Point | °C | 80-110 |
| Flash Point | °C | 7 |
| Density @ 25°C | g/ml | 0.87 |
| Flammability Limits | %(v/v) | 1-7 |
| Volatile content | %(w/w) | 100% |
| Solubility in water | - | Insoluble |

SECTION 10- STABILITY AND REACTIVITY**Chemical stability**

Stable at room temperature and pressure.

Conditions to avoid

Source of heat and ignition, open flames.

Incompatible materials

Not specified.

Hazardous decomposition products

Carbon oxides and other organic complexes on incomplete burning or oxidation.

Hazardous reactions

Oxidizing agents, mineral acids, halogenated organic compounds and peroxides.

SECTION 11- TOXICOLOGICAL INFORMATION**Acute effects*****Ingestion***

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

Eye Contact

Irritating, causing redness and burning sensation.

Skin Contact

Irritating, causing redness and burning sensation.

Inhalation

Harmful by inhalation. The vapour is irritating to the upper respiratory tract. May cause nausea, dizziness and narcosis. Extreme exposure may result in unconsciousness, and possibly death.

Chronic effects

Prolonged and repeated contact with the skin may irritate, and cause dermatitis. Prolonged overexposure to the solvents (inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems.

Toxicology information

| Chemical Entity | Weight % | Oral LD ₅₀ (Rat) mg/kg | Dermal LD ₅₀ (Rat or rabbit) mg/kg | LC ₅₀ Inhalation (Rat) mgL ⁻¹ /4 hr |
|----------------------|----------|---|---|---|
| Toluene | 30-60% | > 5580 | > 12500 | >12.5 |
| Butyl Acetate | 30-60% | >10700 | >17600 | >9.6 |
| Acetone | 10-30% | >3000 | >15700 | >76 |

SECTION 12- ECOLOGICAL INFORMATION

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SECTION 13- DISPOSAL CONSIDERATIONS

Do not let this product enter the environment. Dispose of this material and its container as hazardous waste. Do not pour unwanted paint or paint-related material down the drain. Keep unwanted material in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities check with your local council first.

SECTION 14- TRANSPORT INFORMATION

For local transportation within New Zealand refer NZS 5433:1999: For Australia refers ADG code.

| | |
|-----------------------------|----------------|
| UN No. | 1263 |
| Proper Shipping Name | Paint |
| DG Class | 3 |
| Subsidiary Risk | Not Applicable |
| Packing Group | II |
| Hazchem Code | 3[Y] E |

SECTION 15-REGULATORY INFORMATION

HMIS Code: 230H

SECTION 16- OTHER INFORMATION

Contact Apco Coatings
Person/Point Technical Manager
Ph 02 98 32 0000 Mob 0422237710

Other Information Principal toxic properties of this product are due to the solvent composition and vapour inhalation hazards.
Abbreviations: N/A - Not Applicable N/AV - Not Available

Abbreviations:

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number