

## OilPrep Wood Primer Int Ext

### SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	OilPrep Wood Primer Int Ext
Manufacturing Product Code:	Various, depending on color (clear and colored)
Recommended Uses:	For timber surfaces
Supplier:	Asian Paints (Queensland) Pty Ltd
Street Address	111, Kurrajong Ave, Mount Druitt, NSW, 2770
Telephone Number:	(02) 9832 0000
Fax:	(02) 9677 0566
Emergency phone:	<b>Poison Information Center:</b> 13 11 26

### SECTION 2- HAZARDS IDENTIFICATION

#### **Health Hazard Classification**

This product is classified as hazardous under SafeWork Australia criteria.

#### **Hazard Category**

F: Flammable; Xn: Harmful; Xi: Irritant

#### **Risk Phrases**

R11: Highly Flammable  
R20/21/22/48: Harmful by inhalation, in contact with skin or swallowed  
R36/37/38: Irritating to eyes, respiratory system and skin  
R51/52: Toxic and harmful to aquatic organisms.  
R53: May cause long-term adverse effects in the aquatic environment  
R63: Possible risk of harm to the unborn child.  
R65: Harmful: may cause lung damage if swallowed.  
R67: Vapors may cause drowsiness and dizziness.

#### **Safety Phrases**

S16: Keep away from sources of ignition  
S23: Do no breather vapor/mist/aerosol  
S24: Avoid contact with skin.  
S57: Use appropriate container to avoid environmental contamination.  
S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.  
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**SECTION 3- COMPOSITION/ INFORMATION ON INGREDIENTS**

<b>Chemical Entity</b>	<b>CAS No.</b>	<b>Proportion (%w/w)</b>
<b>White Spirit</b>	8052-41-3	10-30 %
<b>Solvent Naphtha (Petroleum), Light Aromatic</b>	64742-95-6	10-30 %
<b>Toluene</b>	108-88-3	<10%
<b>Cobalt Octoate</b>	13586-82-8	<1 %
<b>Zirconium Octoate</b>	22464-99-9	<1 %
Ingredients determined to be non-hazardous Or below the hazardous threshold		TO 100%

**SECTION4- FIRST AID MEASURES****Ingestion**

If swallowed, do not induce vomiting. Give 250 ml water to rinse out mouth and drink. Seek immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

**Eye contact**

Immediately flush eyes with large amount of water for at least 15 minutes. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling persist, transport to the nearest medical facility for additional treatment.

**Skin contact**

Flush thoroughly with soap and water. Immediately remove contaminated clothing including footwear. Seek medical attention in event of persisting skin irritations.

**Inhalation**

Remove victim from exposure to fresh air. Keep at rest. If breathing is difficult, administer artificial respiration. Seek immediate medical attention.

**First aid facilities**

Provide eye baths and safety showers.

**Medical attention**

Treat symptomatically.

**SECTION 5- FIRE FIGHTING MEASURES****Suitable extinguishing equipment**

Foam, Dry Powder, CO<sub>2</sub>, Water Fog. Do not use water except as fog to cool nearby containers. Do not use water in a jet.

**Hazards arising from combustion of product**

Oxides of Carbon.

**Special protective equipment and precautions for fire fighters**

Wear breathing apparatus when fighting fire.

**Hazchem Code:** 3[Y]E

**SECTION 6- ACCIDENTAL RELEASE MEASURES****Minor spill**

Extinguish naked flames. And avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

**Major spill**

Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor, in accordance with local regulations.

**SECTION 7- HANDLING AND STORAGE****Precaution for safe handling**

This product is flammable. Avoid sources of heat, naked flames and sparks. Avoid contact with skin, eyes, and clothing. Use in well-ventilated area. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity.

**Conditions for safe storage**

Store in a cool, well-ventilated area and place away from heat, sunlight, naked flames and sparks. Store away from oxidizing agents, alkaline materials and strong acids. Keep container closed at all times. Keep away from food, and drink and clothing.

**SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION**

Chemical Entity	Cas No	Weight%	TWA <sup>1</sup> (ppm)	STEL <sup>2</sup> (ppm)
White Spirit	8052-41-3	10-30 %	480	N/A
Solvent Naphtha (Petroleum), Light Aromatic	64742-95-6	10-30 %	50	150
Toluene	108-88-3	<10	100	150

<sup>1</sup> Time weighted average concentration

<sup>2</sup> Short-term exposure limit

**Engineering controls**

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TWA. Ventilation equipment should be explosion proof.

Date of revision: 15<sup>th</sup> March 2014

Page 3 of 5

**APCO COATINGS**

**Personal protective equipment**

Wear chemical safety glasses/goggles or face shield. Wear half face respirator, with organic vapor cartridge. Wear PVC or Nitrile chemical handling gloves.

**SECTION9- PHYSICAL AND CHEMICAL PROPERTIES**

Property	Unit of measurement	Typical value
Appearance	-	Clear/coloured Liquid
Odour	-	Solvent Odour
Vapor Pressue @ 25°C	kPa	1.50
Boiling Point	°C	142.9
Flash Point	°C	16.1
Density @ 25°C	g/ml	1.1-1.2 (depending on colour)
Flammability Limits	%(v/v)	3.1-7.0
Volatile content	%(w/w)	>50

**SECTION 10- STABILITY AND REACTIVITY****Chemical stability**

Stable at room temperature and pressure.

**Conditions to avoid**

Source of heat and ignition, open flames.

**Incompatible materials**

Not specified.

**Hazardous decomposition products**

Carbon oxides and other organic complexes on incomplete burning or oxidation.

**Hazardous reactions**

Oxidizing agents, mineral acids, halogenated organic compounds and peroxides.

**SECTION 11- TOXICOLOGICAL INFORMATION****Acute effects*****Ingestion***

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

***Eye Contact***

Irritating, causing redness and burning sensation.

***Skin Contact***

Irritating, causing redness and burning sensation.

***Inhalation***

Date of revision: 15<sup>th</sup> March 2014

Page 4 of 5

Harmful by inhalation. The vapor is irritating to the upper respiratory tract. May cause nausea, dizziness and narcosis. Extreme exposure may result in unconsciousness, and possibly death.

**Chronic effects**

Prolonged and repeated contact with the skin may irritate, and cause dermatitis. Prolonged overexposure to the solvents (inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems.

**Toxicology information**

No LD data available for this product.

**SECTION 12- ECOLOGICAL INFORMATION**

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

**SECTION 13- DISPOSAL CONSIDERATIONS**

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Advise flammable nature. Product is normally suitable for incineration by an approved agent.

**SECTION 14- TRANSPORT INFORMATION**

For local transportation within New Zealand refer NZS 5433:1999: For Australia refers ADG code.

UN No.	1263
Proper Shipping Name	Paint
DG Class	3
Subsidiary Risk	Not Applicable
Packing Group	II
Hazchem Code	3[Y] E

**SECTION 15-REGULATORY INFORMATION**

**HMIS Code:** 230H

**SECTION 16- OTHER INFORMATION**

**Contact** Apco Coatings  
**Person/Point** Technical Manager  
Ph 02 98 32 0000 Mob 0422237710

**Other Information** Principal toxic properties of this product are due to the solvent composition and vapour inhalation hazards.  
Abbreviations: N/A - Not Applicable N/AV - Not Available

Date of revision: 15<sup>th</sup> March 2014

Page 5 of 5

**APCO COATINGS**

**Abbreviations:**

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number