

Php artisan serve http copy kore paste in google.

Xampp-htdocs-project-upore gie cmd open.

Php artisan make:model model__name

Php artisan make:controller controller__name

Php artisan make:controller controller__name

Php artisan make:migration table__name

Crud

Create

Read view

Update edit

Delete

Crud.blade.php

```
<!doctype html>
```

```
<html lang="en">
```

```
<head>
```

```
<!-- Required meta tags -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport"
```

```
content="width=device-width, initial-scale=1,
```

```
shrink-to-fit=no">
```

```
<!-- Bootstrap CSS -->
<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.4.
1/dist/css/bootstrap.min.css" integrity="sha384-
Vkoo8x4CGsO3+Hhvx8T/Q5PaXtkKtu6ug5TOeNV6
gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
```

```
<title>Forms</title>
</head>
<body>
  <h1>Registration Form</h1>
  <form action="submit" method="POST">
    @csrf                                <!--Token used
for validating the form-->
    <div class="form-group row">
      <label for="inputEmail3" class="col-sm-2 col-
form-label">Name</label>
      <div class="col-sm-10">
        <input type="text" name="Name" class="form-
control" id="inputEmail3">
      </div>
    </div>
    <div class="form-group row">
      <label for="inputPassword3" class="col-sm-2
col-form-label">Department</label>
      <div class="col-sm-10">
```

```

        <input type="text" name="Department"
class="form-control" id="inputPassword3">
    </div>
</div>
<div class="form-group row">
    <div class="col-sm-10">
        <button type="submit" class="btn btn-
primary">Submit</button>
        <div class="alert alert-success alert-dismissible
fade show" role="alert">
            <strong>Success!!</strong> You should check
in on some of those fields below.
            <button type="button" class="close" data-
dismiss="alert" aria-label="Close">
                <span aria-hidden="true">&times;</span>
            </button>
        </div>
    </div>
</div>
</form>

```

```

<!-- Optional JavaScript -->
<!-- jQuery first, then Popper.js, then Bootstrap
JS -->
<script src="https://code.jquery.com/jquery-
3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7

```

```

imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script
src="https://cdn.jsdelivr.net/npm/popper.js@1.16.
0/dist/umd/popper.min.js" integrity="sha384-
Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zz
Ttml3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.4.
1/dist/js/bootstrap.min.js" integrity="sha384-
wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4lh7YwaYd1i
qfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

Controller code

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Student;
class StudentController extends Controller
{
    public function input(Request $req)

```

```
{  
    //return $req->input();  
    $mem= new Student;  
    $mem->name=$req->Name;  
    $mem->department=$req->Department;  
    $mem->save();  
    return redirect("/");  
}
```

```
public function table()  
{  
    $data = Student::all();  
    $data1 = Student::find('Cid');  
    return view("table",["data"=>$data]);  
}
```

```
public function updateform($id){  
    $data=Student::find($id);  
    return view('edit',["editdata"=>$data]);  
}
```

```
public function edit(Request $req){  
    $data=Student::find($req->id);  
    $data->name::$req->name;  
    $data->department::$req->Department;  
    $data->save();  
    return redirect("table");  
}
```

```

public function delete($id)
{
    $data=Student::find($id);
    $data->delete();
    return redirect('table');
}
}

```

Web.php

```
<?php
```

```

use Illuminate\Support\Facades\Route;
use App\Http\Controllers\UserController;
use App\Http\Controllers\StudentController;

```

```
/*
```

```
|-----
```

```
-----
```

```
| Web Routes
```

```
|-----
```

```
-----
```

```
|
```

```

| Here is where you can register web routes for
your application. These
| routes are loaded by the RouteServiceProvider
and all of them will

```

| be assigned to the "web" middleware group.
Make something great!

|
*/

```
Route::get('/', function () {  
    return view('welcome');  
});
```

```
Route::get('home',[UserController::class,'index']);  
Route::view('form','crud');  
Route::post("submit",[StudentController::class,'input']);  
Route::get("table",[StudentController::class,"table"]);
```

```
Route::get("update/{id}",[StudentController::class,"updateform"]);  
Route::get("update/",[StudentController::class,"edit"]);
```

```
Route::get("delete/{id}",[StudentController::class,"delete"]);
```