

NETSCOPE

Deep Packet Inspection (DPI) & AI Classifier Engine
Technical Blueprint, Code Structure, and Interview Guide

Developer: Subham

Engineering Scope: Deep Packet Ingestion, Stateful Flow Tracking, Ensemble Machine Learning Classifiers, Multi-threaded Load Balancing, and Real-time WebSockets Dashboard.

Purpose: Technical Interview Preparation & Production-Ready Code Blueprint

Date: July 18, 2026

Version: 2.0 (Verified Stable)

This guide details NetScope's technical implementation file-by-file. It explains the project's motivation, components, multi-threaded pipelines, machine learning structures, and provides interview frameworks.

1. Project Motivation: Why I Built NetScope

Traditional firewalls and network classification systems are failing in modern security environments. Historically, identifying what application generated a network packet was trivial: security engineers used static port mappings (e.g., port 80 for HTTP, port 25 for SMTP) or matched plain-text signatures in unencrypted packet payloads.

However, three major architectural shifts in internet protocols have rendered traditional approaches obsolete:

- 1. Universal Encryption (TLS 1.3 & ESNI):** Almost all modern web and application traffic is encrypted. With TLS 1.3, handshake messages are encrypted, and features like Encrypted Server Name Indication (ESNI) hide domain targets. There is no payload text to inspect.
- 2. Port Tunneling & Multiplexing:** Apps run over standard ports like TCP 443 to bypass corporate firewalls. A connection to port 443 could be YouTube video streaming, GitHub commits, Zoom calls, or a data exfiltration tunnel.
- 3. Dynamic & Evasive Ports:** Protocols like Torrent, Gaming, and WebRTC allocate random ports dynamically. Static rule sets cannot keep pace.

The Solution: I built NetScope to solve this exact problem. By implementing a **hybrid packet inspection pipeline**, NetScope leverages high-speed signature extraction where possible (for O(1) matching efficiency) and falls back to **advanced machine learning models (RandomForest and XGBoost)** when traffic headers are missing, spoofed, or encrypted.

NetScope does not attempt to read the private contents of the packets. Instead, it behaves like a **behavioral analyst**, extracting 16 mathematical, temporal, and statistical features of the communication flow (such as the standard deviation of packet sizes, byte velocity, and payload entropy) to identify the app with high accuracy.

2. File-by-File System Architecture

NetScope's codebase is divided into modular directory layers. Below is the file structure and what each component is responsible for:

Core Engine (src/ Directory):

- **src/packet_parser.py:** The entry point for packet data. It performs high-speed bitwise unpacking on raw binary frames. Using Python's struct.unpack, it extracts Layer 3 (IP version, source IP, destination IP) and Layer 4 (ports and TCP control flags like SYN, ACK, FIN) in microseconds. It avoids parsing unnecessary higher-layer protocol trees to minimize latency.
- **src/pcap_reader.py:** Custom high-performance binary file reader. It bypasses heavy third-party wrappers, reading the PCAP global header to establish endianness, and yields individual packets alongside their microsecond-accurate epoch timestamps directly from the byte stream.
- **src/connection_tracker.py:** Tracks packets into bidirectional, stateful conversation flows. It maps a packet to a FlowContext using a normalized FiveTuple (src/dst IP, src/dst port, protocol). It continuously computes the 16 behavioral features on the fly, including cumulative byte sizes, squares of packet sizes (for standard deviation calculation), TCP flag counters, and Shannon entropy indices of raw payload bytes.

- **src/sni_extractor.py**: Direct byte scanner for TLS Client Hello packets. It extracts the Server Name Indication (SNI) extension in plain text, providing an immediate classification label for early-stage TLS handshakes.
- **src/rule_manager.py**: Enforces active network policies. It stores rules created by the user (blocking apps, IP addresses, or domain keywords) and checks if the classified packet flow matches any restriction.
- **src/dpi_engine.py**: The central orchestrator. It ties the parser, tracker, SNI extractor, rule manager, and ML predictor together. It handles the dual-path logic: fast-path SNI check → slow-path ML check if SNI fails → rules enforcement.
- **src/dpi_mt.py**: Multi-threaded engine. It spins up **Load Balancer (LB)** threads and a worker pool of **Fast-Path (FP)** threads. The LB threads distribute packets to thread-safe worker queues, ensuring packet processing scales across multi-core processors.

Machine Learning Brain (ml/ Directory):

- **ml/feature_extractor.py:** Serializes the raw statistics kept in FlowContext into a normalized 16-element NumPy array. Features include duration, packet volume, byte counts, standard deviation of packet sizes, speeds (bps, pps), TCP flags, and payload entropy.
- **ml/predictor.py:** Loads the pre-trained models and scaler. It scales the 16 features using StandardScaler and feeds them to the XGBoost and RandomForest classifiers. It averages their probabilities via soft voting to return the predicted class and its confidence.
- **ml/dataset_generator.py:** Generates synthetic flow data using defined app profiles (YouTube, Netflix, Facebook, TikTok, DNS, HTTP, etc.) with random noise to train the models.
- **ml/trainer.py:** Splits data into train/test sets, fits the RandomForest and XGBoost classifiers, prints classification reports, and outputs the confusion matrix and feature importance graphs.

Dashboard & Entrypoints:

- **app.py:** The main command-line entry point. It parses CLI arguments, loads blacklists, boots single-threaded or multi-threaded pipelines, and writes a processing report (report.txt).
- **dashboard/server.py:** The web entry point. It hosts a Flask server with **Flask-SocketIO**. It launches a background packet-processing thread that feeds packets into the DPI engine and broadcasts live JSON statistics to the UI every 100ms.

3. Deep Dive: How the Main Entry Points Work

To understand the project runtime, it is important to trace how the two main entry scripts (app.py and dashboard/server.py) execute under the hood.

A. Command-Line Entry Point (app.py):

1. ****CLI Parsing:**** Accepts inputs including PCAP file paths, output destination, blocked applications/IPs/domains, thread counts (LBs and FPs), and ML parameters (confidence threshold).
2. ****Rule Initializer:**** Populates the RuleManager with blocked items.
3. ****Engine Choice:****
 - ****Multi-Threaded Mode (Default):**** Runs `run\_mt` from src/dpi_mt.py. It starts Load Balancer threads which read packets, hash their 5-tuple to maintain flow affinity (sending packets of the same flow to the same worker), and push them to worker queues. Worker threads retrieve packets, parse them, query the classification pipeline, check block rules, and write safe packets to the output PCAP.
 - ****Single-Threaded Mode:**** Runs `run\_simple` from src/main_simple.py. It processes packets sequentially in a simple loop.
4. ****Report Output:**** Prints the ASCII-art table showing packet statistics, thread work distributions, and application classifications, writing the text report to report.txt.

B. Web Dashboard Server (dashboard/server.py):

1. ****Flask & SocketIO Setup:**** Initializes the Flask application and registers WebSocket routes.

2. **Background Thread Spawn:** Starts a daemon thread running `process_pcap`` before booting the web server. This thread reads packets from the PCAP file in a loop, pausing briefly (50ms) between packets to simulate a real-time live traffic stream.
3. **DPI Pipeline Execution:** For each packet, the background thread runs `DPIEngine.process_packet_detailed``. If the packet is blocked by the firewall rules, it logs a dropped status and adds a security alert to a thread-safe global queue.
4. **WebSocket Broadcast:** Every 100ms, the background thread serializes active stats (flow throughput, cumulative bytes, application percentages, and security alerts) into a JSON payload and emits it via `SocketIO`. The UI client catches this event, updating animated `Chart.js` widgets in the browser.

