In [ ]:
```
# we are developers
# we will develop the code
# the code application can be use public
```

input

In [2]:
```
number=100  # hard coded
number
```

Out[2]: 100

In [4]:
```
input()
```

Out[4]: '100'

In [ ]:
```
a=10
```

In [6]:
```
input()
```

Out[6]: '500'

In [8]:
```
input()
input()
input()
```

Out[8]: '10'

In [10]:
```
#n1=100
n1=input()
```

In [12]:
```
n1
```

Out[12]: '200'

In [16]:
```
n1=input('enter a value:')
name=input('enter a name:')
```

In [18]:
```
n1,name
```

Out[18]: ('200', 'python')

In [20]:
```
n1=100
n2=200
n1+n2
```

Out[20]: 300

In [22]:
```
n1=input('enter n1:')  # '100'
n2=input('enter n2:')  # '200'
n1+n2  # '100'+'200'='100200'
```

Out[22]: '100200'

In [26]:
```
'100'+'200'
```

Out[26]:
```
'100200'
```

In [28]:
```
n1=int(input('enter a n1:'))
n2=int(input('enter a n2:'))
n1+n2
```

Out[28]:
```
300
```

In [52]:
```
n22=1000
```

In [30]:
```
n1='100'
n2='200'
int(n1)+int(n2)  #int('100')+int('200')
```

Out[30]:
```
300
```

In [32]:
```
n1=input('enter a n1:')
n2=input('enter a n2:')
int(n1)+int(n2)
```

Out[32]:
```
300
```

In [34]:
```
n1=input('enter a n1:')
n2=input('enter a n2:')
int(n1+n2)
```

Out[34]:
```
'100200'
```

In [38]:
```
float(input())
```

Out[38]:
```
100.25
```

In [42]:
```
int(input())
```

Out[42]:
```
100
```

In [46]:
```
int(input())  # int('100.25')
```

```
---------------------------------------------------------------------------
ValueError                                Traceback (most recent call last)
Cell In[46], line 1
----> 1 int(input())

ValueError: invalid literal for int() with base 10: '100.25'
```

In [ ]:
```
int('100')  # works
int('100.5') # fail
```

In [1]:
```
n1=input('enter a number1:') # '100'
n2=input('enter a number2:') # '200'
n1+n2  # '100'+'200' = '100200'
```

Out[1]:
```
'100200'
```

In [3]:
```
n1=int(input('enter a number1:')) #  int('100')=100
n2=int(input('enter a number2:')) # int('200')=200
n1+n2  # 100+200 = 300
```

Out[3]: 300

In [7]:
```
n1=int(input('enter a number1:')) #  int('100')=100
n2=float(input('enter a number2:')) # int('200.5')=error
n1+n2  # 100+200 = 300
```

Out[7]: 300.5

In [11]:
```
n1=float(input('enter a number1:')) #  int('100')=100
n2=float(input('enter a number2:')) # int('200.5')=error
print(n1,n2)
n1+n2  # 100+200 = 300
```

```
100.0 200.5
```

Out[11]: 300.5

eval

In [14]:
```
eval('100')
```

Out[14]: 100

In [16]:
```
eval('200.5')
```

Out[16]: 200.5

In [18]:
```
n1=eval(input('enter a number1:')) #  int('100')=100
n2=eval(input('enter a number2:')) # int('200.5')=error
print(n1,n2)
n1+n2  # 100+200 = 300
```

```
100 200.5
```

Out[18]: 300.5

In [20]:
```
eval('apple')
```

```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
Cell In[20], line 1
----> 1 eval('apple')

File <string>:1

NameError: name 'apple' is not defined
```

In [22]:
```
int('100')  #  100
int('100.5') #  error
float('100.5') # 100.5

eval('100')  # 100
eval('100.5') # 100.5
```

Out[22]: 100

In [26]:
```
# wap ask the user take 3 numbers find the average
n1=11
n2=20
n3=30
avg=(n1+n2+n3)/3
avg1=round(avg,2)
print(f'the average of {n1},{n2} and {n3} is:{avg1}')
```

```
the average of 11,20 and 30 is:20.33
```

In [28]:
```
# ask the user enter a value
n1=eval(input('enter n1:'))
n2=eval(input('enter n2:'))
n3=eval(input('enter n3:'))
avg=(n1+n2+n3)/3
avg1=round(avg,2)
print(f'the average of {n1},{n2} and {n3} is:{avg1}')
```

```
the average of 11,20 and 30 is:20.33
```

In [30]:
```
n1=eval(input('enter n1:')
```

```
  Cell In[30], line 1
    n1=eval(input('enter n1:')
                              ^
SyntaxError: incomplete input
```

In [32]:
```
n1=eval(input('enter n1:))
```

```
  Cell In[32], line 1
    n1=eval(input('enter n1:))
                  ^
SyntaxError: unterminated string literal (detected at line 1)
```

In [ ]:
```
# wap ask the user take two number print subtraction multiplication and division
# wap ask the user take the radius find the area of circle
    # pi=3.14
    # r=100
   # area_of_circle=pi*r*r

# wap ask the user take height and breadth find the area of traingle
#       area_of_traingle=0.5*b*h

# wap ask the user take 3 numbers find the average
# wap ask the user take the bill amount and tip amount calculate total bill
# wap ask the user take the salary, percetage of tax calculate tax amount
# wap ask the user take the value in dollar convert into rupees
#         1$=80rs
# wap ask the use take weight in kgs convert into pounds
#     1kg=2.2pounds
```

In [36]:
```
# wap ask the user take the radius find the area of circle
    # pi=3.14
    # r=100
   # area_of_circle=pi*r*r

pi= eval(input('enter pi value:'))
r=eval(input('enter radius:'))
area_of_circle=pi*r*r
print(f'the area of circle is:{area_of_circle} units')
```

```
the area of circle is:1256.0 units
```

In [40]:
```
# wap ask the user take height and breadth find the area of traingle
#       area_of_traingle=0.5*b*h
height=eval(input('enter height:'))
breath=eval(input('enter breadth:'))
area_of_traingle=0.5*height*breath
print('area of traingle is:',area_of_traingle)
```

```
area of traingle is: 750.0
```

In [46]:
```
# bill amount  tip perce=10% on bill
# how much total bill
bill_amount=eval(input('enter bill amount:'))
tip_per=eval(input('enter tip perecentage:'))
tip_amount=bill_amount*tip_per/100
total_bill=bill_amount+tip_amount
print('the total bill is:',total_bill)
```

```
the total bill is: 1100.0
```

In [48]:
```
# wap ask the use take weight in kgs convert into pounds
#     1kg=2.2pounds
weight_in_kgs=eval(input('enter weight in kgs:'))
one_kg_in_pounds=eval(input('enter the pounds value of 1 kg:'))
total_weight_in_pounds=weight_in_kgs*one_kg_in_pounds
print(f"for {weight_in_kgs} kgs the weight in pounds is {total_weight_in_pounds}
#print("for 60 kgs the weight in pounds is 132 pounds")
```

```
for 60 kgs the weight in pounds is 132.0 pounds
for 60 kgs the weight in pounds is 132 pounds
```

In [ ]:
```
for 60  the weight in pounds is 132.0
for 60 kgs the weight in pounds is 132.0 pounds
```

In [54]:
```
n1=100
n2=200
n3=n1+n22
n3
```

Out[54]:
```
1100
```

In [1]:
```
eval('100.5')

# str object not callable
```

Out[1]:
```
100.5
```

In [ ]:
```
eval(input('enter the n1:')

eval(input(""))  # Omkar
eval(input("     # bf student
eval(input(""))
```

In [ ]:
```
# I recommend
# avoid the syntax error

# Those who are struggling  10times  6 codes

# 60 times you need to type
```