

All the tasks that I have shared in our whatsapp group

1. DATAWAREHOUSE TASKS:

Team,

I have uploaded the upto date ppts in our gdrive and webpage also, Please try to complete the following tasks before we meet tomorrow and get prepared for the quick quiz of 12 questions on the below points(1,2,3).

https://drive.google.com/drive/folders/1nK-DQK_M2QBvqHsFgvNQWRxj1Jk5lqhc?usp=drive_link

1. Simply go through & recognize the terminologies/abbreviations from 1_Inceptez_BIGDATA_Upto_Speed_WE49.pptx Slide 50 to 59.
2. Go through slide 8 to 11 in project1_datawarehouse_WE49.pptx
3. Go through the upgraded version of <https://inceptezlabs.com/bigdata/> (refresh the page and try, you should see the color menus, otherwise press ctrl+shift+del and cached images & files -> delete data), go through menu - all about bigdata & data architecture overview & datawarehouse deepdive.
4. Follow slide 9 & 10 Just create a github repository (task1) for your future need (I will explain it in detail soon on how to push/pull code, just do only registration & repository creation alone for now).
5. Follow slide 11 to do (task2) to create 'Conceptual data model' of legacy DWH.
6. Can you go through slide 5 (business objectives) and create a flowchart referring slide 11 example for flowchart creation?
7. After completing the task 4, fill your git repo info alone in the below gsheet <https://docs.google.com/spreadsheets/d/1MAu50LJzUvwUqJ4frtfNjJGWceXz14gvbu5BkYLYLmU/edit?usp=sharing>
8. Follow the attached image and FOLLOW the git repository of our other aspirants.
9. I have modified our quiz tool to show the score also in the last, pls try the quiz once again taking your own time
10. Refer slide 12 example and can you create an erDiagram with the below scenario and push/upload the erdiagram into your git repository.
Employee & Department ER Scenarios
One Employee may have zero or one Manager.
→ 1 : 0..1
One Employee may got on zero or many Promotions
→ 1 : 0..Many
One Employee belongs to exactly one Department.
→ 1 : 1
One Department can have one or many Employees.
→ 1 : 1..Many
One Employee can work on one or many Projects, and one Project can have one or many Employees.
→ 1..Many : 1..Many

11. Refer the 'Mermaid DFD Diagram Sample Code' and try to build the DFD diagram for the entities of EMPLOYEES, BRANCHES & CUST_PROFILE for the layers of Source to Staging to DSA to ODS.

12. Refer the 'Physical Data Model - Data Definition Language Script (DDL)' and customize the schema name adding yourname as a suffix then use the mysql workbench to create stgdb_yourname, tables inside the DSA(Staging) database and create odsdb_yourname, tables inside the ODS database.

13. Follow the video/steps & install Python in your Windows/Mac.

<https://inceptezlabs.com/bigdata/> -> Projects -> BFSILegacyDWProject1 -> Prerequisite Setup -> Programming / ETL Code

14. Go through & understand under 'Development — End to End Implementation' -> Mapping Document (Source → Transform → Target)

15. Go through & understand under 'How this Python script works — Step by Step' -> click on the > step 1 to 6 and read through the way how python program works.

16. In your Windows/Mac PC open the command prompt
Search -> cmd -> python

17. Run the below program to load data into one table (Branches)

#a. Import Libraries

```
import pandas as pd
```

```
from sqlalchemy import create_engine
```

#b. Connection Credentials

#Change these to match your MySQL server details

```
username = 'inceptez'
```

```
password = "Inceptez%40123" # %40 is URL-encoded @
```

```
host = '34.174.250.128'
```

```
db = 'stgdb_mkirfan'#Change this to your schema
```

```
table = 'stg_branches'
```

#c. Create DB Engine (pymysql driver)

```
engine = create_engine(
```

```
    f"mysql+pymysql://{username}:{password}@{host}:3306/{db}")
```

#d. Source Folder Path

#Change this to where you uncompressed the dataset zip

```
folder =
```

```
"E:\2026_BATCHES\inceptezlearn\dwhproject\source_landing_pad\bfsi_dataset\branches.csv"
```

#e. Load the data from the file to pandas dataframe to do structured queries

```
df = pd.read_csv(folder)
```

#f. Write the dataframe data into the table (stg_branches) using the engine, without index value in the first column & replace/overwrite the table data.

```
df.to_sql(table, con=engine, index=False, if_exists="replace")
print(f"Rows loaded into table: {table}")
```

18. Task18: Goto our portal <https://inceptezlabs.com/bigdata/> and go through the 'Development — End to End Implementation' -> 'Creation of Mapping Documents' and understand how a mapping document looks like and how ETL rules are provided to developers by a lead/architects.

19. Task19: Explore 'Staging Layer Load', download the data into your windows drive, execute 'Staging → DSA Load' (If you already completed the python load on one table, run the below code by changing the 'Python — stg_load.py' code copied from the portal, ensure to change the following credentials

```
username = 'testusr' # Change to inceptez
password = "Inceptez%40123" # %40 is URL-encoded @
host     = '34.63.107.222' # Change to 34.174.250.128
db       = 'stgdb' # Change to your dbname
```

```
folder = "D:\\Downloads\\bfsi_dataset\\" # Change to your folder name for eg.
E:\\2026_BATCHES\\inceptezlearn\\dwhproject\\source_landing_pad\\bfsi_dataset\\
```

20. Task20: DSA to ODS (Operational Data Store) Layer Load
Execute the 'SQL — ods_load.sql' task in the portal to load data from DSA to ODS.

21. Task21: ODS to DWH Load
Execute the 'SQL — 4_load_dwh_dim_fact_aggr.sql' task in the portal to load data from ODS to DWH. Just try only this load - # SCD Type1 - History is not maintained, We will see '# SCD Type 2 Starts here' on next weekend..

#SCD type1 dim load

```
create table learning.ods_cust_src(id int,name varchar(100),finstatus varchar(100),address
varchar(100));
```

#Source send the data in a complete fashion, not incremental fashion

```
insert into learning.ods_cust_src (id,name,address) values(1,'sojiv','1,xyz street,
area,city');#day1
```

```
insert into learning.ods_cust_src (id,name,address) values(2,'rizwan','2,abc street,
area,city');#day2
```

```
insert into learning.ods_cust_src (id,name,address) values(3,'sujithra','2,abc street,
area,city');#day3
```

```
update learning.ods_cust_src set address='100,xyz street, area,city' where id=1;
```

#melting of columns

```
create table learning.dwh_cust_tgt(id int,name varchar(100),address varchar(100));
```

#day1 load

```
truncate table learning.dwh_cust_tgt;
```

```
insert into learning.dwh_cust_tgt select id,name,address from learning.ods_cust_src;
```

```
select * from learning.dwh_cust_tgt;
```

#Source send the data in an incremental fashion (only inserted and updated), not complete fashion

#SCD type1 dim load

```
truncate table learning.ods_cust_src;
```

```
truncate table learning.dwh_cust_tgt;
```

#Source send the data in an incremental fashion (only inserted and updated), not complete fashion

```
insert into learning.ods_cust_src (id,name,address) values(1,'sojiv','1,xyz street, area,city');#day1 (10 customers)
```

```
insert into learning.ods_cust_src (id,name,address) values(2,'rizwan','2,abc street, area,city');#day2 (20 customers)
```

```
insert into learning.ods_cust_src (id,name,address) values(3,'sujithra','2,abc street, area,city');#day3
```

```
update learning.ods_cust_src set address='100,xyz street, area,city' where id=1;#day3
```

#melting of columns

```
create table learning.dwh_cust_tgt(id int,name varchar(100),address varchar(100));
```

#day1 load

```
insert into learning.dwh_cust_tgt select id,name,address from learning.ods_cust_src;
```

```
select * from learning.dwh_cust_tgt;
```

#If the source send data in an incremental fashion

```
#select s.*,t.* from learning.ods_cust_src s
```

```
insert into learning.dwh_cust_tgt
```

```
select s.id,s.name,s.address from learning.ods_cust_src s
```

```
left join learning.dwh_cust_tgt t #left join
```

```
on t.id=s.id
```

```
where t.id is null;
```

```
update learning.dwh_cust_tgt t
```

```
#select s.*,t.* from
```

```
join learning.ods_cust_src s #join
```

```
on t.id=s.id
```

```
set t.address=s.address, s.name=t.name
```

```
WHERE t.address<>s.address or t.name<>s.name;
```

22. Task 22: Loading SCD Type2 table

Try to understand the concepts of SCD type2 load (first by using the examples given below with

some small table, then try the actual usecases provided in the portal)

#Source send the data in an incremental fashion (only inserted and updated), not complete fashion

#SCD type2 dim load

```
truncate table learning.ods_cust_src;
```

```
truncate table learning.dwh_cust_tgt;
```

#Source send the data in an incremental fashion (only inserted and updated), not complete fashion

```
insert into learning.ods_cust_src (id,name,address) values(1,'sojiv','1,xyz street, area,city');#day1 (10 customers)
```

```
insert into learning.ods_cust_src (id,name,address) values(2,'rizwan','2,abc street, area,city');#day2 (20 customers)
```

```
insert into learning.ods_cust_src (id,name,address) values(3,'sujithra','2,abc street, area,city');#day3
```

```
update learning.ods_cust_src set address='100,xyz street, area,city' where id=1;#day3
```

```
update learning.ods_cust_src set address='200,abc street, area,city' where id=2;#day3
```

#melting of columns

```
create table learning.dwh_cust_tgt(id int,name varchar(100),address varchar(100));
```

```
create table learning.dwh_cust_scd2_tgt(id int,name varchar(100),address varchar(100),start_date DATE,end_date DATE, is_current TINYINT);
```

```
select * from learning.ods_cust_src;
```

```
select * from learning.dwh_cust_scd2_tgt;
```

#day2 load

```
update learning.dwh_cust_scd2_tgt t
```

```
#select s.*,t.* from
```

```
join learning.ods_cust_src s
```

```
on t.id=s.id
```

```
set t.end_date='2026-08-29',is_current=0
```

```
where s.address<>t.address
```

```
or s.name<>t.name;
```

```
insert into learning.dwh_cust_scd2_tgt
```

```
select s.id,s.name,s.address,current_date,null,1
```

```
from learning.ods_cust_src s
```

```
left outer join learning.dwh_cust_scd2_tgt t
```

```
on s.id=t.id
```

```
and t.is_current=1
```

```
where t.id is null#suchithra
```

```
or s.address<>t.address#sojiv data
```

```
or s.name<>t.name;
```

```
#day2 load
insert into learning.ods_cust_src (id,name,address) values(3,'sujithra','2,abc street,
area,city');#day2
update learning.ods_cust_src set address='100,xyz street, area,city' where id=1;#day2
```

#Try the same above update & insert queries..

```
select * from learning.dwh_cust_scd2_tgt;
```

23. Task 23: Loading Fact Tables and Data Mart tables.

Try simple transformation functions like substr, case etc., functions like given below.

```
select substr('inceptez',6,3),case when 1=1 then 'one' else 'two' end;
```

Implement the Datawarehouse fact tables such as fact_loans and fact_loan_summary tables following the portal.

24. Task 24: Complete the Data mart load task by loading rest of the fact tables.

Fact_creditcards, fact_payments, fact_transactions, agg_branch_trans_summary &
fact_high_value_loans

25. Task 25: Go through the ‘**Project Learnings**’ section under ‘**BFSI Legacy DW Project1**’ and try to realize whether we are able to catch up with the overall project implementation what we did so far.

2. PYTHON TASKS:

A. Python is an indent based programming language

The following program throws an indentation error. Correct it and make sure it prints properly.

```
teams = ['Data', 'AI', 'DevOps']
for t in teams:
print('Hello', t, 'Team from Inceptez Technologies')
    print('Keep Learning and Exploring!')
```

B. Commented line in Python

Use Case 1:

Add single-line and multi-line comments to describe what the below code does for Inceptez Technologies’ training tracker.

```
students = 100
```

```
trainers = 2
total = students + trainers
print(total)
```

Use Case 2:

Convert the below block into a “dead code” using comments, then re-activate it later to print

```
print("Welcome to Inceptez Python Learning")
```

C. Playing with Quotes

Use Case 1:

Create three string variables that correctly store and print:

This is Inceptez's "Python" class for Data Engineers & AI Engineers

→ Use single, double, and triple quotes appropriately.

Use Case 2:

Write a multiline string using triple quotes that prints:

Welcome to Inceptez Technologies!

Python Training: Basics

Enjoy your learning journey.

D. Let's learn all about VARIABLES

Use Case 1:

Declare variables to store the following details:

- Student Name
- Course Name (e.g., “Python Fundamentals”)
- Training Institute Name (Inceptez Technologies)

Then print a formatted message:

Name: Arun is learning the course Python Fundamentals at the institute Inceptez Technologies

Use Case 2:

Demonstrate dynamic inference, dynamic typing using with fee by applying .18 gst and prove strongly typing character also by operating it with Eighteen percent gst

fee = 45000

E. Variables Naming Conventions

Use Case 1:

Identify which variable names below are invalid for Inceptez's student database:

- 1) 2student = 'Ravi'
- 2) _student_id = 1001
- 3) studentName = 'Priya'
- 4) class name = 'Python'
- 5) inceptez_batch = 'Morning'

Use Case 2:

Declare 3 variables following naming styles for Inceptez projects:

PascalCase: DataEngineeringBatch

camelCase: dataEngineeringBatch

snake_case: data_engineering_batch

F. Type identification & Casting

Use Case 1:

Write a program that asks for an employee's age.

1. Checks its type is of string (think about using isinstance() function)
2. Converts it to int (continue writing your program from here..)
3. Prints the years pending for retirement, for eg. 60 is the retirement age.

Example:

Enter your age: 40

You will retire in 20 years at Inceptez Technologies.

Use Case 2 (Debug):

Fix the type error in the following code for salary calculation:


```
salary = '50000'
bonus = 10000
print('Total Salary in Inceptez:', salary + bonus)
```

G. Data types and casting

Use Case 1 — Employee Salary Breakdown Using Numeric & String Types

Employee Salary Breakdown

a. Write a program that asks the user for:

- employee_name (string)
- base_salary (float)
- hra_percent (integer)
- bonus_amount (float)

B. Convert inputs to the correct datatype if required.

Calculate:

$HRA = base_salary * (hra_percent / 100)$

$Total\ Salary = base_salary + HRA + bonus_amount$

C. Print the output like this:

Employee: Arun

Base Salary: 40000.0

HRA @ 20%: 8000.0

Bonus: 5000.0

Total Salary Payable: ₹53000.0

Use Case 2: Student Result Classification

a. Write a program that takes marks as input (initially as a string).

B. Check if the value can be converted to float.

C. Then classify (try using if condition with the help of AI, however we will learn about if condition soon):

Marks ≥ 90 --> Outstanding

Marks ≥ 75 --> Excellent

Marks ≥ 50 --> Pass

Marks < 50 --> Fail

D. If the input is not numeric, print:

Invalid marks entered — Please provide numeric input.

Use Case 3: Bug Fixing — Datatype Mismatch

The below code is intended to calculate total price, but it has datatype errors. Fix it.

Incorrect code:

```
item_name = input("Enter product name: ")
price = input("Enter price per item: ")
quantity = input("Enter quantity: ")

total_cost = price * quantity

print("You purchased " + quantity + " units of " + item_name)
print("Total payable: " + total_cost)
```

Expected output after fixing:

Enter product name: Notepad

Enter price per item: 35.50

Enter quantity: 3

You purchased 3 units of Notepad

Total payable: 106.5 INR

H. Python Operators Usecases

Use Case 1: Internet Data Usage Calculator

Write a program that asks the user for:

- Total monthly data limit (in GB)
- Data used so far (in GB)

Calculate using arithmetic operators:

Remaining data = limit - used

Usage percentage = (used / limit) * 100

Print:

- Remaining data
- Usage percentage rounded to 2 decimals

If usage percentage is greater than or equal to 80, print:

"Warning: High usage, consider upgrading your plan."

Use Case 2: Shopping Discount Calculation

Write a program that takes:

- Original price (float)
- Discount percent (int)

Using assignment and arithmetic operators, calculate:

Discount amount = (price * discount_percent) / 100

Final price = price - discount_amount

Print:

Original price, discount applied, and final payable amount.

Use Case 3 (Bug Fixing): Logical and Comparison Operator Errors

The following code should determine voting eligibility, but it contains operator mistakes. Fix it.

Incorrect code:

```
age = input("Enter age: ")
```

```
citizen = input("Are you an Indian citizen? (yes/no)")
```

```
if age > "18" and citizen = "yes":
```

```
    print("Eligible to vote")
```

```
else:
```

```
    print("Not eligible")
```

Expected behavior:

- Convert age to integer before comparison.
- Only print "Eligible to vote" if age is 18 or above AND citizen input is "yes" (case-insensitive).

I. Conditional Structure

Use Case 1: Banking Eligibility Check

Write a program that asks the user for:

- Age
- Monthly income

Conditions:

- If age < 18: print "Not eligible for a bank account."
- If age >= 18 and income < 15000: print "Eligible for basic savings account."
- If age >= 18 and income between 15000 and 50000: print "Eligible for savings + salary account."
- If age >= 18 and income > 50000: print "Eligible for premium account."

Use Case 2: Check room availability

-Check room availability

- If available:

- If guest is VIP

→ Offer complimentary upgrade

- Else if member 5+ years

→ Offer discount

- Else

→ Standard price

- Else:

→ Show: "No rooms available"

Use Case 3 (Bug Fixing): Nested Condition Logic Issue

Fix the following code so that it correctly determines whether the entered temperature indicates normal, fever, or high fever.

Incorrect code:

```
temp = input("Enter body temperature in Celsius: ")
```

```
if temp < "37":  
    print("Normal temperature")  
elif temp > "37" and temp < "39":  
    print("Fever")  
else  
    print("High fever")
```

Expected behavior:

- Convert temperature to float before comparison.
- Conditions should print:
 - Normal temperature (less than 37)
 - Fever (between 37 and 39)
 - High fever (39 and above)