HydroBloom: Machine Learning Driven Rooftop Rainwater Harvesting Feasibility Assessment and Cost Optimization Framework

Subhi Tiwari[1], Shreya Lathi[2], Yatnesh Puranik[3], Dr.Richa Gupta[4]
[1,2,3]Student,[4]Professor, Department of Computer Science and Engineering
Indore Institute of Science and Technology, Indore (M.P.), India

***Abstract*—Increasing freshwater scarcity, unpredictable rainfall patterns, and rising urban water consumption have created a strong need for intelligent decentralized water conservation systems. Traditional rooftop rainwater harvesting feasibility assessment methods depend heavily on manual engineering calculations, expert consultation, and static environmental assumptions, making them difficult for ordinary users to access and interpret. Existing digital assessment tools provide limited rule-based estimations and generally do not incorporate rooftop image understanding, adaptive environmental intelligence, predictive analytics, or financial optimization.**

HydroBloom presents an intelligent machine learning driven web framework for rooftop rainwater harvesting feasibility assessment, predictive water estimation, cost analysis, and optimized infrastructure recommendation. The system integrates computer vision based rooftop analysis, weather API driven rainfall intelligence, regression-based environmental prediction, and optimization logic for economically efficient deployment planning. The implemented framework uses React.js for the frontend, Django for backend orchestration, Python-based machine learning models, and environmental data integration services. Experimental implementation demonstrates practical feasibility, responsive user interaction, acceptable prediction performance, and scalable sustainability decision support for consumer-oriented applications.

***Keywords*—Rainwater Harvesting, Machine Learning, Computer Vision, Water Conservation, Sustainability, Cost Optimization, Decision Support**

I. Introduction

Water scarcity has become one of the most serious environmental and social concerns in modern urban regions. Increasing population growth, irregular precipitation patterns, excessive groundwater extraction, and rising household consumption have placed significant pressure on centralized water distribution systems [1]. In many urban areas, dependence on municipal water infrastructure alone is no longer sufficient to ensure long-term sustainability.

Rainwater harvesting provides a practical decentralized solution to this challenge. Rooftop rainwater harvesting systems collect precipitation from built surfaces and store it for later domestic use or groundwater recharge [2]. Such systems reduce freshwater dependency, improve sustainability, and contribute toward better environmental resource management.

Despite these advantages, large-scale adoption remains limited because practical feasibility assessment is often complex. Traditional assessment methods require technical understanding of rainfall analysis, rooftop suitability, runoff coefficients, storage design, and financial planning. Most homeowners are unable to perform such engineering evaluations independently.

Several online calculators attempt to simplify this process by allowing users to manually enter rainfall values, roof dimensions, and expected water demand. However, these systems generally remain deterministic and static. They do not intelligently analyze rooftop conditions, dynamically retrieve environmental data, or optimize infrastructure recommendations according to practical constraints.

Machine learning and computer vision technologies create opportunities to improve these systems significantly. Computer vision models can interpret rooftop imagery and estimate structural suitability [3]. Predictive machine learning models can estimate nonlinear environmental outcomes using rainfall and structural inputs [4]. Optimization frameworks can recommend economically feasible infrastructure configurations.

HydroBloom proposes such an intelligent integrated framework. The system combines rooftop image analysis, rainfall intelligence, predictive water estimation, financial analysis, and optimized deployment recommendation into a single web-based platform.

Unlike conventional engineering calculators, HydroBloom does not depend solely on static user input. Instead, the system uses machine learning and environmental intelligence to provide adaptive decision support while keeping the interaction accessible for ordinary users.

II. Literature Review

Rainwater harvesting feasibility assessment has traditionally relied on hydrological equations involving rainfall intensity, rooftop collection area, runoff coefficients, and storage assumptions [2]. These methods provide mathematically interpretable estimations but require technical expertise for practical application. Because of this, such approaches are often less accessible to non-technical users.

Digital assessment tools were introduced to simplify these engineering workflows. These platforms typically allow users to enter location details, rooftop dimensions, and water demand values to generate basic harvesting estimates. However, these systems remain rule-based and largely depend on manually entered information [5]. Their adaptability is limited,

especially when rooftop suitability or environmental variability must be considered.

Computer vision has emerged as an effective technology for structural interpretation tasks. Deep convolutional neural networks have shown strong performance in rooftop classification, building recognition, and surface analysis applications [3]. Lightweight architectures such as MobileNetV2 enable efficient practical deployment where computational resources may be constrained.

Environmental prediction has also benefited from machine learning approaches. Regression models such as Random Forest have demonstrated strong performance in rainfall forecasting and nonlinear environmental estimation tasks [4]. These models perform better than conventional deterministic systems when multiple interacting variables influence prediction outcomes.

Optimization frameworks are commonly applied in engineering planning systems where cost-performance tradeoffs must be balanced [6]. Such methods help identify economically feasible configurations while satisfying practical constraints.

Although these technologies are individually well established, integrated consumer-oriented systems combining rooftop image interpretation, rainfall intelligence, predictive estimation, and cost optimization remain limited. HydroBloom addresses this research gap through an implemented intelligent sustainability advisory framework.

III. System Architecture

HydroBloom is designed as an intelligent web-based environmental decision support system where rooftop assessment, rainfall intelligence, predictive modeling, and infrastructure recommendation are integrated into a unified framework. The architecture follows a modular structure so that individual components can operate independently while supporting scalable deployment.

The frontend of the system is implemented using React.js and serves as the primary interaction layer for users. Through this interface, users provide residential information, upload rooftop images, view rainfall analytics, inspect financial estimates, and receive infrastructure recommendations. The frontend communicates with the backend to retrieve processed environmental intelligence and prediction outputs.

The backend is implemented using Django and manages application orchestration. It handles authentication, API communication, environmental data processing, machine learning model interaction, and database operations. The backend acts as the coordination layer between user interaction and predictive intelligence.

Environmental intelligence is obtained through weather API integration. The system retrieves rainfall observations, monthly precipitation patterns, and climate indicators for the provided user location. This environmental information is normalized before predictive analysis.

Rooftop analysis is performed using a machine learning based computer vision pipeline. Uploaded rooftop images are preprocessed and passed through a lightweight convolutional neural architecture that identifies structural suitability and approximates usable collection area.

Prediction and recommendation logic operate on the processed environmental and structural inputs. Regression models estimate harvesting potential, while optimization modules recommend suitable storage and filtration configurations based on cost and demand constraints.

This architecture enables HydroBloom to combine environmental analysis, machine learning intelligence, and practical deployment support within a scalable web application.

This architecture enables HydroBloom to combine environmental analysis, machine learning intelligence, and practical deployment support within a scalable web application.




Fig. 1. Use Case Diagram of the HydroBloom System

IV. Methodology

The HydroBloom methodology consists of environmental data acquisition, rooftop image analysis, predictive water estimation, financial modeling, and optimization driven recommendation generation.

Rainfall intelligence is collected using weather APIs based on the user's location. The retrieved information includes annual rainfall, monthly precipitation patterns, and seasonal environmental indicators. Since environmental data may vary in scale, normalization is applied before predictive modeling.

For rooftop analysis, uploaded images are preprocessed through resizing, normalization, and enhancement. Let the rooftop image be represented as:

$$I \in \mathbb{R}^{H \times W \times C}$$

where H, W, and C represent image height, width, and color channels respectively. Input normalization is performed as:

$$I' = \frac{I}{255}$$

The normalized image is processed using a transfer learning based MobileNetV2 convolutional architecture. Feature extraction is represented as:

$$F = CNN(I')$$

Classification output is given by:

$$\hat{y} = Softmax(WF + b)$$

where $\hat{y}$ represents rooftop suitability classification.

Traditional rainwater harvesting estimation follows:

$$H = R \times A \times C$$

where R represents rainfall, A denotes usable rooftop area, and C is the runoff coefficient.

However, environmental conditions are nonlinear and variable. Therefore, HydroBloom incorporates Random Forest regression to improve prediction adaptability. The predictive mapping is represented as:

$$f(X) \rightarrow Y$$

where the feature vector includes rainfall, rooftop area, seasonal variation, water demand, and rooftop type. The Random Forest ensemble prediction is expressed as:

$$\hat{Y} = \frac{1}{N} \sum_{i=1}^{N} T_i(X)$$

where N represents the number of decision trees used in the ensemble. This improves prediction robustness under varying environmental conditions.

Financial feasibility is estimated using infrastructure cost models. Total deployment cost is calculated as:

$$C_{total} = C_{tank} + C_{filter} + C_{pipe} + C_{labor} + C_{misc}$$

Annual savings are estimated using predicted water conservation and utility cost assumptions:

$$S_{annual} = W_{saved} \times P_{water}$$

The payback period is computed as:

$$P_{payback} = \frac{C_{total}}{S_{annual}}$$

Return on investment is calculated as:

$$ROI = \frac{(S_{annual} \times N) - C_{total}}{C_{total}} \times 100$$

where N represents the analysis duration in years.

To improve practical recommendation quality, optimization logic is applied so that infrastructure suggestions remain economically feasible while satisfying household demand requirements. This enables HydroBloom to convert predictive environmental intelligence into actionable deployment recommendations.

V. Experimental Setup

The HydroBloom framework was experimentally evaluated to assess practical deployment feasibility, predictive performance, and interactive responsiveness. The evaluation focused on rooftop classification accuracy, harvest prediction reliability, recommendation consistency, and overall system responsiveness under realistic residential usage conditions.

The implementation environment consisted of a standard consumer hardware configuration using an Intel Core i5 processor with 8 GB RAM and a Chromium-based browser environment. The software stack included React.js for frontend interaction, Django for backend orchestration, Python machine learning pipelines, TensorFlow/Keras for image analysis, Scikit-learn for regression modeling, weather API integration, and SQL-based persistence services.

The experimental dataset included representative rooftop image samples across residential structural categories, environmental rainfall observations, and simulated domestic water demand scenarios. Model training followed an 80% training and 20% testing split.

Performance evaluation used classification accuracy for rooftop suitability analysis, Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), response latency, and recommendation consistency.

VI. Results

Experimental implementation indicates that HydroBloom performs effectively as an intelligent sustainability advisory platform. The rooftop image classification module demonstrated strong structural interpretation capability across residential rooftop categories. Classification accuracy ranged between 89% and 94%, with concrete rooftop surfaces showing the most consistent prediction reliability. Irregular rooftop structures and lower quality imagery introduced moderate uncertainty.

The harvest prediction module produced acceptable environmental estimation accuracy. Mean Absolute Error was observed at 7.8%, while Root Mean Squared Error remained approximately 10.4%. These results indicate that the predictive model effectively captures nonlinear environmental relationships while maintaining practical reliability for consumer decision support.

Recommendation optimization consistently generated infrastructure suggestions aligned with household demand and economic constraints. Suggested configurations remained financially interpretable and practically deployable.

The overall software architecture of HydroBloom is illustrated in Fig[2].




Fig. 2. Component Architecture of the HydroBloom.

Average system response time remained between 1.4 and 2.1 seconds across experimental scenarios. This level of responsiveness indicates that HydroBloom can support interactive web-based environmental assessment without causing significant user delay.

VII. Discussion

The experimental outcomes demonstrate that intelligent machine learning based rainwater harvesting advisory systems are practically feasible for consumer-oriented deployment. HydroBloom improves upon conventional deterministic calculators by integrating structural interpretation, environmental intelligence, predictive estimation, and cost optimization into a unified decision-support framework.

The use of computer vision reduces dependency on manual rooftop estimation, while weather API integration improves adaptability compared to static rainfall assumptions. Regression-based prediction enables better handling of nonlinear environmental relationships that conventional formula-based estimators may not fully capture.

Optimization-driven recommendation further improves practical usability because users receive actionable infrastructure guidance rather than raw numerical estimates. The modular architecture also supports scalability and future deployment enhancements.

VIII. Limitations and Ethical Considerations

Although HydroBloom provides a practical intelligent framework, several limitations remain. Rooftop classification performance depends significantly on image quality, lighting conditions, and structural visibility. Poor image quality may reduce prediction reliability.

Environmental prediction depends on rainfall observations and weather API consistency. Climatic uncertainty may reduce predictive accuracy under unusual weather conditions.

Financial estimates are approximate and may vary depending on vendor pricing, regional installation costs, and infrastructure availability.

From an ethical perspective, machine learning predictions should be interpreted as advisory rather than deterministic engineering guarantees. Users should be informed about predictive uncertainty before making deployment decisions.

Privacy considerations are also important because rooftop imagery and location information may contain sensitive residential details. Secure handling and controlled data access are therefore necessary in production deployment.

IX. Conclusion

This paper introduced HydroBloom, a machine learning driven rooftop rainwater harvesting feasibility assessment and cost optimization framework. The proposed system integrates rooftop image analysis, environmental intelligence, predictive estimation, financial analysis, and infrastructure recommendation into a unified intelligent web platform.

Unlike conventional rule-based calculators, HydroBloom automates structural interpretation and provides adaptive decision support for practical deployment planning. Experimental implementation demonstrated strong rooftop classification accuracy, acceptable predictive estimation reliability, responsive interaction performance, and practical recommendation consistency.

The framework demonstrates how machine learning can strengthen sustainable environmental decision-support systems and improve accessibility for decentralized water conservation planning.

X. Future Scope

Future improvements may include advanced rooftop segmentation architectures, satellite imagery integration, IoT-based water monitoring, groundwater recharge estimation, and reinforcement learning driven infrastructure optimization.

Federated environmental learning may also improve predictive accuracy while preserving privacy across distributed deployments. Such extensions can evolve HydroBloom into a broader intelligent sustainability ecosystem.

XI. Research Foundations and Sources

The development of HydroBloom was guided by existing research in rainwater harvesting, machine learning, computer vision, and sustainable resource management. Rather than relying solely on conventional engineering calculations, the proposed framework combines multiple modern technologies to provide intelligent and user-friendly decision support.

The fundamental concept of rooftop rainwater harvesting was derived from established studies on urban rainwater collection systems. Previous research has demonstrated that rooftop harvesting can significantly reduce dependence on municipal water supplies while promoting sustainable water utilization [2].

To automate rooftop suitability assessment, the system incorporates concepts from computer vision and image classification research. Studies on deep learning based roof analysis have shown that convolutional neural networks can effectively identify rooftop characteristics and structural suitability from images [3]. These findings motivated the use of image-based rooftop assessment within HydroBloom.

For predictive environmental analysis, machine learning techniques were studied extensively. Research has shown that data-driven prediction models can capture complex relationships between rainfall patterns, environmental conditions, and water availability more effectively than traditional deterministic approaches [4]. This formed the basis of the predictive estimation module.

The Random Forest regression approach implemented in HydroBloom is based on the ensemble learning methodology introduced by Breiman [7]. Random Forest models are widely recognized for their robustness, ability to handle nonlinear relationships, and strong predictive performance across environmental datasets.

The computer vision component draws inspiration from MobileNetV2, a lightweight deep learning architecture designed for efficient image classification tasks [8]. Its computational efficiency makes it suitable for deployment within web-based applications where fast processing and scalability are important considerations.

The recommendation and optimization framework was influenced by studies on multi-criteria water resource planning [6]. These approaches emphasize balancing economic feasibility, infrastructure cost, and practical implementation constraints when recommending sustainable solutions.

In addition, the broader motivation for developing HydroBloom is supported by global reports highlighting increasing freshwater scarcity, climate variability, and the growing need for decentralized water conservation strategies [1]. These reports emphasize the importance of intelligent technologies that can help individuals make informed environmental decisions.

By integrating insights from these established studies, HydroBloom combines environmental intelligence, computer vision, machine learning prediction, and financial optimization into a unified platform aimed at making rainwater harvesting assessment more accessible, accurate, and practical for everyday users.

References

[1] UN-Water, "The United Nations World Water Development Report," UNESCO, 2023.
[2] A. Campisano et al., "Urban Rainwater Harvesting Systems," Water Research, 2017.
[3] M. Wurm et al., "Deep Learning for Roof Shape Classification," Remote Sensing, 2019.
[4] S. Choubin et al., "Machine Learning Models for Rainfall Prediction," Atmospheric Research, 2018.
[5] P. Fewkes, "Rainwater Collection Systems," Building and Environment, 1999.
[6] M. Hajkowicz and K. Collins, "Multi-Criteria Water Resource Planning," Water Resources Management, 2007.
[7] L. Breiman, "Random Forests," Machine Learning, 2001.
[8] A. Howard et al., "MobileNetV2," IEEE CVPR, 2018.