

Edge: Canny

Dr. Tushar Sandhan

Introduction

- Single point thick edges

input



Introduction

- Single point thick edges

input



Introduction

- Single point thick edges

input



Canny edges




Introduction

- Single point thick edges

input



Canny edges



Introduction

- Single point thick edges


input



Canny edges



Canny PCB edges



Edge


- What would be important steps in edge det.

Edge

- What would be important steps in edge det.
 - Smooth derivatives


Edge

- What would be important steps in edge det.
 - Smooth derivatives





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning
 - Linking






Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning
 - Linking



Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning
 - Linking



Canny edge detector

- Objectives

Canny edge detector

- Objectives
 - low error rate
 - all edges should be found

Canny edge detector

- Objectives

- low error rate
 - all edges should be found
- good localization of edges
 - centre of true edge at i^{th} pixel : c_i
 - obtained edge point at i^{th} pixel: e_i
 - minimize the distance $\|c_i - e_i\|_2$

Canny edge detector

- Objectives

- low error rate
 - all edges should be found
- good localization of edges
 - centre of true edge at i^{th} pixel : c_i
 - obtained edge point at i^{th} pixel: e_i
 - minimize the distance $\|c_i - e_i\|_2$
- single point edge response
 - 1 point for each true edge point

Canny edge detector

- Image derivatives
 - input image $f(x, y)$
 - smoothed $f_s(x, y)$
 - any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

Canny edge detector

- Image derivatives
 - input image $f(x, y)$
 - smoothed $f_s(x, y)$
 - any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

Canny edge detector

- Image derivatives

- input image $f(x, y)$
- smoothed $f_s(x, y)$
- any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

$$g_x(x, y) = \partial f_s(x, y) / \partial x \qquad g_y(x, y) = \partial f_s(x, y) / \partial y$$

Canny edge detector

- Image derivatives

- input image $f(x, y)$
- smoothed $f_s(x, y)$
- any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

$$g_x(x, y) = \partial f_s(x, y) / \partial x$$

$$g_y(x, y) = \partial f_s(x, y) / \partial y$$

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

Canny edge detector

- Image derivatives

- input image $f(x, y)$
- smoothed $f_s(x, y)$
- any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

$$g_x(x, y) = \partial f_s(x, y) / \partial x$$

$$g_y(x, y) = \partial f_s(x, y) / \partial y$$

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning
 - $M_s(x, y)$ wide ridges around local maxima
 - ridges thinning is needed
 - non-max suppression
 - suppress where?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges
 - how?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges
 - how?
 - walking along edge normals?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$


Canny edge detector

■ Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges
 - how?
 - walking along edge normals?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p



Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p






Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




$$\frac{y - y_0}{x - x_0} = \frac{y_1 - y_0}{x_1 - x_0}$$




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p





$$\frac{y - y_0}{x - x_0} = \frac{y_1 - y_0}{x_1 - x_0}$$

$$y = y_0 + (x - x_0) \frac{y_1 - y_0}{x_1 - x_0}$$



Canny edge detector


- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p



$$\frac{y - y_0}{x - x_0} = \frac{y_1 - y_0}{x_1 - x_0}$$

$$y = y_0 + (x - x_0) \frac{y_1 - y_0}{x_1 - x_0}$$

$$= y_0 \left(1 - \frac{x - x_0}{x_1 - x_0} \right) + y_1 \left(\frac{x - x_0}{x_1 - x_0} \right)$$



Canny edge detector



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!
 - two instruments of thresholds: Hysteresis



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!
- two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}



Canny edge detector

- Entire algorithm composition:

Canny edge detector

- Entire algorithm composition:
 1. Filter image with derivatives of Gaussian
 2. Get M, α
 3. Non-max suppression
 - thin multi-pixel wide edges to a single pixel widths
 4. Linking: the hysteresis
 - 2 thresholds: TH_{low} , TH^{high}
 - TH^{high} : to start an edge
 - TH_{low} : continue started edge

Canny edge detector

Canny edge detector

- Speeding up the beats of operations
 - binning the α (angles)
 - 4 directions

Canny edge detector

- Speeding up the beats of operations
 - binning the α (angles)
 - 4 directions

Horizontal

+45 degrees

Vertical

-45 degrees

Canny edge detector

- Speeding up the beats of operations


- binning the α (angles)
- 4 directions

Horizontal

+45 degrees

Vertical

-45 degrees



Canny edge detector

- Speeding up the beats of operations



- binning the α (angles)
- 4 directions

Horizontal

+45 degrees


Vertical

-45 degrees



Canny edge detector

- Speeding up the beats of operations
 - binning the α (angles)
 - get the directional bin $Bin()$ closest to α
 - from previous operations edge: $M(x, y)$
 - suppression
 - If $M(x', y') > M(x, y)$ then $M(x, y) \rightarrow 0$
 - where neighbors $x', y' \leftarrow Bin(x, y)$



Canny edge detector

- Varying σ

input



Canny edge detector

- Varying σ

input



Canny edge detector

- Varying σ

input



Canny edge detector

- Varying σ

input



σ small



Canny edge detector

- Varying σ

input



σ small



σ large



Canny edge detector

- Comparing other edge detectors

input



Canny edge detector

- Comparing other edge detectors

input



Sobel with TH




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH



LoG zero crossings




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH



LoG zero crossings



Canny



Canny edge detector

- Comparing other edge detectors

input




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH



LoG zero crossings




Canny edge detector

- Comparing other edge detectors


input




Sobel with TH



LoG zero crossings



Canny



A canny player with a Canny edge!



A canny player with a Canny edge!




Messi

A canny player with a Canny edge!




Messi



A canny player with a Canny edge!



Messi




Sobel


A canny player with a Canny edge!



Messi




Sobel



A canny player with a Canny edge!



Messi



Sobel




Laplacian

A canny player with a Canny edge!



Messi



Sobel



Laplacian




A canny player with a Canny edge!



Messi



Sobel



Laplacian




Canny

A canny player with a Canny edge!



Messi

who will you
go with?



Sobel



Laplacian



Canny

Conclusion

- Canny edge detector

Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Conclusion

- Canny edge detector

□ Single point thick edges

□ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses



Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Go with a 'canny' player, for accuracy



Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Go with a 'canny' player, for accuracy

And with uSΘin BΘLt, for speed!



Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Go with a 'canny' player, for accuracy

And with uSΘin BΘLt, for speed!

