

Accurate estimation of neural population dynamics without spike sorting

S. Lahiri³ E.M. Trautmann¹ S.D. Stavisky^{1,2} K.C. Ames^{1,8} M.T. Kaufman^{1,9} D.J. O'Shea^{1,5} S. Vyas⁶ X. Sun⁶ S.I. Ryu^{4,10} S. Ganguli^{3,5,7} K.V. Shenoy^{1,5,7}

¹Neurosciences Program, Depts of ²Neurosurgery, ³Applied Physics, ⁴Biology, ⁵Electrical Engineering, ⁶Bioengineering, ⁷Neurobiology, Stanford University, ⁸Dept of Neuroscience, Columbia University, ⁹Dept of Organismal Biology and Anatomy, University of Chicago, ¹⁰Palo Alto Medical Foundation

Background

Spike sorting is laborious \Rightarrow miserable students / grumpy postdocs.

Manual methods: several hours, different people \rightarrow different results.

Automatic methods: promising, but computationally intensive, sensitive to electrode drift, no ground truth.

When studying popn. dynamics (PSTH geometry) or using dim. reduction: doesn't matter if axes are aligned with neurons.

[tedious twitter row re. #manifolds].

We argue that, in such situations, spike sorting may be unnecessary.

[Trautmann et al. 2017]

Random Projections


Neural recordings as projections

Relevant neurons \rightarrow Recorded neurons \rightarrow Electrodes.

Both steps are projections. Spike sorting \sim "unprojection".

Previous work argued: 1st projection \Rightarrow distorted popn. dynamics.

Does the same logic apply to the 2nd projection?



Theory of random projections

Distortion of S under a projection **A**:

$$\epsilon = \min_{\lambda} \max_{\mathbf{x}, \mathbf{y} \in S} \frac{|\lambda \|\mathbf{A}(\mathbf{x} - \mathbf{y})\| - \|\mathbf{x} - \mathbf{y}\||}{\|\mathbf{x} - \mathbf{y}\|}$$


λ : don't care about overall scale.

Theory of random projections:

$$\epsilon^2 \sim \frac{\log ntc}{M} + \frac{K}{M} \dots$$

[Clarkson 2008; Eftekhar and Wakin 2015; Lahiri et al. 2016]

N: #Neurons, M: #Electrodes, K: #Task variables,
ntc: Neural task complexity \sim Task volume / neural corr. volume.



Potential problems

Projections not random? Special neurons?

Theory doesn't account for noise (multi-unit hash).

These projection matrices are of different types to theory.

Examples

Summing different tuning curves


Simulation: 200 channels, each sums 2-10 neurons.

Tuning curves on same channel correlated $\rho = -\frac{2M}{N}, \dots, 1$.

Amplitude-angle vectors $\sim N(0, \begin{bmatrix} 1 & \rho \\ \rho & 1 \end{bmatrix})$.

$\rho = 0$: each channel has poor, but nonzero, tuning. Across 200 channels – still enough tuning to see structure and decode angle. Because PCA / linear decoder care about directions, not units.

Has to get very anti-correlated to see much distortion.



Simulations

Truly random projections: simulated PSTHs

See if random projection theory applies.

Simulate randomly oriented PSTHs to compare with data

$$e_\mu(t, c) = \sum_n A_{\mu n} r_n(t, c) + h_\mu(t, c),$$

$$r_n(t, c) = R(t, c) + \beta_r(z_n(t, c) + k_r z(t, c)),$$

$$h_\mu(t, c) = H(t, c) + \beta_h(\epsilon_\mu(t, c) + k_h \epsilon(t, c)) + \frac{1}{N} \sum_n (M k_s A_{\mu n} + k_d) r_n(t, c),$$

e_μ, r_n, h_μ : PSTHs of electrodes, neurons, multiunit hash.

$Z_n, Z, \epsilon_\mu, \epsilon$: independent Gaussian processes with covariance across t, c fit.

$\beta_r, \beta_h, k_r, k_h, k_s, k_d$: constants fit to 2nd order stats across units.


R, H: means across t, c .
 $A_{\mu n}$: projection matrix.

Neural dynamics of reaching from Neuropixels

Instructed delay reaching task.

Recording: Neuropixel probes in PMd.
 \Rightarrow excellent spike sorting.

Distortion higher than Utah array cases.




Neural dynamics of reaching following incorrect/absent preparation

Is preparatory neural state necessary for accurate reaches?

No delay period/change target @ go-cue
 \rightarrow bypass preparatory state.

[Ames et al. 2014]




Neural population dynamics during reaching

Churchland et al. argue: motor cortex uses oscillatory basis functions to construct complex time-varying signals to control muscles.

Rotational dynamics: from fast, short patterns in individual firing rates.

[Churchland et al. 2012]



Does summing units wash out precise temporal features?

Cortical activity in the null space: preparation without movement

Large firing rate changes in delay period \rightarrow motion?


#Neurons > #Muscles

\Rightarrow some neural directions cause movement.


Use output-null directions during delay, output-potent during motion.

Note: different directions, not different neurons.

[Kaufman et al. 2014]



Comparing data, simulation and theory



Discussion

Conclusions

Don't need to spike sort if you're studying (simple) manifolds.

Place electrodes further apart?

Theory of random projections \Rightarrow domain of validity?

We need a theory of noisy random projections.

References

- Eric Trautmann, Sergey Stavisky, Subhaneil Lahiri, Katherine Ames, Matthew Kaufman, Stephen Ryu, Surya Ganguli, and Krishna Shenoy, "Accurate estimation of neural population dynamics without spike sorting", (December, 2017), [bioRxiv:229252](https://arxiv.org/abs/1712.02925).
- Peiran Gao, Eric Trautmann, Byron M. Yu, Gopal Santhanam, Stephen Ryu, Krishna Shenoy, and Surya Ganguli, "A theory of multineuronal dimensionality, dynamics and measurement", (November, 2017), [bioRxiv:214262](https://arxiv.org/abs/1711.06058).
- Kenneth L. Clarkson, "Tighter Bounds for Random Projections of Manifolds". In Proc. 24th Annual Symp. on Computational Geometry, SCG '08, pages 39–48, New York, NY, USA, 2008. ACM. ISBN 978-1-60558-071-5.
- Arman Etekhari and Michael B. Wakin, "New analysis of manifold embeddings and signal recovery from compressive measurements", *Appl. Comput. Harmon. Anal.*, 39(1):67–109, (2015), [arXiv:arXiv:1306.4748v1](https://arxiv.org/abs/1306.4748v1).
- Subhaneil Lahiri, Peiran Gao, and Surya Ganguli, "Random projections of random manifolds", (July, 2016), [arXiv:1607.04331 \[stat.ML\]](https://arxiv.org/abs/1607.04331).
- K. Cora Ames, Stephen I. Ryu, and Krishna V. Shenoy, "Neural dynamics of reaching following incorrect or absent motor preparation.", *J. Neurosci.*, 31(2):438–451, (January, 2014).
- Mark M Churchland, John P Cunningham, Matthew T Kaufman, Justin D Foster, Paul Nuyujukian, Stephen I Ryu, and Krishna V Shenoy, "Neural population dynamics during reaching.", *Nature*, 487(7405):51–56, (July, 2012).
- Matthew T Kaufman, Mark M churchland, Stephen I Ryu, and Krishna V Shenoy, "Cortical activity in the null space: permitting preparation without movement", *Nature Neuroscience*, 17(3):440–448, (February, 2014).

Acknowledgments

We thank Tim Harris (Janelia), Barun Dutta (IMEC), Wei-Jung Sun (Janelia), Nick Steinmetz (UCL), Bill Karsch (Janelia) for patient assistance setting up recordings with Neuropixels probes and setting an example of what large-scale collaborations and open tools can accomplish. In addition, we thank Will Allen for assistance and sharing helpful experience with Neuropixels. We thank M. Risch, M. Wechsler, J. Aquayo, C. Sherman, E. Morgan, and Robyn Reeder, for surgical assistance and veterinary care; B. Davis, and E. Castaneda for administrative support; and B. Oskolsky for information technology support. This work was supported by the NIH NRSA 1F31NS083483 (E.M.T.), 1F31NS103409-01, an NSF Graduate Research Fellowship, (E.M.T., C.K.A.), NSF GRFP (S.D.S., M.T.K.), the NSF IGERT 0734683 (E.M.T., S.D.S.), 1F31NS103409-01, an NSF Graduate Research Fellowship, (S.I.R. and K.V.S.), and the Simons Foundation (S.V.). The work was supported by the NIH NIBIB 5R01MH09964703, and the Simons Foundation. S.G. and S.L. are supported by the Burroughs Wellcome Fund Career Awards in the Biomedical Sciences, DARPA REPAIR grant N66001-10-C-2010 and NeuroFAST grant W911NF-14-2-0013, NINDS grant R01NS076460, NICHD grant R01HD075623-04, NIMH grant 5R01MH09964703, and the Simons Foundation. S.G. and S.L. are supported by the Burroughs Wellcome Fund, Sloan, Simons, McKnight, and James S. McDonnell foundations, the Howard Hughes Medical Institute, and the Office of Naval Research.