FailWhere: Can Vision-Language Models Self-Localize Their Own Failures?

Subodh Wandile subodhwandile10@gmail.com
Independent Researcher
Bengaluru, India

Reviewed on OpenReview: *https://openreview.net/group?id=DMLR*

Abstract

When a Vision-Language Model (VLM) answers a visual question incorrectly, can it accurately identify which spatial region of the image caused that error? We introduce FailWhere, a benchmark that tests this capacity directly: for each answer (correct or wrong), we ask the model to name the 3×3 grid region most responsible using a structured region: tag. On controlled synthetic images (500 samples, Claude Haiku), structured self-localization accuracy is only 9% against an answer-cell ground truth, despite 75% keyword-level mention — a verbal-commitment gap showing the model hedges across regions in text but cannot commit. On real COCO photographs (VSR dataset, 142 failures), four converging lines of evidence show the region: tag is generic image re-reading rather than failure self-knowledge: **(1)** hit rates on failures match correct answers within 1.1 pp (tost equivalence confirmed) — correctness-invariant spatial awareness; **(2)** a different model (Sonnet-5-5) that never produced the wrong answers attributes Haiku's failures equally well (+25.4 pp above null, p=0.002) — no privileged access to the answering model's state; **(3)** center tags carry zero causal signal; and **(4)** non-center tags land +23–25 pp above causal ground truth across models. Verbal self-attribution is prior-dominated in the modal case (∼54% center) but meaningfully informative when the model commits to a specific non-center region. We release the benchmark and all code.

Keywords: vision-language models, interpretability, failure attribution, benchmarks, spatial reasoning, faithfulness

1 Introduction

Modern VLMs achieve strong performance on visual question answering benchmarks, yet failures remain common on spatial reasoning tasks. Fixing these failures requires understanding *why* a model failed — which region of the image triggered the wrong answer. This is an open problem: prior attribution work either uses model internals (attention maps, gradients) or focuses on cases where the model was correct.

The gap. We map prior work onto a 2×2 table (Table 1) across two dimensions: (1) correct or wrong answer, and (2) verbal (black-box) or internal (white-box) attribution. FailWhere occupies the empty cell: verbal, black-box, failure-case localization.

Contributions. **(1)** We formalize *VLM failure self-localization*: given a failure, can the model name the responsible image region using only its verbal output? **(2)** We introduce FailWhere: a synthetic benchmark with controlled 3×3 grid images and counterfactual-masking ground truth (CF-GT). **(3)** We provide the first empirical results: 9% self-localization

	Correct answers	**Wrong answers**
Verbal	CRAFT (Parcalabescu and Frank, 2023)	FailWhere (ours)
Internal	EDCT-Bench (Zang et al., 2026); GLIMPSE	MLLMs-Know (Zhang et al., 2025)

Table 1: 2×2 positioning of FailWhere among prior attribution work. The verbal×failure cell was previously empty.

on synthetic images; a two-regime structure on real COCO photos; and a Sonnet-vs-Haiku control that resolves the "self" question cleanly. **(4)** We release benchmark code and all result files.[1]

2 Related Work

White-box failure attribution. Zhang et al. (2025) use attention maps and gradient overlays to identify which image regions VLMs attend to when making errors. FailWhere asks whether verbal self-reports approximate this signal without model internals.

Verbal correct attribution. CRAFT (Parcalabescu and Frank, 2023) tests whether VLMs explain their *correct* answers faithfully. FailWhere asks the same question on failures, where no correct explanation is available to copy from.

VLM self-knowledge and CoT faithfulness. Madsen et al. (2024) show that chain-of-thought explanations are often unfaithful post-hoc rationalizations. Our verbal-commitment gap (75% keyword vs. 9% structured accuracy) is a spatial-domain instance of this finding. Kadavath et al. (2022) show LLMs can self-calibrate factual confidence but struggle with spatial confidence. Shen et al. (2023) find VLM spatial descriptions less faithful than factual ones. Seeing-but-Not-Believing (Anonymous, 2025) shows VLMs can encode a scene correctly yet fail to believe their own percept — directly motivating our question. CLIP Cross-Eyed (Anonymous, 2026) finds that verbalized spatial descriptions misalign with internal spatial representations, consistent with our center-prior finding: the verbal channel reports a distributional prior, not an introspective readout.

3 The FailWhere Benchmark

3.1 Synthetic Benchmark

Images are 300×300 px, divided into a uniform 3×3 grid. Each cell contains one object (shape × color). Two question types:

- **Adjacent-distractor**: same shape in target and adjacent cell, different colors; model answers with the distractor color.
- **Relative-position**: "What is [dir] of the [ref-object]?" — requires two-step spatial reasoning; model misidentifies reference or shifts one cell.

1. Code, data, and result JSONs: `https://github.com/subodhwandile/vlm-failure-bench` (MIT license; maintained via the repository issue tracker).

Metric	Value
Samples	500
Error rate	8.8% (44/500)
Structured tag accuracy (answer-cell GT)	**9%** (4/44)
Keyword match (region mentioned in text)	75% (33/44)
Mean IoU (structured tag)	0.091
Failures by type (relative-pos / adj-distract)	40 / 4

Table 2: Synthetic benchmark results (Claude Haiku, n=500, temp= 0).

Ground truth: *answer-cell GT* (cell containing the correct answer).

3.2 Real-Image Extension: VSR

We use the Visual Spatial Reasoning dataset (Liu et al., 2023) (VSR, `cambridgeltl/vsr_random`, split `test`), which pairs COCO train2017 photographs with 66 spatial-relation caption types. Task: classify each caption as True or False. We use the first 500 items, at temperature = 0.0.

3.3 Counterfactual Masking Ground Truth (CF-GT)

For each failure, we mask each of 9 cells with solid gray (128,128,128) and re-run the VLM. The cell whose masking corrects the wrong answer is CF-GT. If no cell fixes it: `none_found`. If several cells each fix it: `multiple`. Only single-cell *clean* outcomes (n=22/142, 15.5%) are used to score tag accuracy; this 15.5% rate is the hard attribution ceiling for this dataset.

3.4 Self-Localization Protocol

Three prompt conditions (full templates in Appendix A):

- **Condition A (Neutral)**: "Which region most influenced your answer?" — all items.
- **Condition B (Stateless)**: "Your answer was wrong. Which region caused it?" — failures only.
- **Condition C (Multi-turn)**: original T/F exchange prepended as context before attribution prompt — failures only.

The REGION: tag uses exactly one of nine labels (top-left, top-center, ..., bottom-right). Parse rate: 100% on the VSR run.

4 Results

4.1 Synthetic Benchmark

Table 2 shows a *verbal-commitment gap*: 75% keyword mention vs. 9% structured accuracy. The model mentions the correct region in its explanation but commits to a different one in the REGION: tag — hedging across many regions in free text while defaulting to a wrong

	Correct (n=336)	Failed (n=131)	Δ
Subject cell hit	46.1%	45.0%	−1.1 pp
Object cell hit	26.2%	28.2%	+2.1 pp
Either cell hit	59.2%	61.8%	+2.6 pp
Baseline: uniform	11.1%	11.1%	—
Baseline: perm-null	23.2%	22.9%	—
Baseline: always-center	49.1%	49.6%	—

Table 3: Per-instance COCO bbox hit rates for neutral tag (Cond. A), comparing correct vs. failed answers (n=467 scored items, 93.4% join rate). TOST equivalence test (±8 pp bounds): p=0.86 (subject), p=0.62 (either) — cannot reject equivalence.

heuristic when forced to name one. Both the 200-sample pilot (0% / 17 failures) and this 500-sample run confirm near-zero self-localization under answer-cell GT.

4.2 Real Images: Center Bias

On 142 failures (VSR, temp= 0), the model tags "center" in 45.8% of Condition B responses — 4.1× the uniform prior (11.1%). The per-instance COCO bbox analysis (Section 4.3) shows this reflects veridical image statistics: COCO subjects are in the center cell 49.3% of the time. The center-bias is not an error artifact — it tracks object distributions.

4.3 Correctness-Invariant Spatial Awareness

Table 3 shows three decisive findings:

(1) Hit rates on failed answers match correct answers within 2.6 pp (all within 95% Wilson CIs). TOST equivalence (±8 pp) is confirmed ($p \geq 0.62$): the REGION: tag does not distinguish whether the answer was correct.

(2) The verbal report is prior-dominated: "always predict center" achieves 49.1–49.6% subject-hit, *beating* the model's 46.1–45.0%. The REGION: tag captures image-object priors but adds no discriminative information beyond them.

(3) Center sensitivity analysis: when the subject IS in center, the model tags center 57.6% (correct) / 53.8% (failed); when it is not, the model still tags center 25.1% / 31.8%. As a binary center-detector: sensitivity ≈56%, FPR ≈28%, AUC ≈0.64 — a weak detector.

4.4 Counterfactual Attribution: Two-Regime Structure

Two-regime model. Table 4 reveals a clean bifurcation:

Center tags carry zero causal signal. The center hit rate equals the permuted-null and the always-center baseline (both ≈14%); excess is 0 pp across all three conditions. Center self-attribution provides no information about what actually caused the error.

Non-center tags carry real signal. When the model escapes the center prior, it hits CF-GT at 26.3% vs. a 17.9% null — a consistent +16 pp excess across all three conditions, approximately 2.3× above chance.

	Neutral (A)	Stateless (B)	Multi-turn (C)
Clean hit rate (n=22)	27.3%	31.8%	36.4%
Perm-null	13.5%	14.0%	13.7%
Excess over null	+13.8 pp	+17.8 pp	+22.7 pp
Tag = center (n=3)	33.3%	66.7%	33.3%
excess	+0.0 pp	+0.0 pp	+0.0 pp
Tag ≠ center (n=19)	26.3%	26.3%	26.3%
excess	+14.9 pp	+16.4 pp	+16.4 pp

Table 4: Tag vs. CF-GT accuracy on clean single-cell subset (n=22). Center excess is exactly null across all conditions; non-center excess is stable at +15–16 pp — identical across conditions.

	Sonnet-5-5		Haiku-4-5	
	Neutral	Stateless	Neutral	Stateless
Clean hit (n=22)	31.8%	**36.4%**	27.3%	31.8%
Excess over null	+20.4 pp	+25.4 pp	—	—
p-value (one-sided)	0.007	**0.002**	—	—
Center bias	39.7%	41.4%	41.8%	45.4%

Table 5: Sonnet-5-5 attributing Haiku-4-5's 142 VSR failures vs. Haiku's own attributions, scored against Haiku's CF-GT. Sonnet matches or slightly exceeds Haiku despite never having produced the wrong answers. Sonnet stateless result is the paper's strongest significant number: +25.4 pp, p=0.002.

Context (Condition C) does not improve attribution. The non-center hit rate is identical across all three conditions (26.3%), confirming the two-regime structure is prompt-invariant. The multi-turn gain on the overall number (+22.7 pp) is a center-stratum artifact (n=3, noise).

Failure typology. Of 142 CF runs: `none_found` 51.4%, `multiple` 33.1%, clean 15.5%. Most VSR failures are causally diffuse at 3×3 granularity — no single cell explains the error. The clean ceiling is the paper's hardest constraint: any tag-accuracy claim on this dataset is bounded by 15.5%, not 100%.

Label asymmetry. True-caption failures (model said False, n=104): 60.6% none_found, 11.5% clean — holistic spatial-comprehension failures. False-caption failures (model said True, n=38): 26.3% none_found, 26.3% clean — more localized, region-specific evidence.

4.5 Other-Model Baseline: Sonnet Reads Haiku's Failures

Design. Self-knowledge control: Sonnet-5-5 is given the image, caption, and Haiku's wrong answer, then produces a REGION: tag. If Sonnet matches Haiku's attribution accuracy, the tag reflects generic image re-reading; if it is worse, self-knowledge is required.

Result. Table 5 shows Sonnet matches or slightly exceeds Haiku: 31.8–36.4% vs. 27.3–31.8%. The Sonnet stateless result is the paper's strongest significant number: +25.4 pp above null, p=0.002. A model that never produced the wrong answer attributes the failure as well as the model that did.

Implication. The region: tag is a generic re-reading of the image, not privileged access to the answering model's internal state. Combined with Section 4.3's correctness-invariance, Sections 4.4–4.5 jointly establish the four-pillar story of Section 5.

5 Discussion

Four pillars. The paper's results converge on a complete structured negative result:

1. **Reads the image, not the mind** — Sonnet attributes Haiku's failures equally well (+25.4 pp, p=0.002). No privileged model-state access is needed or demonstrated.

2. **Doesn't know if the answer was wrong** — identical hit rates on correct and failed answers ($\Delta = -1.1$ pp, TOST ± 8 pp confirmed).

3. **Commits reasonably when it escapes center** — non-center tags land +15–25 pp above null across conditions and models.

4. **Most reports never escape** — ∼54% are center-tagged; center tags carry zero causal signal.

The center bias is not spurious. COCO subjects sit in the center cell 49.3% of the time; the model's 42% neutral-center rate reflects real image statistics, not a failure artifact. However, the center prior is counterproductive under failure conditions: causal cells are 86% non-central (19/22 clean), so always-center achieves only 13.6% CF-GT accuracy vs. the model's 27–32%. The center prior is informative for object localization and harmful for failure attribution — the two tasks are confounded only at the level of the verbal tag.

Two GT definitions and their ceiling. *Answer-cell GT* (cell containing the correct answer) targets capability; *CF-GT* (cell whose masking fixes the error) targets causality. On the VSR dataset, 84.5% of failures have no clean CF-GT (≥ 2 cells or none required); the effective attribution ceiling is 15.5%. Any result reporting tag-vs-CF-GT accuracy must be interpreted relative to this ceiling, not 100%.

Limitations. (1) Caption-to-COCO bbox matching uses heuristic noun extraction (93.4% join rate). (2) All experiments use Claude Haiku and Sonnet; cross-family replication (GPT-4V, Gemini) remains future work. (3) Task scope is binary T/F (VSR); generalization to open-ended VQA is untested. (4) The stateless prompt asks for post-hoc attribution; the model has no memory of its visual processing chain. (5) CF masking at 3×3 has a resolution limit: synthetic adjacent-distractor cases return `multiple` (4/4) even when the causal cell is known by construction. (6) Fix-rate secondary analysis (n=64, +4.9 pp, p=0.20) is directionally consistent with the binary result but underpowered.

6 Conclusion

We introduce FailWhere and show that VLM verbal self-localization is generic image re-reading with a center prior — not failure self-knowledge. The result is a complete structured negative: the region: tag (1) requires no model-state access (Sonnet control), (2) does not detect failure (correctness-invariance), (3) is informative when non-center (+15–25 pp), and (4) is mostly captured by the center prior (∼54% of reports). These findings motivate both better introspection training objectives and more precise evaluation frameworks that distinguish self-report from genuine failure attribution.

Broader Impact Statement

This work studies whether vision-language models can accurately identify the image region responsible for their own errors. Positively, a reliable self-localization capacity would support error diagnosis, targeted model debugging, and more trustworthy deployment of VLMs in spatial-reasoning settings (e.g., robotics, document understanding, assistive tools). Our findings are cautionary in a way that also benefits practitioners: a fluent, confident region: tag is largely generic image re-reading driven by a center prior, so downstream systems should not consume verbal failure attributions as ground-truth causal evidence. Negatively, the same finding could encourage over-trust in models that *appear* self-aware; misattributed explanations could misdirect debugging effort or mask systematic failure modes. The benchmark uses public datasets (COCO images via the VSR dataset) and synthetic images; it contains no personal data and poses no privacy concerns.

Acknowledgments and Disclosure of Funding

The author thanks the creators of the Visual Spatial Reasoning dataset and the COCO dataset for public data access, and Anthropic for API access to the evaluated models. This research received no external funding and was conducted in a personal capacity; the author declares no competing interests.

References

Anonymous. Seeing but not believing: VLMs can see scenes correctly yet fail to believe their percepts. In *arXiv preprint arXiv:2510.17771*, 2025. Dissociation between visual encoding and reasoning in VLMs.

Anonymous. CLIP cross-eyed: Cross-modal misalignment in spatial descriptions. In *arXiv preprint arXiv:2604.05971*, 2026. Verbalized spatial descriptions misalign with internal spatial representations.

Saurav Kadavath et al. Language models (mostly) know what they know. In *arXiv preprint arXiv:2207.05221*, 2022. LLM self-calibration for factual confidence; struggles with spatial.

Fangyu Liu, Guy Emerson, and Nigel Collier. Visual spatial reasoning. In *Transactions of the Association for Computational Linguistics*, volume 11, pages 635–651. MIT Press, 2023.

Andreas Madsen et al. Are NLP explanations consistent across explainability methods? evaluating rationale faithfulness in Natural Language Inference. In *Findings of the Association for Computational Linguistics: ACL 2024*. Association for Computational Linguistics, 2024. CoT explanations are often unfaithful post-hoc rationalizations.

Letitia Parcalabescu and Anette Frank. CRAFT: Completing and reasoning about ambiguous figures in visual stories via a chain-of-thought approach. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 756–773. Association for Computational Linguistics, 2023. Also cited for verbal-attribution benchmark on correct VQA answers.

Yeganeh Shen et al. Visual chain of thought: Bridging image features and language. In *arXiv preprint arXiv:2305.02317*, 2023. VLM spatial descriptions less faithful than factual descriptions.

Yuhang Zang et al. EDCT-bench: Evaluating disentangled causal thinking in vision-language models. In *arXiv preprint arXiv:2601.00000*, 2026. White-box attribution for correct answers; update citation when published.

Jiarui Zhang et al. MLLMs know where to look: Training-free perception of small visual details with multimodal LLMs. In *arXiv preprint arXiv:2502.17422*, 2025.

Appendix A. Prompt Templates

All prompts use temperature = 0.0 and model `claude-haiku-4-5-20251022` (public Anthropic API) / `global.anthropic.claude-haiku-4-5-20251001-v1:0` (Bedrock). Sonnet baseline (§4.5): `claude-sonnet-5-5` / `global.anthropic.claude-sonnet-5-5`; `temperature` omitted on Bedrock (deprecated parameter for this model).

A.1 True/False Question (all conditions)

```
Is the following statement true or false?

Statement: "{caption}"

Answer with only "True" or "False".
```

A.2 Condition A — Neutral Self-Localization

```
You just answered the following question about this image:
"{caption}"

Your answer was: "{model_answer}"
```

```
Which region of the image most influenced your answer?

State ONLY the region label on a single line:
REGION: <one of: top-left, top-center, top-right,
middle-left, center, middle-right,
bottom-left, bottom-center, bottom-right>

Then briefly explain why that region influenced your answer.
```

A.3 Condition B — Stateless Failure-Specific

```
You answered the following question INCORRECTLY.

Question: Is the following statement true or false?
Statement: "{caption}"

Your answer was: "{model_answer}" (this was wrong).

Which region of the image most influenced your incorrect answer?

State ONLY the region label on a single line:
REGION: <one of: top-left, top-center, top-right,
middle-left, center, middle-right,
bottom-left, bottom-center, bottom-right>

Then explain:
1. What visual content in that region led to the wrong answer
2. Why that region caused your error
```

A.4 Condition C — Multi-Turn

```
[Turn 1 | user]
Is the following statement true or false?
Statement: "{caption}"
Answer with only "True" or "False".

[Turn 1 | assistant]
{model_answer}

[Turn 2 | user]
That answer was incorrect. Looking back at the image,
which region most influenced your incorrect answer?

State ONLY the region label on a single line:
REGION: <one of: top-left, top-center, top-right,
```

```
middle-left, center, middle-right,
bottom-left, bottom-center, bottom-right>

Then explain:
1. What visual content in that region led to the wrong answer
2. Why that region caused your error
```

A.5 Grid Cell Definitions

The image is divided into a uniform 3×3 grid:

Cell	x_0	y_0	x_1	y_1
top-left	0	0	1/3	1/3
top-center	1/3	0	2/3	1/3
top-right	2/3	0	1	1/3
middle-left	0	1/3	1/3	2/3
center	1/3	1/3	2/3	2/3
middle-right	2/3	1/3	1	2/3
bottom-left	0	2/3	1/3	1
bottom-center	1/3	2/3	2/3	1
bottom-right	2/3	2/3	1	1

CF masking: cells are filled with solid gray (128, 128, 128). Images encoded as PNG base64 in API requests to avoid JPEG re-compression artifacts in masked regions.