# 3.3.4 Practice Questions

Candidate: Ethan Bonavida (suborange)

**Date:** 11/14/2022 11:23:45 pm • **Time Spent:** 00:47

Score: 100% Passing Score: 80%

| $\blacksquare$ | Question ' | 1: | ✓ Correct | t |
|----------------|------------|----|-----------|---|
|----------------|------------|----|-----------|---|

Your Linux system was installed for you while you were living in the United States of America. You have since been transferred to a satellite office located in Wood Walton, England, and have taken your computer with you.

Since England uses the larger A4 paper size, you would like to change the LC\_PAPER locale environment variable.

Which of the following is the BEST shell command to use for this purpose?

| ec | ho |  |
|----|----|--|
|    |    |  |

- locale
- iconv
- → localectl
  - export

### **Explanation**

The **localectl** command is used to change locale environment variables. For example, the following command would be used to change the LC\_PAPER locale environment as described in the question:

## localectl set-locale LC\_PAPER=en\_GB.UTF-8

**locale** displays the current locale settings for the computer.

**echo** can be used to view the current locale settings if one has been set. This is accomplished by typing **echo** followed by a dollar sign (\$) and then the name of the environment variable that you want to view.

**Iconv** reads in text using one type of encoding and outputs the text in using another encoding type.

#### References

3.3.3 Localization Facts

q\_local\_facts\_lp5\_01.question.fex

| 1/14/22, 11:23 PM  | TestOut LabSim   |  |  |  |  |
|--|------------------|--|--|--|--|
| <b>▼</b> Question 2:   | <b>✓</b> Correct |  |  |  |  |
| Which environment variable overrides all other locale settings and sets all locales to the same setting?   |                  |  |  |  |  |
| LC_ALL   |                  |  |  |  |  |
| Explanation  |                  |  |  |  |  |
| <b>LC_ALL</b> is a special variable for overriding all other settings. It sets all locales to the same setting. A locale is a set of files that Linux uses to determine country and language-specific settings for various applications. |                  |  |  |  |  |
| References   |                  |  |  |  |  |
| ≔ 3.3.3 Localization   | Facts            |  |  |  |  |
| a local facts In5 02 a   | uestion fev      |  |  |  |  |



**▼** Question 3:

✓ Correct

Match the locale environmental variable name on the left with the description on the right. Specifies personal name format.



✓ LC\_NAME

Specifically used an override for LC\_MESSAGES.



LANGUAGE

A special variable for overriding every other evironment setting. It sets all locales to the same setting.



LC ALL

Defines every locale setting at once while allowing further individual customization via the LC\_\* settings.



LANG

## **Explanation**

A locale is a set of files that Linux uses to determine country and language-specific settings for various applications. Be aware of the following environmental variables:

LANG defines all locale settings at once while allowing further individual customization via the LC \* settings. LANGUAGE is used as an override for LC MESSAGES. LC ALL is a special variable for overriding all other settings. It sets all locales to the same setting, LC NAME specifies personal name format. This includes things like whether the surname comes first or last.

#### References



3.3.3 Localization Facts

q\_local\_facts\_lp5\_03.question.fex



You are trying to pipe data from the **cat** command to another program, but the data output does not make sense. You believe that the system's locale is corrupting the output. To test your hypothesis, you decide to change a locale environment variable.

Which of the following changed variable would MOST likely produce correct data?

- LC\_COLLATE=C
- LC\_NAME=C
- LC\_NUMERIC=C
- → LANG=C

## **Explanation**

When the LANG variable is set to LANG=C, programs will display their output without passing it through the locale translation. This is helpful when the output is being corrupted by the system's locale variables and will help avoid some types of problems, such as when using pipelines and scripts that pass on a program's data to another program in binary form.

Changing any of the following to variable=C will not provide the desired results.

LC\_NAME specifies personal name format. This includes things such as whether the surname comes first or last.

LC\_NUMERIC defines formatting for numeric values that are not monetary. It affects things such as the thousands separator and the decimal separator.

LC\_COLLATE defines the alphabetical ordering of strings. This affects the output of sorted directory listings.

## References

3.3.3 Localization Facts

q\_local\_facts\_lp5\_04.question.fex

**▼ Question 5:** ✓ Correct

Which of the following character sets is a variable length encoding standard of Unicode that uses one to four 8-bit bytes to support many languages and most commonly used on Linux?

- **→** ① UTF-8
  - LANG
  - LC\_ALL
  - ASCII

## **Explanation**

UTF-8 is a variable-length encoding standard of Unicode and is capable of encoding all 1,112,064 valid code points in Unicode using one to four 8-bit bytes. UTF-8 can support many languages and accommodate pages and forms in any mixture of those languages. Its use also eliminates the need for server-side logic to individually determine the character encoding for each page served or each incoming form submission.

ASCII (American Standard Code For Information Interchange) is a seven-bit encoding technique that assigns a number to each of the 128 characters used most frequently in American English.

LANG defines all locale settings at once while allowing further individual customization via the LC\_\* settings.

LC\_ALL sets all locales to the same setting.

#### References

□ 3.3.3 Localization Facts

q\_local\_facts\_lp5\_utf8.question.fex

| ▼ Question 6: ✓ Correct   |  |  |
|---|--|--|
| Which of the following are true about the ASCII character set? (Choose TWO.)  |  |  |
| Is not compatible with UTF-8.   |  |  |
| Support international characters.   |  |  |
| → ✓ Does not include international symbols.   |  |  |
| → V Uses a seven-bit encoding technique.  |  |  |
| Uses a variable-length encoding standard.   |  |  |
| Explanation   |  |  |
| ASCII uses a seven-bit encoding technique. Since Unicode (when using UTF-8) is ASCII-compatible, plain ASCII text still renders properly on modern UTF-8 using systems. However, ASCII does not include symbols frequently used in other countries, such as the British pound symbol (£). |  |  |
| UTF-8 uses a variable-length encoding standard and supports international characters, whereas ASCII does not.   |  |  |
| References  |  |  |
| 3.3.3 Localization Facts  |  |  |
| q_local_facts_lpt_ascii.question.fex  |  |  |

Copyright © 2022 TestOut Corporation All rights reserved.