# Рабочее место №0

## Б1 Полные доменные имена

**R-DT (20007)**
*show hostname*

```
show hostname



r-dt


r-dt#
```

*sh run | i ip domain-name*

```
sh run | i ip domain-name



ip domain-name au.team


r-dt#
```

**FW-DT (20006)**
*hostnamectl hostname*

```
fw-dt.au.team
```

**SW1-HQ (20013)**
*hostnamectl hostname*

```
sw1-hq.au.team
```

**CLI-HQ (20008)**
*hostnamectl hostname*

```
cli-hq.au.team
```

## Б1 Офис HQ имеет правильную адрессацию

**FW-DT (20006)**
*ip -br a*

```
lo               UNKNOWN        127.0.0.1/8 169.254.254.254/32 ::1/128
FWtest           UNKNOWN
lb_local_out@lb_local_in UP             169.254.1.6/29
lb_local_in@lb_local_out UP             169.254.1.1/29 169.254.1.2/29
```

```
Leth2            UP             192.168.33.90/30
Leth3            UP
CCwg_cl          UNKNOWN
Lvpn0@if8        UP             169.254.1.4/32
Lvlan330_1@Leth3 UP             192.168.33.81/29
Lvlan220_4@Leth3 UP             192.168.33.65/28
Lvlan110_5@Leth3 UP             192.168.33.1/26
```

# Б1 Офис DT имеет правильную адрессацию

**R-HQ (20014)**
*show ip interface brief*

```
show ip interface brief



 Interface        IP-Address          Status                 VRF

 ----------------------------------------------------------------

 ge0              172.16.5.14/28      up                     default

 ge1.110          192.168.11.1/26     up                     default

 ge1.220          192.168.11.65/28    up                     default

 ge1.330          192.168.11.81/29    up                     default

 tunnel.0         10.10.10.2/30       up                     default


r-hq#
```

# Б1 GRE между DT и HQ

**R-HQ (20014)**
*show interface | i Tunnel*

```
show interface | i Tunnel



  Tunnel source: 172.16.5.14

  Tunnel destination: 172.16.4.14

  Tunnel mode: GRE

  Tunnel keepalive: disabled
```

```
r-hq#
```

**R-DT (20007)**
*show interface | i Tunnel*

```
show interface | i Tunnel



  Tunnel source: 172.16.4.14

  Tunnel destination: 172.16.5.14

  Tunnel mode: GRE

  Tunnel keepalive: disabled


r-dt#
```

# Б1 Адресация в туннеле из требуемого диапазона с маской 30 и/или 31

**R-HQ (20014)**
*show ip interface brief | i tunnel*

```
show ip interface brief | i tunnel



 tunnel.0         10.10.10.2/30       up                      default


r-hq#
```

**R-DT (20007)**
*show ip interface brief | i tunnel*

```
show ip interface brief | i tunnel



 tunnel.0         10.10.10.1/30       up                      default


r-dt#
```

# Б1 На всех устройствах (кроме FW-DT) создан пользователь sshuser с паролем P@ssw0rd

**SRV1-HQ (20010)**
*id sshuser*

```
uid=500(sshuser) gid=500(sshuser) groups=500(sshuser),10(wheel)
```

**SRV1-DT (20002)**
*id sshuser*

```
uid=500(sshuser) gid=500(sshuser) groups=500(sshuser),10(wheel)
```

# Б1 Пользователь sshuser может запускать sudo без пароля

**SRV1-HQ (20010)**
*grep sshuser /etc/sudoers*

```
-- error: no output --
```

**SRV1-DT (20002)**
*grep sshuser /etc/sudoers*

```
-- error: no output --
```

# Б1 Пользователь sshuser на маршрутизаторах имеет максимальные права

**R-DT (20007)**
*show users localdb*

```
show users localdb



User: admin

 Description: Administrator User

 Docker socket access: disabled

 VR:

  pvr

 Roles:

  admin ''

User: daemon

 Description: The user is used to get configuration data

 Docker socket access: disabled
```

```
 VR:

  pvr

 Roles:

  daemon ''

User: sshuser

 Description:

 Docker socket access: disabled

 VR:

  pvr

 Roles:

  admin ''


r-dt#
```

**R-HQ (20014)**

*show users localdb*

```
show users localdb



User: admin

 Description: Administrator User

 Docker socket access: disabled

 VR:

  pvr

 Roles:

  admin ''

User: daemon

 Description: The user is used to get configuration data

 Docker socket access: disabled

 VR:

  pvr
```

```
 Roles:

  daemon ''

User: sshuser

 Description:

 Docker socket access: disabled

 VR:

  pvr

 Roles:

  admin ''


r-hq#
```

# Б1 На SW-DT создан коммутатора с правильным именем, все порты переданы в управление в Open vSwitch

# Б1 На SW-DT порты находятся в соответсующих vlan

**SW-DT (20005)**

*ovs-vsctl show*

```
87fb3e03-20d3-4e49-8960-2b79363e9609
    Bridge SW-DT
        Port eth1
            tag: 220
            Interface eth1
        Port eth2
            tag: 110
            Interface eth2
        Port SW-DT
            Interface SW-DT
                type: internal
        Port MGMT
            tag: 330
            Interface MGMT
                type: internal
        Port eth3
            tag: 330
            Interface eth3
        Port eth0
            Interface eth0
    ovs_version: "2.17.11"
```

# Б1 На SW1-HQ, SW2-HQ, SW3-HQ создан коммутатора с правильным именем

# Б1 На коммутаторах SW1-HQ, SW2-HQ, SW3-HQ порты находятся в соответсующих vlan

**SW1-HQ (20013)**
*ovs-vsctl show*

```
020e0646-571e-404d-815a-7ec4c5d2e89b
    Bridge SW1-HQ
        Port eth1
            Interface eth1
        Port MGMT
            tag: 330
            Interface MGMT
                type: internal
        Port SW1-HQ
            Interface SW1-HQ
                type: internal
        Port eth2
            Interface eth2
        Port eth0
            Interface eth0
    ovs_version: "2.17.11"
```

**SW2-HQ (20012)**
*ovs-vsctl show*

```
7f0be43e-4e25-4061-aa09-22beb65b7e28
    Bridge SW2-HQ
        Port eth2
            tag: 220
            Interface eth2
        Port SW2-HQ
            Interface SW2-HQ
                type: internal
        Port eth0
            Interface eth0
        Port eth3
            tag: 110
            Interface eth3
        Port eth1
            Interface eth1
        Port MGMT
            tag: 330
            Interface MGMT
                type: internal
    ovs_version: "2.17.11"
```

**SW3-HQ (20011)**
*ovs-vsctl show*

```
72b22548-9c8b-44db-8515-49b13d3408fb
    Bridge SW3-HQ
        Port SW3-HQ
            Interface SW3-HQ
                type: internal
        Port eth2
            tag: 330
            Interface eth2
        Port eth0
            Interface eth0
        Port MGMT
            tag: 330
            Interface MGMT
                type: internal
        Port eth1
            Interface eth1
    ovs_version: "2.17.11"
```

# Б1 На коммутаторах SW1-HQ, SW2-HQ, SW3-HQ создан менеджмент порт

**SW1-HQ (20013)**

*ip -br a*

```
lo               UNKNOWN        127.0.0.1/8 ::1/128
eth0             UP             fe80::250:1ff:fe00:d00/64
eth1             UP             fe80::250:1ff:fe00:d01/64
eth2             UP             fe80::250:1ff:fe00:d02/64
ovs-system       DOWN
MGMT             UNKNOWN        192.168.11.82/29 fe80::7ca9:bff:fe84:c492/64
SW1-HQ           DOWN
```

**SW2-HQ (20012)**

*ip -br a*

```
lo               UNKNOWN        127.0.0.1/8 ::1/128
eth0             UP             fe80::250:1ff:fe00:c00/64
eth1             UP             fe80::250:1ff:fe00:c01/64
eth2             UP             fe80::250:1ff:fe00:c02/64
eth3             UP             fe80::250:1ff:fe00:c03/64
ovs-system       DOWN
MGMT             UNKNOWN        192.168.11.83/29 fe80::3470:2aff:fee8:50b1/64
SW2-HQ           DOWN
```

**SW3-HQ (20011)**

*ip -br a*

```
lo               UNKNOWN        127.0.0.1/8 ::1/128
eth0             UP             fe80::250:1ff:fe00:b00/64
eth1             UP             fe80::250:1ff:fe00:b01/64
eth2             UP             fe80::250:1ff:fe00:b02/64
ovs-system       DOWN
```

```
MGMT              UNKNOWN        192.168.11.84/29 fe80::943c:85ff:fe94:fb9b/64
SW3-HQ            DOWN
```

# Б1 На коммутаторах SW1-HQ, SW2-HQ, SW3-HQ натроен STP, корнем является SW1-HQ

**SW1-HQ (20013)**

*ovs-appctl stp/show*

```
---- SW1-HQ ----
Root ID:
  stp-priority  1
  stp-system-id   00:50:01:00:0d:00
  stp-hello-time  2s
  stp-max-age     20s
  stp-fwd-delay   15s
  This bridge is the root

Bridge ID:
  stp-priority  1
  stp-system-id   00:50:01:00:0d:00
  stp-hello-time  2s
  stp-max-age     20s
  stp-fwd-delay   15s

  Interface  Role       State      Cost  Pri.Nbr
  ---------- ---------- ---------- ----- -------
  eth0       designated forwarding 19    128.1
  eth1       designated forwarding 19    128.2
  eth2       designated forwarding 19    128.3
```

**SW2-HQ (20012)**

*ovs-appctl stp/show*

```
---- SW2-HQ ----
Root ID:
  stp-priority  1
  stp-system-id   00:50:01:00:0d:00
  stp-hello-time  2s
  stp-max-age     20s
  stp-fwd-delay   15s
  root-port       eth1
  root-path-cost  19

Bridge ID:
  stp-priority  32768
  stp-system-id   00:50:01:00:0c:00
  stp-hello-time  2s
  stp-max-age     20s
  stp-fwd-delay   15s

  Interface  Role       State      Cost  Pri.Nbr
```

```
  ---------- ---------- ---------- ----- -------
  eth0       alternate  blocking   19    128.1
  eth2       designated forwarding 19    128.2
  eth3       designated forwarding 19    128.3
  eth1       root       forwarding 19    128.4
```

**SW3-HQ (20011)**
*ovs-appctl stp/show*

```
---- SW3-HQ ----
Root ID:
  stp-priority  1
  stp-system-id   00:50:01:00:0d:00
  stp-hello-time  2s
  stp-max-age     20s
  stp-fwd-delay   15s
  root-port       eth0
  root-path-cost  19

Bridge ID:
  stp-priority  32768
  stp-system-id   00:50:01:00:0b:00
  stp-hello-time  2s
  stp-max-age     20s
  stp-fwd-delay   15s

  Interface  Role       State      Cost  Pri.Nbr
  ---------- ---------- ---------- ----- -------
  eth0       root       forwarding 19    128.1
  eth2       designated forwarding 19    128.2
  eth1       designated forwarding 19    128.3
```

# Б1 Маршрутизаторы подключены к провайдеру в соответсвии с заданием

**R-DT (20007)**
*traceroute 192.168.100.1*

```
traceroute 192.168.100.1


traceroute to 192.168.100.1 (192.168.100.1), 30 hops max, 60 byte packets

 1  172.16.4.1 (172.16.4.1)  12.414 ms  12.312 ms  12.223 ms

 2  192.168.100.1 (192.168.100.1)  12.148 ms  12.063 ms  11.987 ms

r-dt#
```

**R-HQ (20014)**
*traceroute 192.168.100.1*

```
traceroute 192.168.100.1


traceroute to 192.168.100.1 (192.168.100.1), 30 hops max, 60 byte packets

 1  172.16.5.1 (172.16.5.1)  17.807 ms  17.704 ms  17.621 ms

 2  192.168.100.1 (192.168.100.1)  17.546 ms  17.459 ms  17.376 ms

r-hq#
```

# Б1 NAT для офиса DT

**R-DT (20007)**
*sh run | i overload*

```
sh run | i overload



ip nat source dynamic inside-to-outside pool NAT overload interface ge0


r-dt#
```

# Б1 NAT для офиса HQ

**R-HQ (20014)**
*sh run | i overload*

```
sh run | i overload



ip nat source dynamic inside-to-outside pool NAT overload interface ge0


r-hq#
```

# Б1 DHCP CLI на R-HQ

**CLI-HQ (20008)**
*ip a | grep dynamic*

```
    inet 192.168.11.2/26 brd 192.168.11.63 scope global dynamic noprefixroute
eth0
```

*ip r | grep default*

```
default via 192.168.11.1 dev eth0 proto dhcp src 192.168.11.2 metric 100
```

*cat /etc/resolv.conf*

```
# Generated by resolvconf
# Do not edit manually, use
# /etc/net/ifaces/<interface>/resolv.conf instead.
search au.team
nameserver 192.168.11.66
nameserver 192.168.33.66
nameserver 192.168.100.1
```

# Б1 DHCP CLI на R-DT

**CLI-DT (20000)**

*ip a | grep dynamic*

```
    inet 192.168.33.2/26 brd 192.168.33.63 scope global dynamic noprefixroute
eth0
```

*ip r | grep default*

```
default via 192.168.33.1 dev eth0 proto dhcp src 192.168.33.2 metric 100
```

*cat /etc/resolv.conf*

```
# Generated by resolvconf
# Do not edit manually, use
# /etc/net/ifaces/<interface>/resolv.conf instead.
search au.team
nameserver 192.168.33.66
nameserver 192.168.11.66
nameserver 192.168.100.1
```

# Б1 OSPF over GRE между DT и HQ

**R-HQ (20014)**

*sh ip ospf neighbor | nopager*

```
sh ip ospf neighbor | nopager




Total number of full neighbors: 1

OSPF process 1 VRF(default):

Neighbor ID     Pri   State           Dead Time   Address         Interface
Instance ID

192.168.33.89     1   Full/DR         00:00:32    10.10.10.1      tunnel.0
0

r-hq#
```

# Б1 OSPF over GRE между DT и HQ passive interface

**R-HQ (20014)**
*sh run | i passive*

```
sh run | i passive



 passive-interface ge0


r-hq#
```

# Б1 OSPF over GRE между DT и HQ authentication

**R-HQ (20014)**
*sh run | i ospf authentication*

```
sh run | i ospf authentication



 ip ospf authentication

 ip ospf authentication-key 0xeb5442f9b26607db


r-hq#
```

# Б1 OSPF между R-DT и FW-DT

**R-DT (20007)**
*sh ip ospf neighbor | nopager*

```
sh ip ospf neighbor | nopager




Total number of full neighbors: 2

OSPF process 1 VRF(default):

Neighbor ID     Pri   State           Dead Time   Address         Interface
Instance ID

192.168.11.81     1   Full/Backup     00:00:39    10.10.10.2      tunnel.0
0
```

```
192.168.33.90     1   Full/Backup      00:00:31    192.168.33.90   ge1
0

r-dt#
```

# Б1 OSPF между R-DT и FW-DT default gateway

**FW-DT (20006)**

*vtysh -c "show ip ospf route"*

```
============ OSPF network routing table ============
N    10.10.10.0/30         [2] area: 0.0.0.0
                           via 192.168.33.89, Leth2
N    192.168.11.0/26       [12] area: 0.0.0.0
                           via 192.168.33.89, Leth2
N    192.168.11.64/28      [12] area: 0.0.0.0
                           via 192.168.33.89, Leth2
N    192.168.11.80/29      [12] area: 0.0.0.0
                           via 192.168.33.89, Leth2
N    192.168.33.88/30      [1] area: 0.0.0.0
                           directly attached to Leth2

============ OSPF router routing table =============

============ OSPF external routing table ===========
```

# Б1 На SRV1-HQ настроен NTP сервер в соответсвии с заданием

**SRV1-HQ (20010)**

*chronyc tracking*

```
Reference ID    : 596DFB16 (ntp2.vniiftri.ru)
Stratum         : 2
Ref time (UTC)  : Tue Mar 11 12:43:35 2025
System time     : 0.000712627 seconds fast of NTP time
Last offset     : +0.000254993 seconds
RMS offset      : 0.003923936 seconds
Frequency       : 10.851 ppm slow
Residual freq   : +0.008 ppm
Skew            : 0.425 ppm
Root delay      : 0.024121687 seconds
Root dispersion : 0.002111900 seconds
Update interval : 1031.0 seconds
Leap status     : Normal
```

*chronyc sources*

```
MS Name/IP address         Stratum Poll Reach LastRx Last sample
===============================================================================
^* ntp2.vniiftri.ru              1  10   377   390  +9465us[+9720us] +/-   20ms
```

# Б1 Все устройства синхронизируют время с SRV1-HQ

**ADMIN-DT (20001)**
*chronyc tracking*

```
Reference ID    : C0A80B42 (srv1-hq.au.team)
Stratum         : 3
Ref time (UTC)  : Tue Mar 11 12:49:34 2025
System time     : 0.000016474 seconds slow of NTP time
Last offset     : -0.000079057 seconds
RMS offset      : 0.000231144 seconds
Frequency       : 10.614 ppm slow
Residual freq   : -0.014 ppm
Skew            : 1.062 ppm
Root delay      : 0.057944983 seconds
Root dispersion : 0.002232254 seconds
Update interval : 65.2 seconds
Leap status     : Normal
```

**CLI-HQ (20008)**
*chronyc tracking*

```
Reference ID    : C0A80B42 (srv1-hq.au.team)
Stratum         : 3
Ref time (UTC)  : Tue Mar 11 12:49:29 2025
System time     : 0.000000957 seconds slow of NTP time
Last offset     : +0.000015230 seconds
RMS offset      : 0.000259154 seconds
Frequency       : 10.172 ppm slow
Residual freq   : +0.008 ppm
Skew            : 1.759 ppm
Root delay      : 0.036755290 seconds
Root dispersion : 0.002357584 seconds
Update interval : 64.8 seconds
Leap status     : Normal
```

**SW1-HQ (20013)**
*chronyc tracking*

```
Reference ID    : C0A80B42 (srv1-hq.au.team)
Stratum         : 3
Ref time (UTC)  : Tue Mar 11 12:49:09 2025
System time     : 0.000778031 seconds slow of NTP time
Last offset     : -0.001725663 seconds
RMS offset      : 0.000865726 seconds
Frequency       : 10.730 ppm slow
Residual freq   : +0.708 ppm
Skew            : 2.827 ppm
Root delay      : 0.037107054 seconds
Root dispersion : 0.002798290 seconds
Update interval : 260.5 seconds
Leap status     : Normal
```

**SRV1-DT (20002)**

*chronyc tracking*

```
Reference ID    : C0A80B42 (srv1-hq.au.team)
Stratum         : 3
Ref time (UTC)  : Tue Mar 11 12:39:21 2025
System time     : 0.000134953 seconds fast of NTP time
Last offset     : +0.000179291 seconds
RMS offset      : 0.000296174 seconds
Frequency       : 10.449 ppm slow
Residual freq   : +0.000 ppm
Skew            : 0.265 ppm
Root delay      : 0.059020948 seconds
Root dispersion : 0.003432851 seconds
Update interval : 1028.8 seconds
Leap status     : Normal
```

**R-DT (20007)**

*show ntp status*

```
show ntp status



Status  Description

*       best

+       sync

-       failed

?       unknown



-------------------------------------------------------------------------------
-[7m>[27m

Status |     VR name     |     Server      | Stratum |   Delay   | Version |
[7m>[27m

-------------------------------------------------------------------------------
-[7m>[27m

      *|         default |   192.168.11.66 |       2 |    0.0637 |       4 |
[7m>[27m
```

**R-HQ (20014)**

*show ntp status*

```
show ntp status
```

# Б1 На клиентах корректный часовой пояс

**R-DT (20007)**
*sh run | i timezone*

```
-
```

**ADMIN-HQ (20009)**
*timedatectl | grep zone*

```
               Time zone: Europe/Saratov (+04, +0400)
```

# Б1 DNS установлен на SRV1-HQ

**SRV1-HQ (20010)**
*whereis bind*

```
bind: /usr/lib64/bind /etc/bind /usr/share/man/man1/bind.1.xz
```

# Б1 Для всех устройств офисов созданы A и PTR

**SRV1-HQ (20010)**
*nslookup r-dt.au.team 127.0.0.1*

```
Server:         127.0.0.1
Address:        127.0.0.1#53

Name:   r-dt.au.team
Address: 192.168.33.89
```

# Б1 Для всех сервисов офисов созданы CNAME

**SRV1-HQ (20010)**
*nslookup www.au.team 127.0.0.1*

```
Server:         127.0.0.1
Address:        127.0.0.1#53

www.au.team     canonical name = srv1-dt.au.team.
Name:   srv1-dt.au.team
Address: 192.168.33.66
```

*nslookup zabbix.au.team 127.0.0.1*

```
Server:         127.0.0.1
Address:        127.0.0.1#53

zabbix.au.team  canonical name = srv1-dt.au.team.
```

```
Name:   srv1-dt.au.team
Address: 192.168.33.66
```

# Б1 Загрузка записей с SRV1-HQ разрешена только для SRV1-DT

**SRV1-HQ (20010)**
*grep -R transfer /etc/bind/*.conf /etc/samba/*

```
/etc/bind/options.conf: allow-transfer { 192.168.33.66; };
```

# Б1 Резервный DNS на SRV1-DT

**SRV1-DT (20002)**
*whereis bind*

```
bind: /usr/lib64/bind /etc/bind /usr/share/man/man1/bind.1.xz
```

*nslookup srv1-dt.au.team 127.0.0.1*

```
Server:         127.0.0.1
Address:        127.0.0.1#53

Name:   srv1-dt.au.team
Address: 192.168.33.66
```

# Б1 Все устройства используют только внутренние DNS сервера

**R-DT (20007)**
*sh run | i name-server*

---

**SW1-HQ (20013)**
*grep nameserver /etc/resolv.conf*

```
nameserver 192.168.11.66
nameserver 192.168.33.66
nameserver 192.168.100.1
```

**SW-DT (20005)**
*grep nameserver /etc/resolv.conf*

```
nameserver 192.168.33.66
nameserver 192.168.11.66
nameserver 192.168.100.1
```

**ADMIN-DT (20001)**
*grep nameserver /etc/resolv.conf*

```
nameserver 192.168.33.66
nameserver 192.168.11.66
```

```
nameserver 192.168.100.1
```

**ADMIN-HQ (20009)**

*grep nameserver /etc/resolv.conf*

```
nameserver 192.168.11.66
nameserver 192.168.33.66
nameserver 192.168.100.1
```

# Б1 SAMBA AD на SRV1-HQ установлен и использует модуль BIND9_DLZ

**SRV1-HQ (20010)**

*samba-tool domain info 127.0.0.1*

```
Forest           : au.team
Domain           : au.team
Netbios domain   : AU
DC name          : srv1-hq.au.team
DC netbios name  : SRV1-HQ
Server site      : Default-First-Site-Name
Client site      : Default-First-Site-Name
```

*grep -R samba /etc/bind/*.conf*

```
/etc/bind/named.conf:include "/var/lib/samba/bind-dns/named.conf";
/etc/bind/options.conf: tkey-gssapi-keytab "/var/lib/samba/bind-
dns/dns.keytab";
```

# Б1 Samba users and group

**SRV1-HQ (20010)**

*samba-tool group listmembers group1*

```
user7
user4
user9
user3
user10
user1
user8
user2
user6
user5
```

*samba-tool group listmembers group2*

```
user14
user15
user18
user13
user17
user20
user11
```

```
user16
user19
user12
```

*samba-tool group listmembers group3*

```
user30
user29
user24
user22
user23
user21
user28
user26
user27
user25
```

# Б1 Подразделения CLI ADMIN

**SRV1-HQ (20010)**

*samba-tool ou list*

```
OU=CLI
OU=ADMIN
OU=Domain Controllers
```

# Б1 Клиенты введены в домен

**SRV1-HQ (20010)**

*samba-tool computer list*

```
ADMIN-HQ$
CLI-HQ$
CLI-DT$
ADMIN-DT$
SRV1-DT$
SRV1-HQ$
```

# Б1 Резервный контроллер домена SRV1-DT

**SRV1-DT (20002)**

*samba-tool domain info 127.0.0.1*

```
Forest           : au.team
Domain           : au.team
Netbios domain   : AU
DC name          : srv1-dt.au.team
DC netbios name  : SRV1-DT
Server site      : Default-First-Site-Name
Client site      : Default-First-Site-Name
```

*samba-tool drs showrepl | grep "Last success"*

```
                Last success @ Tue Mar 11 16:47:53 2025 +04
                Last success @ Tue Mar 11 16:47:53 2025 +04
                Last success @ Tue Mar 11 16:47:53 2025 +04
                Last success @ Tue Mar 11 16:47:53 2025 +04
                Last success @ Tue Mar 11 16:47:53 2025 +04
                Last success @ NTTIME(0)
                Last success @ NTTIME(0)
                Last success @ NTTIME(0)
                Last success @ NTTIME(0)
                Last success @ NTTIME(0)
```

# Б1 Общая директория на SRV1-HQ

**SRV1-HQ (20010)**

*smbclient -L localhost -U Administrator --password=P@ssw0rd*

```
        Sharename       Type      Comment
        ---------       ----      -------
        sysvol          Disk
        netlogon        Disk
        SAMBA           Disk      SAMBA
        IPC$            IPC       IPC Service (Samba 4.19.9-alt4)
SMB1 disabled -- no workgroup available
```