Рабочее место №0

Б2 Групповые политики для CLI в ADMC на ADMIN-HQ backgraund

CLI-HQ (20008)
dconf dump / | grep background

```
org.mate.background.color-shading-type=1
org.mate.background.picture-filename=1
org.mate.background.picture-options=1
org.mate.background.primary-color=1
org.mate.background.secondary-color=1
org.mate.background.color-shading-type='horizontal-gradient'
org.mate.background.picture-filename='smb://srv1-hq.au.team/samba/img.jpg'
org.mate.background.picture-options='none'
org.mate.background.primary-color='aqua'
org.mate.background.secondary-color='aqua'
org.mate.background.color-shading-type=1
org.mate.background.picture-filename=1
org.mate.background.picture-options=1
org.mate.background.primary-color=1
org.mate.background.secondary-color=1
org.mate.background.color-shading-type='horizontal-gradient'
org.mate.background.picture-filename='smb://srv1-hq.au.team/samba/img.jpg'
org.mate.background.picture-options='none'
org.mate.background.primary-color='aqua'
org.mate.background.secondary-color='aqua'
org.mate.background.color-shading-type="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-filename="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-options="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.primary-color="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.secondary-color="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.color-shading-type="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-filename="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-options="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.primary-color="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.secondary-color="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
```

Б2 Групповые политики для CLI в ADMC на ADMIN-HQ network

CLI-HQ (20008)

dconf dump / | grep NetworkManager

```
org.freedesktop.NetworkManager.checkpoint-rollback='No'
org.freedesktop.NetworkManager.enable-disable-connectivity-check='No'
org.freedesktop.NetworkManager.enable-disable-network='No'
org.freedesktop.NetworkManager.enable-disable-statistics='No'
org.freedesktop.NetworkManager.enable-disable-wifi='No'
org.freedesktop.NetworkManager.enable-disable-wimax='No'
org.freedesktop.NetworkManager.enable-disable-wwan='No'
org.freedesktop.NetworkManager.network-control='No'
org.freedesktop.NetworkManager.reload='No'
org.freedesktop.NetworkManager.settings.modify.global-dns='No'
org.freedesktop.NetworkManager.settings.modify.hostname='No'
org.freedesktop.NetworkManager.settings.modify.own='No'
org.freedesktop.NetworkManager.settings.modify.system='No'
org.freedesktop.NetworkManager.sleep-wake='No'
org.freedesktop.NetworkManager.wifi.scan='No'
org.freedesktop.NetworkManager.wifi.share.open='No'
org.freedesktop.NetworkManager.wifi.share.protected='No'
org.freedesktop.NetworkManager.checkpoint-rollback=1
org.freedesktop.NetworkManager.enable-disable-connectivity-check=1
org.freedesktop.NetworkManager.enable-disable-network=1
org.freedesktop.NetworkManager.enable-disable-statistics=1
org.freedesktop.NetworkManager.enable-disable-wifi=1
org.freedesktop.NetworkManager.enable-disable-wimax=1
org.freedesktop.NetworkManager.enable-disable-wwan=1
org.freedesktop.NetworkManager.network-control=1
org.freedesktop.NetworkManager.reload=1
org.freedesktop.NetworkManager.settings.modify.global-dns=1
org.freedesktop.NetworkManager.settings.modify.hostname=1
org.freedesktop.NetworkManager.settings.modify.own=1
org.freedesktop.NetworkManager.settings.modify.system=1
org.freedesktop.NetworkManager.sleep-wake=1
org.freedesktop.NetworkManager.wifi.scan=1
org.freedesktop.NetworkManager.wifi.share.open=1
org.freedesktop.NetworkManager.wifi.share.protected=1
org.freedesktop.NetworkManager.checkpoint-rollback='No'
org.freedesktop.NetworkManager.enable-disable-connectivity-check='No'
org.freedesktop.NetworkManager.enable-disable-network='No'
org.freedesktop.NetworkManager.enable-disable-statistics='No'
org.freedesktop.NetworkManager.enable-disable-wifi='No'
org.freedesktop.NetworkManager.enable-disable-wimax='No'
org.freedesktop.NetworkManager.enable-disable-wwan='No'
org.freedesktop.NetworkManager.network-control='No'
org.freedesktop.NetworkManager.reload='No'
org.freedesktop.NetworkManager.settings.modify.global-dns='No'
org.freedesktop.NetworkManager.settings.modify.hostname='No'
org.freedesktop.NetworkManager.settings.modify.own='No'
org.freedesktop.NetworkManager.settings.modify.system='No'
org.freedesktop.NetworkManager.sleep-wake='No'
```

```
org.freedesktop.NetworkManager.wifi.scan='No'
org.freedesktop.NetworkManager.wifi.share.open='No'
org.freedesktop.NetworkManager.wifi.share.protected='No'
org.freedesktop.NetworkManager.checkpoint-rollback=1
org.freedesktop.NetworkManager.enable-disable-connectivity-check=1
org.freedesktop.NetworkManager.enable-disable-network=1
org.freedesktop.NetworkManager.enable-disable-statistics=1
org.freedesktop.NetworkManager.enable-disable-wifi=1
org.freedesktop.NetworkManager.enable-disable-wimax=1
org.freedesktop.NetworkManager.enable-disable-wwan=1
org.freedesktop.NetworkManager.network-control=1
org.freedesktop.NetworkManager.reload=1
org.freedesktop.NetworkManager.settings.modify.global-dns=1
org.freedesktop.NetworkManager.settings.modify.hostname=1
org.freedesktop.NetworkManager.settings.modify.own=1
org.freedesktop.NetworkManager.settings.modify.system=1
org.freedesktop.NetworkManager.sleep-wake=1
org.freedesktop.NetworkManager.wifi.scan=1
org.freedesktop.NetworkManager.wifi.share.open=1
org.freedesktop.NetworkManager.wifi.share.protected=1
org.freedesktop.NetworkManager.checkpoint-rollback="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-connectivity-check="
{'policy_name': 'cli-polic', 'type': 1, 'reloaded_with_policy_key': None,
'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-network="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-statistics="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-wifi="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-wimax="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-wwan="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.network-control="{'policy_name': 'cli-polic',
'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.reload="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.global-dns="{'policy_name':
'cli-polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.hostname="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.own="{'policy_name': 'cli-
polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
```

org.freedesktop.NetworkManager.settings.modify.system="{'policy_name': 'cli-polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.sleep-wake="{'policy_name': 'cli-polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.wifi.scan="{'policy_name': 'cli-polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.wifi.share.open="{'policy_name': 'cli-polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.wifi.share.protected="{'policy_name': 'cli-polic', 'type': 1, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.checkpoint-rollback="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-connectivity-check="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-network="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-statistics="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-wifi="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-wimax="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.enable-disable-wwan="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.network-control="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.reload="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.global-dns="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.hostname="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.own="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.settings.modify.system="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.freedesktop.NetworkManager.sleep-wake="{'policy_name': 'cli-polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value':

```
None}"
org.freedesktop.NetworkManager.wifi.scan="{'policy_name': 'cli-polic', 'type':
4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value':
None}"
org.freedesktop.NetworkManager.wifi.share.open="{'policy_name': 'cli-polic',
'type': 4, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.freedesktop.NetworkManager.wifi.share.protected="{'policy_name': 'cli-
polic', 'type': 4, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
```

Б2 Групповые политики для CLI в ADMC на ADMIN-HQ mate change settings

CLI-HQ (20008)

dconf dump / | grep mate

```
org.mate.Marco.general.theme=1
org.mate.Marco.general.titlebar-uses-system-font=1
org.mate.background.color-shading-type=1
org.mate.background.picture-filename=1
org.mate.background.picture-options=1
org.mate.background.primary-color=1
org.mate.background.secondary-color=1
org.mate.lockdown.disable-theme-settings=1
org.mate.Marco.general.theme=''
org.mate.Marco.general.titlebar-uses-system-font=1
org.mate.background.color-shading-type='horizontal-gradient'
org.mate.background.picture-filename='smb://srv1-hq.au.team/samba/img.jpg'
org.mate.background.picture-options='none'
org.mate.background.primary-color='aqua'
org.mate.background.secondary-color='aqua'
org.mate.lockdown.disable-theme-settings=1
org.mate.Marco.general.theme=1
org.mate.Marco.general.titlebar-uses-system-font=1
org.mate.background.color-shading-type=1
org.mate.background.picture-filename=1
org.mate.background.picture-options=1
org.mate.background.primary-color=1
org.mate.background.secondary-color=1
org.mate.lockdown.disable-theme-settings=1
org.mate.Marco.general.theme=''
org.mate.Marco.general.titlebar-uses-system-font=1
org.mate.background.color-shading-type='horizontal-gradient'
org.mate.background.picture-filename='smb://srv1-hq.au.team/samba/img.jpg'
org.mate.background.picture-options='none'
org.mate.background.primary-color='aqua'
org.mate.background.secondary-color='aqua'
org.mate.lockdown.disable-theme-settings=1
org.mate.Marco.general.theme="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.Marco.general.titlebar-uses-system-font="{'policy_name': 'cli-polic',
'type': 4, 'reloaded_with_policy_key': None, 'is_list': None,
```

```
'mod_previous_value': None}"
org.mate.background.color-shading-type="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-filename="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-options="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.primary-color="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.secondary-color="{'policy_name': 'cli-polic', 'type': 4,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.lockdown.disable-theme-settings="{'policy_name': 'cli-polic', 'type':
4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value':
None}"
org.mate.Marco.general.theme="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.Marco.general.titlebar-uses-system-font="{'policy_name': 'cli-polic',
'type': 4, 'reloaded_with_policy_key': None, 'is_list': None,
'mod_previous_value': None}"
org.mate.background.color-shading-type="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-filename="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.picture-options="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.primary-color="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.background.secondary-color="{'policy_name': 'cli-polic', 'type': 1,
'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': None}"
org.mate.lockdown.disable-theme-settings="{'policy_name': 'cli-polic', 'type':
4, 'reloaded_with_policy_key': None, 'is_list': None, 'mod_previous_value': 0}"
```

Б2 Групповые политики для ADMIN в ADMC на ADMIN-HQ samba share

ADMIN-HQ (20009)

dconf dump / | grep Drives

```
Drives="[{'login': '', 'password': '', 'dir': 'A', 'path': 'smb://srv1-
hq.au.team/samba', 'action': 'U', 'thisDrive': 'SHOW', 'allDrives': 'SHOW',
'label': 'SAMBA', 'persistent': '1', 'useLetter': '1', 'policy_name': 'adm-
polic'}]"
Drives="[{'login': '', 'password': '', 'dir': 'A', 'path': 'smb://srv1-
hq.au.team/samba', 'action': 'U', 'thisDrive': 'SHOW', 'allDrives': 'SHOW',
'label': 'SAMBA', 'persistent': '1', 'useLetter': '1', 'policy_name': 'adm-
polic'}]"
```

Б2 Межсетевой экран: сервера и Администраторы офиса DT имеют доступ ко всем устройствам

Б2 Межсетевой экран: клиенты офиса DT имеют доступ только к серверам

Б2 Межсетевой экран: ICMP-запросы разрешены администраторами офиса DT на внутренние интерфейсы межсетевого экрана

Б2 Межсетевой экран: администратораы офиса DT имеют возможность удаленного управления межсетевым экраном по SSH и HTTP

FW-DT (20006)

iptables -nvL forward_user_rules

```
Chain forward_user_rules (1 references)
 pkts bytes target     prot opt in     out     source               destination
 6653  392K ACCEPT     0    --  *      *       0.0.0.0/0            0.0.0.0/0
match-set fw.zone.7wh21glmSwK4jzcAQHtCVQ src,src /* 2 */ -m logger --mask
268435456 --value 268435456 --prefix fwd.ngfw.2,accept
 1169 73676 ACCEPT     0    --  *      *       0.0.0.0/0            0.0.0.0/0
match-set fw.zone.xHI+ViVdRnqwJem1DeINHg src,src /* 3 */ -m logger --mask
268435456 --value 268435456 --prefix fwd.ngfw.3,accept
  719 44437 ACCEPT     0    --  Lvlan110_5 *       0.0.0.0/0
0.0.0.0/0            match-set fw.zone.7wh21glmSwK4jzcAQHtCVQ dst,dst /* 4 */ -
m logger --mask 268435456 --value 268435456 --prefix fwd.ngfw.4,accept
  105  6617 ACCEPT     0    --  *      *       0.0.0.0/0            0.0.0.0/0
match-set fw.zone.1/PlfZyjQZ21VVyAYQ7DMw src,src match-set fw.ip.fwd.da.5 dst
/* 5 */ -m logger --mask 268435456 --value 268435456 --prefix fwd.ngfw.5,accept
    0     0 ACCEPT     1    --  *      L+      0.0.0.0/0            0.0.0.0/0
match-set fw.zone.xHI+ViVdRnqwJem1DeINHg src,src /* 6 */ -m logger --mask
268435456 --value 268435456 --prefix fwd.ngfw.6,accept
 1958  104K ACCEPT     0    --  *      *       0.0.0.0/0            0.0.0.0/0
match-set fw.ip.fwd.sa.8 src /* 8 */ -m logger --mask 268435456 --value
268435456 --prefix fwd.ngfw.8,accept
11262  675K smart_drop  0    --  *      *       0.0.0.0/0            0.0.0.0/0
/* 1 */ -m logger --mask 268435456 --value 268435456 --prefix fwd.ngfw.1,drop
```

Б2 Центр сбора логов SRV1-HQ

SRV1-HQ (20010)

ss -ntulp | grep 514

```
tcp   LISTEN 0      25           0.0.0.0:514        0.0.0.0:*    users:
(("rsyslogd",pid=20165,fd=4))
tcp   LISTEN 0      25              [::]:514           [::]:*    users:
(("rsyslogd",pid=20165,fd=5))
```

Б2 Клиены для отправления логов SRV1-DT, SRV2-DT, SRV3-DT

SRV1-DT (20002)
grep 514 -R /etc/rsyslog.conf /etc/rsyslog.d/

```
/etc/rsyslog.d/all.conf:*.6 @@192.168.11.66:514
/etc/rsyslog.d/00_common.conf:#input(type="imudp" port="514")
/etc/rsyslog.d/00_common.conf:#input(type="imtcp" port="514")
```

SRV2-DT (20003)
grep 514 -R /etc/rsyslog.conf /etc/rsyslog.d/

```
/etc/rsyslog.d/all.conf:*.6 @@192.168.11.66:514
/etc/rsyslog.d/00_common.conf:#input(type="imudp" port="514")
/etc/rsyslog.d/00_common.conf:#input(type="imtcp" port="514")
```

SRV3-DT (20004)
grep 514 -R /etc/rsyslog.conf /etc/rsyslog.d/

```
/etc/rsyslog.d/all.conf:*.6 @@192.168.11.66:514
/etc/rsyslog.d/00_common.conf:#input(type="imudp" port="514")
/etc/rsyslog.d/00_common.conf:#input(type="imtcp" port="514")
```

Б2 Логи хранятся на SRV1-HQ /var/logz/<ХОСТНЕЙМ>.log

SRV1-HQ (20010)
find /var/logz -iname srv.log -exec tail -n 3 {} \;*

```
Mar 12 15:01:01 srv2-dt crond: pam_tcb(crond:session): Session opened for root
by (uid=0)
Mar 12 15:01:01 srv2-dt crond[5593]: (root) CMD (run-parts /etc/cron.hourly)
Mar 12 15:01:01 srv2-dt crond: pam_tcb(crond:session): Session closed for root
Mar 12 15:01:01 srv1-dt crond: pam_tcb(crond:session): Session opened for root
by (uid=0)
Mar 12 15:01:01 srv1-dt crond[17394]: (root) CMD (run-parts /etc/cron.hourly)
Mar 12 15:01:01 srv1-dt crond: pam_tcb(crond:session): Session closed for root
Mar 12 15:01:01 srv3-dt crond: pam_tcb(crond:session): Session opened for root
by (uid=0)
Mar 12 15:01:01 srv3-dt crond[22118]: (root) CMD (run-parts /etc/cron.hourly)
Mar 12 15:01:01 srv3-dt crond: pam_tcb(crond:session): Session closed for root
Mar 12 15:01:01 srv1-hq crond: pam_tcb(crond:session): Session opened for root
by (uid=0)
Mar 12 15:01:01 srv1-hq crond[21152]: (root) CMD (run-parts /etc/cron.hourly)
Mar 12 15:01:01 srv1-hq crond: pam_tcb(crond:session): Session closed for root
```

Б2 Бекап общей папки на SRV1-HQ

SRV1-HQ (20010)
ls -ls /var/bacrr/

```
total 76
76 -rw-r--r-- 1 root root 75019 Mar 11 20:00 samb-bac.tar.gz
```

Б2 Создан и работает юнит для бекапа

SRV1-HQ (20010)

systemctl status backup

```
â⍰⍰ backup.service - backup
     Loaded: loaded (/etc/systemd/system/backup.service; enabled; vendor
preset: disabled)
     Active: inactive (dead) since Tue 2025-03-11 20:00:02 +04; 19h ago
TriggeredBy: â⍰⍰ backup.timer
   Main PID: 15526 (code=exited, status=0/SUCCESS)
        CPU: 15ms

Mar 11 20:00:02 srv1-hq.au.team systemd[1]: Starting backup...
Mar 11 20:00:02 srv1-hq.au.team tar[15526]: tar: Removing leading `/' from
member names
Mar 11 20:00:02 srv1-hq.au.team systemd[1]: backup.service: Deactivated
successfully.
Mar 11 20:00:02 srv1-hq.au.team systemd[1]: Finished backup.
```

find /etc/systemd/ -maxdepth 2 -name backup. -exec cat {} \;*

```
[Unit]
Description=backup

[Service]
Type=oneshot
ExecStart=tar czf /var/bacrr/samb-bac.tar.gz /opt/data
StandardOutput=journal

[Install]
WantedBy=multi-user.target
[Unit]
Description=backup timer

[Timer]
OnCalendar=*-*-* 20:00:00
Persistent=true
Unit=backup.service
[Install]
WantedBy=timers.target
[Unit]
Description=backup

[Service]
Type=oneshot
ExecStart=tar czf /var/bacrr/samb-bac.tar.gz /opt/data
StandardOutput=journal

[Install]
WantedBy=multi-user.target
```

```
[Unit]
Description=backup timer

[Timer]
OnCalendar=*-*-* 20:00:00
Persistent=true
Unit=backup.service
[Install]
WantedBy=timers.target
```

Б2 Docker Registry установлен на SRV2-DT

SRV2-DT (20003)
docker ps | grep registry

```
8b4d93474245   registry:2.7             "/entrypoint.sh /etcâ¦"   4 hours ago
Up 4 hours   0.0.0.0:5000->5000/tcp, :::5000->5000/tcp   registry
```

Б2 Образ приложения собран в соответсвии с заданием и загружен в выбранный репозиторий Docker

SRV2-DT (20003)
find /root /home -type f -name Dockerfile -exec cat {} \;

```
FROM nginx:alpine
COPY index.html /usr/share/nginx/html/
```

curl http://127.0.0.1:5000/v2/_catalog

```
{"repositories":["web"]}
```

Б2 Развернут Docker контенйнер WEB в соответсвии с заданием

SRV2-DT (20003)
docker ps | grep web

```
d7e2a9f4ed72   localhost:5000/web:1.0   "/docker-entrypoint.â¦"   4 hours ago
Up 4 hours   0.0.0.0:80->80/tcp, :::80->80/tcp           web
```

docker inspect web | grep -A3 RestartPolicy

```
            "RestartPolicy": {
                "Name": "always",
                "MaximumRetryCount": 0
            },
```

Б2 SRV3-DT Zabbix установлен с базой данных PostgreSQL

SRV3-DT (20004)
*systemctl list-units zabbix_**

```
  UNIT                   LOAD   ACTIVE SUB     DESCRIPTION
  zabbix_agentd.service loaded active running ZABBIX Monitor Agent
  zabbix_pgsql.service  loaded active running ZABBIX Server with PostgreSQL DB

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
2 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

Б2 SRV3-DT Zabbix HTTP

SRV3-DT (20004)

curl -s http://127.0.0.1/zabbix/ | grep -iE "zabbix"

```
                <meta name="Author" content="Zabbix SIA" /><title>SRV3-DT:
Zabbix</title>          <link rel="icon" href="favicon.ico">
<body><div class="wrapper"><main><div class="server-name">SRV3-DT</div><div
class="signin-container"><div class="signin-logo"><div class="zabbix-logo">
</div></div><form method="post" action="index.php" accept-charset="utf-8" aria-
label="Sign in"><ul><li><label for="name">Username</label><input type="text"
id="name" name="name" value="" maxlength="255" autofocus="autofocus"></li><li>
<label for="password">Password</label><input type="password" id="password"
name="password" value="" maxlength="255" autocomplete="off"></li><li><input
type="checkbox" id="autologin" name="autologin" value="1" class="checkbox-
radio" checked="checked"><label for="autologin"><span></span>Remember me for 30
days</label></li><li><button type="submit" id="enter" name="enter" value="Sign
in">Sign in</button></li></ul></form></div><div class="signin-links"><a
target="_blank" rel="noopener noreferrer" class="grey link-alt"
href="https://www.zabbix.com/documentation/7.0/">Help</a>  •  <a
target="_blank" rel="noopener noreferrer" class="grey link-alt"
href="https://www.zabbix.com/support">Support</a></div></main><footer
role="contentinfo">© 2001–2025, <a class="grey link-alt" target="_blank"
rel="noopener noreferrer" href="https://www.zabbix.com/">Zabbix SIA</a>
</footer></div></body>
```

Б2 SRV3-DT Zabbix добавлены хосты SRV1-DT, SRV2-DT, SRV3-DT, SRV1-HQ

SRV1-DT (20002)

*systemctl list-units zabbix_**

```
  UNIT                   LOAD   ACTIVE SUB     DESCRIPTION
  zabbix_agentd.service loaded active running ZABBIX Monitor Agent

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
1 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

SRV2-DT (20003)
*systemctl list-units zabbix_**

```
  UNIT                   LOAD   ACTIVE SUB     DESCRIPTION
  zabbix_agentd.service loaded active running ZABBIX Monitor Agent

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
1 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

SRV3-DT (20004)
*systemctl list-units zabbix_**

```
  UNIT                   LOAD   ACTIVE SUB     DESCRIPTION
  zabbix_agentd.service loaded active running ZABBIX Monitor Agent
  zabbix_pgsql.service  loaded active running ZABBIX Server with PostgreSQL DB

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
2 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

SRV1-HQ (20010)
*systemctl list-units zabbix_**

```
  UNIT                   LOAD   ACTIVE SUB     DESCRIPTION
  zabbix_agentd.service loaded active running ZABBIX Monitor Agent

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
1 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

Б2 SRV3-DT Zabbix мониторится шаблоном Linux-agent

SRV3-DT (20004)
psql -U postgres -d zabbix -c "SELECT h.name AS hostname, t.name AS template_name FROM hosts h JOIN hosts_templates ht ON h.hostid = ht.hostid JOIN hosts t ON ht.templateid = t.hostid WHERE h.name ~ 'srv'"

```
    hostname     |     template_name
-----------------+-----------------------
 srv1-dt.au.team | Linux by Zabbix agent
 srv3-dt.au.team | Zabbix server health
 srv3-dt.au.team | Linux by Zabbix agent
 srv2-dt.au.team | Linux by Zabbix agent
 srv1-hq.au.team | Linux by Zabbix agent
(5 rows)
```

Б2 На SRV1-DT развернут nginx

SRV1-DT (20002)

*systemctl list-units nginx**

```
  UNIT          LOAD   ACTIVE SUB     DESCRIPTION
  nginx.service loaded active running The nginx HTTP and reverse proxy server

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
1 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

grep -A4 -R -E "au.team" /etc/nginx/sites-enabled.d/

```
/etc/nginx/sites-enabled.d/default.conf:        server_name www.au.team;
/etc/nginx/sites-enabled.d/default.conf-        location / {
/etc/nginx/sites-enabled.d/default.conf-                proxy_pass
http://192.168.33.67;
/etc/nginx/sites-enabled.d/default.conf-        }
/etc/nginx/sites-enabled.d/default.conf-}
--
/etc/nginx/sites-enabled.d/default.conf:        server_name zabbix.au.team;
/etc/nginx/sites-enabled.d/default.conf-        location /zabbix {
/etc/nginx/sites-enabled.d/default.conf-                proxy_pass
http://192.168.33.68/zabbix;
/etc/nginx/sites-enabled.d/default.conf-        }
/etc/nginx/sites-enabled.d/default.conf-}
--
/etc/nginx/sites-enabled.d/default.conf~:       server_name www.au.team;
/etc/nginx/sites-enabled.d/default.conf~-       location / {
/etc/nginx/sites-enabled.d/default.conf~-               proxy_pass
http://192.168.33.67;
/etc/nginx/sites-enabled.d/default.conf~-       }
/etc/nginx/sites-enabled.d/default.conf~-}
--
/etc/nginx/sites-enabled.d/default.conf~:        server_name zabbix.au.team;
/etc/nginx/sites-enabled.d/default.conf~-        location /zabbix {
/etc/nginx/sites-enabled.d/default.conf~-                proxy_pass
http://192.168.33.68/zabbix;
/etc/nginx/sites-enabled.d/default.conf~-        }
/etc/nginx/sites-enabled.d/default.conf~-}
```

Б2 По имени www.au.team открывается сайт, расположенный на SRV2-DT

SRV1-DT (20002)

curl -s http://www.au.team

```
<html>
        <body>
                <center><h2><b>SPOWellcome!!!</b></h2></center>
```

```
        </body>
</html>
```

Б2 По имени zabbix.au.team открывается zabbix, расположенный на SRV3-DT

SRV1-DT (20002)
curl -s http://zabbix.au.team/zabbix/ | grep -iE "zabbix"

```
                <meta name="Author" content="Zabbix SIA" /><title>SRV3-DT:
Zabbix</title>          <link rel="icon" href="favicon.ico">
<body><div class="wrapper"><main><div class="server-name">SRV3-DT</div><div
class="signin-container"><div class="signin-logo"><div class="zabbix-logo">
</div></div><form method="post" action="index.php" accept-charset="utf-8" aria-
label="Sign in"><ul><li><label for="name">Username</label><input type="text"
id="name" name="name" value="" maxlength="255" autofocus="autofocus"></li><li>
<label for="password">Password</label><input type="password" id="password"
name="password" value="" maxlength="255" autocomplete="off"></li><li><input
type="checkbox" id="autologin" name="autologin" value="1" class="checkbox-
radio" checked="checked"><label for="autologin"><span></span>Remember me for 30
days</label></li><li><button type="submit" id="enter" name="enter" value="Sign
in">Sign in</button></li></ul></form></div><div class="signin-links"><a
target="_blank" rel="noopener noreferrer" class="grey link-alt"
href="https://www.zabbix.com/documentation/7.0/">Help</a>  •  <a
target="_blank" rel="noopener noreferrer" class="grey link-alt"
href="https://www.zabbix.com/support">Support</a></div></main><footer
role="contentinfo">© 2001–2025, <a class="grey link-alt" target="_blank"
rel="noopener noreferrer" href="https://www.zabbix.com/">Zabbix SIA</a>
</footer></div></body>
```

Б2 Ansible установлен на ADMIN-DT

ADMIN-DT (20001)
ansible --version

```
ansible 2.9.27
  config file = /etc/ansible/ansible.cfg
  configured module search path = ['/root/.ansible/plugins/modules',
'/usr/share/ansible/plugins/modules']
  ansible python module location = /usr/lib/python3/site-packages/ansible
  executable location = /usr/bin/ansible
  python version = 3.9.6 (default, Jun 29 2021, 10:42:27) [GCC 10.2.1 20210313
(ALT Sisyphus 10.2.1-alt3)]
```

Б2 Ansible inventory содержит нужные хосты и группы

ADMIN-DT (20001)
cat /etc/ansible/inventory

```
[Networking]
R-DT ansible_host=r-dt ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_connection=network_cli ansible_network_os=ios
ansible_python_interpreter=/usr/bin/python3
R-HQ ansible_host=r-hq ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_connection=network_cli ansible_network_os=ios
ansible_python_interpreter=/usr/bin/python3
[Servers]
SRV1-DT ansible_host=srv1-dt ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
SRV2-DT ansible_host=srv2-dt ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
SRV3-DT ansible_host=srv3-dt ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
SRV1-HQ ansible_host=srv1-hq ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
[Clients]
ADMIN-DT ansible_host=admin-dt ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
ADMIN-HQ ansible_host=admin-hq ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
CLI-DT ansible_host=cli-dt ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
CLI-HQ ansible_host=cli-hq ansible_user=sshuser ansible_ssh_pass=P@ssw0rd
ansible_python_interpreter=/usr/bin/python3
```

Б2 Ansible ping-pong

ADMIN-DT (20001)

ansible all -m ping

```
SRV3-DT | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
SRV2-DT | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
SRV1-DT | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
R-DT | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
R-HQ | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
SRV1-HQ | SUCCESS => {
    "changed": false,
```

```
    "ping": "pong"
}
CLI-DT | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
ADMIN-DT | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
ADMIN-HQ | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
CLI-HQ | SUCCESS => {
    "changed": false,
    "ping": "pong"
}
```

Б2 ADMIN-HQ Кибер Бекап

Если службы не запущены, дальше КИБЕРБЕКАП не проверяем

ADMIN-HQ (20009)
*systemctl list-units acronis_**

```
  UNIT                                LOAD   ACTIVE SUB     DESCRIPTION
  acronis_ams.service                 loaded active running Acronis Management
Server
  acronis_asm.service                 loaded active running Acronis service
manager
  acronis_mms.service                 loaded active running Acronis machine
management service
  acronis_monitoring_service.service loaded active running Acronis Monitoring
Server Service
  acronis_schedule.service            loaded active running Acronis schedule
service
  acronis_zmqgw.service               loaded active running Acronis ZMQ Gateway

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
6 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

Б2 Организация wsr

В браузере на ADMIN-HQ http://localhost:9877, логин root пароль toor

Б2 Пользователи администраторы

В браузере на ADMIN-HQ http://localhost:9877, логин root пароль toor

Б2 CLI-HQ агент Кибер Бекап

CLI-HQ (20008)
*systemctl list-units acronis_**

```
  UNIT                          LOAD   ACTIVE SUB     DESCRIPTION
  acronis_agent.service         loaded active running Acronis Remote Agent
Service
  acronis_mms.service           loaded active running Acronis machine
management service
  acronis_schedule.service      loaded active running Acronis schedule service
  acronis_storageserver.service loaded active running Acronis Storage Node

LOAD   = Reflects whether the unit definition was properly loaded.
ACTIVE = The high-level unit activation state, i.e. generalization of SUB.
SUB    = The low-level unit activation state, values depend on unit type.
4 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
```

Б2 Устройство хранения sdb

CLI-HQ (20008)
df -h

```
Filesystem           Size  Used Avail Use% Mounted on
udevfs               5.0M   96K  5.0M   2% /dev
runfs                2.0G  1.2M  2.0G   1% /run
/dev/mapper/vg-root   30G   18G   11G  62% /
tmpfs                2.0G  118M  1.8G   7% /dev/shm
/dev/vda1            485M  103M  353M  23% /boot
tmpfs                2.0G  5.8M  2.0G   1% /tmp
/dev/vdb              30G   17G   14G  54% /backups
tmpfs                392M   80K  392M   1% /run/user/1618001113
tmpfs                392M   60K  392M   1% /run/user/501
```

Б2 План полного резервного копирования

В браузере на ADMIN-HQ http://localhost:9877, логин root пароль toor

Б2 Успешно выполнено полное резервное копирование

В браузере на ADMIN-HQ http://localhost:9877, логин root пароль toor