

Confidentiality Statement

This document contains confidential information of Tata Consultancy Services Limited, which is provided for the sole purpose of permitting the recipient to evaluate the proposal submitted herewith. In consideration of receipt of this document, the recipient agrees to maintain such information in confidence and to not reproduce or otherwise disclose this information to any person outside the group directly responsible for evaluation of its contents, except that there is no obligation to maintain the confidentiality of any information which was known to the recipient prior to receipt of such information from Tata Consultancy Services Limited, or becomes publicly known through no fault of recipient, or is received without obligation of confidentiality from a third party owing no obligation of confidentiality to Tata Consultancy Services Limited.

Tata Code of Conduct

We, in our dealings, are self-regulated by a Code of Conduct as enshrined in the Tata Code of Conduct. We request your support in helping us adhere to the Code in letter and spirit. We request that any violation or potential violation of the Code by any person be promptly brought to the notice of the Local Ethics Counselor or the Principal Ethics Counselor or the CEO of TCS. All communication received in this regard will be treated and kept as confidential.



vILP – Level 2

Content Manual

Version 1.1

December 2014

(ILP Guwahati)

Table of Content

1.	Filters	5
1.5	sort	5
1.6	uniq	8

1. Filters

When a program takes its input from another program, performs some operation on that input, and writes the result to the standard output, it is referred to as a filter. A common use of filters is to modify output. UNIX filters can restructure output.

Some common filters in UNIX are:

- `sort` – sorts files by line (lexically or numerically)
- `uniq` – Removes identical adjacent lines

1.5 `sort`

`sort` reorders the lines of a file in ascending or descending order.

Syntax:

The default order is ASCII: whitespace, numbers, uppercase, and finally, lowercase letters.

Options:

- k n** sort on the nth field of the line
- tchar** use char as the field delimiter
- n** sort numerically
- r** reverse order sort
- u** removes repeated lines
- m** list merge sorted files in list

Examples:

Below examples will help you to understand `sort` used with different options:

Consider a file named `list` has below data

Example:

1, Justin Timberlake, Title 545, Price \$7.30
2, Lady Gaga, Title 118, Price \$7.30

```
3, Johnny Cash, Title 482, Price $6.50
4, Elvis Presley, Title 335, Price $7.30
5, John Lennon, Title 271, Price $7.90
```

Sort on the 2nd field of file named “list”. File list is comma separated file.

```
$sort -t , -k 2 list
```

Output:

```
4, Elvis Presley, Title 335, Price $6.30
5, John Lennon, Title 271, Price $7.90
3, Johnny Cash, Title 482, Price $6.50
1, Justin Timberlake, Title 545, Price $6.30
2, Lady Gaga, Title 118, Price $6.30
```

Example: Numerically sorting:

sort -n list, numerically sort file named list

```
$cat list
20
19
5
49
200
```

Output:

```
$sort list
19
20
200
49
5
```

However the below command with the help of option -n will output

```
$sort -n list
5
19
20
```

```
200
```

Example:

```
$cat list1  
25  
18  
5  
48  
200
```

Sort can sort multiple files also.

```
$sort -n list list1 will produce  
5  
5  
18  
19  
20  
25  
48  
200  
200
```

Example: Numerically sort in reverse order

```
$sort -nr list  
200  
48  
25  
20  
19  
18  
5
```

Syntax:

```
$sort -u list
```

Example: Sort the file list removing the repeated lines.

```
$cat list
Unix
Linux
Solaris
AIX
Linux
HPUX
```

Output: The duplicate 'Linux' record got removed.

```
$sort -u list
Unix
Linux
Solaris
AIX
HPUX
```

Sort file1 & file2 and merge

```
$sort -m file1 file2
```

Video Link:

http://www.youtube.com/watch?v=ZLjo_yL6g5s

1.6 uniq

uniq command is used to suppress the duplicate lines from a file. It discards all the successive identical lines except one from the input and writes the output.

Syntax:

uniq [option] filename

Options:

- u lists only the lines that are unique
- d lists only the lines that are duplicates
- c counts the frequency of occurrences

Consider following example.txt file in your unix operating system.

```
$cat example.txt
Unix operating system
unix operating system
unix dedicated server
linux dedicated server
```

Suppress duplicate lines:

The default behaviour of the uniq command is to suppress the duplicate line. Note that, you have to pass sorted input to the uniq, as it compares only successive lines.

```
$uniq example.txt
unix operating system
unix dedicated server
linux dedicated server
```

If the lines in the file are not in sorted order, then use the sort command and then pipe the output to the uniq command.

```
$sort example.txt | uniq
```

Count of lines:

The -c option is used to find how many times each line occurs in the file. It prefixes each line with the count.

```
$uniq -c example.txt
2 unix operating system
1 unix dedicated server
1 linux dedicated server
```

Display only duplicate lines:

You can print only the lines that occur more than once in a file using the -d option. The -D option prints all the duplicate lines.

```
$uniq -d example.txt
unix operating system

$uniq -D example.txt
unix operating system
unix operating system
```

Skip first N fields in comparison

the -f option is used to skip the first N columns in comparison. Here the fields are delimited by the space character.

```
$uniq -f2 example.txt
unix operating system
unix dedicated server
```

In the above example the uniq command, just compares the last fields. For the first two lines, the last field contains the string "system". Uniq prints the first line and skips the second. Similarly it prints the third line and skips the fourth line.

Print only unique lines

You can skip the duplicate lines and print only unique lines using the -u option

```
$uniq -u example.txt
unix dedicated server
linux dedicated server
```