

Confidentiality Statement

This document contains confidential information of Tata Consultancy Services Limited, which is provided for the sole purpose of permitting the recipient to evaluate the proposal submitted herewith. In consideration of receipt of this document, the recipient agrees to maintain such information in confidence and to not reproduce or otherwise disclose this information to any person outside the group directly responsible for evaluation of its contents, except that there is no obligation to maintain the confidentiality of any information which was known to the recipient prior to receipt of such information from Tata Consultancy Services Limited, or becomes publicly known through no fault of recipient, or is received without obligation of confidentiality from a third party owing no obligation of confidentiality to Tata Consultancy Services Limited.

Tata Code of Conduct

We, in our dealings, are self-regulated by a Code of Conduct as enshrined in the Tata Code of Conduct. We request your support in helping us adhere to the Code in letter and spirit. We request that any violation or potential violation of the Code by any person be promptly brought to the notice of the Local Ethics Counselor or the Principal Ethics Counselor or the CEO of TCS. All communication received in this regard will be treated and kept as confidential.



vILP – CPP – Operating System

Command for searching files

Version 1.1

July 2015

(ILP Guwahati)

Table of Content

1.1. Find5

Find command

The command find is one of the powerful utility of Unix (or Linux). It can search the entire file-system to locate files and directories according to the specific search criteria. Other than searching files in can perform actions(executing commands) on searched files.

Syntax:

```
$ find <search-in directory> <search-parameter> <action>
```

Examples :

1 . File Type based Search:

>> The following command finds the file named Abc in current(.) directory and all its sub-directories

```
[390119@InGhyUnix ~]$ find . -name Abc  
./Abc  
./Dir1/Abc
```

>> To find a directory named bin from root (/) directory and all its sub-directories the command will be :

```
[390119@InGhyUnix ~]$ find / -name bin -type d  
/bin  
/usr/bin  
/usr/lib/jvm/java-1.7.0-openjdk-1.7.0.9.x86_64/jre/bin
```

The -type d option searches for the file of type directory

2 . Wild-Card based Search : Wild-card characters like * and ? can be used:

>> To find all files where filename starts with Abc the command will be:

```
[390119@InGhyUnix ~]$ find . -name "Abc*"

./Abc
./Dir1/Abc
./Dir1/Abc.php
./Abc.txt
./Abc.dat
```

>> The following command finds all files with three character extension ended with t.

```
[390119@InGhyUnix ~]$ find . -name "Abc.??t"

./Abc.txt
./Abc.dat
```

3 . Source Location based Search

>>The command find can search in multiple source location :

```
[390119@InGhyUnix ~]$ find Dir1 Dir2 -name "Abc.*"

Dir1/Abc.php
Dir2/Abc.htm
```

Searches for the file Abc with any extension only in directories Dir1 and Dir2

4 . Size Based Search : Using find files can be searched based on its size .

>> To find the files with size more than 10Mb the command will be

```
[390119@InGhyUnix ~]$ find . -size +10M  
./Abc.dat
```

>> To find the files with size smaller than 2048 bytes the command will be

```
[390119@InGhyUnix ~]$ find . -size -2048c  
./Abc  
./Abc.txt
```

5 . Access/Modification-Time Based Search : Using find files can be searched based on the time of last access/modification :

>> To find the files which are accessed within last 3 days the command will be

```
[390119@InGhyUnix ~]$ find . -atime -3  
./Abc
```

>> To find the files which are not modified within last 30 minute the command will be

```
[390119@InGhyUnix ~]$ find . -not -mmin -30  
./Abc.txt
```

6 . Permission Based Search : Using find command files can be searched based on the access permission they have

>> To find the files having read write and execute permission only for the owner the command will be :

```
[390119@InGhyUnix ~]$ find . -perm 700  
./Abc.txt
```

7 . Perform Action on the search result : Using exec option any action (command) can be executed on the search result.

>> To remove all the files having extension .swp from the current directory the command will be :

```
[390119@InGhyUnix ~]$ find . -name "*.swp" -exec rm {} \;
```