Storage Conversion Calculator
Calculator: storage-conversion-calculator | Engine version: 1
Raw engine values: full numeric precision; no display rounding or sampled rows.
Units appear only where supplied by the calculation or bound display metadata.
Embedded Unicode glyphs are readable.
Unsupported characters and controls use explicit Unicode escapes.
Tagged PDF; PDF/UA conformance: UNVERIFIED.
Text follows document order; charts include complete numeric text alternatives.

INPUTS
Value [GiB]
input["value"] = 1
From unit
input["fromUnit"] = "GiB"
To unit
input["toUnit"] = "MiB"

RESULTS
Converted storage [MiB]
output["value"] = 1024
output["steps"][0] = "Storage Conversion = 1024"

METHODOLOGY
Binary IEC storage conversion only: B, KiB, MiB, GiB and TiB use exact powers of 1024 by tes. Decimal MB/GB and provider billing conventions are not silently substituted. The im mutable v1 schema requires a strictly positive value.\u000aTechnical calculation revisio n: technology.storage-conversion@1\u000a\u000aBinary IEC storage-unit conversion using 1 024-based multiples.\u000aConverted value = input bytes ÷ target-unit bytes

DECLARED FORMULAS
storage-conversion-calculator: Converted value = input bytes ÷ target-unit bytes
Binary IEC storage-unit conversion using 1024-based multiples.

SOURCES
NIST — Binary prefixes
https://physics.nist.gov/cuu/Units/binary.html
IEC binary prefixes distinguish 1024-based units such as MiB and GiB from decimal SI MB and GB.