Bandwidth Calculator
Calculator: bandwidth-calculator | Engine version: 1
Raw engine values: full numeric precision; no display rounding or sampled rows.
Units appear only where supplied by the calculation or bound display metadata.
Embedded Unicode glyphs are readable.
Unsupported characters and controls use explicit Unicode escapes.
Tagged PDF; PDF/UA conformance: UNVERIFIED.
Text follows document order; charts include complete numeric text alternatives.

INPUTS
Data (MB) [MB]
input["dataMegabytes"] = 100
Time (s) [s]
input["timeSeconds"] = 10

RESULTS
Bandwidth [Mbps]
output["value"] = 80
output["steps"][0] = "Bandwidth = 80"

METHODOLOGY
Ideal deterministic arithmetic using decimal MB (1 MB = 1,000,000 octets) and Mbps (1 Mbps = 1,000,000 bits/second), eight bits per octet. Strictly positive supplied quantities; not measured bandwidth, provider speed or a delivery guarantee. Protocol overhead, latency, congestion and changing rates are excluded.\u000aTechnical calculation revision: technology.bandwidth@1\u000a\u000aAverage transfer rate from data size and elapsed time.\u000aBandwidth (Mbps) = data MB × 8 ÷ time seconds

DECLARED FORMULAS
bandwidth-calculator: Bandwidth (Mbps) = data MB × 8 ÷ time seconds
Average transfer rate from data size and elapsed time.

SOURCES
RFC 1547 — octet terminology
https://www.rfc-editor.org/rfc/rfc1547
RFC 1547 defines an octet as eight bits. CalcuMint uses that unit relationship for its idealized MB/Mbps transfer-rate arithmetic; protocol overhead, latency and congestion are intentionally outside these simple estimates.