13.4 billion tokens in 8 days.

Roughly **5–7 sessions**, running nearly **24/7**. Many sessions last **20–40 hours**.

1.67B tokens per day on average


2026-10-05	All		22,920,885	3,171,017	0	1,025,325,184	1,051,417,086
	- Codex	- gpt-6-luna - gpt-6.1-sol	22,920,885	3,171,017	0	1,025,325,184	1,051,417,086
2026-10-06	All		38,080,225	5,801,484	0	1,847,434,368	1,891,316,077
	- Codex	- gpt-6-luna - gpt-6.1-sol	38,080,225	5,801,484	0	1,847,434,368	1,891,316,077
2026-10-07	All		27,697,279	4,168,198	0	1,092,886,016	1,124,751,493
	- Codex	- gpt-6-luna - gpt-6.1-sol	27,697,279	4,168,198	0	1,092,886,016	1,124,751,493
2026-10-08	All		42,544,619	6,976,510	0	1,896,151,680	1,945,672,809
	- Codex	- gpt-6-luna - gpt-6.1-sol	42,544,619	6,976,510	0	1,896,151,680	1,945,672,809
2026-10-09	All		43,408,079	7,558,899	0	1,848,873,984	1,899,840,962
	- Codex	- gpt-6-luna - gpt-6.1-sol	43,408,079	7,558,899	0	1,848,873,984	1,899,840,962
2026-10-10	All		40,899,666	6,482,878	0	1,472,235,392	1,519,617,936
	- Codex	- gpt-6-luna - gpt-6.1-sol	40,899,666	6,482,878	0	1,472,235,392	1,519,617,936
2026-10-11	All		43,459,370	7,520,475	0	1,706,033,280	1,757,013,125
	- Codex	- gpt-6-luna - gpt-6.1-sol	43,459,370	7,520,475	0	1,706,033,280	1,757,013,125
2026-10-12	All		40,088,969	6,887,092	0	1,426,293,376	1,473,269,437
	- Codex	- gpt-6-luna - gpt-6-sol - gpt-6.1-sol	40,088,969	6,887,092	0	1,426,293,376	1,473,269,437
2026-10-13	All		42,562,493	8,266,719	0	1,734,050,304	1,784,879,516
	- Codex	- gpt-6-astra - gpt-6-luna - gpt-6.1-sol	42,562,493	8,266,719	0	1,734,050,304	1,784,879,516

Publication-safe table · October 5 is shown but excluded from the headline.

Source: supplied usage data · anonymized table · daily totals counted once

Session count and operating pattern: user estimate

Subyard Workspaces for coding agents.



Architecture diagram from the Subyard README.

Isolated agent environments

Containers or VMs with per-yard CPU and memory limits.

Shared staging

Run services and test changes on your own compute.

Across your machines

Manage hosts over SSH and sync settings through Git.

github.com/subyard/subyard

Source: Subyard README

Reference environment for this work

What each harness records and exports.

Our comparison categories, not vendor-defined levels. Metrics, events and traces are all telemetry.

Collection method	Codex CLI	Claude Code	OpenCode
01 / LOCAL **Saved by default** Read after a session	**Messages, tool calls/results, timestamps and token usage.** Input, cached input, output and reasoning counts in local rollouts. `~/.codex/ · local session files`	**Messages, tool calls/results and token/cost statistics.** JSONL transcripts, including subagents. CLI session cleanup defaults to 30 days. `~/.claude/ · transcripts + stats`	**Sessions, messages, tool inputs/results, tokens and cost.** Usage fields include input/output, cache read/write and reasoning.* `~/.local/share/opencode/`
02 / EXPORT **Metrics & logs** Configure collection	**Token counts; API/tool durations, outcomes and approvals.** Configure OTel log and metric exporters plus the collector endpoint. `otel.exporter · otel.metrics_exporter`	**Tokens/cache, cost, active time, API calls and tool events.** Enable telemetry; select metric/log exporters and the collector endpoint. `CLAUDE_CODE_ENABLE_TELEMETRY=1`	**Native OTLP/HTTP logs; metrics via plugins.*** Built-in JSON session export and token/cost summaries remain available. `opencode export · opencode stats`
03 / TRACING **Timed spans** Optional telemetry: what ran, for how long	**Native OTLP trace exporter.** Enable separately and set the destination. Actual span coverage needs a real-run check. `otel.trace_exporter`	**Interaction → API / tool spans** Beta Includes nested subagent calls. Enable enhanced telemetry and a trace exporter. `Beta flag + trace exporter`	**Native OTLP/HTTP traces in v1.19.0.*** Set the endpoint; enable AI SDK spans with `experimental.openTelemetry`. MLflow/Langfuse plugins also exist. `OTEL_EXPORTER_OTLP_ENDPOINT`


Our integration work Normalize these records; correlate task → agent → step; add process CPU/RAM measurements.

OTel = OpenTelemetry; OTLP = its export protocol. *OpenCode: v1.19.0 source; metrics plugin documented separately. Coverage varies by version/provider. Export delivery and span linkage need a live check. Provider analytics have separate defaults.

Docs/source checked October 14, 2026 · export controls and caveats in Sources

Codex ↗ · Claude Code ↗ · OpenCode ↗

Activity, cost and tokens. One dashboard.



Official AI Observer example · the image underlying the supplied annotated slide

1 Explore the data
Metrics, Logs and Traces in the sidebar.

2 Start with the overview
Trace count, log records, metric points and error rate.

3 Read service metrics
Claude Code active time, cost and lines of code.


4 See usage over time
Token charts for Claude Code, Gemini CLI and Codex CLI.

5 Choose the view
Timeframe and dashboard editing controls.

Source: official AI Observer dashboard image, reused from presentation 2

Example data · last 1 hour

AI Observer Default Dashboard.




Metrics and logs are present; no traces are shown. With zero spans, the displayed error rate does not establish error-free operation.

Source: user-supplied original screenshot

Captured view · last 1 hour

AI Observer Metrics.




Available metric choices in the captured menu. No metric is selected and no series is plotted.

Source: user-supplied original screenshot


Captured view · last 15 minutes

MLflow Trace explorer.




Span hierarchy and timings on the left; selected LLM call attributes on the right.

OpenLIT LLM dashboard.



Captured 24H view: request volume and duration, token/cost counters, and requests over time.

OpenLIT Custom evals.



Define an evaluation type and its judge prompt. The on-screen guidance describes scores, classifications and explanations, with rules based on trace attributes.

Ask the worker agent how to improve.

EXAMPLE REQUEST

Review recent agent work. Where did we repeat checks, wait unnecessarily or hold resources longer than needed?

Reduce coordination chatter.

Report completion or a meaningful change.

Rerun affected checks.

Reuse evidence when code and environment are unchanged.

Validate prerequisites early.

Check tools and fixtures before expensive setup.

Release resources promptly.

Keep a lease only while the check needs it.

Example: ask for a review of recent sessions, then validate the findings.

Anonymized prompt and recommendation summary

Thank you.

LLMs are great tools.

Use them wisely.