

# LogisticRegression

---

[Go Up](#)

Name	LogisticRegression
Version	1.0.0
Description	Logistic Regression implementation
License	<a href="http://www.apache.org/licenses/LICENSE-2.0">http://www.apache.org/licenses/LICENSE-2.0</a>
Copyright	Copyright (C) 2017 HPCC Systems
Authors	HPCCSystems
DependsOn	ML_Core, PBblas
Platform	6.2.0

## Table of Contents

<a href="#">BinomialConfusion.ecl</a>
Binomial confusion matrix
<a href="#">BinomialLogisticRegression.ecl</a>
Binomial logistic regression using iteratively re-weighted least squares
<a href="#">Confusion.ecl</a>
Detail confusion records to compare actual versus predicted response variable values
<a href="#">Constants.ecl</a>
<a href="#">DataStats.ecl</a>
Information about the datasets
<a href="#">Deviance_Analysis.ecl</a>
Compare deviance information for an analysis of deviance
<a href="#">Deviance_Detail.ecl</a>
Detail deviance for each observation
<a href="#">dimm.ecl</a>
Matrix multiply when either A or B is a diagonal and is passed as a vector
<a href="#">Distributions.ecl</a>
<a href="#">ExtractBeta.ecl</a>

<a href="#">ExtractBeta_CI.ecl</a>
Extract the beta values form the model dataset
<a href="#">ExtractBeta_pval.ecl</a>
Extract the beta values form the model dataset
<a href="#">ExtractReport.ecl</a>
Extract Report records from model
<a href="#">LogitPredict.ecl</a>
Predict the category values with the logit function and the the supplied beta coefficients
<a href="#">LogitScore.ecl</a>
Calculate the score using the logit function and the the supplied beta coefficients
<a href="#">Model_Deviance.ecl</a>
Model Deviance
<a href="#">Null_Deviance.ecl</a>
Deviance for the null model, that is, a model with only an intercept
<a href="#">Types.ecl</a>

# LogisticRegression/ BinomialConfusion

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** BinomialConfusion

<code>DATASET(Types.Binomial_Confusion_Summary)</code>	<b>BinomialConfusion</b>
<code>(DATASET(Core_Types.Confusion_Detail) d)</code>	

Binomial confusion matrix. Work items with multinomial responses are ignored by this function. The higher value lexically is considered to be the positive indication.

**PARAMETER** `d` confusion detail for the work item and classifier

**RETURN** confusion matrix for a binomial classifier

---

# LogisticRegression/ BinomialLogisticRegression

---

[Go Up](#)

## IMPORTS

LogisticRegression | LogisticRegression.Constants | ML\_Core.Interfaces |  
ML\_Core.Types |

## DESCRIPTIONS

### **MODULE** BinomialLogisticRegression

	<b>BinomialLogisticRegression</b>
	(UNSIGNED max_iter=200, REAL8 epsilon=Constants.default_epsilon, REAL8 ridge=Constants.default_ridge)

Binomial logistic regression using iteratively re-weighted least squares.

**PARAMETER** max\_iter maximum number of iterations to try

**PARAMETER** epsilon the minimum change in the Beta value estimate to continue

**PARAMETER** ridge a value to populate a diagonal matrix that is added to a matrix help assure that the matrix is invertible.

### Children

1. [GetModel](#) : Calculate the model to fit the observation data to the observed classes

2. [Classify](#) : Classify the observations using a model
  3. [Report](#) : Report the confusion matrix for the classifier and training data
- 

## FUNCTION **GetModel**

[BinomialLogisticRegression](#) \

<code>DATASET(Types.Layout_Model)</code>	<b>GetModel</b>
<code>(DATASET(Types.NumericField) observations, DATASET(Types.DiscreteField) classifications)</code>	

Calculate the model to fit the observation data to the observed classes.

**PARAMETER** observations the observed explanatory values

**PARAMETER** classifications the observed classification used to build the model

**RETURN** the encoded model

**OVERRIDE** True

---

## FUNCTION **Classify**

[BinomialLogisticRegression](#) \

<code>DATASET(Types.Classify_Result)</code>	<b>Classify</b>
<code>(DATASET(Types.Layout_Model) model, DATASET(Types.NumericField) new_observations)</code>	

Classify the observations using a model.

**PARAMETER** model The model, which must be produced by a corresponding getModel function.

**PARAMETER** new\_\_observations observations to be classified

**RETURN** Classification with a confidence value

**OVERRIDE**  True

---

## **FUNCTION** Report

BinomialLogisticRegression \

<code>DATASET(Types.Confusion_Detail)</code>	Report
<pre>(DATASET(Types.Layout_Model) model, DATASET(Types.NumericField) observations, DATASET(Types.DiscreteField) classifications)</pre>	

Report the confusion matrix for the classifier and training data.

**PARAMETER** model the encoded model

**PARAMETER** observations the explanatory values.

**PARAMETER** classifications the classifications associated with the observations

**RETURN** the confusion matrix showing correct and incorrect results

**OVERRIDE**  True

---

# LogisticRegression/ Confusion

---

[Go Up](#)

## IMPORTS

ML\_Core | ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** Confusion

<code>DATASET(Confusion_Detail)</code>	<b>Confusion</b>
<code>(DATASET(DiscreteField) dependents, DATASET(DiscreteField) predicts)</code>	

Detail confusion records to compare actual versus predicted response variable values.

**PARAMETER** dependents the original response values

**PARAMETER** predicts the predicted responses

**RETURN** confusion counts by predicted and actual response values.

---

# LogisticRegression/ Constants

---

[Go Up](#)

## DESCRIPTIONS

### **MODULE** Constants

	Constants
--	-----------

### Children

1. [limit\\_card](#)
2. [default\\_epsilon](#)
3. [default\\_ridge](#)
4. [local\\_cap](#)
5. [id\\_base](#)
6. [id\\_iters](#)
7. [id\\_delta](#)
8. [id\\_correct](#)
9. [id\\_incorrect](#)
10. [id\\_stat\\_set](#)
11. [id\\_betas](#)
12. [id\\_betas\\_coef](#)
13. [id\\_betas\\_SE](#)
14. [base\\_builder](#)
15. [base\\_max\\_iter](#)



- 16. [base\\_epsilon](#)
  - 17. [base\\_ind\\_vars](#)
  - 18. [base\\_dep\\_vars](#)
  - 19. [base\\_obs](#)
  - 20. [builder\\_irls\\_local](#)
  - 21. [builder\\_irls\\_global](#)
  - 22. [builder\\_softmax](#)
- 

## **ATTRIBUTE** limit\_card

[Constants](#) \

<b>UNSIGNED2</b>	limit_card
------------------	------------

---

## **ATTRIBUTE** default\_epsilon

[Constants](#) \

<b>REAL8</b>	default_epsilon
--------------	-----------------

---

## **ATTRIBUTE** default\_ridge

[Constants](#) \

<b>REAL8</b>	default_ridge
--------------	---------------

---

## ATTRIBUTE local\_cap

Constants \

UNSIGNED4	local_cap
-----------	-----------

---

## ATTRIBUTE id\_base

Constants \

	id_base
--	---------

---

## ATTRIBUTE id\_iters

Constants \

	id_iters
--	----------

---

## ATTRIBUTE id\_delta

Constants \

	id_delta
--	----------

---

## ATTRIBUTE id\_correct

Constants \

	id_correct
--	------------

---

## ATTRIBUTE id\_incorrect

Constants \

	id_incorrect
--	--------------

---

## ATTRIBUTE id\_stat\_set

Constants \

	id_stat_set
--	-------------

---

## ATTRIBUTE id\_betas

Constants \

	id_betas
--	----------

---

## ATTRIBUTE id\_betas\_coef

Constants \

	id_betas_coef
--	---------------

## ATTRIBUTE id\_betas\_SE

Constants \

	id_betas_SE
--	-------------

---

## ATTRIBUTE base\_builder

Constants \

	base_builder
--	--------------

---

## ATTRIBUTE base\_max\_iter

Constants \

	base_max_iter
--	---------------

---

## ATTRIBUTE base\_epsilon

Constants \

	base_epsilon
--	--------------

---

## ATTRIBUTE base\_ind\_vars

Constants \

	base_ind_vars
--	---------------

---

## ATTRIBUTE base\_dep\_vars

Constants \

	base_dep_vars
--	---------------

---

## ATTRIBUTE base\_obs

Constants \

	base_obs
--	----------

---

## ATTRIBUTE builder\_irls\_local

Constants \

	builder_irls_local
--	--------------------

---

## ATTRIBUTE builder\_irls\_global

Constants \

	builder_irls_global
--	---------------------

**ATTRIBUTE** builder\_softmax

Constants \

	builder_softmax
--	-----------------

---

# LogisticRegression/ DataStats

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |  
LogisticRegression.Constants |

## DESCRIPTIONS

### **FUNCTION** DataStats

<code>DATASET(Types.Data_Info)</code>	DataStats
<pre>(DATASET(Core_Types.NumericField) indep, DATASET(Core_Types.DiscreteField) dep, BOOLEAN field_details=FALSE)</pre>	

Information about the datasets. Without details the range for the x and y (independent and dependent) columns. Note that a column of all zero values cannot be distinguished from a missing column. When details are requested, the cardinality, minimum, and maximum values are returned. A zero cardinality is returned when the field cardinality exceeds the Constants.limit\_card value.

**PARAMETER** indep data set of independent variables

**PARAMETER** dep data set of dependent variables

**PARAMETER** field\_details Boolean directive to provide field level info

---

# LogisticRegression/ Deviance\_\_Analysis

---

[Go Up](#)

## IMPORTS

LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** Deviance\_\_Analysis

<code>DATASET(Types.AOD_Record)</code>	Deviance__Analysis
<code>(DATASET(Types.Deviance_Record) proposed, DATASET(Types.Deviance_Record) base)</code>	

Compare deviance information for an analysis of deviance.

**PARAMETER** proposed the proposed model

**PARAMETER** base the base model for comparison

**RETURN** the comparison of the deviance between the models

---



# LogisticRegression/ Deviance\_\_Detail

---

[Go Up](#)

## IMPORTS

ML\_Core | ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** Deviance\_\_Detail

<code>DATASET(Types.Observation_Deviance)</code>	Deviance__Detail
<code>(DATASET(Core_Types.DiscreteField) dependents, DATASET(Types.Raw_Prediction) predicts)</code>	

Detail deviance for each observation.

**PARAMETER** dependents original dependent records for the model

**PARAMETER** predicts the predicted values of the response variable

**RETURN** the deviance information by observation and the log likelihood of the predicted result.

---

# LogisticRegression/ dimm

---

[Go Up](#)

## IMPORTS

std.blas | std.BLAS.Types |

## DESCRIPTIONS

### **EMBED** dimm

<code>Types.matrix_t</code>	<code>dimm</code>
<code>(BOOLEAN transposeA, BOOLEAN transposeB, BOOLEAN diagonalA, BOOLEAN diagonalB, Types.dimension_t m, Types.dimension_t n, Types.dimension_t k, Types.value_t alpha, Types.matrix_t A, Types.matrix_t B, Types.value_t beta=0.0, Types.matrix_t C=[])</code>	

Matrix multiply when either A or B is a diagonal and is passed as a vector.  $\alpha * \text{op}(A) \text{ op}(B) + \beta * C$  where  $\text{op}()$  is transpose

**PARAMETER** transposeA true when transpose of A is used

**PARAMETER** transposeB true when transpose of B is used

**PARAMETER** diagonalA true when A is the diagonal matrix

**PARAMETER** diagonalB true when B is the diagonal matrix

**PARAMETER** m number of rows in product

**PARAMETER** n number of columns in product

**PARAMETER** **k** number of columns/rows for the multiplier/multiplicand

**PARAMETER** **alpha** scalar used on A

**PARAMETER** **A** matrix A

**PARAMETER** **B** matrix B

**PARAMETER** **beta** scalar for matrix C

**PARAMETER** **C** matrix C or empty

---

# LogisticRegression/ Distributions

---

[Go Up](#)

## IMPORTS

ML\_Core.Constants | ML\_Core.Math |

## DESCRIPTIONS

### **MODULE** Distributions

	Distributions
--	---------------

### Children

1. [Normal\\_CDF](#) : Cumulative Distribution of the standard normal distribution, the probability that a normal random variable will be smaller than x standard deviations above or below the mean
  2. [Normal\\_PPF](#) : Normal Distribution Percentage Point Function
  3. [T\\_CDF](#) : Students t distribution integral evaluated between negative infinity and x
  4. [T\\_PPF](#) : Percentage point function for the T distribution
  5. [Chi2\\_CDF](#) : The cumulative distribution function for the Chi Square distribution
  6. [Chi2\\_PPF](#) : The Chi Squared PPF function
-

## FUNCTION Normal\_CDF

[Distributions](#) \

REAL8	Normal_CDF
(REAL8 x)	

Cumulative Distribution of the standard normal distribution, the probability that a normal random variable will be smaller than x standard deviations above or below the mean. Taken from C/C++ Mathematical Algorithms for Scientists and Engineers, n. Shamma, McGraw-Hill, 1995

**PARAMETER** x the number of standard deviations

---

## FUNCTION Normal\_PPF

[Distributions](#) \

REAL8	Normal_PPF
(REAL8 x)	

Normal Distribution Percentage Point Function. Translated from C/C++ Mathematical Algorithms for Scientists and Engineers, N. Shamma, McGraw-Hill, 1995

**PARAMETER** x probability

---

## FUNCTION T\_CDF

[Distributions](#) \

REAL8	T_CDF
(REAL8 x, REAL8 df)	

Students t distribution integral evaluated between negative infinity and x. Translated from NIST SEL DATAPAC Fortran TCDF.f source

**PARAMETER** x value of the evaluation

**PARAMETER** df degrees of freedom

---

## FUNCTION T\_PPF

[Distributions](#) \

<b>REAL8</b>	<b>T_PPF</b>
(REAL8 x, REAL8 df)	

Percentage point function for the T distribution. Translated from NIST SEL DATAPAC Fortran TPPF.f source

---

## FUNCTION Chi2\_CDF

[Distributions](#) \

<b>REAL8</b>	<b>Chi2_CDF</b>
(REAL8 x, REAL8 df)	

The cumulative distribution function for the Chi Square distribution. the CDF for the specified degrees of freedom. Translated from the NIST SEL DATAPAC Fortran subroutine CHSCDF.

---

## FUNCTION Chi2\_PPF

[Distributions](#) \

<b>REAL8</b>	<b>Chi2_PPF</b>
(REAL8 x, REAL8 df)	

The Chi Squared PPF function. Translated from the NIST SEL DATAPAC Fortran subroutine CHSPPF.

---

## LogisticRegression/ ExtractBeta

---

[Go Up](#)

### IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

### DESCRIPTIONS

#### **FUNCTION** ExtractBeta

<b>ExtractBeta</b>
(DATASET(Core_Types.Layout_Model) mod_ds)

Extract the beta values form the model dataset.

**PARAMETER** mod\_ds the model dataset

**RETURN** a beta values as Model Coefficient records, zero as the constant term.

---

# LogisticRegression/ ExtractBeta\_CI

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** ExtractBeta\_CI

<code>DATASET(Types.Confidence_Model_Coef)</code>	<code>ExtractBeta_CI</code>
<code>(DATASET(Core_Types.Layout_Model) mod_ds, REAL8 level)</code>	

Extract the beta values form the model dataset.

**PARAMETER** mod\_ds the model dataset

**PARAMETER** level the significance value for the intervals

**RETURN** the beta values with confidence intervals term.

---



# LogisticRegression/ ExtractBeta\_pval

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** ExtractBeta\_pval

<code>DATASET(Types.pval_Model_Coef)</code>	<code>ExtractBeta_pval</code>
<code>(DATASET(Core_Types.Layout_Model) mod_ds)</code>	

Extract the beta values form the model dataset.

**PARAMETER** mod\_ds the model dataset

**RETURN** the beta values with p-values as Model Coefficient records, zero as the constant term.

---

# LogisticRegression/ ExtractReport

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |  
LogisticRegression.Constants |

## DESCRIPTIONS

### **FUNCTION** ExtractReport

<code>DATASET(Types.Model_Report)</code>	<b>ExtractReport</b>
<code>(DATASET(Core_Types.Layout_Model) mod_ds)</code>	

Extract Report records from model

**PARAMETER** mod\_ds the model dataset

**RETURN** the model report dataset

---

# LogisticRegression/ LogitPredict

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** LogitPredict

<code>DATASET(Classify_Result)</code>	<b>LogitPredict</b>
<code>(DATASET(Model_Coef) coef, DATASET(NumericField) independents)</code>	

Predict the category values with the logit function and the the supplied beta coefficients.

**PARAMETER** coef the model beta coefficients

**PARAMETER** independents the observations

**RETURN** the predicted category values and a confidence score

---

# LogisticRegression/ LogitScore

---

[Go Up](#)

## IMPORTS

ML\_Core.Types | LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** LogitScore

<code>DATASET(Raw_Prediction)</code>	<b>LogitScore</b>
<code>(DATASET(Model_Coef) coef, DATASET(NumericField) independents)</code>	

Calculate the score using the logit function and the the supplied beta coefficients.

**PARAMETER** coef the model beta coefficients

**PARAMETER** independents the observations

**RETURN** the raw prediction value

---

# LogisticRegression/ Model\_Deviance

---

[Go Up](#)

## IMPORTS

LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** Model\_Deviance

<code>DATASET(Types.Deviance_Record)</code>	Model_Deviance
<code>(DATASET(Types.Observation_Deviance) od, DATASET(Types.Model_Coef) mod)</code>	

Model Deviance.

**PARAMETER** od observation deviance record

**PARAMETER** mod model co-efficients

**RETURN** model deviance

---

# LogisticRegression/ Null\_Deviance

---

[Go Up](#)

## IMPORTS

LogisticRegression | LogisticRegression.Types |

## DESCRIPTIONS

### **FUNCTION** Null\_Deviance

<code>DATASET(Types.Deviance_Record)</code>	<code>Null_Deviance</code>
<code>(DATASET(Types.Observation_Deviance) od)</code>	

Deviance for the null model, that is, a model with only an intercept.

**PARAMETER** od Observation Deviance record set.

**RETURN** a data set of the null model deviances for each work item and classifier.

---

# LogisticRegression/ Types

---

[Go Up](#)

## IMPORTS

ML\_Core.Types |

## DESCRIPTIONS

### **MODULE** Types

	Types
--	-------

### Children

1. [t\\_Universe](#)
2. [Field\\_Desc](#)
3. [Data\\_Info](#)
4. [NumericField\\_U](#)
5. [DiscreteField\\_U](#)
6. [Layout\\_Column\\_Map](#)
7. [Classifier\\_Stats](#)
8. [Model\\_Report](#)
9. [Binomial\\_Confusion\\_Summary](#)
10. [Model\\_Coef](#)

11. [Confidence\\_Model\\_Coef](#)
  12. [pval\\_Model\\_Coef](#)
  13. [Raw\\_Prediction](#)
  14. [Observation\\_Deviance](#)
  15. [Deviance\\_Record](#)
  16. [AOD\\_Record](#)
- 

## **ATTRIBUTE** t\_Universe

[Types](#) \

	t_Universe
--	------------

---

## **RECORD** Field\_Desc

[Types](#) \

	Field_Desc
--	------------

---

## **RECORD** Data\_Info

[Types](#) \

	Data_Info
--	-----------

---



## **RECORD** NumericField\_U

Types \

	NumericField_U
--	----------------

---

## **RECORD** DiscreteField\_U

Types \

	DiscreteField_U
--	-----------------

---

## **RECORD** Layout\_Column\_Map

Types \

	Layout_Column_Map
--	-------------------

---

## **RECORD** Classifier\_Stats

Types \

	Classifier_Stats
--	------------------

---

## **RECORD** Model\_Report

Types \

	Model_Report
--	--------------

---

## **RECORD** Binomial\_Confusion\_Summary

Types \

	Binomial_Confusion_Summary
--	----------------------------

---

## **RECORD** Model\_Coef

Types \

	Model_Coef
--	------------

---

## **RECORD** Confidence\_Model\_Coef

Types \

	Confidence_Model_Coef
--	-----------------------

---

## **RECORD** pval\_Model\_Coef

Types \

	pval_Model_Coef
--	-----------------

## **RECORD** Raw\_Prediction

Types \

	Raw_Prediction
--	----------------

---

## **RECORD** Observation\_Deviance

Types \

	Observation_Deviance
--	----------------------

---

## **RECORD** Deviance\_Record

Types \

	Deviance_Record
--	-----------------

---

## **RECORD** AOD\_Record

Types \

	AOD_Record
--	------------

---