

Utils

[Go Up](#)

Table of Contents

Fat.ecl
Will take a potentially sparse file d and fill in the missing
FatD.ecl
Will take a potentially sparse file d and fill in the missing
Gini.ecl
Creates a file of pivot/target pairs with a Gini impurity value
SequenceInField.ecl
Given a file which is sorted by the work item identifier and INFIELD (and possibly other values), add sequence numbers within the range of each infield

ML_Core/ Utils/ Fat

[Go Up](#)

IMPORTS

ML_Core.Types |

DESCRIPTIONS

FUNCTION Fat

<code>DATASET(Types.NumericField)</code>	Fat
<code>(DATASET(Types.NumericField) d0, Types.t_FieldReal v=0)</code>	

Will take a potentially sparse file d and fill in the missing with value v for Numeric Field datasets

PARAMETER v ||| REAL8 — The value to assign missing records

PARAMETER d0 ||| TABLE (NumericField) — They myriad format Numeric Field dataset to be filled

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , REAL8 value }) — A full Numeric Field dataset with every field populated

ML_Core/ Utils/ FatD

[Go Up](#)

IMPORTS

ML_Core.Types |

DESCRIPTIONS

FUNCTION FatD

<code>DATASET(Types.DiscreteField)</code>	FatD
<code>(DATASET(Types.DiscreteField) d0, Types.t_Discrete v=0)</code>	

Will take a potentially sparse file d and fill in the missing with value v for Discrete Field datasets

PARAMETER v ||| INTEGER4 — The value to assign missing records

PARAMETER d0 ||| TABLE (DiscreteField) — They myriad format Discrete Field dataset to be filled

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , INTEGER4 value }) — A full Discrete Field dataset with every field populated

[Go Up](#)

DESCRIPTIONS

MACRO Gini

	Gini
<code>(infile, pivot, target, wi_name='wi')</code>	

Creates a file of pivot/target pairs with a Gini impurity value.

PARAMETER target ||| INTEGER8 — the name of the field used as the target

PARAMETER wi_name ||| INTEGER8 — the name of the work item field, default is "wi" return A table by Work Item and Pivot value giving count and Gini impurity value

PARAMETER infile ||| INTEGER8 — the input file, any type with a work item field

PARAMETER pivot ||| INTEGER8 — the name of the pivot field

RETURN BOOLEAN —

ML_Core/ Utils/ SequenceInField

[Go Up](#)

DESCRIPTIONS

MACRO SequenceInField

SequenceInField
<code>(infile,infield,seq,wi_name='wi')</code>

Given a file which is sorted by the work item identifier and INFIELD (and possibly other values), add sequence numbers within the range of each infield. Slightly elaborate code is to avoid having to partition the data to one value of infield per node and to work with very large numbers of records where a global count project would be inappropriate. This is useful for assigning rank positions with the groupings.

PARAMETER wi_name ||| INTEGER8 — work item field name, default is wi

PARAMETER infile ||| INTEGER8 — the input file, any type

PARAMETER seq ||| INTEGER8 — name of the field to receive the sequence number

PARAMETER infield ||| INTEGER8 — field name of grouping field

RETURN **BOOLEAN** — a file of the same type with sequence numbers applied
