# root

Go Up

## **Table of Contents**

import_test.ecl
This module exists to turn a dataset of numberfields into a dataset of DiscreteFields
import_test_2.ecl
mod_1.ecl
mod_2.ecl

# import\_test

Go Up

#### **IMPORTS**

ML\_Core.Generate | ML\_Core.Constants | std.Str | ML\_Core | ML\_Core.Discretize | PBblas.MatUtils |

#### **DESCRIPTIONS**

#### **MODULE** import\_test

 $import\_test$ 

This module exists to turn a dataset of numberfields into a dataset of DiscreteFields. This is not quite as trivial as it seems as there are a number of different ways to make the underlying data discrete; and even within one method there may be different parameters. Further - it is quite probable that different methods are going to be desired for each field.

INTERNAL True

#### Children

- 1. c Method: No Documentation Found
- 2. r Method: No Documentation Found
- 3. i\_ByRounding: No Documentation Found
- 4. ByRounding: No Documentation Found
- 5. i\_ByBucketing: No Documentation Found

- 6. ByBucketing: No Documentation Found
- 7. i\_ByTiling: No Documentation Found
- 8. ByTiling: No Documentation Found
- 9. Do: No Documentation Found

### ATTRIBUTE c\_Method

import\_test \

c Method

No Documentation Found

RETURN UNSIGNED4 —

## **RECORD** r\_Method

import\_test \

 $r\_Method$ 

- FIELD rparam2 ||| REAL8 No Doc
- FIELD rparam1 ||| REAL8 No Doc
- FIELD fields ||| SET ( UNSIGNED4 ) No Doc
- **FIELD** method ||| UNSIGNED4 No Doc
- FIELD iparam1 || INTEGER8 No Doc

### FUNCTION i\_ByRounding

```
import_test \
```

```
i_ByRounding
```

```
(SET OF Types.t_FieldNumber f, REAL Scale=1.0, REAL Delta=0.0)
```

No Documentation Found

```
PARAMETER delta ||| REAL8 — No Doc
```

```
PARAMETER \mathbf{\underline{f}} \parallel \parallel \text{SET} (\text{UNSIGNED4}) - \text{No Doc}
```

PARAMETER scale ||| REAL8 — No Doc

RETURN TABLE ( r\_Method ) —

#### **FUNCTION** ByRounding

import test \

#### **ByRounding**

(DATASET(Types.NumericField) d, REAL Scale=1.0, REAL Delta=0.0)

No Documentation Found

PARAMETER delta ||| REAL8 — No Doc

PARAMETER  $\underline{\mathbf{d}} \parallel \parallel \text{TABLE}$  ( NumericField ) — No Doc

PARAMETER scale ||| REAL8 — No Doc

RETURN TABLE ( { UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , INTEGER4 value } ) —

### **FUNCTION** i\_ByBucketing

import\_test \

```
i_ByBucketing
```

(SET OF Types.t\_FieldNumber f, Types.t\_Discrete N=ML\_Core.Config.Discrete)

No Documentation Found

```
PARAMETER \underline{\mathbf{f}} \parallel \parallel \text{SET} (\text{UNSIGNED4}) - \text{No Doc}
```

PARAMETER <u>n</u> ||| INTEGER4 — No Doc

RETURN TABLE ( r\_Method ) —

#### **FUNCTION** ByBucketing

import\_test \

#### ByBucketing

(DATASET(Types.NumericField) d, Types.t\_Discrete N=ML\_Core.Config.Discrete)

No Documentation Found

PARAMETER  $\underline{\mathbf{d}} \parallel \parallel \text{TABLE} (\text{NumericField}) - \text{No Doc}$ 

PARAMETER <u>n</u> ||| INTEGER4 — No Doc

RETURN TABLE ( { UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , INTEGER4 value } ) —

#### FUNCTION i\_ByTiling

import\_test \

#### i\_ByTiling

(SET OF Types.t\_FieldNumber f, Types.t\_Discrete N=ML\_Core.Config.Discrete)

No Documentation Found

PARAMETER  $\underline{\mathbf{f}} \parallel \parallel \text{SET} (\text{UNSIGNED4}) - \text{No Doc}$ 

PARAMETER <u>n</u> || INTEGER4 — No Doc

RETURN TABLE ( r\_Method ) —

## **FUNCTION** ByTiling

import\_test \

#### ByTiling

(DATASET(Types.NumericField) d, Types.t\_Discrete N=ML\_Core.Config.Discrete)

No Documentation Found

PARAMETER  $\underline{\mathbf{d}} \parallel \parallel \text{TABLE} (\text{NumericField}) - \text{No Doc}$ 

PARAMETER  $\underline{\mathbf{n}} \parallel \parallel \text{INTEGER4} - \text{No Doc}$ 

RETURN TABLE ( { UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , INTEGER4 value } ) —

#### **FUNCTION Do**

import\_test \

Do

(DATASET(Types.NumericField) d, DATASET(r\_Method) to\_do)

PARAMETER  $\underline{\mathbf{d}} \parallel \parallel \text{TABLE}$  ( NumericField ) — No Doc

RETURN TABLE ( DiscreteField ) -

# $import\_test\_2$

Go Up

### **IMPORTS**

ML\_Core.Constants | PBblas | Example\_3 |

#### **DESCRIPTIONS**

## **MODULE** import\_test\_2

 $import\_test\_2$ 

No Documentation Found

#### Children

1. nod\_1: Useful constants

2. mod\_1: No Documentation Found

## MODULE nod\_1

import\_test\_2 \

 $nod_1$ 

Useful constants

#### Children

 $mod\_1$ 

1. Pi : Constant PI
2. Root_2: Constant square root of 2
ATTRIBUTE Pi
$import\_test\_2 \setminus nod\_1 \setminus$
Pi
Constant PI
RETURN REAL8 —
ATTRIBUTE Root_2
$import\_test\_2 \setminus nod\_1 \setminus$
Root_2
Constant square root of 2
RETURN REAL8 —
MODULE mod_1
import_test_2 \

# $mod_1$

Go Up

## **DESCRIPTIONS**

## MODULE mod\_1

 $mod\_1$ 

No Documentation Found

#### Children

1. v1: No Documentation Found

2. m1v4: No Documentation Found

3. m1v6: No Documentation Found

## **ATTRIBUTE** v1

 $\bmod\_1 \setminus$ 

v1

No Documentation Found

RETURN REAL8 —

## MODULE m1v4

 $mod_1 \setminus$ 

m1v4

(REAL8 a1)

No Documentation Found

PARAMETER <u>a1</u> ||| REAL8 — No Doc

#### Children

1. m1v5: No Documentation Found

## ATTRIBUTE m1v5

 $mod_1 \setminus m1v4 \setminus$ 

m1v5

No Documentation Found

RETURN REAL8 —

## ATTRIBUTE m1v6

 $\bmod\_1 \ \backslash$ 

m1v6

# $mod_2$

Go Up

## **IMPORTS**

 $mod_1 \mid$ 

## **DESCRIPTIONS**

## MODULE mod\_2

 $mod_2$ 

No Documentation Found

#### Children

1. v2: No Documentation Found

2. v3: No Documentation Found

3. v4: No Documentation Found

4. v5: No Documentation Found

5. v6: No Documentation Found

#### MODULE v2

 $\text{mod}\_2 \setminus$ 

No Documentation Found

#### Children

1. v1: No Documentation Found

2. m1v4: No Documentation Found

3. m1v6: No Documentation Found

## ATTRIBUTE v1

 $mod_2 \setminus v2 \setminus$ 

 $\mathbf{v1}$ 

No Documentation Found

RETURN REAL8 —

## MODULE m1v4

 $mod_2 \setminus v2 \setminus$ 

m1v4

(REAL8 a1)

No Documentation Found

PARAMETER <u>a1</u> ||| REAL8 — No Doc

Children

1. m1v5: No Documentation Found

ATTRIBUTE m	1	.v5
-------------	---	-----

 $mod_2 \setminus v2 \setminus m1v4 \setminus$ 

m1v5

No Documentation Found

RETURN REAL8 —

## ATTRIBUTE m1v6

 $\bmod \_2 \ \backslash \ v2 \ \backslash$ 

m1v6

No Documentation Found

RETURN REAL8 —

## ATTRIBUTE v3

 $\bmod \_2 \ \backslash$ 

v3

#### RETURN REAL8 —

## **MODULE** v4

 $\text{mod}\_2 \setminus$ 

v4

(REAL8 a2)

No Documentation Found

PARAMETER <u>a2</u> ||| REAL8 — No Doc

#### Children

1. m1v5: No Documentation Found

## ATTRIBUTE m1v5

 $mod_2 \setminus v4 \setminus$ 

m1v5

No Documentation Found

RETURN REAL8 —

## **ATTRIBUTE** v5

 $\bmod \_2 \setminus$ 

v5

No Documentation Found

RETURN REAL8 —

# ATTRIBUTE v6

 $\text{mod}\_2 \setminus$ 

v6

No Documentation Found

RETURN REAL8 —