

Math

[Go Up](#)

Table of Contents

Beta.ecl
Return the beta value of two positive real numbers, x and y
Distributions.ecl
DoubleFac.ecl
The 'double' factorial is defined for ODD n and is the product of all the odd numbers up to and including that number
Fac.ecl
Factorial function
gamma.ecl
Return the value of gamma function of real number x A wrapper for the standard C tgamma function
log_gamma.ecl
Return the value of the log gamma function of the absolute value of X
lowerGamma.ecl
Return the lower incomplete gamma value of two real numbers,
NCK.ecl
Poly.ecl
Evaluate a polynomial from a set of co-effs
StirlingFormula.ecl
Stirling's formula
upperGamma.ecl
Return the upper incomplete gamma value of two real numbers, x and y

ML_Core/ Math/ Beta

[Go Up](#)

IMPORTS

ML_Core.Math |

DESCRIPTIONS

FUNCTION Beta

	Beta
(REAL8 x, REAL8 y)	

Return the beta value of two positive real numbers, x and y

PARAMETER x ||| REAL8 — the value of the first number

PARAMETER y ||| REAL8 — the value of the second number

RETURN REAL8 — the beta value

ML_Core/ Math/ Distributions

[Go Up](#)

IMPORTS

ML_Core.Constants | ML_Core.Math |

DESCRIPTIONS

MODULE Distributions

	Distributions
--	---------------

No Documentation Found

Children

1. [Normal_CDF](#) : Cumulative Distribution of the standard normal distribution, the probability that a normal random variable will be smaller than x standard deviations above or below the mean
 2. [Normal_PPF](#) : Normal Distribution Percentage Point Function
 3. [T_CDF](#) : Students t distribution integral evaluated between negative infinity and x
 4. [T_PPF](#) : Percentage point function for the T distribution
 5. [Chi2_CDF](#) : The cumulative distribution function for the Chi Square distribution
 6. [Chi2_PPF](#) : The Chi Squared PPF function
-

FUNCTION Normal_CDF

[Distributions \](#)

REAL8	Normal_CDF
(REAL8 x)	

Cumulative Distribution of the standard normal distribution, the probability that a normal random variable will be smaller than x standard deviations above or below the mean. Taken from C/C++ Mathematical Algorithms for Scientists and Engineers, n. Shamma, McGraw-Hill, 1995

PARAMETER x ||| REAL8 — the number of standard deviations

RETURN REAL8 —

FUNCTION Normal_PPF

[Distributions \](#)

REAL8	Normal_PPF
(REAL8 x)	

Normal Distribution Percentage Point Function. Translated from C/C++ Mathematical Algorithms for Scientists and Engineers, N. Shamma, McGraw-Hill, 1995

PARAMETER x ||| REAL8 — probability

RETURN REAL8 —

FUNCTION T_CDF

[Distributions \](#)

REAL8	T_CDF
(REAL8 x, REAL8 df)	

Students t distribution integral evaluated between negative infinity and x. Translated from NIST SEL DATAPAC Fortran TCDF.f source

PARAMETER x ||| REAL8 — value of the evaluation

PARAMETER df ||| REAL8 — degrees of freedom

RETURN REAL8 —

FUNCTION T_PPF

[Distributions \](#)

REAL8	T_PPF
(REAL8 x, REAL8 df)	

Percentage point function for the T distribution. Translated from NIST SEL DATAPAC Fortran TPPF.f source

PARAMETER x ||| REAL8 — No Doc

PARAMETER df ||| REAL8 — No Doc

RETURN REAL8 —

FUNCTION Chi2_CDF

[Distributions \](#)

REAL8	Chi2_CDF
(REAL8 x, REAL8 df)	

The cumulative distribution function for the Chi Square distribution. the CDF for the specied degrees of freedom. Translated from the NIST SEL DATAPAC Fortran subroutine CHSCDF.

PARAMETER x ||| REAL8 — No Doc

PARAMETER df ||| REAL8 — No Doc

RETURN REAL8 —

FUNCTION Chi2_PPF

[Distributions \](#)

REAL8	Chi2_PPF
(REAL8 x, REAL8 df)	

The Chi Squared PPF function. Translated from the NIST SEL DATAPAC Fortran subroutine CHSPPF.

PARAMETER x ||| REAL8 — No Doc

PARAMETER df ||| REAL8 — No Doc

RETURN REAL8 —

ML_Core/ Math/ DoubleFac

[Go Up](#)

DESCRIPTIONS

EMBED DoubleFac

REAL8	DoubleFac
(INTEGER2 i)	

The 'double' factorial is defined for ODD n and is the product of all the odd numbers up to and including that number. We are extending the meaning to even numbers to mean the product of the even numbers up to and including that number. Thus $\text{DoubleFac}(8) = 8*6*4*2$ We also defend against $i < 2$ (returning 1.0)

PARAMETER *i* ||| INTEGER2 — the value used in the calculation

RETURN **REAL8** — the factorial of the sequence, declining by 2

ML_Core/ Math/ Fac

[Go Up](#)

DESCRIPTIONS

EMBED Fac

REAL8	Fac
(UNSIGNED2 i)	

Factorial function

PARAMETER **i** ||| UNSIGNED2 — the value used, $(i)(i-1)(i-2) \dots (2)$

RETURN **REAL8** — the factorial $i!$

ML_Core/ Math/ gamma

[Go Up](#)

DESCRIPTIONS

EMBED gamma

REAL8	gamma
(REAL8 x)	

Return the value of gamma function of real number x A wrapper for the standard C tgamma function.

PARAMETER x ||| REAL8 — the input x

RETURN REAL8 — the value of GAMMA evaluated at x

ML_Core/ Math/ log_gamma

[Go Up](#)

DESCRIPTIONS

EMBED log_gamma

REAL8	log_gamma
(REAL8 x)	

Return the value of the log gamma function of the absolute value of X. A wrapper for the standard C lgamma function. Avoids the race condition found on some platforms by taking the absolute value of the of the input argument.

PARAMETER x ||| REAL8 — the input x

RETURN **REAL8** — the value of the log of the GAMMA evaluated at ABS(x)

ML_Core/ Math/ lowerGamma

[Go Up](#)

DESCRIPTIONS

EMBED lowerGamma

REAL8	lowerGamma
(REAL8 x, REAL8 y)	

Return the lower incomplete gamma value of two real numbers, x and y

PARAMETER x ||| REAL8 — the value of the first number

PARAMETER y ||| REAL8 — the value of the second number

RETURN REAL8 — the lower incomplete gamma value

ML_Core/ Math/ NCK

[Go Up](#)

IMPORTS

ML_Core.Math |

DESCRIPTIONS

FUNCTION NCK

REAL8	NCK
(INTEGER2 N, INTEGER2 K)	

No Documentation Found

PARAMETER n ||| INTEGER2 — No Doc

PARAMETER k ||| INTEGER2 — No Doc

RETURN REAL8 —

ML_Core/ Math/ Poly

[Go Up](#)

DESCRIPTIONS

EMBED Poly

REAL8	Poly
(REAL8 x, SET OF REAL8 Coeffs)	

Evaluate a polynomial from a set of co-effs. Co-effs 1 is assumed to be the HIGH order of the equation. Thus for ax^2+bx+c - the set would need to be $\text{Coef} := [a,b,c]$;

PARAMETER Coeffs ||| SET (REAL8) — a set of coefficients for the polynomial. The ALL set is considered to be all zero values

PARAMETER x ||| REAL8 — the value of x in the polynomial

RETURN **REAL8** — value of the polynomial at x

ML_Core/ Math/ StirlingFormula

[Go Up](#)

IMPORTS

ML_Core.Math | ML_Core.Constants |

DESCRIPTIONS

FUNCTION StirlingFormula

	StirlingFormula
(REAL x)	

Stirling's formula

PARAMETER x ||| REAL8 — the point of evaluation

RETURN REAL8 — evaluation result

ML_Core/ Math/ upperGamma

[Go Up](#)

DESCRIPTIONS

EMBED upperGamma

REAL8	upperGamma
(REAL8 x, REAL8 y)	

Return the upper incomplete gamma value of two real numbers, x and y.

PARAMETER x ||| REAL8 — the value of the first number

PARAMETER y ||| REAL8 — the value of the second number

RETURN REAL8 — the upper incomplete gamma value
