MCL-BB — Full Plan

Overview

MCL-BB is a complaint registration and management system for Lufthavne Municipal Corporation. Complaints are received by citizens through calls, emails, or other channels and entered into the system by a documentation operator. There is no citizen-facing dashboard. The system handles location-based officer mapping, status tracking through a defined hierarchy, and escalation approval before closure.

End-to-End System Workflow





Complaint Entry — Two Paths



Path 1: Manual Entry

The operator fills all fields in the complaint form. Every field is required; the form does not allow submission with missing data.

Fields:

- Citizen name
- Phone number
- Complaint type
- Complaint description
- Zone → Block → Ward
- Address
- Images / multimedia (upload)

Location Selection Logic:

Zone, Block, and Ward are interdependent but flexible in any direction of entry:

- If the operator selects **Zone** first → **Block** dropdown filters to blocks under that zone → **Ward** filters to wards under that block
- If the operator enters **Block** directly → **Zone** auto-fills → **Ward** filters accordingly
- If the operator enters **Ward** directly → **Zone** and **Block** both auto-fill

The data-driving this logic lives in a `LOCATIONS` lookup table. Nothing is hardcoded. The structure reflects Lufthavne's actual 4 zones and 13 blocks, with each ward mapped to its parent block and zone.

GIS Mapping (Optional):

The operator can optionally enter a pincode to drop a visual pin on a map. This uses Leaflet.js with OpenStreetMap — no paid API needed.

Any MMC has a visual reference only. It does not drive officer mapping. The reason: pincode boundaries in India frequently overlap or cover multiple wards, and Lufthavne ward-pincode boundaries data (GeoJSON) is not publicly available. Once MCL-BB's pincode-officer boundary classifiers, the map can be upgraded to confirm which ward a pincode falls in and use that for mapping. Until then, officer mapping is based entirely on the manually selected Ward.

On Submit:

1. System reads the selected Ward
2. Looks up the officer(s) assigned to that ward from the officer data
3. Looks up the ATP for that ward
4. Generates a unique complaint ID
5. Saves complaint record to database and syncs to Google Sheets
6. Screen confirms "Complaint registered — assigned to [Officer Name]. Phone Number]"
7. WhatsApp notifications sent to assigned officer and ATP

Path 2: Image / PDF Upload

The operator uploads a scanned image or PDF of the complaint (physical form, letter, etc.)

Processing flow:

1. File is passed through OCR to extract raw text
2. LLM processes the extracted text to identify and populate ward, address, citizen name, phone, complaint description, and all other required fields
3. The operator is shown a prefilled edit page with the auto-filled data
4. The operator reviews, corrects any errors, and confirms
5. On confirmation, the same submit flow as manual entry — officer mapping, complaint ID generation, DB + Sheets sync, notifications

Why a preview step: OCR accuracy on handwritten or low-quality scans is imperfect. The LLM extraction improves it significantly but cannot guarantee 100% accuracy. The operator's review step ensures no complaint goes in with wrong ward or citizen data.

WhatsApp Integration

WhatsApp is split into two separate problems with different complexity levels.

Sending Notifications (Outbound)

When a complaint is registered, a WhatsApp message is sent to the assigned officer and ATP containing the complaint ID, citizen name, ward, and complaint title.

How this works:

Via a WhatsApp Business API provider — Twilio, Gupshup, or eGates are available options for India. These providers handle Meta's API layer and offer simpler REST APIs to call from the backend.

The Whatsapp Business API supports webhooks — when a message is received on the business number, Meta sends a POST request to a configured webhook URL on the backend. The backend receives this, passes the message text to an LLM, which extracts the complaint ID and resolution summary, then updates the complaint status to "Resolution Submitted" in the database and Sheets.

Problems to solve before this works.

- The webhook endpoint must be publicly accessible (not localhost). During development, a tunneling tool like ngrok can expose a local server. In production, the server must be deployed with a real domain/IP.
- Officers may send messages in mixed Hindi/English or with inconsistent formatting. The LLM prompt must be robust enough to handle this and still extract a valid complaint ID.
- If a complaint ID in the message is wrong or missing, the system cannot match it to a record. It flatters is needed — either the system replies asking for clarification, or a manual lookup option is available on the portal.
- The officer's phone number must be registered in the system so the incoming message can be attributed to the right person. Unrecognised numbers should be flagged.

This part requires more testing and iteration than outbound notifications. It should be built and tested in a sandboxed environment before going live.

Officer Mapping

Officer data supports many-to-many assignment — one officer can cover multiple blocks and wards.

Officer record structure:

```
{
  "officerId": "OFF-001",
  "name": "Ramesh Kumar",
  "phone": "+919876543210",
  "designation": "Junior Engineer",
  "department": "Roads & Drainage",
  "zones": ["Zone A", "Zone B"],
  "blocks": ["Block 1", "Block 2", "Block 3"],
  "wards": ["Ward 1", "Ward 2", "Ward 3"]
}
```

When a complaint is submitted for a ward, the system queries all officers whose `wards` array includes that ward. If multiple officers are found, all are assigned and notified. ATP is mapped separately based on zone/block.

Complaint Status Workflow

Resolution and closure are always separate states. An officer cannot close their own complaint.

Complaint Data Structure

```
{
  "complaintId": "LUM-2026-00042",
  "citizen": {
    "name": "Vikram Seth",
    "phone": "+919876543210"
  },
  "complaint": {
    "type": "Roads",
    "description": "Pothole near main market area",
    "attachments": ["Photos/ward_road_main_01.jpg"]
  },
  "location": {
    "zone": "Zone A",
    "block": "Block 1",
    "ward": "Ward 3",
    "address": "Near Gate No. 2",
    "gridRef": { "lat": 28.661, "lng": 77.227 }
  },
  "mapping": {
    "officerIds": ["OFF-001", "OFF-002"],
    "atpId": "ATP-003",
    "appId": null
  },
  "workflow": {
    "status": "In Progress",
    "resolutionSubmittedAt": null,
    "approvedAt": null,
    "closedAt": null,
    "rejectionReason": null,
    "reworkCount": 0
  },
  "timestamps": {
    "createdAt": "2026-04-01T14:30:00Z",
    "lastUpdatedAt": "2026-04-02T09:15:00Z"
  }
}
```

Multimedia file binaries are stored in an `/uploads` folder on the server. Only metadata (name, type, path, time) is stored in the complaint record.

Authority Hierarchy

For MVP, the approval step involves ATP or APP. Higher levels (JC, CC) are part of the data model but not actively involved in the MVP workflow.

Analytics Dashboard

The portal includes an analytics view accessible based on designation and login credentials. Login is username + area + designation based.

Dashboard shows:

- Complaint counts by status
- Filtering by zone, block, ward
- Top performers (officers with most resolved/approved complaints)

Google Sheets Sync

Every complaint registration and every status update syncs to a linked Google Sheet. This gives non-technical stakeholders a live view of all complaints without needing portal access. The sync uses the Google Sheets API with a service account.

Implementation Order

Key Rules (Non-Negotiable)

1. **No citizen dashboard or citizen login**
2. Complaint ID is generated on submission — returned via call, email, or any channel.
3. All form fields are required.
4. Zone → Block → Ward are interdependent and auto-fill in any direction.
5. If zones, 13 blocks — data-driven, nothing hardcoded.
6. One officer can be assigned to multiple blocks and wards.
7. Multiple officers can be assigned to one complaint.
8. Resolution submission does not close a complaint.
9. Closure requires explicit approval from ATP or APP.
10. Resolution and closure are always separate states.
11. Multimedia binary never goes into the complaint record — metadata only.
12. Google Sheets is a mirror, not the source of truth.
13. WhatsApp inbound webhook is a public-accessible webhook — not available on localhost in production.
14. All status changes sync to Google Sheets.