RAJALAKSHMI ENGINEERING COLLEGE

Started on	Friday, 24 October 2025, 1:53 PM
State	Finished
Completed on	Friday, 24 October 2025, 2:19 PM
Time taken	26 mins 12 secs
Marks	1.00/1.00
Grade	**4.00** out of 4.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findDuplicate(int arr[], int n) {
    int seen[n + 1];
    for (int i = 0; i <= n; i++)
        seen[i] = 0;
    for (int i = 0; i < n; i++) {
        if (seen[arr[i]] == 1)
            return arr[i];
        seen[arr[i]] = 1;
    }
    return -1;
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    int dup = findDuplicate(arr, n);
    if (dup != -1)
        printf("%d", dup);
    else
        printf("No duplicate");
    return 0;
}

```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Started on	Friday, 24 October 2025, 1:54 PM
State	Finished
Completed on	Friday, 24 October 2025, 2:24 PM
Time taken	29 mins 57 secs
Marks	1.00/1.00
Grade	**4.00** out of 4.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findDuplicate(int arr[], int n) {
    int seen[n + 1];
    for (int i = 0; i <= n; i++)
        seen[i] = 0;
    for (int i = 0; i < n; i++) {
        if (seen[arr[i]] == 1)
            return arr[i];
        seen[arr[i]] = 1;
    }
    return -1;
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    int dup = findDuplicate(arr, n);
    if (dup != -1)
        printf("%d", dup);
    else
        printf("No duplicate");
    return 0;
}

```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Started on	Friday, 24 October 2025, 1:57 PM
State	Finished
Completed on	Friday, 24 October 2025, 2:23 PM
Time taken	26 mins 30 secs
Marks	1.00/1.00
Grade	**30.00** out of 30.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void intersection(int arr1[], int n1, int arr2[], int n2) {
    int i = 0, j = 0;
    while (i < n1 && j < n2) {
        if (arr1[i] < arr2[j])
            i++;
        else if (arr1[i] > arr2[j])
            j++;
        else {
            printf("%d ", arr1[i]);
            i++;
            j++;
        }
    }
    printf("\n");
}

int main() {
    int T;
    scanf("%d", &T);
    while (T--) {
```

```
        int n1, n2;
        scanf("%d", &n1);
        int arr1[n1];
        for (int i = 0; i < n1; i++)
            scanf("%d", &arr1[i]);
        scanf("%d", &n2);
        int arr2[n2];
        for (int i = 0; i < n2; i++)
            scanf("%d", &arr2[i]);
        intersection(arr1, n1, arr2, n2);
    }
    return 0;
}

```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Started on	Friday, 24 October 2025, 1:58 PM
State	Finished
Completed on	Friday, 24 October 2025, 2:25 PM
Time taken	27 mins 28 secs
Marks	1.00/1.00
Grade	**30.00** out of 30.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void intersection(int arr1[], int n1, int arr2[], int n2) {
    int i = 0, j = 0;
    while (i < n1 && j < n2) {
        if (arr1[i] < arr2[j])
            i++;
        else if (arr1[i] > arr2[j])
            j++;
        else {
            printf("%d ", arr1[i]);
            i++;
            j++;
        }
    }
    printf("\n");
}

int main() {
    int T;
    scanf("%d", &T);
    while (T--) {
```

```
    while (1) {
        int n1, n2;
        scanf("%d", &n1);
        int arr1[n1];
        for (int i = 0; i < n1; i++)
            scanf("%d", &arr1[i]);

        scanf("%d", &n2);
        int arr2[n2];
        for (int i = 0; i < n2; i++)
            scanf("%d", &arr2[i]);

        intersection(arr1, n1, arr2, n2);
    }
    return 0;
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Started on	Friday, 24 October 2025, 1:59 PM
State	Finished
Completed on	Friday, 24 October 2025, 2:12 PM
Time taken	13 mins 30 secs
Marks	1.00/1.00
Grade	**4.00** out of 4.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n, k;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    scanf("%d", &k);

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (i != j && arr[j] - arr[i] == k) {
                printf("1");
                return 0;
            }
        }
    }
    printf("0");
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔

	Input	Expected	Got	
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Started on	Friday, 24 October 2025, 1:59 PM
State	Finished
Completed on	Friday, 24 October 2025, 2:26 PM
Time taken	26 mins 44 secs
Marks	1.00/1.00
Grade	**4.00** out of 4.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n, k;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    scanf("%d", &k);

    int i = 0, j = 1;
    while (i < n && j < n) {
        if (i != j && arr[j] - arr[i] == k) {
            printf("1");
            return 0;
        } else if (arr[j] - arr[i] < k)
            j++;
        else
            i++;
    }
    printf("0");
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔

	Input	Expected	Got	
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course