
DIMENSIONS — INCHES

PART NUMBER	TUBE OD	THREAD B (JIC)	THREAD A (NPTF)	L	C	HEX
2404-02-02	1/8	5/16-24	1/8-27	1.11	0.44	0.4375
2404-03-02	3/16	3/8-24	1/8-27	1.14	0.44	0.4375
2404-04-02 *	1/4	7/16-20	1/8-27	1.22	0.5	0.5
2404-04-04	1/4	7/16-20	1/4-18	1.42	0.56	0.5625
2404-05-02 *	5/16	1/2-20	1/8-27	1.22	0.56	0.5625
2404-05-04	5/16	1/2-20	1/4-18	1.42	0.56	0.5625
2404-06-04 *	3/8	9/16-18	1/4-18	1.43	0.63	0.625
2404-06-06	3/8	9/16-18	3/8-18	1.43	0.75	0.75
2404-08-06 *	1/2	3/4-16	3/8-18	1.53	0.81	0.8125
2404-10-08	5/8	7/8-14	1/2-14	1.89	0.94	0.9375
2404-10-12 *	5/8	7/8-14	3/4-14	1.95	1.13	1.125
2404-12-08 *	3/4	1 1/16-12	1/2-14	2.06	1.13	1.125
2404-12-12	3/4	1 1/16-12	3/4-14	2.06	1.13	1.125
2404-12-16 *	3/4	1 1/16-12	1-11 1/2	2.25	1.38	1.375
2404-16-08 *	1	1 5/16-12	1/2-14	2.11	1.38	1.375
2404-16-12 *	1	1 5/16-12	3/4-14	2.11	1.38	1.375
2404-16-16	1	1 5/16-12	1-11 1/2	2.3	1.38	1.375
2404-16-20 *	1	1 5/16-12	1 1/4-11 1/2	2.4	1.69	1.6875

UNLESS OTHERWISE SPECIFIED — GENERAL TOLERANCES

DECIMALS .X = ±0.030 .XX = ±0.015 .XXX = ±0.005
ANGLES ±0°30' THREADS PER APPLICABLE STANDARD
SURFACE FINISH 125 MICROIN. Ra BREAK SHARP EDGES 0.010 MAX
SEAT ANGLE TOLERANCE ±0°15' CONCENTRICITY 0.010 TIR

THIRD ANGLE PROJECTION



DRAWN BY	CHECKED	DATE	SCALE	REV	SHEET
		2026-08-05	NTS	A	1 OF 2

NOTES

1. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED. DO NOT SCALE DRAWING.
2. END A THREAD PER ASME B1.20.3
3. END B THREAD PER SAE J514 / J514-1
4. MATERIAL PER
5. FINISH PER
6. PARTS MARKED * ARE NOT STANDARDS-VERIFIED AND ARE NOT RELEASED FOR PRODUCTION.

DATA STATUS: MIXED **STD CHECK:** MATCH **GEOM ROOT:** 2404

OM

OM INDUSTRIAL PRODUCTS CORP.

3334 Creekmont Drive
Houston, TX 77091, USA
Ph: 713-462-7900 | 1-888-663-4884
sales@omindustrial.com

PART NUMBER	2404 SERIES
DESCRIPTION	Male Connector — TABULATED
MATERIAL	SEE NOTE 4
FINISH / COATING	SEE NOTE 5