

# IS-ZC444: ARTIFICIAL INTELLIGENCE

## Lecture-13: Machine Learning



**Dr. Kamlesh Tiwari**

Assistant Professor

Department of Computer Science and Information Systems,  
BITS Pilani, Pilani, Jhunjhunu-333031, Rajasthan, INDIA

Nov 15, 2020

**FLIPPED**

(WILP @ BITS-Pilani Jul-Nov 2020)

# Classification

Finding the right label



# Classification

Finding the right label



# Classification

Finding the right label



What feature (attributes) would you choose?

Color, texture, weight, density, hardness .....

# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)

# K Nearest Neighbor (KNN)


You are most likely as your friends (Bias)

- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting

# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)

- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias






# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)


- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# K Nearest Neighbor (KNN)

You are most likely as your friends (Bias)

- Two step algorithm
  - 1 Search  $k$  other datum points (most difficult part)
  - 2 Apply majority voting
- A lazy learner
- To avoid ties,  $k$  should NOT be a multiple of number of classes
- Small  $k$  is sensitive to noise and large one has high bias



# Decision Tree

## Decision Tree


is a method for approximating discrete-valued functions. It is robust to noisy data and capable of learning disjunctive expressions. Primarily useful for classification.



# Decision Tree

## Decision Tree

is a method for approximating discrete-valued functions. It is robust to noisy data and capable of learning disjunctive expressions. Primarily useful for classification.




- Each node in the tree specifies a test for some attribute

# Decision Tree

## Decision Tree

is a method for approximating discrete-valued functions. It is robust to noisy data and capable of learning disjunctive expressions. Primarily useful for classification.




- Each node in the tree specifies a test for some attribute
- Each branch descending from the node corresponds to one of the possible value

# Decision Tree

## Decision Tree

is a method for approximating discrete-valued functions. It is robust to noisy data and capable of learning disjunctive expressions. Primarily useful for classification.




- Each node in the tree specifies a test for some attribute
- Each branch descending from the node corresponds to one of the possible value
- Decision trees represent a disjunction of conjunctions

# Decision Tree

## Decision Tree

is a method for approximating discrete-valued functions. It is robust to noisy data and capable of learning disjunctive expressions. Primarily useful for classification.



- Each node in the tree specifies a test for some attribute
- Each branch descending from the node corresponds to one of the possible value
- Decision trees represent a disjunction of conjunctions

$$(Outlook = Sunny \wedge Humidity = Normal) \vee (Outlook = Overcast) \vee (Outlook = Rain \wedge Wind = Weak)$$

# Entropy

Characterizes the impurity of an arbitrary collection of examples

# Entropy

Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

# Entropy

Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

Range is 0 to 1, *i.e.*  $0 \leq Entropy(S) \leq 1$

- 0** – when all members are of same class.
- 1** – if equal number of positive and negative


# Entropy

Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

Range is 0 to 1, *i.e.*  $0 \leq Entropy(S) \leq 1$

- 0** – when all members are of same class.
- 1** – if equal number of positive and negative





# Entropy


Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

Range is 0 to 1, *i.e.*  $0 \leq Entropy(S) \leq 1$

**0** – when all members are of same class.

**1** – if equal number of positive and negative



Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

# Entropy


Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

Range is 0 to 1, i.e.  $0 \leq Entropy(S) \leq 1$

**0** – when all members are of same class.

**1** – if equal number of positive and negative



Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

$Entropy([9+, 5-])$


# Entropy

Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

Range is 0 to 1, i.e.  $0 \leq Entropy(S) \leq 1$

- 0** – when all members are of same class.
- 1** – if equal number of positive and negative



Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

$$Entropy([9+, 5-])$$

$$= -(9/14) \log_2(9/14) - (5/14) \log_2(5/14)$$

# Entropy


Characterizes the impurity of an arbitrary collection of examples

$$Entropy(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

Range is 0 to 1, i.e.  $0 \leq Entropy(S) \leq 1$

**0** – when all members are of same class.

**1** – if equal number of positive and negative



Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

$$Entropy([9+, 5-])$$

$$\begin{aligned} &= -(9/14) \log_2(9/14) \\ &\quad - (5/14) \log_2(5/14) \\ &= 0.94 \end{aligned}$$

# Information Gain

Information Gain of an **attribute**  $A^1$  is the expected reduction in entropy caused by partitioning the dataset  $S$  according to that attribute

---

<sup>1</sup>Outlook, Temperature, Humidity, Wind

# Information Gain

Information Gain of an **attribute**  $A^1$  is the expected reduction in entropy caused by partitioning the dataset  $S$  according to that attribute

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

here  $S_v$  contains that data items of  $S$  where the value of attribute  $A$  is  $v$

---

<sup>1</sup>Outlook, Temperature, Humidity, Wind

# Information Gain

Information Gain of an **attribute**  $A^1$  is the expected reduction in entropy caused by partitioning the dataset  $S$  according to that attribute

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

here  $S_v$  contains that data items of  $S$  where the value of attribute  $A$  is  $v$

Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

<sup>1</sup>Outlook, Temperature, Humidity, Wind

# Information Gain

Information Gain of an **attribute**  $A^1$  is the expected reduction in entropy caused by partitioning the dataset  $S$  according to that attribute

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

here  $S_v$  contains that data items of  $S$  where the value of attribute  $A$  is  $v$

Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

For example

$$\begin{aligned} S_{Sunny} &= \{D1, D2, D8, D9, D11\} \\ S_{Overcast} &= \{D3, D7, D12, D13\} \\ S_{Cool} &= \{D5, D6, D7, D9\} \\ S_{Hot} &= \{D1, D2, D3, D13\} \\ S_{Normal} &= \{D5, D6, D7, D9, D10, D11, D13\} \\ S_{High} &= \{D1, D2, D3, D4, D8, D12, D14\} \end{aligned}$$

And so on....

<sup>1</sup>Outlook, Temperature, Humidity, Wind



# Information Gain

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

$S_{High}$  = {D1, D2, D3, D4, D8, D12, D14}  
 $S_{Normal}$  = {D5, D6, D7, D9, D10, D11, D13}


$S_{Weak}$  = {D1, D3, D4, D5, D8, D9, D10, D13}  
 $S_{Strong}$  = {D2, D6, D7, D11, D12, D14}

# Information Gain

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

$S_{High} = \{D1, D2, D3, D4, D8, D12, D14\}$   
 $S_{Normal} = \{D5, D6, D7, D9, D10, D11, D13\}$

$S_{Weak} = \{D1, D3, D4, D5, D8, D9, D10, D13\}$   
 $S_{Strong} = \{D2, D6, D7, D11, D12, D14\}$




# Information Gain

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

$S_{High} = \{D1, D2, D3, D4, D8, D12, D14\}$   
 $S_{Normal} = \{D5, D6, D7, D9, D10, D11, D13\}$

$S_{Weak} = \{D1, D3, D4, D5, D8, D9, D10, D13\}$   
 $S_{Strong} = \{D2, D6, D7, D11, D12, D14\}$





$$Gain(S, Humidity) = 0.940 - (7/14)0.985 - (7/14)0.592 = 0.151$$

# Information Gain

$$\text{Gain}(S, A) = \text{Entropy}(S) - \sum_{v \in \text{Value}(A)} \frac{|S_v|}{|S|} \text{Entropy}(S_v)$$

$S_{\text{High}}$  = {D1, D2, D3, D4, D8, D12, D14}  
 $S_{\text{Normal}}$  = {D5, D6, D7, D9, D10, D11, D13}

$S_{\text{Weak}}$  = {D1, D3, D4, D5, D8, D9, D10, D13}  
 $S_{\text{Strong}}$  = {D2, D6, D7, D11, D12, D14}





$$\text{Gain}(S, \text{Humidity}) = 0.940 - (7/14)0.985 - (7/14)0.592 = 0.151$$

# Information Gain

$$Gain(S, A) = Entropy(S) - \sum_{v \in Value(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$

$S_{High} = \{D1, D2, D3, D4, D8, D12, D14\}$   
 $S_{Normal} = \{D5, D6, D7, D9, D10, D11, D13\}$

$S_{Weak} = \{D1, D3, D4, D5, D8, D9, D10, D13\}$   
 $S_{Strong} = \{D2, D6, D7, D11, D12, D14\}$



$$Gain(S, Humidity) = 0.940 - (7/14)0.985 - (7/14)0.592 = 0.151$$

$$Gain(S, Wind) = 0.940 - (8/14)0.811 - (6/14)1.000 = 0.048$$

# Information Gain and Decision Tree

$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

# Information Gain and Decision Tree

$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

$[D_1, D_2, D_3, D_4, D_5, D_6, D_7, D_8, D_9, D_{10}, D_{11}, D_{12}, D_{13}, D_{14}]$   
 $\{9+, 5-\}$

Outlook

# Information Gain and Decision Tree


$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

$[D_1, D_2, D_3, D_4, D_5, D_6, D_7, D_8, D_9, D_{10}, D_{11}, D_{12}, D_{13}, D_{14}]$   
 $\{9+, 5-\}$





# Information Gain and Decision Tree


$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

$[D_1, D_2, D_3, D_4, D_5, D_6, D_7, D_8, D_9, D_{10}, D_{11}, D_{12}, D_{13}, D_{14}]$   
 $\{9+, 5-\}$



# Information Gain and Decision Tree


$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

$[D_1, D_2, D_3, D_4, D_5, D_6, D_7, D_8, D_9, D_{10}, D_{11}, D_{12}, D_{13}, D_{14}]$   
 $\{9+, 5-\}$



# Information Gain and Decision Tree


$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

$[D_1, D_2, D_3, D_4, D_5, D_6, D_7, D_8, D_9, D_{10}, D_{11}, D_{12}, D_{13}, D_{14}]$   
 $\{9+, 5-\}$



# Information Gain and Decision Tree


$$\text{Gain}(S, \text{Humidity}) = 0.151$$

$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$

$$\text{Gain}(S, \text{Temperature}) = 0.029$$

$[D_1, D_2, D_3, D_4, D_5, D_6, D_7, D_8, D_9, D_{10}, D_{11}, D_{12}, D_{13}, D_{14}]$   
 $\{9+, 5-\}$




# Information Gain and Decision Tree

$$\text{Gain}(S, \text{Humidity}) = 0.151$$


$$\text{Gain}(S, \text{Wind}) = 0.048$$

$$\text{Gain}(S, \text{Outlook}) = 0.246$$


$$\text{Gain}(S, \text{Temperature}) = 0.029$$




# Recursively apply the same



# Recursively apply the same




# Recursively apply the same



$$S_{\text{sunny}} = [D_1, D_2, D_8, D_9, D_{11}]$$




# Recursively apply the same



$$S_{\text{sunny}} = [D_1, D_2, D_8, D_9, D_{11}]$$

$$\text{Gain}(S_{\text{sunny}}, \text{Humidity}) = 0.970 - (3/5)0.0 - (2/5)0.0 = 0.970$$

# Recursively apply the same




$$S_{\text{sunny}} = [D_1, D_2, D_8, D_9, D_{11}]$$

$$\text{Gain}(S_{\text{sunny}}, \text{Humidity}) = 0.970 - (3/5)0.0 - (2/5)0.0 = 0.970$$

$$\text{Gain}(S_{\text{sunny}}, \text{Temperature}) = 0.970 - (2/5)0.0 - (2/5)1.0 - (1/5)0.0 = 0.57$$

# Recursively apply the same




$$S_{\text{sunny}} = [D_1, D_2, D_8, D_9, D_{11}]$$

$$\text{Gain}(S_{\text{sunny}}, \text{Humidity}) = 0.970 - (3/5)0.0 - (2/5)0.0 = 0.970$$

$$\text{Gain}(S_{\text{sunny}}, \text{Temperature}) = 0.970 - (2/5)0.0 - (2/5)1.0 - (1/5)0.0 = 0.57$$

$$\text{Gain}(S_{\text{sunny}}, \text{Wind}) = 0.970 - (2/5)1.0 - (3/5)1.0 = 0.019$$

# Recursively apply the same




$$S_{\text{sunny}} = [D_1, D_2, D_8, D_9, D_{11}]$$

$$\text{Gain}(S_{\text{sunny}}, \text{Humidity}) = 0.970 - (3/5)0.0 - (2/5)0.0 = 0.970$$


$$\text{Gain}(S_{\text{sunny}}, \text{Temperature}) = 0.970 - (2/5)0.0 - (2/5)1.0 - (1/5)0.0 = 0.57$$

$$\text{Gain}(S_{\text{sunny}}, \text{Wind}) = 0.970 - (2/5)1.0 - (3/5)1.0 = 0.019$$

# Recursively apply the same



# Recursively apply the same



# Decision Tree

A method for approximating discrete-valued functions that is robust to noisy data and capable of learning disjunctive expressions

Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

# Decision Tree

A method for approximating discrete-valued functions that is robust to noisy data and capable of learning disjunctive expressions

Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

What is classification for

(*Outlook = Rain, Humidity = High, Wind = Weak*)



# Decision Tree

A method for approximating discrete-valued functions that is robust to noisy data and capable of learning disjunctive expressions


Day	Outlook	Temperature	Humidity	Wind	Play
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rainy	Mild	High	Weak	Yes
D5	Rainy	Cool	Normal	Weak	Yes
D6	Rainy	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rainy	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rainy	Mild	High	Strong	No

What is classification for

(*Outlook = Rain, Humidity = High, Wind = Weak*)

**ALERT:** (missing value) what is Temperature?

# Example



Classification for (*Outlook = Rain, Humidity = High, Wind = Weak*) is

YES

## Algorithm 1: ID3(Examples, Target\_attribute, Attributes)

- 1 *Examples* are the training data, *Target\_attribute* is the attribute whose value is to be predicted by the tree. *Attributes* is a list of other attributes that may be tested by the learned decision tree. Algorithm returns a decision tree that correctly classify the given example.
- 2 Create a single-node tree *Root*
- 3 **IF** *Examples* are all +ve **THEN return** *Root* with label +ve
- 4 **IF** *Examples* are all -ve **THEN return** *Root* with label -ve
- 5 **IF** *Attributes* =  $\phi$  **THEN return** *Root* with most common *Target\_attribute*
- 6  $A \leftarrow$  attribute from *Attributes* that **best classifies** *Examples*
- 7 Decision attribute for *Root*  $\leftarrow A$
- 8 **foreach** value  $v_i$  of *A* **do**
  - 9 Add a new tree branch below *Root*, to test  $A=v_i$
  - 10  $\text{Examples}_{v_i} \leftarrow$  subset of *Examples* having value  $v_i$  for *A*
  - 11 **IF**  $\text{Examples}_{v_i} = \phi$  **THEN** below this branch add a leaf with label = most common value of *Target\_attribute* in *Examples*
  - 12 **ELSE** below this branch add subtree  
ID3( $\text{Examples}_{v_i}$ , *Target\_attribute*, *Attributes* - {*A*})
- 13 **return** *Root*

# Issues Decision Tree

Given a collection of training examples, there could be many decision trees consistent with the examples

- ID3 search strategy
  - ▶ selects in favor of shorter trees over longer ones, and
  - ▶ selects trees that place the attributes with highest information gain closest to the root

# Issues Decision Tree


Given a collection of training examples, there could be many decision trees consistent with the examples

- ID3 search strategy
  - ▶ selects in favor of shorter trees over longer ones, and
  - ▶ selects trees that place the attributes with highest information gain closest to the root
- Issues in decision trees include
  - 1 how deeply to grow
  - 2 handling continuous attributes
  - 3 choosing an appropriate attribute selection measure
  - 4 missing attribute values
  - 5 attributes with differing costs, and
  - 6 improving computational efficiency

# Issues in Decision Tree

## Overfitting

Given a hypothesis space  $H$ , a hypothesis  $h \in H$  is said to overfit the training data if there exists some alternative hypothesis  $h' \in H$ , such that  $h$  has smaller error than  $h'$  over the training examples, but  $h'$  has a smaller error than  $h$  over the entire distribution of instances.



- This can occur when training examples contain random errors or noise.

# Approaches to avoid overfitting

- Stop growing the tree earlier, before it reaches the point where it perfectly classifies the training data

# Approaches to avoid overfitting

- Stop growing the tree earlier, before it reaches the point where it perfectly classifies the training data
- Allow the tree to overfit the data, and then post-prune the tree



## Approaches to avoid overfitting

- Stop growing the tree earlier, before it reaches the point where it perfectly classifies the training data
- Allow the tree to overfit the data, and then post-prune the tree

### **Criterion to determine the correct final tree size include:**

- Use a separate set of examples (called validation), distinct from the training examples, to evaluate the utility of post-pruning nodes from the tree

# Approaches to avoid overfitting

- Stop growing the tree earlier, before it reaches the point where it perfectly classifies the training data
- Allow the tree to overfit the data, and then post-prune the tree

## **Criterion to determine the correct final tree size include:**

- Use a separate set of examples (called validation), distinct from the training examples, to evaluate the utility of post-pruning nodes from the tree
- Use all the available data for training, but apply a statistical test (such as chi-square test) to estimate whether expanding (or pruning) a particular node is likely to produce an improvement beyond the training set.

# Approaches to avoid overfitting

- Stop growing the tree earlier, before it reaches the point where it perfectly classifies the training data
- Allow the tree to overfit the data, and then post-prune the tree

## **Criterion to determine the correct final tree size include:**

- Use a separate set of examples (called validation), distinct from the training examples, to evaluate the utility of post-pruning nodes from the tree
- Use all the available data for training, but apply a statistical test (such as chi-square test) to estimate whether expanding (or pruning) a particular node is likely to produce an improvement beyond the training set.
- Use an explicit measure of the complexity for encoding the training examples (such as Minimum Description Length) and the decision tree, halting growth of the tree when this encoding size is minimized.

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

---


<sup>2</sup>Leo Breiman, "Random Forests", ML 45, pp 5-32, 2001

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest**<sup>2</sup> is a large collection of decorrelated decision trees

---

<sup>2</sup>Leo Breiman, "Random Forests", ML 45, pp 5-32, 2001 

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest**<sup>2</sup> is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)

---

<sup>2</sup>Leo Breiman, "Random Forests", ML 45, pp 5-32, 2001

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest**<sup>2</sup> is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)




- For every subset, built a decision tree
- To classify new element: **apply voting**

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest**<sup>2</sup> is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)



- For every subset, built a decision tree
- To classify new element: **apply voting**




# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest<sup>2</sup>** is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)




- For every subset, built a decision tree
- To classify new element: **apply voting**

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest<sup>2</sup>** is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)




- For every subset, built a decision tree
- To classify new element: **apply voting**

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest<sup>2</sup>** is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)




- For every subset, built a decision tree
- To classify new element: **apply voting**

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest<sup>2</sup>** is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)




- For every subset, built a decision tree
- To classify new element: **apply voting**

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest<sup>2</sup>** is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)




- For every subset, built a decision tree
- To classify new element: **apply voting**

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest<sup>2</sup>** is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)



- For every subset, built a decision tree


<sup>2</sup>Leo Breiman, "Random Forests", ML 45, pp 5-32, 2001

# Random Forest

Combination of learning models (ensemble of classifiers) increases classification accuracy. Averaging compensates noise. Resulting model has low variance

**Random Forest**<sup>2</sup> is a large collection of decorrelated decision trees

- Training data is divided into a number of sub-sets (delete row or columns) that may have overlap (or subset of attributes)



- For every subset, built a decision tree
- To classify new element: **apply voting**

<sup>2</sup>Leo Breiman, "Random Forests", ML 45, pp 5-32, 2001

# Regression

**Regression** predicts value of continuous a target variable

$x_1$	$x_2$	$x_3$	$y$
10	50	20	10
11	31	22	12
11	12	15	4
20	55	20	22
23	41	27	1
31	12	35	9
13	18	12	23
21	55	16	16
32	56	27	22
8	22	35	??

What should come at the place of ??



# Regression

**Regression** predicts value of continuous a target variable

# Regression

**Regression** predicts value of continuous a target variable

- A simplest model for regression can be a **linear combination** of the input variables

$$y(x, w) = w_0 + w_1 x_1 + \dots + w_n x_n$$

where  $x$  is a  $n$  dimensional vector  $(x_1, x_2, \dots, x_n)$  representing some feature

# Regression

**Regression** predicts value of continuous a target variable

- A simplest model for regression can be a **linear combination** of the input variables

$$y(x, w) = w_0 + w_1 x_1 + \dots + w_n x_n$$

where  $x$  is a  $n$  dimensional vector  $(x_1, x_2, \dots, x_n)$  representing some feature

- It can be extended by considering linear combination of fixed nonlinear functions  $\phi$  (called basis functions)

$$y(x, w) = w_0 + \sum_{i=1}^n w_i \phi_i(x)$$

# Regression

**Regression** predicts value of continuous a target variable

- A simplest model for regression can be a **linear combination** of the input variables

$$y(x, w) = w_0 + w_1 x_1 + \dots + w_n x_n$$

where  $x$  is a  $n$  dimensional vector  $(x_1, x_2, \dots, x_n)$  representing some feature

- It can be extended by considering linear combination of fixed nonlinear functions  $\phi$  (called basis functions)

$$y(x, w) = w_0 + \sum_{i=1}^n w_i \phi_i(x)$$

- In short  $y(x, w) = w^T \phi(x)$

# Regression

**Regression** predicts value of continuous a target variable

- A simplest model for regression can be a **linear combination** of the input variables

$$y(x, w) = w_0 + w_1 x_1 + \dots + w_n x_n$$

where  $x$  is a  $n$  dimensional vector  $(x_1, x_2, \dots, x_n)$  representing some feature

- It can be extended by considering linear combination of fixed nonlinear functions  $\phi$  (called basis functions)

$$y(x, w) = w_0 + \sum_{i=1}^n w_i \phi_i(x)$$

- In short  $y(x, w) = w^T \phi(x)$
- Objective is to choose  $w$  such that it makes  $y(x^{(i)}, w)$  as close to  $y^{(i)}$  as possible

# Our Regression Example

- If we could correct estimate the values of  $w$ 's we could determine  $y(x^{(i)}, w)$  for all values

$x_1$	$x_2$	$x_3$	$y$	$y(x^{(i)}, w)$
10	50	20	10	8
11	31	22	12	9
11	12	15	4	3
20	55	20	22	26
23	41	27	1	1
31	12	35	9	4
13	18	12	23	30
21	55	16	16	13
32	56	27	22	21
8	22	35	??	6

Now the question is that how good this  $w$  is?

# Regression

- Determining  $w$ , is similar to solving a minimization problem. Let us define a **squared error cost function** as

$$J(w) = \frac{1}{2m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)})^2$$

where  $m$  is number of training examples

# Regression

- Determining  $w$ , is similar to solving a minimization problem. Let us define a **squared error cost function** as

$$J(w) = \frac{1}{2m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)})^2$$

where  $m$  is number of training examples

- Then one have to minimize the value of  $J(w)$

$$\operatorname{argmin}_w J(w)$$



# Regression

- Determining  $w$ , is similar to solving a minimization problem. Let us define a **squared error cost function** as

$$J(w) = \frac{1}{2m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)})^2$$

where  $m$  is number of training examples

- Then one have to minimize the value of  $J(w)$

$$\operatorname{argmin}_w J(w)$$

- Basic idea: Push  $w_i$  a bit against the direction of its gradient

# Linear Regression

$x_1$	$x_2$	$x_3$	$y$	$y(x^{(i)}, w)$	$(y(x^{(i)}, w) - y)^2$
10	50	20	10	8	4
11	31	22	12	9	9
11	12	15	4	3	1
20	55	20	22	26	16
23	41	27	1	1	0
31	12	35	9	4	25
13	18	12	23	30	49
21	55	16	16	13	9
32	56	27	22	21	1

Assume for some  $w$  we computed  $y(x^{(i)}, w)$  then

$$\begin{aligned} J(w) &= \frac{1}{2 \times 9} \times 114 \\ &= 6.33 \end{aligned}$$

# Gradient Descent

---

## Algorithm 2: Gradient Descent

---

- 1 Initialize  $w$  randomly
  - 2 **repeat**
  - 3     Simultaneously update all  $w_j$  with  
        $w_j - \alpha \frac{\partial}{\partial w_j} J(w)$
  - 4 **until** *converge*;
  - 5 **return**  $w$
-

# Gradient Descent

---

## Algorithm 3: Gradient Descent

---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |    $w_j - \alpha \frac{\partial}{\partial w_j} J(w)$ 
4 until converge;
5 return  $w$ 
```

---

- Here  $\alpha$  is a learning rate. If  $\alpha$  is small enough then  $J(w)$  would decrease in every iteration

# Gradient Descent

---

## Algorithm 4: Gradient Descent

---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |    $w_j - \alpha \frac{\partial}{\partial w_j} J(w)$ 
4 until converge;
5 return  $w$ 
```

---

- Here  $\alpha$  is a learning rate. If  $\alpha$  is small enough then  $J(w)$  would decrease in every iteration  
(large  $\alpha$  can overshoot the minimum and may fail to converge)

# Gradient Descent

---

## Algorithm 5: Gradient Descent

---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |    $w_j - \alpha \frac{\partial}{\partial w_j} J(w)$ 
4 until converge;
5 return  $w$ 
```

---

- Here  $\alpha$  is a learning rate. If  $\alpha$  is small enough then  $J(w)$  would decrease in every iteration (large  $\alpha$  can overshoot the minimum and may fail to converge)
- Susceptible to local minimum

# Gradient Descent

---

## Algorithm 6: Gradient Descent

---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |    $w_j - \alpha \frac{\partial}{\partial w_j} J(w)$ 
4 until converge;
5 return  $w$ 
```

---

- Here  $\alpha$  is a learning rate. If  $\alpha$  is small enough then  $J(w)$  would decrease in every iteration (large  $\alpha$  can overshoot the minimum and may fail to converge)
- Susceptible to local minimum
- As it moves closer to local minimum, it automatically takes smaller steps as gradient decreases

# Batch-Gradient Descent

---

## Algorithm 7: Batch-Gradient Descent

---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |  $w_j - \alpha \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$ 
4 until converge;
5 return  $w$ 
```

---



# Batch-Gradient Descent

---

## Algorithm 8: Batch-Gradient Descent

---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |  $w_j - \alpha \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$ 
4 until converge;
5 return  $w$ 
```

---

- At every step it evaluate all training examples

# Batch-Gradient Descent

---

## Algorithm 9: Batch-Gradient Descent


---

```
1 Initialize  $w$  randomly
2 repeat
3   | Simultaneously update all  $w_j$  with
   |  $w_j - \alpha \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$ 
4 until converge;
5 return  $w$ 
```

---

- At every step it evaluate all training examples
- Some time it is also called multi-variate linear regression

# Real Landscape



## Example: Gradient Descent (learning rate $\alpha$ )

**Consider following data**

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

## Example: Gradient Descent (learning rate $\alpha$ )

Consider following data

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

Learning rate  $\alpha = 0.1$

# Example: Gradient Descent (learning rate $\alpha$ )

Consider following data

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

Learning rate  $\alpha = 0.1$

$J=396.662506$

$w=(0.500\ 0.500\ 0.500\ 0.500)$

$J=19454472.000000$

$w=(-2.055\ -51.070\ -100.970\ -62.640)$

$J=1036526813184.000000$

$w=(590.236\ 11518.771\ 23902.906\ 13778.349)$

$J=55230041021218816.000000$

$w=(-135891.922\ -2653678.250\ -5525792.000\ -3170425.000)$

$J=2942865354556228763648.000000$

$w=(31365378.000\ 612476928.000\ 1275658624.000\ 731686912.000)$

$J=156806972273681738831495168.000000$

$w=(-7240111104.000\ -141378551808.000\ -294465732608.000\ -168895037440.000)$

$J=8355266546526971027269827428352.000000$

$w=(1671254376448.000\ 32634791002112.000\ 67972370530304.000\ 38986479304704.000)$

$J=445200079222591879770706068887306240.000000$

$w=(-385780270759936.000\ -7533178826784768.000$

$-15690251045437440.000\ -8999357718200320.000)$

## Example: Gradient Descent (learning rate $\alpha$ )

Consider following data

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

Learning rate  $\alpha = 0.001$

# Example: Gradient Descent (learning rate $\alpha$ )

Consider following data

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

Learning rate  $\alpha = 0.001$

J	w
396.663	( 0.500 0.500 0.500 0.500)
664.137	( 0.474 -0.016 -0.515 -0.131)
1131.021	( 0.508 0.631 0.881 0.628)
1943.882	( 0.464 -0.249 -0.910 -0.435)
3357.625	( 0.523 0.888 1.492 0.914)
5815.401	( 0.446 -0.630 -1.641 -0.908)
10087.491	( 0.549 1.356 2.518 1.456)
17512.684	( 0.415 -1.274 -2.941 -1.693)
30417.834	( 0.592 2.183 4.276 2.432)
52847.020	( 0.359 -2.383 -5.221 -3.028)
91828.805	( 0.668 3.630 7.314 4.151)
159578.781	( 0.263 -4.302 -9.200 -5.330)
277327.562	( 0.799 6.152 12.580 7.155)
481973.594	( 0.093 -7.633 -16.125 -9.316)
837646.250	( 1.025 10.537 21.725 12.387)
1455801.375	( -0.201 -13.418 -28.168 -16.234)
2530147.500	( 1.417 18.162 37.611 21.491)
4397349.000	( -0.715 -23.472 -49.103 -28.249)
7642525.500	( 2.097 31.415 65.218 37.319)
13282603.000	( -1.608 -40.944 -85.492 -49.126)
23084998.000	( 3.278 54.449 113.196 64.832)
40121436.000	( -3.162 -71.310 -148.738 -85.405)
69730584.000	( 5.329 94.483 196.578 112.653)
121190936.000	( -5.863 -124.085 -258.660 -148.456)
210628448.000	( 8.894 164.060 341.494 195.769)
366069856.000	( -10.559 -215.809 -449.705 -258.035)
636225152.000	( 15.088 284.983 593.355 340.226)
1105751936.000	( -18.721 -375.224 -781.739 -448.479)
1921783808.000	( 25.852 495.147 1031.086 591.291)
3340036608.000	( -32.908 -652.287 -1358.811 -779.468)



## Example: Gradient Descent (learning rate $\alpha$ )

Consider following data

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

Learning rate  $\alpha = 0.0001$

# Example: Gradient Descent (learning rate $\alpha$ )

Consider following data

	$x_1$	$x_2$	$x_3$	$y$
1	10	50	20	10
2	11	31	22	12
3	11	12	15	4
4	20	55	20	22
5	23	41	27	1
6	31	12	35	9
7	13	18	12	23
8	21	55	16	16
9	32	56	27	22
10	8	22	35	11

Learning rate  $\alpha = 0.0001$

J	w
396.663	( 0.500 0.500 0.500 0.500)
246.798	( 0.497 0.448 0.399 0.437)
158.286	( 0.495 0.408 0.321 0.388)
105.980	( 0.494 0.377 0.262 0.349)
75.041	( 0.493 0.353 0.218 0.319)
56.711	( 0.492 0.334 0.184 0.295)
45.826	( 0.491 0.320 0.159 0.276)
39.335	( 0.491 0.308 0.140 0.260)
35.439	( 0.490 0.299 0.126 0.248)
33.077	( 0.490 0.291 0.115 0.238)
31.621	( 0.490 0.285 0.108 0.229)
30.703	( 0.490 0.280 0.103 0.222)
30.104	( 0.490 0.276 0.099 0.216)
29.694	( 0.489 0.273 0.097 0.210)
29.399	( 0.489 0.270 0.096 0.206)
29.172	( 0.489 0.268 0.095 0.202)
28.987	( 0.489 0.266 0.096 0.198)
28.830	( 0.489 0.264 0.096 0.194)
28.689	( 0.489 0.262 0.097 0.191)
28.560	( 0.489 0.260 0.098 0.188)
28.439	( 0.489 0.259 0.099 0.185)
28.325	( 0.489 0.258 0.101 0.182)
28.216	( 0.489 0.256 0.102 0.179)
28.111	( 0.489 0.255 0.104 0.177)
28.011	( 0.489 0.254 0.105 0.174)
27.913	( 0.489 0.253 0.107 0.172)
27.819	( 0.489 0.252 0.109 0.170)
27.728	( 0.489 0.251 0.110 0.167)
27.555	( 0.490 0.249 0.114 0.163)
24.926	( 0.507 0.207 0.215 0.020) Iteration 300
24.768	( 0.710 0.219 0.213 0.005) Iteration 3000

# Example: Gradient Descent (Feature scaling)

## Feature scaling

	$x_1$	$x_2$	$x_3$	$y$
1	0.08	0.86	0.35	10
2	0.12	0.43	0.43	12
3	0.12	0.00	0.13	4
4	0.50	0.98	0.35	22
5	0.62	0.66	0.65	1
6	0.96	0.00	1.00	9
7	0.21	0.14	0.00	23
8	0.54	0.98	0.17	16
9	1.00	1.00	0.65	22
10	0.00	0.23	1.00	11

**Learning rate**  $\alpha = 0.1$

# Example: Gradient Descent (Feature scaling)

## Feature scaling

	$x_1$	$x_2$	$x_3$	$y$
1	0.08	0.86	0.35	10
2	0.12	0.43	0.43	12
3	0.12	0.00	0.13	4
4	0.50	0.98	0.35	22
5	0.62	0.66	0.65	1
6	0.96	0.00	1.00	9
7	0.21	0.14	0.00	23
8	0.54	0.98	0.17	16
9	1.00	1.00	0.65	22
10	0.00	0.23	1.00	11

Learning rate  $\alpha = 0.1$

J	w
95.472	( 0.500 0.500 0.500 0.500)
73.399	( 1.679 1.025 1.220 0.983)
58.326	( 2.658 1.455 1.822 1.364)
48.020	( 3.470 1.808 2.326 1.663)
40.961	( 4.147 2.096 2.749 1.893)
36.116	( 4.710 2.331 3.106 2.066)
32.778	( 5.180 2.522 3.407 2.193)
30.468	( 5.574 2.677 3.662 2.283)
28.859	( 5.903 2.803 3.880 2.341)
27.729	( 6.181 2.904 4.066 2.373)
26.925	( 6.415 2.985 4.226 2.385)
26.344	( 6.613 3.049 4.364 2.379)
25.916	( 6.782 3.100 4.485 2.360)
25.593	( 6.926 3.140 4.590 2.329)
25.342	( 7.050 3.170 4.683 2.289)
25.141	( 7.158 3.193 4.766 2.241)
24.974	( 7.252 3.210 4.839 2.188)
24.833	( 7.334 3.222 4.906 2.129)
<b>24.708</b>	( 7.407 3.230 4.966 2.067)
24.596	( 7.472 3.234 5.021 2.003)
24.493	( 7.530 3.236 5.071 1.935)
24.397	( 7.583 3.235 5.118 1.866)
24.306	( 7.632 3.233 5.161 1.796)
24.219	( 7.677 3.229 5.202 1.725)
24.136	( 7.718 3.225 5.241 1.653)
24.056	( 7.757 3.219 5.277 1.581)
23.979	( 7.794 3.213 5.311 1.509)
23.903	( 7.830 3.206 5.344 1.436)
23.830	( 7.863 3.198 5.375 1.364)
23.759	( 7.896 3.191 5.405 1.292)
20.174	( 12.021 4.618 4.794 -7.329)

Iteration 18

Iteration 30

Iteration 3000

# Similar Mechanism for Classification

Classification have predefined fixed number of labels (0 and 1 in this case)

$x_1$	$x_2$	$x_3$	<i>Class</i>
10	50	20	1
11	31	22	1
11	12	15	0
20	55	20	0
23	41	27	0
31	12	35	1
13	18	12	0
21	55	16	1
32	56	27	0
8	22	35	??

What should come at the place of ??

# Logistic Regression

Moving from linear regression  $y(x, w) = w_0 + w_1x_1 + \dots + w_nx_n$  to **logistic regression**


$$y(x, w) = \sigma(w_0 + w_1x_1 + \dots + w_nx_n)$$

# Logistic Regression

Moving from linear regression  $y(x, w) = w_0 + w_1x_1 + \dots + w_nx_n$  to **logistic regression**

$$y(x, w) = \sigma(w_0 + w_1x_1 + \dots + w_nx_n)$$

- Enables “classification” apart from the regression. Where  $\sigma$  is called as **sigmoid function** that produces values in range  $[0, 1]$  and is defined as  $\sigma(v) = \frac{1}{1+e^{-v}}$



## Decision on classification


$$classification = \begin{cases} 1 & \text{if } y(x, w) \geq 0.5 \\ 0 & \text{otherwise} \end{cases}$$

# Logistic Regression

Moving from linear regression  $y(x, w) = w_0 + w_1x_1 + \dots + w_nx_n$  to **logistic regression**

$$y(x, w) = \sigma(w_0 + w_1x_1 + \dots + w_nx_n)$$

- Enables “classification” apart from the regression. Where  $\sigma$  is called as **sigmoid function** that produces values in range  $[0, 1]$  and is defined as  $\sigma(v) = \frac{1}{1+e^{-v}}$



## Decision on classification

$$classification = \begin{cases} 1 & \text{if } y(x, w) \geq 0.5 \\ 0 & \text{otherwise} \end{cases}$$



# Decision Boundary in Logistic Regression


$$classification = \begin{cases} 1 & \text{if } y(x, w) \geq 0.5 \\ 0 & \text{otherwise} \end{cases}$$

- This choice of  $w$  partitions the space into two sections and the hyper-plane separating them is called **decision boundary**

# Decision Boundary in Logistic Regression

$$\text{classification} = \begin{cases} 1 & \text{if } y(x, w) \geq 0.5 \\ 0 & \text{otherwise} \end{cases}$$

- This choice of  $w$  partitions the space into two sections and the hyper-plane separating them is called **decision boundary**
- By adding more complex or polynomial terms one can get more complex decision boundary



# Cost Function

- Cost function used for the liner regression

$$J(w) = \frac{1}{2m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)})^2$$

becomes a **non convex** function in case of logistic regression

# Cost Function

- Cost function used for the liner regression

$$J(w) = \frac{1}{2m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)})^2$$

becomes a **non convex** function in case of logistic regression

Therefore, a different cost function is chosen

$$J(w) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(y(x^{(i)}, w), y^{(i)})$$

where

$$\text{Cost}(y(x^{(i)}, w), y^{(i)}) = \begin{cases} -\log(y(x^{(i)}, w)) & \text{if } y^{(i)} = 1 \\ -\log(1 - y(x^{(i)}, w)) & \text{otherwise} \end{cases}$$

A simplified version of this cost function is

$$\text{Cost}(y(x^{(i)}, w), y^{(i)}) = -y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))$$

# Learning With This Cost Function

- Learning corresponds to the minimization of  $J(w)$  by changing  $w$

$$\operatorname{argmin}_w J(w) = \frac{1}{m} \sum_{i=1}^m \operatorname{Cost}(y(x^{(i)}, w), y^{(i)})$$

# Learning With This Cost Function

- Learning corresponds to the minimization of  $J(w)$  by changing  $w$

$$\operatorname{argmin}_w J(w) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(y(x^{(i)}, w), y^{(i)})$$

$$\operatorname{argmin}_w J(w) = \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))]$$

# Learning With This Cost Function

- Learning corresponds to the minimization of  $J(w)$  by changing  $w$

$$\operatorname{argmin}_w J(w) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(y(x^{(i)}, w), y^{(i)})$$

$$\operatorname{argmin}_w J(w) = \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))]$$

- Gradient Descent can be used for this purpose

---

## Algorithm 12: Logistic Regression

---

- 1 Initialize  $w$  randomly
- 2 **repeat**
- 3     Simultaneously update all  $w_j$  with  $w_j - \alpha \frac{\partial}{\partial w_j} J(w)$
- 4 **until** *converge*;
- 5 **return**  $w$

# The Partial Derivative

Partial derivative term

$$\frac{\partial}{\partial w_j} J(w) = \frac{\partial}{\partial w_j} \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))]$$



# The Partial Derivative

Partial derivative term

$$\frac{\partial}{\partial w_j} J(w) = \frac{\partial}{\partial w_j} \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))]$$

comes out to be

$$\frac{\partial}{\partial w_j} J(w) = \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$$

# The Partial Derivative

Partial derivative term

$$\frac{\partial}{\partial w_j} J(w) = \frac{\partial}{\partial w_j} \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))]$$

comes out to be

$$\frac{\partial}{\partial w_j} J(w) = \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$$

---

## Algorithm 15: Logistic Regression

---

- 1 Initialize  $w$  randomly
- 2 **repeat**
- 3     Simultaneously update all  $w_j$  with  
       $w_j - \alpha \times \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$
- 4 **until** *converge*;
- 5 **return**  $w$

# The Partial Derivative

Partial derivative term

$$\frac{\partial}{\partial w_j} J(w) = \frac{\partial}{\partial w_j} \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))]$$

comes out to be

$$\frac{\partial}{\partial w_j} J(w) = \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$$

---

## Algorithm 16: Logistic Regression

---

- 1 Initialize  $w$  randomly
  - 2 **repeat**
  - 3     Simultaneously update all  $w_j$  with  
       $w_j - \alpha \times \frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)}) x_j^{(i)}$
  - 4 **until** converge;
  - 5 **return**  $w$
- 

It looks identical to  
linear regression **but**,  
 $y(x^{(i)}, w)$  is **different**  
**here**  $y(x^{(i)}, w) =$   
$$\frac{1}{1 + e^{-(w_0 + w_1 x_1^{(i)} + \dots + w_n x_n^{(i)})}}$$

# Example: Logistic Regression

Consider following data

	$x_1$	$x_2$	$x_3$	<i>Class</i>
1	2	2	2	1
2	3	2	2	1
3	2	3	2	1
4	2	2	3	1
5	7	6	9	0
6	9	7	6	0
7	9	6	7	0
8	6	8	9	0
9	8	9	6	0
10	8	9	9	0

Learning rate  $\alpha = 0.01$

# Example: Logistic Regression

Consider following data

	$x_1$	$x_2$	$x_3$	Class
1	2	2	2	1
2	3	2	2	1
3	2	3	2	1
4	2	2	3	1
5	7	6	9	0
6	9	7	6	0
7	9	6	7	0
8	6	8	9	0
9	8	9	6	0
10	8	9	9	0

Learning rate  $\alpha = 0.01$

J	w
6.912	( 0.500 0.500 0.500 0.500)
6.496	( 0.494 0.453 0.455 0.454)
5.944	( 0.488 0.406 0.410 0.408)
5.316	( 0.482 0.360 0.366 0.363)
4.692	( 0.477 0.313 0.321 0.317)
4.072	( 0.471 0.267 0.277 0.272)
3.460	( 0.465 0.221 0.233 0.227)
2.860	( 0.460 0.175 0.189 0.182)
2.279	( 0.454 0.130 0.146 0.138)
1.735	( 0.449 0.086 0.104 0.095)
1.262	( 0.445 0.044 0.064 0.054)
0.906	( 0.441 0.008 0.029 0.018)
0.685	( 0.438 -0.022 0.000 -0.011)
0.566	( 0.437 -0.044 -0.020 -0.032)
0.504	( 0.436 -0.060 -0.035 -0.048)
0.470	( 0.436 -0.072 -0.046 -0.059)
0.451	( 0.436 -0.081 -0.055 -0.068)
0.438	( 0.436 -0.088 -0.061 -0.074)
0.431	( 0.437 -0.093 -0.066 -0.080)
0.425	( 0.438 -0.098 -0.070 -0.084)
0.422	( 0.439 -0.101 -0.074 -0.088)
0.419	( 0.440 -0.105 -0.077 -0.091)
0.417	( 0.441 -0.107 -0.079 -0.093)
0.416	( 0.443 -0.110 -0.081 -0.095)
0.415	( 0.444 -0.112 -0.082 -0.097) <b>Iteration 25</b>
0.412	( 0.451 -0.119 -0.088 -0.103) <b>Iteration 30</b>
0.348	( 0.857 -0.179 -0.084 -0.132) <b>Iteration 300</b>
0.116	( 3.256 -0.409 -0.135 -0.291) <b>Iteration 3000</b>
0.012	( 7.596 -0.748 -0.361 -0.588) <b>Iteration 30000</b>
0.001	( 11.975 -1.091 -0.599 -0.896) <b>Iteration 300000</b>

## Example: Find J

As  $(w_0, w_1, w_2, w_3) = (0.5, 0.5, 0.5, 0.5)$ ,  $v = w_0 + w_1x_1 + w_2x_2 + w_3x_3$   
 $y(x^{(i)}, w) = \sigma(v)$

And log term is  $-y^{(i)} \log(y(x^{(i)}, w)) - (1 - y^{(i)}) \log(1 - y(x^{(i)}, w))$

$i$	$x_1$	$x_2$	$x_3$	$y^{(i)}$	$v$	$y(x^{(i)}, w)$	log term
1	2	2	2	1	3.5	0.970	0.029
2	3	2	2	1	4.0	0.982	0.018
3	2	3	2	1	4.0	0.982	0.018
4	2	2	3	1	4.0	0.982	0.018
5	7	6	9	0	11.5	0.999	11.49
6	9	7	6	0	11.5	0.999	11.49
7	9	6	7	0	11.5	0.999	11.49
8	6	8	9	0	12	0.999	11.51
9	8	9	6	0	12	0.999	11.51
10	8	9	9	0	13	0.999	11.51
Total/10:							6.9118

## Example: Find next W

Let  $(w_0, w_1, w_2, w_3) = (0.5, 0.5, 0.5, 0.5)$  and  $t_i = (y(x^{(i)}, w) - y^{(i)})x_j^{(i)}$

Then  $\frac{1}{m} \sum_{i=1}^m (y(x^{(i)}, w) - y^{(i)})x_j^{(i)} = \frac{1}{m} \sum_{i=1}^m t_i$  let  $\hat{y}^{(i)} = y(x^{(i)}, w)$

Then update  $w_j$  with  $w_j - \alpha \times \frac{1}{m} \sum_{i=1}^m t_i$  we have set  $\alpha = 0.01$

$i$	$x_0$	$x_1$	$x_2$	$x_3$	$y^{(i)}$	$\hat{y}^{(i)}$	$t_0$	$t_1$	$t_2$	$t_3$
1	1	2	2	2	1	0.970	-0.029	-0.058	-0.058	-0.058
2	1	3	2	2	1	0.982	-0.017	-0.053	-0.035	-0.035
3	1	2	3	2	1	0.982	-0.017	-0.035	-0.053	-0.035
4	1	2	2	3	1	0.982	-0.017	-0.035	-0.035	-0.053
5	1	7	6	9	0	0.999	0.999	6.999	5.999	8.999
6	1	9	7	6	0	0.999	0.999	8.999	6.999	5.999
7	1	9	6	7	0	0.999	0.999	8.999	5.999	6.999
8	1	6	8	9	0	0.999	0.999	5.999	7.999	8.999
9	1	8	9	6	0	0.999	0.999	7.999	8.999	5.999
10	1	8	9	9	0	0.999	0.999	7.999	8.999	8.999
Total							5.916	46.815	44.815	45.815
$w_j - \alpha \times (total/m)$							0.494	0.453	0.455	0.454

## Example: Classification across Iterations

Following table shows classification as the weights get modified along  $1^{st}$ ,  $100^{th}$ ,  $300^{th}$  and  $500^{th}$  iteration

$i$	$x_1$	$x_2$	$x_3$	$y^{(i)}$	1	100	300	500
1	2	2	2	1	1	0	1	1
2	3	2	2	1	1	0	0	1
3	2	3	2	1	1	0	1	1
4	2	2	3	1	1	0	1	1
5	7	6	9	0	1	0	0	0
6	9	7	6	0	1	0	0	0
7	9	6	7	0	1	0	0	0
8	6	8	9	0	1	0	0	0
9	8	9	6	0	1	0	0	0
10	8	9	9	0	1	0	0	0





# Clustering

Grouping data based on their homogeneity (similarity or closeness).


# Clustering

Grouping data based on their homogeneity (similarity or closeness).



# Clustering


Grouping data based on their homogeneity (similarity or closeness).



Objects within a group are similar (or related) and are different from the objects in other groups.

# Clustering

Grouping data based on their homogeneity (similarity or closeness).



Objects within a group are similar (or related) and are different from the objects in other groups. When it is better?

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)

---

<sup>3</sup>object is closer (more similar) to a prototype

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization,

---

<sup>3</sup>object is closer (more similar) to a prototype

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization, 2) Compression,

---

<sup>3</sup>object is closer (more similar) to a prototype

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization, 2) Compression, and 3) Efficiently Finding Nearest Neighbors

---

<sup>3</sup>object is closer (more similar) to a prototype



# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization, 2) Compression, and 3) Efficiently Finding Nearest Neighbors
- **Type:**
  - ▶ Hierarchical (nested) versus Partitional

---

<sup>3</sup>object is closer (more similar) to a prototype

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization, 2) Compression, and 3) Efficiently Finding Nearest Neighbors
- **Type:**
  - ▶ Hierarchical (nested) versus Partitional
  - ▶ Exclusive versus Overlapping versus Fuzzy

---

<sup>3</sup>object is closer (more similar) to a prototype

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization, 2) Compression, and 3) Efficiently Finding Nearest Neighbors
- **Type:**
  - ▶ Hierarchical (nested) versus Partitional
  - ▶ Exclusive versus Overlapping versus Fuzzy
  - ▶ Complete versus Partial

---

<sup>3</sup>object is closer (more similar) to a prototype

# Clustering

- **Unsupervised** in nature (i.e. right answers are not known)
- Clustering is useful to 1) Summarization, 2) Compression, and 3) Efficiently Finding Nearest Neighbors
- **Type:**
  - ▶ Hierarchical (nested) versus Partitional
  - ▶ Exclusive versus Overlapping versus Fuzzy
  - ▶ Complete versus Partial
- **K-means:** This is a prototype-based<sup>3</sup>, partitional clustering technique that attempts to find a user-specified number of clusters (K), which are represented by their centroids.


---

<sup>3</sup>object is closer (more similar) to a prototype


# Clustering Approaches




Well-separated clusters.




Center-based clusters.




Contiguity-based clusters.



Density-based clusters.



Conceptual clusters.



# K-means Algorithm

Number of clusters *i.e.* the value of  $K$  is provided by the user

# K-means Algorithm

Number of clusters *i.e.* the value of  $K$  is provided by the user

---

## Algorithm 18: K-means

---

```
1 Randomly select  $K$  points as centroids
2 repeat
3   foreach datum point  $d_i$  do
4     Assign  $d_i$  to one of the closest centroids
      (thereby forming  $K$  clusters)
5   Recompute centroid (mean) for each cluster
6 until The centroids converge;
```

---

# K-means Algorithm

Number of clusters *i.e.* the value of  $K$  is provided by the user

---

## Algorithm 19: K-means

---







```
1 Randomly select  $K$  points as centroids
2 repeat
3   foreach datum point  $d_i$  do
4     Assign  $d_i$  to one of the closest centroids
      (thereby forming  $K$  clusters)
5   Recompute centroid (mean) for each cluster
6 until The centroids converge;
```

---

Closeness is measured by **Euclidean distance**, cosine similarity, correlation, Bregman divergence *etc*



# K-means in Action




# Evaluation of K-means<sup>4</sup>

For a given data set  $\{x_1, x_2, \dots, x_n\}$ , let K-means partitions it in  $\{S_1, S_2, \dots, S_K\}$  then the objective is

$$\operatorname{argmin}_S \sum_{i=1}^K \sum_{x \in S_i} \operatorname{dist}^2(x, \mu_i)$$

---

<sup>4</sup>Hamerly, Greg and Elkan, Charles, "Learning the k in k-means", pp 281–288, NIPS-2003 

## Evaluation of K-means<sup>4</sup>


For a given data set  $\{x_1, x_2, \dots, x_n\}$ , let K-means partitions it in  $\{S_1, S_2, \dots, S_K\}$  then the objective is

$$\operatorname{argmin}_S \sum_{i=1}^K \sum_{x \in S_i} \operatorname{dist}^2(x, \mu_i)$$

where  $\mu_i$  corresponds to  $i^{\text{th}}$  centroid.  $\mu_i = \frac{1}{|S_i|} \sum_{x \in S_i} x$

- Typical choice for *dist* function is Euclidean Distance

---

<sup>4</sup>Hamerly, Greg and Elkan, Charles, "Learning the k in k-means", pp 281–288, NIPS-2003 

# Evaluation of K-means<sup>4</sup>

For a given data set  $\{x_1, x_2, \dots, x_n\}$ , let K-means partitions it in  $\{S_1, S_2, \dots, S_K\}$  then the objective is

$$\operatorname{argmin}_S \sum_{i=1}^K \sum_{x \in S_i} \operatorname{dist}^2(x, \mu_i)$$


where  $\mu_i$  corresponds to  $i^{\text{th}}$  centroid.  $\mu_i = \frac{1}{|S_i|} \sum_{x \in S_i} x$

- Typical choice for *dist* function is Euclidean Distance

## How to proceed?

- Choose a  $K$  (How?)
  - ▶ Run K-means algorithm multiple times
  - ▶ Choose clusters corresponding to the one that minimized sum of squared error (SSE)

---

<sup>4</sup>Hamerly, Greg and Elkan, Charles, "Learning the k in k-means", pp 281–288, NIPS-2003 

# Evaluation of K-means<sup>4</sup>

For a given data set  $\{x_1, x_2, \dots, x_n\}$ , let K-means partitions it in  $\{S_1, S_2, \dots, S_K\}$  then the objective is

$$\operatorname{argmin}_S \sum_{i=1}^K \sum_{x \in S_i} \operatorname{dist}^2(x, \mu_i)$$


where  $\mu_i$  corresponds to  $i^{\text{th}}$  centroid.  $\mu_i = \frac{1}{|S_i|} \sum_{x \in S_i} x$

- Typical choice for *dist* function is Euclidean Distance

## How to proceed?

- Choose a  $K$  (How?)
  - ▶ Run K-means algorithm multiple times
  - ▶ Choose clusters corresponding to the one that minimized sum of squared error (SSE)
- If  $K == n$ , no error.

---

<sup>4</sup>Hamerly, Greg and Elkan, Charles, "Learning the k in k-means", pp 281–288, NIPS-2003 

# Evaluation of K-means<sup>4</sup>

For a given data set  $\{x_1, x_2, \dots, x_n\}$ , let K-means partitions it in  $\{S_1, S_2, \dots, S_K\}$  then the objective is


$$\operatorname{argmin}_S \sum_{i=1}^K \sum_{x \in S_i} \operatorname{dist}^2(x, \mu_i)$$

where  $\mu_i$  corresponds to  $i^{\text{th}}$  centroid.  $\mu_i = \frac{1}{|S_i|} \sum_{x \in S_i} x$

- Typical choice for *dist* function is Euclidean Distance

## How to proceed?

- Choose a  $K$  (How?)
  - ▶ Run K-means algorithm multiple times
  - ▶ Choose clusters corresponding to the one that minimized sum of squared error (SSE)
- If  $K == n$ , no error.
- Good clustering has smaller  $K$



<sup>4</sup>Hamerly, Greg and Elkan, Charles, "Learning the k in k-means", pp 281–288, NIPS-2003

# Evaluation of K-means

- **Choosing K:**

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge,



# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm,

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:**

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space,

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space, 2) Random point of data,

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space, 2) Random point of data, 3) look for dense region, 4) Space uniformly in feature space
- **Cluster Quality:**

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space, 2) Random point of data, 3) look for dense region, 4) Space uniformly in feature space
- **Cluster Quality:** 1) Diameter of cluster verses Inter-cluster distance,

# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space, 2) Random point of data, 3) look for dense region, 4) Space uniformly in feature space
- **Cluster Quality:** 1) Diameter of cluster verses Inter-cluster distance, 2) Distance between members of a cluster and the cluster center,

# Evaluation of K-means



- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space, 2) Random point of data, 3) look for dense region, 4) Space uniformly in feature space
- **Cluster Quality:** 1) Diameter of cluster verses Inter-cluster distance, 2) Distance between members of a cluster and the cluster center, 3) Diameter of smallest sphere,





# Evaluation of K-means

- **Choosing K:** 1) Domain Knowledge, 2) Preprocessing with another algorithm, 3) Iteration on  $K$
- **Initialization of Centers:** 1) Random point in space, 2) Random point of data, 3) look for dense region, 4) Space uniformly in feature space
- **Cluster Quality:** 1) Diameter of cluster verses Inter-cluster distance, 2) Distance between members of a cluster and the cluster center, 3) Diameter of smallest sphere, 4) Ability to discover hidden patterns

# Limitations of K-means





# Limitations of K-means





- Has problem when data has
  - ▶ Different size clusters

# Limitations of K-means





- Has problem when data has
  - ▶ Different size clusters
  - ▶ Different densities

# Limitations of K-means





- Has problem when data has
  - ▶ Different size clusters
  - ▶ Different densities
  - ▶ Non-globular shape

# Limitations of K-means





- Has problem when data has
  - ▶ Different size clusters
  - ▶ Different densities
  - ▶ Non-globular shape
- Handling Empty Clusters

# Limitations of K-means



- Has problem when data has
  - ▶ Different size clusters
  - ▶ Different densities
  - ▶ Non-globular shape
- Handling Empty Clusters
- When there are outliers

# Limitations of K-means



- Has problem when data has
  - ▶ Different size clusters
  - ▶ Different densities
  - ▶ Non-globular shape
- Handling Empty Clusters
- When there are outliers
- Updating Centroids Incrementally



## Important Note:

- K-Means and K-NN are different (K nearest neighbors)



K-NN is a **supervised** approach for **classification**

# Other Clustering Approaches

- **K-Medoids:** chooses data point as center and minimizes a sum of pairwise dissimilarities. Resistance to noise and/or outliers


# Other Clustering Approaches

- **K-Medoids:** chooses data point as center and minimizes a sum of pairwise dissimilarities. Resistance to noise and/or outliers
- **Agglomerative Hierarchical Clustering:** repeatedly merging the two closest clusters until a single (Single Link)



# Other Clustering Approaches

- **K-Medoids:** chooses data point as center and minimizes a sum of pairwise dissimilarities. Resistance to noise and/or outliers
- **Agglomerative Hierarchical Clustering:** repeatedly merging the two closest clusters until a single (Single Link)



- **DBSCAN:** density-based clustering algorithm that produces a partitional clustering, in which the number of clusters is automatically determined by the algorithm.