


# Peer Evaluation System UI/UX


## Screenshots of the UI/UX design: -


• The changes from the today's code are reflected below: -











#### Python Code: -

#### 1. App.py -

```
import io
import re
import time
import berypt
import gspread
import requests
import streamlit as st
import plotly.express as px
import pandas as pd
from Rename File import process signatures, load stored signatures
from googleapiclient.discovery import build
from googleapiclient.http import MediaIoBaseUpload
from googleapiclient.http import MediaIoBaseDownload
from oauth2client.service account import ServiceAccountCredentials
# Google Sheets and Google Drive setup
SCOPE = [
  "https://spreadsheets.google.com/feeds",
  "https://www.googleapis.com/auth/drive"
CREDENTIALS FILE = "peer-evaluation-sem1-e2fcf8b5fc27.json"
SHEET NAME = "UserRoles"
# Initialize connection to Google Sheets
def connect to google sheets():
 creds =
ServiceAccountCredentials.from json keyfile name(CREDENTIALS FILE,
SCOPE)
 client = gspread.authorize(creds)
 sheet = client.open(SHEET_NAME).sheet1
 return sheet
```

```
# Google Drive authentication
def authenticate drive():
 creds =
ServiceAccountCredentials.from json keyfile name(CREDENTIALS FILE,
SCOPE)
 service = build('drive', 'v3', credentials=creds)
 return service
# Fetch users from Google Sheets
def get users from sheets():
 sheet = connect to google sheets()
 records = sheet.get all records()
 return records
def validate password(password):
 pattern =
re.compile(r'^(?=.*[A-Z])(?=.*[a-z])(?=.*\d)(?=.*[@$!%*?&])[A-Za-z\d@$!%*?
&]{8,}$')
 return pattern.match(password)
# Add new user to Google Sheets with role auto-assignment
def register user(username, password, name):
 sheet = connect to google sheets()
 # Check if the email contains numeric values (assumed to be student)
 if re.search(r'\d', username):
    role = "Student"
 else:
    role = "Teacher"
 # Hash the password before saving
 hashed password = bcrypt.hashpw(password.encode('utf-8'), bcrypt.gensalt())
 new user = [username, hashed password.decode('utf-8'), role, name]
 #new user = [username, password, role, name]
 sheet.append row(new user)
 return role
```

```
# Update role from Student to TA (only for Teachers)
def update role to ta(username):
  sheet = connect to google sheets()
  records = sheet.get all records()
  for i, user in enumerate(records, start=2): # start=2 to account for 1-based index
in Google Sheets
    if user['username'] == username and user['role'] == 'Student':
       sheet.update cell(i, 3, 'TA') # Assuming role is in column 3
      return True
  return False
# Update role from TA to Student (only for Teachers)
def update role to Student(username):
  sheet = connect to google sheets()
  records = sheet.get all records()
  for i, user in enumerate(records, start=2): # start=2 to account for 1-based index
in Google Sheets
    if user['username'] == username and user['role'] == 'TA':
       sheet.update cell(i, 3, 'Student') # Assuming role is in column 3
      return True
  return False
# Verify user credentials
def login(username, password, users):
  for user in users:
    if user['username'] == username:
      # Check if the password matches the stored hash
      if bcrypt.checkpw(password.encode('utf-8'),
user['password'].encode('utf-8')):
         st.session state["login status"] = True
         st.session state["role"] = user["role"]
         st.session state["username"] = username
         st.session state["page"] = "dashboard"
         st.session state["message"] = None
         st.session state["name"] = user["name"]
         return
       else:
```

```
st.error("Incorrect Password!")
         time.sleep(2)
         st.rerun()
         return
  st.error("Incorrect Username or Password!")
  time.sleep(2)
  st.rerun()
# Logout function
def logout():
  st.session state["login status"] = False
 st.session_state["role"] = None
  st.session state["username"] = None
  st.session_state["name"] = None
  st.session state["page"] = "login"
  st.success("Logging out!")
  time.sleep(0.5)
  #st.session state["message"] = "Logged out successfully"
# Function to change password
def change password(username, current password, new password):
  sheet = connect to google sheets()
  records = sheet.get_all records()
  # Find the user in the records
  for i, user in enumerate(records, start=2): # start=2 for 1-based indexing
(Google Sheets)
    if user['username'] == username:
      # Check if the current password matches the stored hash
      if bcrypt.checkpw(current password.encode('utf-8'),
user['password'].encode('utf-8')):
         # Hash the new password
         hashed new password = bcrypt.hashpw(new password.encode('utf-8'),
bcrypt.gensalt()).decode('utf-8')
         # Update the password in the sheet
         sheet.update cell(i, 2, hashed new password)
         return True # Password changed successfully
      else:
```

```
return False # Current password is incorrect return False # User not found
```

```
def change password dashboard():
  st.header("Change Password")
 current password = st.text input("Current Password", type="password")
  new password = st.text input("New Password", type="password")
  confirm password = st.text input("Confirm New Password", type="password")
 if st.button("Change Password"):
    if new password != confirm password:
      st.error("New password and confirm password do not match!")
    elif not validate password(new password):
      st.error(
         "Password must include at least: - \n1. One uppercase letter. \n2. One
lowercase letter. \n3. One special character. \n4. One numerical digit. \n5. Must be
at least 8 characters long.")
    else:
      success = change password(st.session state['username'],
current password, new password)
      if success:
        st.success("Password changed successfully!")
        time.sleep(2)
        logout()
        st.rerun()
      else:
        st.error("Failed to change password. Incorrect current password.")
def trigger google apps script(function name):
 #web app url =
"https://script.google.com/macros/s/AKfycbwlBil062YhNYcbIqmP9obfLBKgoeI
dTdRDQ BOB4rF1S6JhTxvVFH8MhW2x84bgyAVag/exec" # Replace with
your web app URL
 #web app url =
"https://script.google.com/macros/s/AKfycbwyD-ImNegaa7NzPCU5AZ6978PSR
vQuuyEreskmCnrzoM0P30EGHuR-sIoqklHBHlNlxQ/exec"
```

```
web app url =
"https://script.google.com/macros/s/AKfycbyyeKLZfm5VihTXPqu5qloIl2CEs8m
RU3iJuepZJ4AvWm3R0w3yWBG8INj9v2-TUeGk3w/exec"
  url = f"{web app url}?action={function name}" # Append the function name
as the 'action' parameter
  try:
    response = requests.get(url)
    if response.status code == 200:
      st.success(f"{function name} executed successfully!")
    else:
      st.error(f"Failed to execute {function name}. Status code:
{response.status code}")
  except Exception as e:
    st.error(f"An error occurred: {str(e)}")
# Function to check if a file already exists in Google Drive folder
def file exists(drive service, folder id, file name):
  query = f'''{folder id}' in parents and name='{file name}'''
  results = drive_service.files().list(q=query, spaces='drive', fields='files(id,
name)').execute()
  files = results.get('files', [])
  return any(file['name'] == file name for file in files)
# Function to upload PDF files to Google Drive
def upload pdfs(uploaded files, folder id):
  drive service = authenticate drive()
  count = 0
  for uploaded file in uploaded files:
    if file exists(drive service, folder id, uploaded file.name):
      #st.warning(f"PDF file '{uploaded file.name}' already exists in the
folder.")
      continue
    file metadata = {
      'name': uploaded file.name,
      'parents': [folder id]
```

```
media = MediaIoBaseUpload(uploaded file, mimetype='application/pdf')
    drive service.files().create(body=file metadata, media body=media,
fields='id').execute()
    count = count + 1
    #st.session state["success message"] = f"Uploaded PDF file
'{uploaded file.name}' to Google Drive"
 st.success(f" The {count} files are uploaded to the Google Drive.")
# Function to upload Google Sheets files to Google Drive
def upload sheets(uploaded file, folder id):
 drive service = authenticate drive()
 if file exists(drive service, folder id, uploaded file.name):
    st.warning(f"Google Sheet file '{uploaded_file.name}' already exists in the
folder.")
    return
 file metadata = {
    'name': uploaded file.name,
    'parents': [folder id]
  }
 # Upload the file to Google Drive
 media = MediaIoBaseUpload(uploaded file, mimetype=uploaded file.type,
resumable=True)
  uploaded = drive service.files().create(body=file metadata,
media body=media, fields='id').execute()
 st.success("The Excel sheet has been uploaded to the Google Drive.")
# Helper function to connect to a specific Google Sheet
def connect to google sheets with name(sheet name):
 creds =
ServiceAccountCredentials.from json keyfile name(CREDENTIALS FILE,
SCOPE)
 client = gspread.authorize(creds)
```

```
sheet = client.open(sheet name)
 return sheet
def connect to google sheets with id(file id):
 creds =
ServiceAccountCredentials.from json keyfile name(CREDENTIALS FILE,
SCOPE)
 client = gspread.authorize(creds)
 sheet = client.open by key(file id)
 return sheet
def get student details(username):
 # Connect to the specific Google Sheet containing marks
 sheet name = "UI/UX Copy of Peer Evaluation2"
 sheet = connect to google sheets with name(sheet name) # Modify to accept
a sheet name
  peer eval sheet = sheet.worksheet('PeerEval') # Open the "PeerEval" sheet
 # Fetch all the data from the "PeerEval" sheet
 records = peer eval sheet.get all records()
 # Find marks for the current user
  for record in records:
    if record['EMail ID'] == username: # Ensure this matches your column name
      return record['Average Marks'], record['Unique ID'], record['Assigned
Folder Link'], record['Spreadsheet Link'] # Returning the Average Mark's and
Unique id
 return None, None, None, None # If no details found for the user
# Fetch the student's PDF from Google Drive using unique ID
def get student pdf(unique id):
 drive service = authenticate drive()
  folder id = "1fT-inciLQut85BGEQrjMSWbVRcTsdWfQ"
 query = f'''{folder id}' in parents and name contains '{unique id}'''
 results = drive service.files().list(q=query, fields="files(id, name)").execute()
 files = results.get('files', [])
 if files:
    file id = files[0]['id']
```

```
file name = files[0]['name']
    # Download the PDF
    request = drive service.files().get media(fileId=file id)
    fh = io.BytesIO()
    downloader = MediaIoBaseDownload(fh, request)
    done = False
    while not done:
      status, done = downloader.next chunk()
    fh.seek(0)
    return fh, file name
 return None, None
def renaming files():
 # Authenticate Google Drive
 service = authenticate drive()
 # Google Drive folder IDs
 stored signatures folder id = '14QLNPdIRUZ3ici-GePoEewUCmxemjhUD'
#The folder where we want to keep the Stored signature
  uploaded signatures folder id = '1ORVrU-UoXyDS-1ovyuk7FAjb p94gnsx'
#This will be the folder where our pdf files are kept
  destination folder id = '1bPhLMZONpsPDxM9z vQD2J9jAjtwG3FG' #
Folder where renamed files will be moved
 # Load stored signatures directly from Google Drive
 stored signatures, stored filenames = load stored signatures(service,
stored signatures folder id)
 # Process uploaded signatures and copy renamed files to the destination folder
 matched files = process signatures(service, uploaded signatures folder id,
stored signatures, stored filenames, destination folder id)
 print(f"Matching process completed. Total matched files:
{len(matched files)}")
# Connect to Google Sheets
```

```
def fetch sheet data(sheet name, worksheet name):
 # gc = gspread.service account(filename=CREDENTIALS FILE)
 # spreadsheet = gc.open(sheet_name)
 # worksheet = spreadsheet.worksheet (worksheet name)
 # return worksheet.get all values()
 creds =
ServiceAccountCredentials.from json keyfile name(CREDENTIALS FILE,
SCOPE) # Replace with your credentials file
 client = gspread.authorize(creds)
 sheet = client.open(sheet name).worksheet(worksheet name) # Open the
specific worksheet
 return sheet
# Fetch Peer Average and Standard Deviation data
def get peer average data(sheet):
  data = sheet.get all values()
  for index, row in enumerate(data):
    if row[0] == "Peer": # Check the first column of each row
      st idx = index
    if row[0] == "SD": # Check the first column of each row
      std idx = index
    if row[0] == "Peer Average": # Check the first column of each row
      pavg idx = index
 # Extract student IDs, Standard Deviations, and Peer Averages
  student ids = data[st idx][1:] # First row has student IDs starting from B1
 std devs = list(map(float, data[std idx][1:])) # Row 6 has Standard Deviations
starting from B6
  peer averages = list(map(float, data[pavg idx][1:])) # Row 7 has Peer
Averages starting from B7
 # Create a DataFrame with relevant data
 df = pd.DataFrame({
    'Student': student ids,
    'Standard Deviation': std devs,
    'Average Score': peer averages
  })
```

```
# Generate Standard Deviation Chart
def create standard deviation chart(df):
  fig = px.bar(df, x='Student', y='Standard Deviation', title='Standard Deviation of
Scores for Each Student',
          color discrete sequence=['#4682B4'])
  fig.update layout(yaxis title='Standard Deviation', xaxis title='Student',
             plot bgcolor='white', paper bgcolor='white', # Set background
colors to white
             font color='black', title font color='black',
             xaxis=dict(title font=dict(color='black'),
tickfont=dict(color='black')),
             yaxis=dict(title font=dict(color='black'),tickfont=dict(color='black'))
             )
  return fig
# Generate Peer Average Scores Chart
def create average scores chart(df):
  fig = px.bar(df, x='Student', y='Average Score', title='Peer Average Scores for
Each Student',
          color discrete sequence=['#FF6347'])
  fig.update layout(yaxis title='Peer Average', xaxis title='Student',
             plot bgcolor='white', paper bgcolor='white', # Set background
colors to white
             font color='black', title font color='black',
             xaxis=dict(title font=dict(color='black'),
tickfont=dict(color='black')),
             yaxis=dict(title font=dict(color='black'),
tickfont=dict(color='black'))
 return fig
# Trigger when "Generate Charts" button is clicked
def generate charts():
  sheet = fetch sheet data('UI/UX Copy of Peer Evaluation2', 'Evaluation
Results')
  df = get peer average data(sheet) # Get the data
```

```
# Display two charts
  st.plotly chart(create standard deviation chart(df))
  st.plotly chart(create average scores chart(df))
# Function to convert Excel file to Google Sheets
def convert excel to google sheet(file id):
  drive service = authenticate drive()
  # File metadata for conversion
  file metadata = {
    'mimeType': 'application/vnd.google-apps.spreadsheet'
  }
 # Convert the file and get the new file ID
  converted file = drive service.files().copy(fileId=file id,
body=file metadata).execute()
  return converted file['id']
# Function to list all files in the given folder (Google Drive)
def list spreadsheets in folder(folder id):
  service = authenticate drive() # Authenticate Drive using the new function
  query = f'''{folder id}' in parents and
(mimeType='application/vnd.google-apps.spreadsheet' OR
mimeType='application/vnd.openxmlformats-officedocument.spreadsheetml.sheet
  results = service.files().list(q=query).execute()
  files = results.get('files', [])
  if not files:
    print('No spreadsheets found in the folder.')
    return []
  return files
# Function to copy data from each spreadsheet to the target sheet
def copy data to peer eval(folder id, target spreadsheet name,
target worksheet name):
 # Get the target spreadsheet using the new function
```

```
target spreadsheet =
connect to google sheets with name(target spreadsheet name)
 try:
    target worksheet = target spreadsheet.worksheet(target worksheet name)
 except gspread. WorksheetNotFound:
    print(f"Worksheet '{target worksheet name}' not found in the target
spreadsheet.")
    return
 # List all spreadsheets in the folder
  files = list spreadsheets in folder(folder id)
  for file in files:
    file id = file['id']
    file name = file['name']
    mime type = file['mimeType']
    print(f"Processing file: {file name}")
    # If it's an Excel file, convert it to a Google Sheet
    if mime type ==
'application/vnd.openxmlformats-officedocument.spreadsheetml.sheet':
      file id = convert excel to google sheet(file id)
    # Now open the file as a Google Sheet
    source spreadsheet = connect to google sheets with id(file id)
    source worksheet = source spreadsheet.get worksheet(0) # Assuming data
is in the first worksheet
    source data = source worksheet.get all values()
    # Append data to the target worksheet
    if source data:
      target worksheet.append rows(source data, value input option="RAW")
      return
 print("Data copied to PeerEval worksheet successfully.")
def admin dashboard():
```

```
st.title("Admin Dashboard")
 st.write(f"Welcome, {st.session state['name']}")
 # Create tabs for each action
 tab, tab0, tab1, tab2, tab3, tab4, tab5, tab6, tab7, tab8 = st.tabs(
   ["Upload Data", "Rename Files", "Assign/De-Assign TA", "Pre Evaluation",
"Reminder Mail", "Post Evaluation", "Generate Charts",
    "Send Marks", "Cumulative Score", "Change Password"])
 # Tab for File upload option
 with tab:
   # Folder ID for the Google Drive folder where the files will be saved
   folder id = "1fT-inciLQut85BGEQrjMSWbVRcTsdWfQ" # Replace this
with your folder ID
   # Allow file upload for multiple Google Sheets
   st.subheader("Upload Student Information")
   sheet files = st.file uploader("Upload Google Sheet", type=["xlsx"],
accept multiple files=False,
                      key="sheet uploader")
   if sheet files:
      upload sheets(sheet_files, folder_id)
   # Allow file upload for multiple PDFs
   st.subheader("Upload PDF Files")
   pdf files = st.file uploader("Upload PDF files", type=["pdf"],
accept multiple files=True, key="pdf uploader")
   if pdf files:
      upload pdfs(pdf files, folder id)
 with tab0:
   if st.button("Rename Files"):
      renaming files()
 # Tab for TA update
 with tab1:
```

```
student username = st.text input("Enter Student's Username")
   if st.button("Update Role to TA"):
      if update role to ta(student username):
        st.success(f"{student username.split('.')[0].capitalize()}'s role updated to
TA.")
      else:
        st.error("Failed to update the role. Check if the username exists and
belongs to a student.")
   if st.button("Update Role to Student"):
      if update role to Student(student username):
        st.success(f"{student username.split('.')[0].capitalize()}'s role updated to
Student.")
      else:
        st.error("Failed to update the role. Check if the username exists and
belongs to a TA.")
 # Tab for Pre Evaluation
 with tab2:
   target spreadsheet name = "UI/UX Copy of Peer Evaluation2"
   #target spreadsheet name = "Sample Run"
   target worksheet name = "PeerEval"
   if st.button("Pre Evaluation"):
      copy data to peer eval(folder id, target spreadsheet name,
target worksheet name)
      trigger google apps script("PreEval")
 # Tab for Checking Pending Evaluations
 with tab3:
   if st.button("Reminder Mail"):
      trigger google apps script("CheckEval")
 # Tab for Post Evaluation
 with tab4:
   if st.button("Post Evaluation"):
      trigger google apps script("PostEval")
 # Tab for Generating Charts
 with tab5:
   if st.button("Generate Charts"):
      generate charts()
```

```
#trigger google apps script("GenChart")
 # Tab for Sending Marks
 with tab6:
   if st.button("Send Marks"):
      trigger google apps script("SendMail")
 with tab7:
   if st.button("Send Cumulative Score"):
      trigger google apps script("SendFinalM")
 with tab8:
   change password dashboard()
def teacher dashboard():
  st.title("Teacher Dashboard")
  #var user = st.session state['username'].split('@')[0]
 #if'.' in var user:
  # st.write(f"Welcome, Dr. {var user.split('.')[0].capitalize()}")
 #else:
     st.write(f"Welcome, Dr. {var user.capitalize()}")
  st.write(f"Welcome, {st.session state['name']}")
 # Create tabs for each action
  tab, tab0, tab1, tab2, tab3, tab4, tab5, tab6, tab7 = st.tabs(["Rename Files",
"Assign/De-Assign TA", "Pre Evaluation", "Reminder Mail",
                             "Post Evaluation", "Generate Charts", "Send
Marks", "Cumulative Score", "Change Password"])
 # Tab for TA update
  with tab:
    if st.button("Rename Files"):
      renaming files()
 with tab0:
    student username = st.text input("Enter Student's Username")
    if st.button("Update Role to TA"):
      if update role to ta(student username):
         st.success(f"{student username.split('.')[0].capitalize()}'s role updated to
TA.")
```

```
else:
         st.error("Failed to update the role. Check if the username exists and
belongs to a student.")
    if st.button("Update Role to Student"):
      if update role to Student(student username):
         st.success(f"{student username.split('.')[0].capitalize()}'s role updated to
Student.")
      else:
         st.error("Failed to update the role. Check if the username exists and
belongs to a TA.")
 # Tab for Pre Evaluation
 with tab1:
    folder id = "1fT-inciLQut85BGEQrjMSWbVRcTsdWfQ"
    target spreadsheet name = "UI/UX Copy of Peer Evaluation2"
    #target spreadsheet name = "Sample Run"
    target worksheet name = "PeerEval"
    if st.button("Pre Evaluation"):
      copy_data_to_peer_eval(folder id, target spreadsheet name,
target worksheet name)
      trigger google apps script("PreEval")
 # Tab for Checking Pending Evaluations
 with tab2:
    if st.button("Reminder Mail"):
      trigger google apps script("CheckEval")
 # Tab for Post Evaluation
 with tab3:
    if st.button("Post Evaluation"):
      trigger google apps script("PostEval")
 # Tab for Generating Charts
 with tab4:
    if st.button("Generate Charts"):
      generate charts()
      #trigger google apps script("GenChart")
 with tab5:
    if st.button("Send Marks"):
```

```
trigger google apps script("SendMail")
 with tab6:
    if st.button("Send Cumulative Score"):
      trigger google apps script("SendFinalM")
  with tab7:
    change password dashboard()
# Role-based content: Teacher Dashboard with multiple file uploads
def ta dashboard():
 st.title("TA Dashboard")
 #st.write(f"Welcome, {st.session state['username'].split('.')[0].capitalize()}")
 st.write(f"Welcome, {st.session state['name']}")
 # Create tabs for each action
  tab, tab0, tab1, tab2, tab3, tab4, tab5 = st.tabs(
    ["Upload Data", "Rename Files", "Pre Evaluation", "Reminder Mail", "Post
Evaluation", "Generate Charts", "Change Password"])
 # Tab for File upload option
 with tab:
    # Folder ID for the Google Drive folder where the files will be saved
    folder id = "1fT-inciLQut85BGEQrjMSWbVRcTsdWfQ" # Replace this
with your folder ID
    # Allow file upload for multiple Google Sheets
    st.subheader("Upload Student Information")
    sheet files = st.file uploader("Upload Google Sheet", type=["xlsx"],
accept multiple files=False,
                       key="sheet uploader")
    if sheet files:
      upload sheets(sheet files, folder id)
    # Allow file upload for multiple PDFs
    st.subheader("Upload PDF Files")
```

```
pdf files = st.file uploader("Upload PDF files", type=["pdf"],
accept multiple files=True, key="pdf uploader")
    if pdf files:
      upload pdfs(pdf files, folder id)
 with tab0:
    if st.button("Rename Files"):
      renaming files()
 # Tab for Pre Evaluation
 with tab1:
    target spreadsheet name = "UI/UX Copy of Peer Evaluation2"
    #target_spreadsheet_name = "Sample_Run"
    target worksheet name = "PeerEval"
    if st.button("Pre Evaluation"):
      copy data to peer eval(folder id, target spreadsheet name,
target worksheet name)
      trigger google apps script("PreEval")
 # Tab for Checking Pending Evaluations
 with tab2:
    if st.button("Reminder Mail"):
      trigger google apps script("CheckEval")
 # Tab for Post Evaluation
 with tab3:
    if st.button("Post Evaluation"):
      trigger google apps script("PostEval")
 # Tab for Generating Charts
 with tab4:
    if st.button("Generate Charts"):
      generate charts()
      #trigger google apps script("GenChart")
 with tab5:
    change password dashboard()
```

```
def student dashboard():
  st.title("Student Dashboard")
  #st.write(f"Welcome, {st.session state['username'].split('.')[0].capitalize()}")
  st.write(f"Welcome, {st.session state['name']}")
 # Creating tabs
  tab1, tab2, tab3, tab4 = st.tabs(["Evaluation", "View Marks", "Answer Script",
"Change Password"])
 # Tab for opening the peer evaluation spreadsheet
  with tab1:
    if st.session state["username"]:
      # Fetch marks, unique ID, and spreadsheet link using the session's
username
      marks, unique id, folder link, sheet link =
get student details(st.session state["username"])
    else:
       st.error("Username is Incorrect!")
    t1, t2 = st.tabs(["Evaluation Files", "Evaluation Sheet"])
    with t1:
      if folder link:
         st.markdown(f"[Link to open Evaluation Files]({folder link})",
unsafe allow html=True)
      else:
         st.error("Folder link not found,")
    with t2:
      if sheet link:
         st.markdown(f"[Link to open Evaluation Sheet]({sheet link})",
unsafe allow html=True)
       else:
         st.error("Spreadsheet link not found.")
 # Tab for viewing marks
  with tab2:
    if st.button("See Marks"):
      if marks and unique id:
```

```
st.write(f"Your evaluation marks are = {marks}")
      else:
         st.error("No marks are available.")
  # Tab for downloading PDF
  with tab3:
    pdf_file, file_name = get_student_pdf(unique_id)
    if pdf file:
      st.download button(
         label="Download your Evaluation PDF",
         data=pdf file,
         file name=file name,
         mime='application/pdf'
      )
    else:
      st.error("PDF not found.")
  with tab4:
    change password dashboard()
# Main Streamlit app
def main():
 # Initialize session state variables if not present
 if "login status" not in st.session state:
    st.session state["login status"] = False
 if "role" not in st.session state:
    st.session state["role"] = None
 if "username" not in st.session state:
    st.session state["username"] = None
 if "page" not in st.session state:
    st.session_state["page"] = "login"
 if "message" not in st.session state:
    st.session_state["message"] = None
 if "success message" not in st.session state:
    st.session state["success message"] = None
 if "name" not in st.session_state:
    st.session state["name"] = None
```

```
# Set background color and input field styling using HTML
  st.markdown(
    ******
    <style>
    .stApp {
      background-color: #1f3f49; /* Light blue background */
    .stTextInput>div>input, .stPasswordInput>div>input {
      background-color: white; /* White background for text and password
inputs */
      color: black; /* Text color for input fields */
    }
    .stButton>button {
      background-color: #007bff; /* Optional: Style buttons with a color */
      color: white;
    }
    </style>
    unsafe_allow html=True
  )
 # Page routing based on session state
 if st.session state["page"] == "login":
    st.title("Peer Evaluation System")
    # Tabs for Login and Registration
    tab1, tab2 = st.tabs(["Login", "Register"])
    with tab1:
      st.header("Login")
      with st.form(key='login form'):
         username = st.text input("Email ID")
         password = st.text input("Password", type="password")
         submit button = st.form submit button("Login")
         if submit button:
           users = get users from sheets()
```

```
login(username, password, users)
           if st.session state["login status"]:
              st.rerun()
    with tab2:
       st.header("Register")
       with st.form(key='register form'):
         reg name = st.text input("Name",key='reg name')
         reg_username = st.text_input("Email ID", key='reg_username')
         reg_password = st.text_input("Password", type="password",
key='reg password')
         register button = st.form submit button("Register")
         if register button:
           if not reg_username.endswith("@iitrpr.ac.in"):
              st.error("Email ID must end with @iitrpr.ac.in")
           elif not validate password(reg password):
              st.error("Password must include at least One: - \n1. Uppercase
letter. \n2. Lowercase letter. \n3. Special character. \n4. Numerical digit. \n5. Must
be at least 8 characters long.")
           else:
              users = get users from sheets()
              if any(user['username'] == reg_username for user in users):
                 st.error("Username already exists")
              else:
                 role = register user(reg_username, reg_password, reg_name)
                 st.success(f"User registered successfully with role: {role}")
                 time.sleep(2)
                 # Redirect to the login page
                 st.session state["page"] = "login"
                 st.rerun()
  elif st.session state["page"] == "dashboard":
    if st.session state["role"] == "Admin":
       admin dashboard()
    elif st.session_state["role"] == "Teacher":
       teacher dashboard()
    elif st.session state["role"] == "TA":
       ta dashboard()
```

```
elif st.session_state["role"] == "Student":
    student_dashboard()

# Logout button
    if st.button("Logout"):
        logout()
        st.rerun()

if __name__ == "__main__":
    main()
```

### 2. Rename File.py -

```
import os
import io
import cv2
import numpy as np
from googleapiclient.discovery import build
from google.oauth2.service account import Credentials
from skimage.metrics import structural similarity as ssim
from scipy.ndimage import center of mass
from googleapiclient.http import MediaIoBaseDownload
SCOPE = [
  "https://spreadsheets.google.com/feeds",
  "https://www.googleapis.com/auth/drive"
CREDENTIALS FILE = "peer-evaluation-sem1-e2fcf8b5fc27.json"
# Authenticate Google Drive
def authenticate drive():
 creds = Credentials.from service account file(CREDENTIALS FILE)
 service = build('drive', 'v3', credentials=creds)
 return service
# List files in a Google Drive folder
def list files in folder(service, folder id):
 results = service.files().list(
    q=f'''{folder id}' in parents and mimeType !=
'application/vnd.google-apps.folder'",
    pageSize=1000, fields="files(id, name)").execute()
 return results.get('files', [])
# Read file content from Google Drive (read as image data)
def read drive image file(service, file id):
 request = service.files().get media(fileId=file id)
 file bytes = io.BytesIO()
 downloader = MediaIoBaseDownload(file bytes, request)
  done = False
 while not done:
    , done = downloader.next chunk()
```

```
file bytes.seek(0) # Reset pointer to start
  file array = np.frombuffer(file bytes.read(), np.uint8)
  image = cv2.imdecode(file array, cv2.IMREAD GRAYSCALE) # Decode as
gravscale image
  return image
# Copy and rename a file in Google Drive to a new folder
def copy and rename drive file(service, file id, new name,
destination folder id):
  file metadata = {
    'name': new name,
    'parents': [destination folder id] # Move file to this folder
  copied file = service.files().copy(fileId=file id, body=file metadata).execute()
  return copied file
# Delete a file in Google Drive
def delete drive file(service, file id):
  service.files().delete(fileId=file id).execute()
# Preprocess image (resize and normalize)
def preprocess image(image):
  image = cv2.resize(image, (256, 256)) # Resize
  image = image / 255.0 # Normalize pixel values
  return image
# Align signatures by centering the image based on center of mass
def align images(image):
  cy, cx = center of mass(image)
  height, width = image.shape
  shift x = int(width / 2 - cx)
  shift y = int(height / 2 - cy)
  translation matrix = np.float32([[1, 0, shift x], [0, 1, shift y]])
  aligned image = cv2.warpAffine(image, translation matrix, (width, height))
  return aligned image
# Compare signatures using SSIM
def compare signatures(stored sig, uploaded sig):
  aligned stored sig = align images(stored sig)
  aligned uploaded sig = align images(uploaded sig)
```

```
score, = ssim(aligned stored sig, aligned uploaded sig, full=True,
data range=1.0)
  return score
# Load stored signatures directly from Google Drive (in memory)
def load stored signatures(service, stored signatures folder id):
  stored signatures = []
  stored filenames = []
  files = list files in folder(service, stored signatures folder id)
  for file in files:
    image = read drive image file(service, file['id'])
    image = preprocess image(image)
    stored signatures.append(image)
    stored filenames.append(file['name'])
    print(f"Loaded stored signature: {file['name']}") # Debugging info
  return stored signatures, stored filenames
# Compare uploaded signature with stored signatures and copy file to a new
folder if matched
def process signatures(service, uploaded signatures folder id, stored signatures,
stored filenames, destination folder id, threshold=0.85):
  uploaded files = list files in folder(service, uploaded signatures folder id)
  matched files = []
  for uploaded file in uploaded files:
    uploaded image = read drive image file(service, uploaded file['id'])
    uploaded image = preprocess image(uploaded image)
    # Compare each uploaded signature with stored signatures
    matched filename = None
    print(f''Comparing uploaded file: {uploaded file['name']}'') # Debugging
info
    for stored signature, stored filename in zip(stored signatures,
stored filenames):
      similarity score = compare signatures(stored signature, uploaded image)
      print(f"Comparing with stored file: {stored filename}, Similarity:
{similarity score}") # Debugging info
      if similarity score > threshold: # Match threshold
         matched filename = stored filename
```