#### 1

# Control Systems

## G V V Sharma\*

		Contents	10	Oscillator 2
				10.1 Introduction 2
1	_	Flow Graph	1	10.2 Example 2
	1.1	Mason's Gain Formula	1	
	1.2	Matrix Formula	systei	stract—This manual is an introduction to control ms based on GATE problems.Links to sample Python
2	<b>Bode Plot</b>		1 codes	are available in the text.
	2.1 2.2	Introduction Example	1 Do	ownload python codes using
•		_	svn (	co https://github.com/gadepall/school/trunk/control/codes
3		order System	1	control/codes
	3.1	Damping	1	
	3.2 3.3	Example	1 1	1 Signal Flow Graph
			1.1	Mason's Gain Formula
4		Hurwitz Criterion	2	Matrix Formula
	4.1	Routh Array	2	
	4.2	Marginal Stability	2	2 Bode Plot
	4.3	Stability	$\frac{2}{2}$ 2.1	Introduction
	4.4	Example	2 2.2	Example
5	State-Space Model		2	3 Second order System
	5.1	Controllability and Observ-	3.1	Damping
	5.2	ability	$\frac{2}{2}$ 3.2 1	Example
	5.3	Example	2 3.3	Peak Overshoot
	5.4	Example	^	Find the expression of peak overshoot for a
	5.5	Example	2	second order control system.
6	Nyquist	t Plot	2	<b>Solution:</b> The transfer function for a second order control
7	Compe	nsators	2	system is:
	7.1	Phase Lead	2	$C(s)$ $\omega_n^2$
	7.2	Example	2	$\frac{S(s)}{R(s)} = \frac{\omega_n}{s^2 + 2\zeta\omega_n s + \omega_n^2} $ (3.3.1.1)
8	Gain Margin		2	To calculate the unit step response,
	8.1	Introduction	2	$r(t) = 1 \implies R(s) = \frac{1}{s}$ (3.3.1.2)
	8.2	Example	2	$r(t) = 1 \implies R(s) = \frac{1}{s}$ (3.3.1.2)
9	Phase N	Margin	2	On Simplifying,
*The author is with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in. All content in this manual is released under GNU $C(s)$				$C(s) = \frac{1}{s} - \frac{s + \zeta \omega_n}{(s + \zeta \omega_n)^2 + \omega_d^2} - \frac{\zeta \omega_n}{\omega_d} \cdot \frac{\omega_d}{(s + \zeta \omega_n)^2 + \omega_d^2}$

GPL. Free and open source.

where,

$$\omega_d = \omega_n \sqrt{1 - \zeta^2} \tag{3.3.1.4}$$

In time domain.

$$c(t) = \mathcal{L}^{-1}C(s)$$
 (3.3.1.5)

$$\implies c(t) = 1 - e^{-\zeta} \omega_n t (\cos \omega_d t + \frac{\zeta}{\sqrt{1 - \zeta^2}} . \sin \omega_d t)$$
(3.3.1.6)

Peak overshoot (Mp) is defined as the deviation of the response at peak time from the final value of response.

$$\implies M_p = c(t_p) - c(\infty)$$
 (3.3.1.7)

At  $t_p$ :

$$\frac{dc(t)}{d(t)} = 0 (3.3.1.8)$$

Applying this condition on (3.3.1.6):

$$\implies t_p = \frac{\pi}{\omega_n \sqrt{1 - \zeta^2}}$$
 (3.3.1.9)

Substituting  $t_p$  in (3.3.1.6):

$$c(t_p) = 1 + e^{\frac{-\zeta \pi}{\sqrt{1-\zeta^2}}}$$
 (3.3.1.10)

From (3.3.1.6):

$$\lim_{t \to \infty} c(t) = 1 \tag{3.3.1.11}$$

Substituting the value of  $c(t_p)$  and  $c(\infty)$  in (3.3.1.7):

$$M_p(PeakOvershoot) = e^{\frac{-\zeta \pi}{\sqrt{1-\zeta^2}}}$$
 (3.3.1.12)

3.3.2. Find the peak Overshoot for the following second order control system

$$G(S) = \frac{100}{s^2 + 10s + 100}$$
 (3.3.2.1)

### **Solution:**

For the given Equation:


$$\zeta = 0.5$$
 (3.3.2.2)

Substitute this value of zeta in (3.3.1.12) to get:

$$M_p = 0.163$$
 (3.3.2.3)

3.3.3. Verify using a Python Plot

codes/ee18btech11045.py



### 4 ROUTH HURWITZ CRITERION

4.1 Routh Array

4.2 Marginal Stability

4.3 Stability

4.4 Example

5 STATE-SPACE MODEL

5.1 Controllability and Observability

5.2 Second Order System

5.3 Example

5.4 Example

5.5 Example

6 Nyquist Plot

7 Compensators

7.1 Phase Lead

7.2 Example

8 Gain Margin

8.1 Introduction

8.2 Example

9 Phase Margin

10 Oscillator

10.1 Introduction

10.2 Example

**Solution:**