


## A closer look at spatial dimensions:

7




7

7x7 input (spatially)  
assume 3x3 filter

## A closer look at spatial dimensions:

7




7

7x7 input (spatially)  
assume 3x3 filter

## A closer look at spatial dimensions:

7




7

7x7 input (spatially)  
assume 3x3 filter

## A closer look at spatial dimensions:

7



7

7x7 input (spatially)  
assume 3x3 filter

## A closer look at spatial dimensions:


7


7

7x7 input (spatially)  
assume 3x3 filter


**=> 5x5 output**

## A closer look at spatial dimensions:




7x7 input (spatially)  
assume 3x3 filter  
applied **with stride 2**

## A closer look at spatial dimensions:



7x7 input (spatially)  
assume 3x3 filter  
applied **with stride 2**


A closer look at spatial dimensions:



7x7 input (spatially)  
assume 3x3 filter  
applied **with stride 2**  
**=> 3x3 output!**




A closer look at spatial dimensions:




7x7 input (spatially)  
assume 3x3 filter  
applied **with stride 3?**

## A closer look at spatial dimensions:



7x7 input (spatially)  
assume 3x3 filter  
applied **with stride 3?**

**doesn't fit!**  
cannot apply 3x3 filter on  
7x7 input with stride 3.



Output size:  
 $(N - F) / \text{stride} + 1$

e.g.  $N = 7, F = 3$ :

stride 1  $\Rightarrow (7 - 3) / 1 + 1 = 5$

stride 2  $\Rightarrow (7 - 3) / 2 + 1 = 3$

stride 3  $\Rightarrow (7 - 3) / 3 + 1 = 2.33 \therefore \backslash$

# In practice: Common to zero pad the border

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

**3x3** filter, applied with **stride 1**

**pad with 1 pixel** border => what is the output?

(recall:)

$$(N - F) / \text{stride} + 1$$

# In practice: Common to zero pad the border

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

**3x3** filter, applied with **stride 1**

**pad with 1 pixel** border => what is the output?

**7x7 output!**

# In practice: Common to zero pad the border

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

**3x3** filter, applied with **stride 1**

**pad with 1 pixel** border => what is the output?

**7x7 output!**

in general, common to see CONV layers with stride 1, filters of size  $F \times F$ , and zero-padding with  $(F-1)/2$ . (will preserve size spatially)


e.g.  $F = 3 \Rightarrow$  zero pad with 1

$F = 5 \Rightarrow$  zero pad with 2

$F = 7 \Rightarrow$  zero pad with 3

## Remember back to...

E.g. 32x32 input convolved repeatedly with 5x5 filters shrinks volumes spatially! (32  $\rightarrow$  28  $\rightarrow$  24 ...). Shrinking too fast is not good, doesn't work well.




Examples time:

Input volume: **32x32x3**

10 5x5 filters with stride 1, pad 2

Output volume size: ?





Examples time:


Input volume: **32x32x3**

**10** **5x5** filters with stride **1**, pad **2**

Output volume size:

$(32 + 2 * 2 - 5) / 1 + 1 = 32$  spatially, so


**32x32x10**



Examples time:

Input volume: **32x32x3**

10 5x5 filters with stride 1, pad 2




Number of parameters in this layer?

Examples time:

Input volume: **32x32x3**

**10** **5x5** filters with stride 1, pad 2



Number of parameters in this layer?

each filter has  $5*5*3 + 1 = 76$  params (+1 for bias)

=>  $76*10 = 760$

**Summary.** To summarize, the Conv Layer:

- Accepts a volume of size  $W_1 \times H_1 \times D_1$
- Requires four hyperparameters:
  - Number of filters  $K$ ,
  - their spatial extent  $F$ ,
  - the stride  $S$ ,
  - the amount of zero padding  $P$ .
- Produces a volume of size  $W_2 \times H_2 \times D_2$  where:
  - $W_2 = (W_1 - F + 2P)/S + 1$
  - $H_2 = (H_1 - F + 2P)/S + 1$  (i.e. width and height are computed equally by symmetry)
  - $D_2 = K$
- With parameter sharing, it introduces  $F \cdot F \cdot D_1$  weights per filter, for a total of  $(F \cdot F \cdot D_1) \cdot K$  weights and  $K$  biases.
- In the output volume, the  $d$ -th depth slice (of size  $W_2 \times H_2$ ) is the result of performing a valid convolution of the  $d$ -th filter over the input volume with a stride of  $S$ , and then offset by  $d$ -th bias.

## Common settings:


**Summary.** To summarize, the Conv Layer:

- Accepts a volume of size  $W_1 \times H_1 \times D_1$
- Requires four hyperparameters:
  - Number of filters  $K$ ,
  - their spatial extent  $F$ ,
  - the stride  $S$ ,
  - the amount of zero padding  $P$ .
- Produces a volume of size  $W_2 \times H_2 \times D_2$  where:
  - $W_2 = (W_1 - F + 2P)/S + 1$
  - $H_2 = (H_1 - F + 2P)/S + 1$  (i.e. width and height are computed equally by symmetry)
  - $D_2 = K$
- With parameter sharing, it introduces  $F \cdot F \cdot D_1$  weights per filter, for a total of  $(F \cdot F \cdot D_1) \cdot K$  weights and  $K$  biases.
- In the output volume, the  $d$ -th depth slice (of size  $W_2 \times H_2$ ) is the result of performing a valid convolution of the  $d$ -th filter over the input volume with a stride of  $S$ , and then offset by  $d$ -th bias.

$K =$  (powers of 2, e.g. 32, 64, 128, 512)


- $F = 3, S = 1, P = 1$
- $F = 5, S = 1, P = 2$
- $F = 5, S = 2, P = ?$  (whatever fits)
- $F = 1, S = 1, P = 0$

(btw, 1x1 convolution layers make perfect sense)




# Pooling layer

- makes the representations smaller and more manageable
- operates over each activation map independently:



# MAX POOLING





- Accepts a volume of size  $W_1 \times H_1 \times D_1$
- Requires three hyperparameters:
  - their spatial extent  $F$ ,
  - the stride  $S$ ,
- Produces a volume of size  $W_2 \times H_2 \times D_2$  where:
  - $W_2 = (W_1 - F)/S + 1$
  - $H_2 = (H_1 - F)/S + 1$
  - $D_2 = D_1$
- Introduces zero parameters since it computes a fixed function of the input
- Note that it is not common to use zero-padding for Pooling layers

## Common settings:


$$F = 2, S = 2$$

$$F = 3, S = 2$$

- Accepts a volume of size  $W_1 \times H_1 \times D_1$
- Requires three hyperparameters:
  - their spatial extent  $F$ ,
  - the stride  $S$ ,
- Produces a volume of size  $W_2 \times H_2 \times D_2$  where:
  - $W_2 = (W_1 - F)/S + 1$
  - $H_2 = (H_1 - F)/S + 1$
  - $D_2 = D_1$
- Introduces zero parameters since it computes a fixed function of the input
- Note that it is not common to use zero-padding for Pooling layers

# Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images


**First layer (CONV1):** 96 11x11 filters applied at stride 4

=>

Q: what is the output volume size? Hint:  $(227-11)/4+1 = 55$

# Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

**First layer (CONV1):** 96 11x11 filters applied at stride 4


=>

Output volume **[55x55x96]**

Q: What is the total number of parameters in this layer?

# Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

**First layer (CONV1):** 96 11x11 filters applied at stride 4


=>

Output volume **[55x55x96]**

Parameters:  $(11*11*3)*96 = \mathbf{35K}$

# Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images


After CONV1: 55x55x96

**Second layer (POOL1):** 3x3 filters applied at stride 2

Q: what is the output volume size? Hint:  $(55-3)/2+1 = 27$

# Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96


**Second layer (POOL1):** 3x3 filters applied at stride 2

Output volume: 27x27x96

Q: what is the number of parameters in this layer?

# Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96

**Second layer (POOL1):** 3x3 filters applied at stride 2

Output volume: 27x27x96

Parameters: 0!



INPUT: [224x224x3] memory:  $224*224*3=150\text{K}$  params: 0 (not counting biases)

CONV3-64: [224x224x64] memory:  $224*224*64=3.2\text{M}$  params:  $(3*3*3)*64 = 1,728$

CONV3-64: [224x224x64] memory:  $224*224*64=3.2\text{M}$  params:  $(3*3*64)*64 = 36,864$

POOL2: [112x112x64] memory:  $112*112*64=800\text{K}$  params: 0

CONV3-128: [112x112x128] memory:  $112*112*128=1.6\text{M}$  params:  $(3*3*64)*128 = 73,728$

CONV3-128: [112x112x128] memory:  $112*112*128=1.6\text{M}$  params:  $(3*3*128)*128 = 147,456$

POOL2: [56x56x128] memory:  $56*56*128=400\text{K}$  params: 0

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*128)*256 = 294,912$

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*256)*256 = 589,824$

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*256)*256 = 589,824$

POOL2: [28x28x256] memory:  $28*28*256=200\text{K}$  params: 0

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*256)*512 = 1,179,648$

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

POOL2: [14x14x512] memory:  $14*14*512=100\text{K}$  params: 0

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

POOL2: [7x7x512] memory:  $7*7*512=25\text{K}$  params: 0

FC: [1x1x4096] memory: 4096 params:  $7*7*512*4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params:  $4096*4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params:  $4096*1000 = 4,096,000$

ConvNet Configuration			
B	C	D	
13 weight layers	16 weight layers	16 weight layers	19
Input (224 × 224 RGB image)			
conv3-64	conv3-64	conv3-64	conv3-64
<b>conv3-64</b>	conv3-64	conv3-64	conv3-64
maxpool			
conv3-128	conv3-128	conv3-128	conv3-128
<b>conv3-128</b>	conv3-128	conv3-128	conv3-128
maxpool			
conv3-256	conv3-256	conv3-256	conv3-256
conv3-256	conv3-256	conv3-256	conv3-256
	<b>conv1-256</b>	<b>conv3-256</b>	conv3-256
maxpool			
conv3-512	conv3-512	conv3-512	conv3-512
conv3-512	conv3-512	conv3-512	conv3-512
	<b>conv1-512</b>	<b>conv3-512</b>	conv3-512
maxpool			
conv3-512	conv3-512	conv3-512	conv3-512
conv3-512	conv3-512	conv3-512	conv3-512
	<b>conv1-512</b>	<b>conv3-512</b>	conv3-512
maxpool			
FC-4096			
FC-4096			
FC-1000			
soft-max			

INPUT: [224x224x3] memory:  $224*224*3=150\text{K}$  params: 0 (not counting biases)

CONV3-64: [224x224x64] memory:  $224*224*64=3.2\text{M}$  params:  $(3*3*3)*64 = 1,728$

CONV3-64: [224x224x64] memory:  $224*224*64=3.2\text{M}$  params:  $(3*3*64)*64 = 36,864$

POOL2: [112x112x64] memory:  $112*112*64=800\text{K}$  params: 0

CONV3-128: [112x112x128] memory:  $112*112*128=1.6\text{M}$  params:  $(3*3*64)*128 = 73,728$

CONV3-128: [112x112x128] memory:  $112*112*128=1.6\text{M}$  params:  $(3*3*128)*128 = 147,456$

POOL2: [56x56x128] memory:  $56*56*128=400\text{K}$  params: 0

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*128)*256 = 294,912$

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*256)*256 = 589,824$

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*256)*256 = 589,824$

POOL2: [28x28x256] memory:  $28*28*256=200\text{K}$  params: 0

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*256)*512 = 1,179,648$

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

POOL2: [14x14x512] memory:  $14*14*512=100\text{K}$  params: 0

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

POOL2: [7x7x512] memory:  $7*7*512=25\text{K}$  params: 0

FC: [1x1x4096] memory: 4096 params:  $7*7*512*4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params:  $4096*4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params:  $4096*1000 = 4,096,000$

TOTAL memory:  $24\text{M} * 4 \text{ bytes} \approx 93\text{MB} / \text{image}$  (only forward!  $\sim 2$  for bwd)

TOTAL params: 138M parameters

ConvNet Configuration			
B	C	D	
13 weight layers	16 weight layers	16 weight layers	19
put (224 × 224 RGB image)			
conv3-64	conv3-64	conv3-64	cc
<b>conv3-64</b>	conv3-64	conv3-64	cc
maxpool			
conv3-128	conv3-128	conv3-128	co
<b>conv3-128</b>	conv3-128	conv3-128	co
maxpool			
conv3-256	conv3-256	conv3-256	co
conv3-256	conv3-256	conv3-256	co
	<b>conv1-256</b>	<b>conv3-256</b>	co
			co
maxpool			
conv3-512	conv3-512	conv3-512	co
conv3-512	conv3-512	conv3-512	co
	<b>conv1-512</b>	<b>conv3-512</b>	co
			co
maxpool			
conv3-512	conv3-512	conv3-512	co
conv3-512	conv3-512	conv3-512	co
	<b>conv1-512</b>	<b>conv3-512</b>	co
			co
maxpool			
FC-4096			
FC-4096			
FC-1000			
soft-max			

INPUT: [224x224x3] memory:  $224*224*3=150\text{K}$  params: 0 (not counting biases)

CONV3-64: [224x224x64] memory:  $224*224*64=3.2\text{M}$  params:  $(3*3*3)*64 = 1,728$

CONV3-64: [224x224x64] memory:  $224*224*64=3.2\text{M}$  params:  $(3*3*64)*64 = 36,864$

POOL2: [112x112x64] memory:  $112*112*64=800\text{K}$  params: 0

CONV3-128: [112x112x128] memory:  $112*112*128=1.6\text{M}$  params:  $(3*3*64)*128 = 73,728$

CONV3-128: [112x112x128] memory:  $112*112*128=1.6\text{M}$  params:  $(3*3*128)*128 = 147,456$

POOL2: [56x56x128] memory:  $56*56*128=400\text{K}$  params: 0

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*128)*256 = 294,912$

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*256)*256 = 589,824$

CONV3-256: [56x56x256] memory:  $56*56*256=800\text{K}$  params:  $(3*3*256)*256 = 589,824$

POOL2: [28x28x256] memory:  $28*28*256=200\text{K}$  params: 0

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*256)*512 = 1,179,648$

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [28x28x512] memory:  $28*28*512=400\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

POOL2: [14x14x512] memory:  $14*14*512=100\text{K}$  params: 0

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

CONV3-512: [14x14x512] memory:  $14*14*512=100\text{K}$  params:  $(3*3*512)*512 = 2,359,296$

POOL2: [7x7x512] memory:  $7*7*512=25\text{K}$  params: 0

FC: [1x1x4096] memory: 4096 params:  $7*7*512*4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params:  $4096*4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params:  $4096*1000 = 4,096,000$

TOTAL memory:  $24\text{M} * 4 \text{ bytes} \approx 93\text{MB}$  / image (only forward!  $\sim 2$  for bwd)

TOTAL params: 138M parameters

Note:

Most memory is in  
early CONV

Most params are  
in late FC