C: > Users > sudee > lab3.py > ...

```python
class MeansEndAnalysis:
    def __init__(self, operators):
        self.operators = operators

    def solve(self, current, goal):
        print(f"Current State: {current} | Goal State: {goal}")

        if current == goal:
            return []

        # Find difference
        diff = self.find_difference(current, goal)
        if not diff:
            return []

        # Find operator that can resolve the difference
        op = self.select_operator(diff)
        if not op:
            print(f"No operator found to resolve difference: {diff}")
            return None
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

Python

```
PS C:\Users\sudee\AppData\Local\Programs\Microsoft VS Code> & C:\msys64\ucrt64\bin\python.exe c:/Users/sudee/lab3.py
Current State: {'has_money': True, 'has_car': False, 'at_home': True, 'at_work': False} | Goal State: {'at_work': True}
Current State: {'has_money': True, 'has_car': False, 'at_home': True, 'at_work': False} | Goal State: {'has_car': True, 'at_home': True}
Current State: {'has_money': True, 'has_car': False, 'at_home': True, 'at_work': False} | Goal State: {'has_money': True, 'has_car': False}
Current State: {'has_money': True, 'has_car': True, 'at_home': True, 'at_work': False} | Goal State: {'has_car': True, 'at_home': True}
Current State: {'has_money': True, 'has_car': False, 'at_home': False, 'at_work': True} | Goal State: {'at_work': True}

Execution Plan: ['Buy_Car', 'Drive_Car']
PS C:\Users\sudee\AppData\Local\Programs\Microsoft VS Code>
```

Launchpad ⊗ 0 ⚠ 0 Ln 93, Col 37 Spaces: 4 UTF-8 CRLF { } Python Python 3.12.7.final.0