Null Energy Explains SING's Model Ranking: An Audit of a Null-Space Leakage Score

Anonymous Authors
Workshop submission

Abstract

SING [17] ranks 13 ImageNet classifiers by how much class-relevant semantics leak into the null space of their linear heads, and reports that a "DinoViT" leaks least. We audit this ranking and find that the null energy fraction ρ alone reproduces SING's published order as well as SING's own score does (Kendall τ=0.82 for both). Within a model, |AS| rises by $\approx$10$\times$ from d=24 to d=1048 removed null dimensions on 3 of 4 models. On BiT it drops instead (0.06$\times$), which we trace to translator conditioning. Across energy and dimension, $|\mathrm{AS}| \propto \rho^a$ with $a \approx 0.4$–0.5. Size-corrected scores give rankings that differ from SING's (point τ between -0.41 and $+0.33$ under seven of eight normalisers). We do not claim a reversal: the 95% model-bootstrap intervals are wide, the energy-matched correction $\mathrm{AS}_{\mathrm{fair}}$ over-corrects, and model rankings are not stable across null tolerances. No public ViT-L/16 checkpoint consistent with SING's code is a DINO model or matches the reported 84.0% top-1; SING's released DinoViT translator fits the timm AugReg checkpoint best (mean cosine 0.85 vs. $\leq$0.68 for the other four). We also report two pre-registered negative results: a probe-based score (E8) and a 20-candidate score screen (E9) both failed their criteria. A synthetic check later showed that the flatness criterion they share is ill-posed. Under a revised rule, one candidate (debiased null leakage, M1) qualifies post hoc. On a post-hoc holdout it recovers planted leakage well (τ=0.93 vs. 0.17 for $\mathrm{AS}_{\mathrm{fair}}$) but still fails the registered rule, and across the 13 models it orders them much as ρ does. We recommend reporting ρ next to any cross-model null-space score.

1 Introduction

A linear classifier on features $f \in \mathbb{R}^m$ has a null space of dimension $m-\mathrm{rank}(W)$ that leaves the logits unchanged. SING [17] treats class-relevant content in that null space as "leakage": information the head could have used, but did not. Its Absolute Shift (AS) measures how far a CLIP-aligned [11] translation of f moves once the null component is removed. SING uses AS and the IS/AS ratio to rank 13 models, and singles out a ViT labelled "DinoViT" [1]. Null spaces also show up in work on out-of-distribution failure [6], outlier detection [2, 16], overfitting [13] and information hiding [8]. In NLP, nullspace projection is used to remove a property from representations (INLP [12], amnesic probing [4]). Work in that area has also established that probe readouts must be compared against controls [5]. Representation-similarity scores are known to be dominated by high-variance directions [3].

Across architectures, the null dimension d and the null energy fraction $\rho = \mathbb{E}\|V_n V_n^\top f\|^2 / \mathbb{E}\|f\|^2$ both vary by orders of magnitude. If AS mostly tracks how much energy is removed, then a cross-model comparison of "semantics" is confounded by size.

Contributions. (1) ρ alone reproduces SING's 13-model order (τ=0.82); AS scales as ρ^a, $a \approx 0.4$–0.5 (Exp 1, E1). (2) Size-corrected rankings differ from SING's under most of eight normalisers and three control families, but no correction reverses it with confidence (§7). (3) Under SING's own score, two of its class-level claims (C4, C8) do not reproduce on our pipeline. (4) The "DinoViT" checkpoint cannot be identified as DINO, although SING's translator fits the timm AugReg checkpoint best. (5) We report every pre-registered experiment (Table 1), including two KILLs and the flawed flatness rule behind them.

2 Background and the DinoViT identity

SING AS in brief. Let $T(f) = Af + b$ be SING's released linear translator into CLIP space and V_n an orthonormal basis of $\ker(W)$ (singular-value tolerance 10^{-5} unless stated). For a text direction t, the per-image absolute shift is the change in angle $\theta(T(f), t)$ after removing $V_n V_n^\top f$. $\mathrm{AS}_{\mathrm{SING}}$ denotes the image-averaged |AS| under full null removal, with class text as the target. We match SING's released code (commit e47b37d) on a fixed 10k ImageNet-val subset (10 images/class). SING itself is not consistent about its protocol. Its text mentions a "12-model sweep" while Supp. Table 3 lists 13 models. It describes 16 classes in one place and 10k features over 1000 classes in another. Its bibliography gives the wrong arXiv id for [8].

Exp 0b: "DinoViT" is not DINO. SING reports DinoViT at 84.0% top-1 (Supp. Table 3). The released models.yaml loads a timm AugReg ViT-L/16, while

Exp.	Pre-declared criterion (short)	Outcome	Where
Exp 0	null size correlates with SING IS/AS (d_{null}; ρ as baseline)	GO rests on ρ (-0.94, E2 features); d_{null} alone -0.46, p=0.12	§2
Exp 1	r=AS(1048)/AS(24) ≥ 3 on $\geq 3/4$ models and $\tau_{d=24} \leq 0.5$	GO ($r \approx 10$ on 3/4; BiT 0.06; τ=0.29)	§3
E1	ENERGY-DRIVEN: high/low $\geq 3\times$ at fixed d and $\leq 1.5\times$ across d at fixed ρ	MIXED (first part holds 4/4; second fails)	§4
E2	$\tau(\text{AS}_{\text{fair}}, \text{SING}) \leq 0.5$ or ≥ 1 headline claim reverses	PASS as registered; weakened by round-2 tests (§7)	§7
E3	$\tau(\text{AS}_{\text{fair}}, \text{planted}) \geq 0.8$ and $\tau(\text{AS}_{\text{SING}}, \text{planted}) \leq 0.5$	Not passed (0.109 vs 0.386); KILL condition ($\text{AS}_{\text{SING}} \geq 0.8$) not met	§6
E8	NCP probe: $\tau \geq 0.8$ and flat (max / min ≤ 1.5 across d); KILL if $\tau < 0.6$	KILL (τ=-0.331 [-0.392, -0.273]; flat 0/4)	§8
E9	20-candidate screen: DEV $\tau \geq 0.8$ and flat on $\geq 3/4$ at $\alpha \in \{0.1, 1\}$	KILL (best M1 τ=0.976, flat 0/4). Post-hoc holdout: no candidate passes as registered; M1 τ=0.93, passes only with revised flatness	§8
R2	KILL-R: drop "disagrees" unless fix 2 and D-weak pass on all 13 and screened set	Not fired; "differs from" allowed, "reverses" not (D-strong fails)	§7
R2	Tolerance stability: adjacent-tolerance $\tau \geq 0.9$ for every score	FAIL (AS_{fair} 0.87/0.82; AS_{SING} 0.87 on all 13)	§7
R2	Synthetic oracle passes the E8/E9 flatness rule	FAIL (ratio 3.55 / 3.48): rule ill-posed	§8
R2	DinoViT translator fidelity: used checkpoint best by ≥ 0.05	PASS (0.848 vs. next best 0.677; margin 0.171)	§2

Table 1: All pre-registered experiments and their outcomes. Pre-registrations and results are in the repository (FULL_PAPER_PLAN.md, e8/PREREG_E8.md, E9_SCORE_SCREEN_PREREG.md, PREREG_R2.md). R2 = the round-2 pre-registration written in response to review.




Figure 1: Exp 0b top-1 on ImageNet-val (native eval transform). No candidate matches SING's reported 84.0%.




Figure 2: Exp 1: mean |AS| vs. subspace size d (a) and removed energy ρ_d (b). BiT collapses at the full null (translator cancellation).

the wrapper in the supplement uses torchvision attribute names. We evaluated five public ViT-L/16 candidates on the full 50k validation set: torchvision IMAGENET1K_V1 (79.67%), timm AugReg (85.85%), SWAG linear [14] (85.14%), SWAG E2E (88.07%) and HF google/vit-large-patch16-224 (81.98%). None falls in 84.0 ± 0.3 (Fig. 1). All five are supervised or SWAG weakly supervised, and DINO never released a ViT-L with a 1000-way head [1]. The checkpoint we use (timm AugReg, the one SING's models.yaml loads) gives mean $\cos(T(f), \text{CLIP}) = 0.848$ with SING's dinovit1 translator. On the first 1000 subset images, re-extracted with each candidate's native transform, the other four give 0.677 (torchvision IMAGENET1K_V1), 0.631 (HF), 0.615 (SWAG linear) and 0.608 (SWAG E2E). The used checkpoint is best by 0.171, above the pre-registered 0.05 margin. Its re-extracted features match our cached ones exactly. SING's translator was therefore most likely fit on this timm AugReg model, regardless of how it is labelled.

Exp 0 (re-analysis). We digitised the 13 IS/AS bars in SING Supp. Fig. 12b (the extended ratio comparison) and correlated them with measured null quantities. The GO decision rests on the energy condition: Spearman(ρ, IS/AS)=-0.94 (p=1.9×10^{-6}). The dimension condition is not significant on its own (Spearman -0.46, p=0.12; DenseNet null dim 27 at tol 10^{-5}). DeiT3-L [15] has null dim 24 yet the worst ratio, so dimension alone cannot explain the ranking.

Model	r	2σ band	R^2 (vs $d \equiv$ vs ρ_d)
ResNet50	10.15	[5.83, 14.48]	0.983
ResNeXt101	11.44	[6.93, 15.95]	0.977
DINOv2-L	10.48	[8.85, 12.10]	0.974
BiT-R50x1	0.060	[0.057, 0.063]	0.512

Table 2: Exp 1: r=AS(1048)/AS(24). For random sub-subspaces ρ_d is linear in d, so the two R^2 coincide.

3 Within-model size dependence (Exp 1)

On the 10k subset we remove random d-dimensional subspaces of each model's own null space ($d \in \{24, 48, 100, 280, 536, 1048\}$, 20 seeds for d<d_{null}). The models are ResNet50, ResNeXt101, BiT-R50x1 [7] and DINOv2-L [10], all with d_{null}=1048, and SING's released translators. Because random sub-subspaces remove energy nearly linearly in d, the fits against d and against ρ_d are indistinguishable (R^2 in Table 2), and Exp 1 by itself cannot separate them. The ratio is $r \approx 10$ on 3 of 4 models (Fig. 2). At matched d=24 across 8 models, Kendall τ against the Supp. Fig. 12b order is 0.29 (p=0.40).

BiT anomaly. BiT's full-null AS collapses (r=0.06), even though partial subspaces give large AS (9–13°). The singular values of AV_n are extreme (top 284 vs. 5.6 for ResNet50), and the orthogonal null blocks nearly cancel through the translator. BiT also fails our degeneracy screen: a retained row-space direction with σ=8.9×10^{-4} carries 26% of the feature energy.




Figure 3: E1 cells: |AS| vs. ρ. Solid: pooled fit (a=0.43, cell bootstrap $[0.39, 0.48]$); dashed: $\sqrt{\rho}$.

4 Energy vs. dimension (E1)

Geometry. If a linear translator maps a removed component of relative energy ρ into CLIP space and the residual is small relative to $\|T(f)\|$, the first-order angular change scales with $\|\Pi f\| \propto \sqrt{\rho}$, i.e. exponent 0.5.

Design and result. On ResNet50, ResNeXt101, DINOv2-L, VGG16 and EVA02-L we compare high- with low-energy null PCs at fixed $d \in \{24, 100, 280\}$, and hit fixed $\rho \in \{0.5\%, 2\%, 8\%\}$ at several d by mixing top and bottom PCs. The pooled fit over 76 cells, $\log|\text{AS}| = a\log\rho + b\log d + c_{\text{model}}$, gives a=0.431 and b=0.010 (R^2=0.93; Fig. 3). The cell-level bootstrap gives $a \in [0.388, 0.485]$ and the model-clustered bootstrap gives $[0.382, 0.464]$. Leaving one model out gives $a \in [0.408, 0.452]$, and per-model fits give 0.38–0.46. b covers 0 under both bootstraps. We therefore claim only $a \approx 0.4$–0.5. At fixed d, the high/low ratio exceeds 3× on all 4 evaluable models. At fixed ρ, however, the max/min across d exceeds 1.5 in several cells (up to 2.29). We therefore rate E1 as mixed: energy dominates the fit, and the pre-registered flatness part still fails.

Energy as confound or as signal (round 2). If high-variance null directions were the semantic ones, energy would partly be the signal. At matched d, we compare G=AS/$\sqrt{\rho}$ for the top-variance null PCs against random null sub-subspaces (1000× image bootstrap). At d=24, $G_{\text{top}}/G_{\text{rand}}$ is 0.60 (ResNeXt), 0.87 (DINOv2) and 0.008 (BiT), all with CIs below 1, but 1.16 $[1.15, 1.17]$ for ResNet50. At d=100: 1.01, 0.85, 0.83, 0.011. Top PCs therefore carry less AS per unit $\sqrt{\rho}$ than random directions on 3 of 4 models. High-energy directions are not disproportionately semantic, which supports the confound reading. G is not constant across bands, though, so $\sqrt{\rho}$ is only an approximate nuisance model.

5 Size-fair scores

$\text{AS}_{\text{fair}} = \text{AS}_{\text{null}}/\text{AS}_{\text{rand}}$, where AS_{rand} is the mean |AS| after removing an energy-matched random subspace. In the original analysis (family A), the random subspace is Haar over the full feature space (seed 10000+r, 20 draws). This changes the logits, so in round 2 we added two control families that preserve them better. Family B draws an energy-matched subspace from the span of the lowest-σ row-space directions of W. These directions do change the logits, by up to 14–74 logit SDs for models with a large span (VGG, ResNeXt). Family C compares a random 24-dim null sub-subspace, which changes no logit, against a family-B control of matched energy. Every score is reported on all 13 models and on a pre-declared screened set of 11. The screen excludes models with $\rho<10^{-4}$ or with a retained direction of $\sigma<10^{-3}$ holding >5% of the energy, which removes DenseNet (ρ=1.8×10^{-8}) and BiT.

6 Planted leakage (E3)

We plant a CLIP concept direction (red/striped/water) into the null spaces of 8 models, at log-uniform $\alpha \in [0.01, 1]$ over 50 trials (plant seed 0, bootstrap seed 1). The logits stay unchanged (max $|\Delta\text{logit}| \leq 2.3\times10^{-5}$). Both scores are α=0-subtracted per (model, concept). Kendall τ against the planted ranking, averaged over concepts, is 0.386 $[0.324, 0.448]$ for AS_{SING} and 0.109 $[0.046, 0.171]$ for AS_{fair}. Without the subtraction, AS_{fair} gives 0.071 $[0.004, 0.141]$. Without DenseNet, the values are 0.343 and 0.135. Neither score recovers planted strength well, so a size correction should not be read as a leakage oracle.

7 The 13-model ranking (E2) and round-2 tests

On the 10k subset, plus a 200-image claim-class set (all 50 val images each of jellyfish, porcupine, Arabian camel and sports car), we recompute every score for all 13 released translators.

The energy confound. Against the digitised Supp. Fig. 12b order, $\tau(\text{AS}_{\text{SING}})$=0.821 (model-bootstrap 95% CI $[0.56, 1]$), which reproduces SING. Ranking models by ρ alone gives the same τ=0.821 $[0.56, 1]$ (Fig. 4). Over 13 models, Spearman(ρ, AS_{SING})=0.87. SING's model order therefore matches the order that null energy alone predicts.

Do size corrections change the order? Point τ vs. SING is −0.18 (family A), −0.41 (B) and −0.13 (C) on all 13 models, and −0.56, −0.60 and −0.27 on the screened set. All are below the pre-registered 0.3 bar. Over eight




Figure 4: Left: ranks (1 = least leakage, ⋆ marks rank 1) under SING Supp. Fig. 12b, AS_{SING} and AS_{fair} (family A). Right: τ vs. SING for each normaliser, with 2000× model-bootstrap 95% CIs, on all 13 models and on the screened 11. Dotted line: the τ=0.3 bar of fix 2.




Figure 5: (a) AS_{SING} rises with ρ_{null}. (b) AS_{fair} (family A) falls with ρ_{null}: it over-corrects (Spearman −0.79 on the screened set). ×: models excluded by the degeneracy screen.

ID	Claim (short)	Effect AS_{SING} [95% CI]	AS_{SING}	AS_{fair}
C1	DinoViT best ratio (proxy)	+0.149 [.142, .156]	holds	opp.
C2	ResNeXt worst ratio (proxy)	+0.323 [.302, .342]	holds	opp.
C3	ResNet > DinoViT	+1.383 [1.37, 1.39]	holds	opp.
C4	DinoViT least leakage	−0.293 [−.298, −.289]	rev.	opp.
C5	ResNeXt top-2 of 5	+1.442 [1.42, 1.46]	holds	opp.
C6	ResNet per-class > DinoViT	mean +1.38, SD +0.74	holds	opp.
C7	DinoViT per-class $\lvert AS\rvert<1°$	+0.50 [.497, .50]	holds	n/a
C8	Porcupine/sports car ≥90th pct	−5.2 / −29 pct	rev.	opp.
C9	No ResNet–DinoViT class corr.	−0.033 [−.056, .009]	holds	contra.
C10	Jellyfish ≫ camel	−0.107 [−.206, .001]	n.c.	opp.
C11	DinoViT least steerable (proxy)	+0.149 [.142, .156]	holds	opp.
C12	Supp. Fig. 12b order (τ)	0.821 [.56, 1]†	holds	n.c.†
C13	EVA02 target-space order	–	untestable	untestable

Table 3: E2 claim audit (round 2). rev. = CI on the opposite side of 0; n.c. = not confirmed; opp. = opposite side under AS_{fair}, which over-corrects (Fig. 5b); contra. = a correlation is found. C7 has no AS_{fair} analogue (AS_{fair} is unitless). †Model bootstrap; AS_{fair} τ=−0.18 [−0.78, 0.35]. C1/C2/C11 use |AS| proxies.

normalisers (AS/ρ^a for $a \in \{.25, .43, .5, 1\}$, AS/d, families A–C), the 95% CI excludes AS_{SING}'s 0.821 for 7 of 8 normalisers on all 13 models. On the screened set it does so for exactly 5 of 8, which is the minimum the rule allows. Only family B on the screened set has a CI entirely below 0 ($[-0.89, -0.23]$). Normalising by the fitted exponent leaves a positive τ ($\rho^{0.43}$: +0.33 $[-0.15, 0.77]$; $\sqrt{\rho}$: +0.26), so the answer depends on which normaliser is chosen. The data support the claim that size-corrected rankings differ from SING's, and not the stronger claim that they reverse it.

AS_{fair} over-corrects. Spearman(AS_{fair}, ρ) is −0.26 $[-0.96, 0.41]$ on all 13 models and −0.79 $[-1, -0.23]$ on the screened set (Fig. 5b). Low-ρ models such as DinoViT and EVA02 are pushed to the bottom. Instead of removing the energy trend, AS_{fair} inverts it.

Tolerance sensitivity. At null tolerances 10^{-6} to 10^{-3}, the null dimension of DenseNet grows from 25 to 221, while that of the other models barely changes. Rank agreement between adjacent tolerances drops below the pre-registered 0.9 for both scores: AS_{fair} gives 0.87 (all 13) and 0.82 (screened) from 10^{-5} to 10^{-4}, and AS_{SING} gives 0.87 from 10^{-4} to 10^{-3}. Null dim and ρ stay at or above 0.92. This test fails, so model rankings from either score should not be read to single-rank precision.

Class-level claims. For each claim we define a signed effect (positive = SING's direction) and bootstrap images within class (1000×, seed 0). A claim holds if the CI is above 0, reverses if it is below, and is not confirmed if the CI covers 0 (Table 3). These CIs capture image resampling only, not the choice of model set or normaliser, so they are narrow. Under AS_{SING}, two claims do not reproduce on our pipeline:

- C4: DinoViT does not have the lowest class AS (effect −0.29°); ConvNeXt and DenseNet are lower.
- C8: ResNet's porcupine and sports-car classes are not in the top decile (percentile gaps −5.2 $[-9.7, -2.4]$ and −29).

C10 (jellyfish ≫ camel) is not confirmed (−0.11 $[-0.21, 0.001]$). These are discrepancies between SING and our re-implementation, possibly due to protocol (SING used ≈30 concepts and ≈1300 images for C10), and they do not come from size correction. Under AS_{fair}, every testable claim has a CI on the opposite side, and C9 ("no correlation") is contradicted. Because of the over-correction noted above, we treat these as diagnostics rather than as reversals. By AS_{fair} (family A), DinoViT ranks 12th of 13; under AS_{SING} it ranks 3rd.

DinoViT ratio gap. Our DinoViT IS/|AS| is 20.95, against 70.16 in Supp. Fig. 12b, a 3.35× gap. For the other 12 models SING's ratio is 0.98–2.5× ours (EVA02 2.5×, BiT 1.9×, DenseNet 1.7×), so the gap is largest for DinoViT, while the AS_{SING} order still agrees. Candidate causes include SING's image and class subset (16 classes vs. our 1000), its concept set, and the checkpoint (§2). We cannot tell them apart without SING's evaluation lists.

8 Score search: E8, E9 and the flatness rule

E8 (pre-registered, KILL). A probe-based null-content score (NCP: ridge-probe R^2 on null coordinates, z-scored against energy-matched random subspaces) gave τ=−0.331 [−0.392, −0.273] on the E3 planted task, and was flat on 0/4 eligible models. Three implementation flags apply. The z-score saturates because both R^2 values approach 1. λ was chosen by approximate closed-form LOO rather than the exact CV in the pre-registration. And λ sat at the grid floor in 18 of 96 fits.

E9 (pre-registered, KILL). We screened 20 candidate scores on two DEV concepts. The rule was DEV $\tau \geq 0.8$ and flatness (max / min ≤ 1.5 across nested null sub-subspaces) on $\geq 3/4$ models at both $\alpha \in \{0.1, 1\}$. No candidate qualified. The best was M1 (debiased null leakage, $\hat{L}^2 = (\|\sum_i Pf_i s_i\|^2 - \sum_i \|Pf_i\|^2 s_i^2)/(n(n-1)\mathbb{E}\|f\|^2)$ with standardised concept scores s_i; score $\sqrt{\max(\hat{L}^2, 0)}$), with DEV τ=0.976 [0.963, 0.988] but flat on 0/4. Others: M2 0.540, S9 (a mutual-information score) 0.522, S10 0.395 (the only flat one), M5 (AS/$\sqrt{\rho}$) 0.323, S4 (AS/ρ) −0.051.

The flatness rule is ill-posed (round 2). On synthetic Gaussian features with a known head (m=400, null dim 300), we planted a direction either in the full null or in a fixed 24-dim sub-subspace. We then scored an exact oracle, the planted amplitude inside the removed subspace B, $\alpha\|B^\top u\|$. The oracle itself fails the rule, with max / min 3.55 and 3.48 ($\approx \sqrt{300/24}$), because a larger B genuinely contains more of the plant. A revised rule, max / min of score/oracle ≤ 1.5, is passed by M1 in both settings (ratios 1.00–1.03). Re-judged post hoc on the saved DEV values, M1 is revised-flat on 4/4 models at both α and is the only E9 candidate that qualifies. E8's NCP is flat on 0/4. This is exploratory, and E8 and E9 remain KILLs as registered.

E9 holdout (round 2, post hoc). We ran the E9 holdout on four held-out concepts (water, green, thin, knitted; 50 trials at seed 1; linear and nonlinear plants) for the six candidates declared in the round-2 pre-registration plus AS_{SING} and AS_{fair}, with the E9 pass rule (Table 4). Only M1 meets both τ thresholds. Under the registered flatness rule no candidate passes; that rule also fails for the oracle (above). Under the revised rule, M1 passes. Paired over trials (1000×, seed 0), τ(M1)−$\tau(\text{AS}_{\text{fair}})$ is 0.77 [0.71, 0.82] for the linear plant and 1.01 [0.96, 1.06] for the nonlinear plant, so M1 tracks the planted leakage better than AS_{fair} under both plants. M1 is given the concept score that defines the plant, while the AS-family scores are not, so this comparison favours M1 by construction. M1 was picked after the DEV results and the flatness rule was revised after the oracle test, so this holdout is post hoc. E9 stays a KILL as registered, and M1 is a candidate for a future pre-registered test, not a validated score.

Score	lin. τ [95% CI]	nl. τ	flat	rev. flat	pass
M1	0.93 [0.91, 0.95]	0.97	0/0	4/4	rev.
M2	0.44 [0.39, 0.48]	0.46	0/0	0/0	no
S9	0.45 [0.40, 0.51]	0.44	0/1	2/0	no
S10	0.37 [0.33, 0.42]	0.52	3/4	0/0	no
M5 (AS/$\sqrt{\rho}$)	0.22 [0.18, 0.27]	0.15	0/0	0/0	no
S4 (AS/ρ)	−0.08 [−0.15, −0.01]	−0.14	0/0	0/0	no
AS_{SING} (raw)	0.33 [0.27, 0.40]	0.36	0/0	0/0	no
AS_{fair} (sub.)	0.17 [0.11, 0.22]	−0.04	0/0	0/0	no

Table 4: E9 holdout (post hoc; AS_{fair} is α=0-subtracted; water, green, thin, knitted; 50 trials, seed 1; 8 models). Flat = number of the 4 large-null models flat at α=0.1/1 under the registered rule; rev. flat = under the revised score/oracle rule. Pass: lin. $\tau \geq 0.8$, CI lower ≥ 0.7, nl. $\tau \geq 0.6$, flat on $\geq 3/4$ at both α (yes = registered rule, rev. = only with the revised rule).

M1 on the 13 models (descriptive). Because M1 beats AS_{fair} on the holdout, we also rank the 13 models by M1 (post hoc, descriptive; r2/e2_m1.py). At α=0, on the full null and averaged over SING's 173 concepts, M1 gives τ=0.667 [0.29, 0.94] against SING's order (0.600 [0.06, 0.92] on the screened set). Both intervals include AS_{SING}'s 0.821. M1's order is close to ρ's (τ=0.79, Spearman 0.90; screened 0.75, 0.85). We expected this, because M1 is scaled by total feature energy and not by null size. It gives no ranking that differs from SING's.

9 Discussion

Within a model, AS is a useful probe of null content as seen through the translator. Used as a cross-model league table, however, it orders models as null energy alone would: ρ reproduces its order to the same τ. We cannot conclude from this that SING's ranking is wrong. The ranking cannot be told apart from an energy ranking, and none of the size corrections we tried gives a confident alternative. Energy-matched corrections either over-correct (AS_{fair}) or leave a positive τ ($\rho^{0.43}$), and model ranks shift with the null tolerance. Top-variance null directions are not more semantic per unit energy than random ones, which argues against reading energy as signal.

Recommendations.

1. Name the exact checkpoint and its measured top-1.
2. Report d_{null}, ρ_{null} and the null tolerance next to any null-space score, and check rank stability across tolerances.
3. Compare any cross-model score against the ranking by ρ alone, as a control in the sense of [5].
4. Flag translator conditioning when full-null and block-wise AS disagree (BiT).

5. Prefer within-model interventions to cross-architecture league tables.
6. Validate flatness or invariance criteria on a synthetic oracle before using them to accept or reject scores.

Limitations. E1 does not cleanly separate energy from dimension. The claim CIs reflect image resampling only. Several claims rely on proxies (C1/C2/C11), and C13 is untestable. The E9 holdout and the revised flatness rule are post hoc. In the holdout, M1 is given the concept score that defines the plant, and the AS-family scores are not. The translator-fidelity check uses 1000 images. We did not retrain translators or evaluate a true DINO model [1]. Nor did we extend the audit to other null-space scores [2, 13, 16], or to information-theoretic leakage measures for concept models [9], which target a different notion of leakage.

10 Conclusion

Using the released translators, we reproduce SING's 13-model ranking, and we find that null energy ρ alone reproduces it equally well. Size-corrected scores produce orders that differ from SING's, but none reverses it with confidence, and the energy-matched correction over-corrects. We report all pre-registered experiments, including the two KILLs (E8, E9) and the flaw in their shared flatness criterion. Cross-model null-space comparisons should report ρ and an energy-only baseline next to the score.

Reproducibility. Code, aggregated results, pinned environment, the image-subset list and a one-command make reproduce are at https://github.com/sudeshgm/ic014-sing-null-dimension. ImageNet-derived features are not redistributed; checksums and the extraction scripts are provided.

References

[1] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pages 9650–9660, 2021.

[2] Matthew Cook, Alina Zare, and Paul Gader. Outlier detection through null space analysis of neural networks. arXiv preprint arXiv:2007.01263, 2020.

[3] MohammadReza Davari, Stefan Horoi, Amine Natik, Guillaume Lajoie, Guy Wolf, and Eugene Belilovsky. Reliability of CKA as a similarity measure in deep learning. In International Conference on Learning Representations (ICLR), 2023.

[4] Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. Transactions of the Association for Computational Linguistics, 9:160–175, 2021.

[5] John Hewitt and Percy Liang. Designing and interpreting probes with control tasks. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 2733–2743, 2019.

[6] Daksh Idnani, Vivek Madan, Naman Goyal, David J. Schwab, and Shanmukha Ramakrishna Vedantam. Don't forget the nullspace! Nullspace occupancy as a mechanism for out of distribution failure. In International Conference on Learning Representations (ICLR), 2023. OpenReview id 39z0zPZ0AvB.

[7] Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (BiT): General visual representation learning. In European Conference on Computer Vision (ECCV), pages 491–507, 2020.

[8] Xiang Li and Kevin M. Short. Null space properties of neural networks with applications to image steganography. arXiv preprint arXiv:2401.10262, 2024.

[9] Mikael Makonnen, Moritz Vandenhirtz, Sonia Laguna, and Julia E. Vogt. Measuring leakage in concept-based methods: An information theoretic approach. arXiv preprint arXiv:2504.09459, 2025.

[10] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. DINOv2: Learning robust visual features without supervision. Transactions on Machine Learning Research, 2024. arXiv:2304.07193.

[11] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In International Conference on Machine Learning (ICML), pages 8748–8763, 2021.

[12] Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL), pages 7237–7256, 2020.

[13] Hossein Rezaei and Mohammad Sabokrou. Quantifying overfitting: Evaluating neural network performance through analysis of null space. arXiv preprint arXiv:2305.19424, 2023.

[14] Mannat Singh, Laura Gustafson, Aaron Adcock, Vinicius de Freitas Reis, Bugra Gedik, Raj Prateek Kosaraju, Dhruv Mahajan, Ross Girshick, Piotr Dollár, and Laurens van der Maaten. Revisiting weakly supervised pre-training of visual perception models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 804–814, 2022. arXiv:2201.08371.

[15] Hugo Touvron, Matthieu Cord, and Hervé Jégou. DeiT III: Revenge of the ViT. In European Conference on Computer Vision (ECCV), pages 516–533, 2022.

[16] Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. ViM: Out-of-distribution with virtual-logit matching. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 4921–4930, 2022.

[17] Harel Yadid, Meir Yossef Levi, Roy Betser, and Guy Gilboa. Make it SING: Analyzing semantic invariants in classifiers. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 9911–9920, 2026. arXiv:2603.14610 (v2 supplement cited for Supp. Table 3 and Supp. Fig. 12b).

A Additional numerical detail

Seeds. $\mathrm{AS}_{\mathrm{rand}}$ family A: 10000+r, r<20. Family B: 50000+r. Family C sub-subspaces: 30000+j, controls 60000+j. Exp 1 subspaces: 20 seeds per d. E3 plants: seed 0 (log-uniform α), bootstrap 10000× seed 1. Model bootstrap: 2000× seed 0. Claim bootstrap: 1000× seed 0. E1 bootstraps: 2000× seed 0. E9 and holdout α: seed 1. Flatness sub-null bases: 20000+j. PC-band random draws: 40000+j.

Exp 1 full-null anchors. Mean |AS| at full null: ResNet50 1.682°, ResNeXt101 1.999°, BiT 0.556°, DINOv2-L 1.499°; at d=24: 0.166, 0.175, 9.30, 0.143.

Model	d_{null}	ρ_{null}	$\mathrm{AS}_{\mathrm{SING}}$	fair A	fair B	fair C
VGG16	3096	0.350	1.088	0.708	0.867	1.324
VGG19	3096	0.339	1.256	0.716	1.087	1.347
DenseNet121*	27	1.8e-8	0.00025	0.152	0.671	0.711
ResNet50	1048	0.146	1.676	0.855	0.989	1.142
DinoViT	24	0.0054	0.294	1.632	1.220	1.203
EffNet-B0	280	0.130	0.443	0.889	1.267	1.436
BiT-R50x1*	1048	0.046	0.557	0.042	1.142	135.6
ResNeXt101	1048	0.451	1.999	0.707	0.591	1.038
ConvNeXt-B	24	0.0135	0.080	0.974	0.961	0.972
Swin-L	536	0.274	1.019	0.829	1.130	1.075
DINOv2-L	1048	0.322	1.499	0.712	0.961	0.997
DeiT3-L	24	0.348	5.048	1.065	0.776	0.786
EVA02-L	24	0.0089	0.417	2.612	1.306	1.329

Table 5: Per-model class-text scores on the 10k subset at tol 10^{-5} (r2/results/fix2_models.csv). *Excluded by the degeneracy screen. Family B's low-σ span reaches its cap for ResNeXt and DeiT3.