Cross-Model Null-Space Scores Can Rank Models by Energy Alone: A Sanity Check, Three Lessons and a SING Case Study

Anonymous authors
Paper under double-blind review

Abstract

Scores that compare models through the null space of their linear heads, or through residual feature energy, can rank models by energy and a constant offset alone, without reading any content. We give a cheap, partly pre-registered sanity check for this. It centres the features, compares the score with content-free surrogates matched in null energy, and reports how the result changes with the head. We work it through on SING, which ranks 13 ImageNet classifiers by null-space leakage. The uncentred null-energy fraction ρ reproduces SING's order as well as SING's own score (Kendall τ=0.82 for both; paired difference $[-0.36, 0.29]$). Post hoc, one constant null vector per model makes up 92% and 85% of ρ for DeiT3-L and ResNet50 and produces 83% of their AS. Centred ρ gives τ=0.56, and content-free surrogates at the centred energy still give 0.67. Refitting the head on one backbone moves ρ from 0.014 to 0.930. With 13 models the intervals are wide, we ran no equivalence test, and two pre-registered direct measures of null content failed. Energy suffices to reproduce the order. We do not show that it causes it. We release the check as a script.

1 Introduction

A linear classifier W on features $f \in \mathbb{R}^m$ ignores every component of f in its null space $\ker W$. Several recent methods read that null space, or the residual part of a feature, to say something about a model. SING (Yadid et al., 2026) reads class-relevant content there as "leakage": information the head could have used but did not. To measure it, SING maps features into CLIP space (Radford et al., 2021) with a learned linear translator, removes the null component, and records how far the translated feature turns relative to the class text (the absolute shift, AS). It uses AS and an IS/AS ratio to rank 13 ImageNet models and reports that a model labelled "DinoViT" (Caron et al., 2021) leaks least.

Beyond SING, null spaces appear in work on out-of-distribution failure (Idnani et al., 2023), outlier and OOD detection (Wang et al., 2022; Cook et al., 2020; Zöngür et al., 2025; Sun et al., 2022; Ben Ammar et al., 2024), failure prediction (Shin & Kim, 2026), overfitting (Rezaei & Sabokrou, 2023) and information hiding (Li & Short, 2024). Invariance-based adversarial examples show that class information can sit in directions a classifier ignores (Jacobsen et al., 2019). In NLP, nullspace projection and closed-form erasure remove a property from representations (Ravfogel et al., 2020; Elazar et al., 2021; Belrose et al., 2023). Linear maps between a vision model and CLIP, the kind of translator SING relies on, have been studied by Moayeri et al. (2023). Probing work has also shown that readouts need controls (Hewitt & Liang, 2019), and similarity scores are known to be dominated by high-variance directions (Davari et al., 2023).

Across architectures, the null dimension d_{null} and the null energy fraction

$$\rho = \mathbb{E}\|\Pi f\|^2 / \mathbb{E}\|f\|^2, \qquad \Pi = V_n V_n^\top,$$

vary by orders of magnitude (Table 12). Removing more energy should move a readout further whether or not that energy is semantic. A cross-model comparison of null "semantics" can then be tied to energy, and a score can order models without reading any meaning. We turn that concern into a check that anyone can

run on their own score, and work it through on SING as a case study. SING is a natural test case because its code and translators are public and its cross-model claim is explicit. The lessons are about the measurement, not about SING alone.

Contributions.

1. **A sanity check** (§3). Before reading a cross-model null-space or residual-energy score as a comparison of content: (i) centre the features and split ρ into a constant offset, a between-class part and a within-class part; (ii) compare the score with content-free surrogates matched in null energy; (iii) report how the result changes with the head. Each step runs on CPU from cached features and leaves the logits unchanged. A practitioner checklist (§3.1) and a script are provided.
2. **Three lessons** (§5). The constant null offset can dominate: post hoc, it is 92% of ρ for DeiT3-L and 85% for ResNet50, and the offset alone produces 83% of their AS. The result depends on the head: on one ResNet50 backbone, ρ is 0.014 with a nearest-class-mean head, 0.930 with shrinkage LDA and 0.146 with the released head. And criteria for a content score can contradict each other: no score of the null and row energies can pass invariance (B), energy (C) and content (M) calibration criteria together.
3. **A case study and two useful negatives** (§4, §6). On SING's 13 models, ρ alone reproduces SING's order as well as SING's score, and content-free surrogates at each model's energy reproduce it too. Two pre-registered attempts to measure null content directly did not succeed: controlled background edits are matched by a pixel-permuted artefact control (ARTEFACT on 4 of 4 models), and a semantic null share defined from a stated target fails two of its eight gates (NOT VALIDATED). Both show where direct measurement breaks and what a future measure must survive.

What we do not claim. We do not conclude that SING's ranking is wrong, or that AS carries no semantic signal: AS responds to planted concepts at fixed energy. Our claim is narrower. A cross-model AS comparison cannot be read as a comparison of null semantics without an energy baseline, because no control we have separates energy from content. With 13 models every cross-model interval is wide, and "indistinguishable" below means that the paired interval covers zero; we ran no equivalence test. The offset analysis behind step (i) was run after the main experiments and is labelled post hoc wherever it is used. Every pre-registered outcome, including the failures, is listed in Appendix A, and the full analyses are in Appendix B.

2 Setup

SING's score. Let $T(f) = Af + b$ be SING's released linear translator into CLIP space, W the model's head and V_n an orthonormal basis of $\ker W$ from the SVD of W (absolute singular-value tolerance 10^{-5} unless stated). For a text direction t, the per-image absolute shift for a removed component r is $|\theta(T(f), t) - \theta(T(f - r), t)|$. $\mathrm{AS}_{\mathrm{SING}}$ is its mean over images with $r = \Pi f$ (full null removal) and the class text (the normalised mean of SING's six prompts) as t. We use SING's released code (commit `e47b37d`) and all 13 released translators on a fixed 10k-image ImageNet-val subset (10 images per class, all 1000 classes). SING's own model comparison also uses 10k features over the 1000 classes; its 16-class, 2000-image subset is the translator-validation set, which we do not use. For the class-level claims we add 200 images (all 50 validation images of jellyfish, porcupine, Arabian camel and sports car).

Reference order and statistics. SING's order is the 13 IS/AS bars of its Supp. Fig. 12b, which we digitised. A lower ratio means more leakage. Agreement is Kendall τ_b between a leakage score and that order. Every correlation with SING's order in this paper uses this sign convention: positive means that more of the score goes with more leakage (a lower IS/AS ratio). Model-level uncertainty comes from 2000 bootstrap resamples of models (seed 0), with percentile and BCa intervals (Efron, 1987). Paired comparisons of two scores use the same resamples. With n=13 these intervals are wide and often reach 1, so we read them as coarse. Sets: *all 13*; *E12*, the 12 models with $\rho \geq 0.005$ (all but DenseNet121, whose ρ=1.8×10^{-8}); and *S11*, a screened set declared in the second pre-registration that also drops BiT. The screen removes models with $\rho < 10^{-4}$ or with a retained row-space direction of singular value $\sigma < 10^{-3}$ that holds more than 5%

of the feature energy. BiT has such a direction (σ=8.9×10^{-4}, 26% of the energy). ResNet50 has one just under the threshold ($\sigma < 10^{-3}$, 4.4% of the energy): at tolerance 10^{-4} that direction joins the null space, ρ rises from 0.146 to 0.190 and $\mathrm{AS}_{\mathrm{SING}}$ falls from 1.68° to 1.33°.

Pre-registration. The main experiments were declared in writing before their numbers were computed. Two addenda were written after some results were known, and each lists the values known when it was written. Results marked *post hoc* or *exploratory* were added after seeing data. The ledger, the order in which the pre-registrations and results were pushed, and the dates are in Appendix A; the chronology of the analyses is in Appendix B.

3 The sanity check

The check applies to any score s that is computed per model from features f, a head W and, optionally, a translator T, and that is then compared across models, against a reference order or a downstream quantity. It asks whether the cross-model pattern of s could arise from null energy and a constant offset, with no image or class content at all? Every step changes only the null part Πf, so the logits stay fixed.

Step 1: centre and decompose (post hoc in our study). Write $z_i = V_n^\top f_i$ for the null coordinates, $\bar{z}$ for their mean over images and m_c for the class means. Then ρ splits exactly as $\rho = \rho_{\mathrm{off}} + \rho_{\mathrm{btw}} + \rho_{\mathrm{wit}}$, the energies of the constant per-model null mean $\bar{z}$, the centred class means and the within-class residuals, each divided by $\mathbb{E}\|f\|^2$. Report centred and uncentred ρ and the offset share. Recompute s twice, with every image's null part replaced by $\bar{z}$ (offset only) and with $\bar{z}$ removed. If the offset alone produces much of s, the score is reading one constant vector per model, which carries no image or class content. We added this step after the main experiments (§4.1).

Step 2: compare with content-free surrogates of matched energy. Replace each model's null coordinates with surrogates that carry no image-specific content but keep its energy: a zero-mean Gaussian with the covariance of the centred null coordinates, rescaled to the centred null energy, and the centred null coordinates permuted across images. Recompute s and its agreement with the reference. Report the paired difference between the real and the surrogate score on the same model resamples, not only the two point values. If the surrogate reproduces the cross-model pattern, that pattern cannot be read as a difference in null content without further controls. Report which surrogate was used, since the result depends on it (§4.2). Surrogates at each model's full energy were part of our pre-registered tests; the centred versions are post hoc.

Step 3: report head dependence. Refit the head on the same backbone with at least one standard alternative, for example nearest class mean (NCM) or shrinkage LDA, and recompute ρ and s. Report each head's accuracy on held-out images. If s moves by orders of magnitude, it is as much a property of the head as of the backbone, and a cross-model comparison must fix or report the head (§4.3).

Optional: equal energy and an energy sweep. Rescale every model's null part to the same energy and sweep it through the observed range. Run the same statistics on positive controls (ρ, an AS-type score, and the score with any built-in normalisation frozen) before trusting a negative result. In our study a pre-registered decision rule of this kind missed SING's own AS, so we report its statistics descriptively (Appendix B.3).

Cost. Steps 1 and 3 need only the cached features, the head and its bias. Step 2 needs one pass of the scoring code per surrogate draw. All of it runs on CPU.

3.1 Practitioner checklist

Before comparing a null-space or residual-energy score across models:

- Report d_{null}, the null tolerance, uncentred and centred ρ, and the offset share ρ_{off}/ρ.
- Recompute the score with the null part replaced by its mean (offset only) and with the mean removed.
- Compare the cross-model ranking with the ranking by ρ alone and with content-free surrogates of matched (centred) energy. Name the surrogate and report the paired difference.
- Name the head and its accuracy, recompute with a second head, and check rank stability across null tolerances.
- If the score uses a translator, repeat the comparison with a second, independently fit one, and check its fidelity against a shuffled floor.
- Before calibrating a content estimator on synthetic worlds, state the target, derive the criteria from it, and check on an oracle that the criteria can be met together.
- With few models, say "not separated" when a paired interval covers zero; claim equivalence only after an equivalence test.

4 Case study: SING's cross-model ranking

Reproduction and the ρ baseline. AS_{SING} agrees with SING's order at τ=0.82 (95% CI $[0.56, 1.00]$); our IS/|AS| ratio against SING's IS/AS ratio gives τ=0.744 $[0.33, 1.00]$ (Appendix B.1 discusses the remaining gap). Ranking models by ρ alone gives τ=0.82 $[0.56, 1.00]$, the same as AS_{SING} (Fig. 1, Table 1). The paired difference $\tau(\rho) - \tau(\text{AS}_{\text{SING}})$ is 0.00 with 95% CI $[-0.36, 0.29]$, and both agreements are far from chance (permutation p=5×10^{-5}). Each keeps a partial association with SING's order given the other (partial Kendall τ=0.61 both ways), so the data cannot tell the two predictors apart, and ρ does not make AS_{SING} redundant. Within a model, AS grows with removed energy roughly as ρ^a with a=0.431, close to the first-order value 0.5 (Appendix B.1).

4.1 Step 1: the null offset (post hoc)

The offset is 92% of ρ for DeiT3-L (ρ=0.348, centred 0.029), 85% for ResNet50 (0.146, centred 0.021) and at most 9% for nine of the other models (Appendix B.1). Centred ρ agrees less with SING's order: τ=0.56 $[0.11, 0.89]$ on all 13, against 0.82 uncentred (paired difference -0.26, percentile $[-0.58, 0.00]$). The offset carries no image or class content, yet it moves AS. AS with the null part replaced by its mean alone is 4.18° of 5.05° for DeiT3-L and 1.38° of 1.68° for ResNet50 (83% and 83%; AS is an angle, so shares do not add), against 5–25% for nine other models. For these two models, most of SING's AS comes from one constant null vector per model, and cross-model AS differences cannot be read as differences in null semantics. These analyses were run after the main experiments and change no pre-registered verdict.

4.2 Step 2: content-free surrogates

Content-free null energy reproduces the order. Replacing each model's null coordinates with a draw from $\mathcal{N}(\mu, \Sigma)$ at its own energy, which keeps every logit and carries no image-specific content, gives AS_{surr} with τ=0.69 $[0.39, 0.92]$ against SING. Across five pre-registered content-free surrogates the point τ runs from 0.49 to 0.72, so the choice of surrogate matters. The result does not rest on the offset. Post hoc, zero-mean Gaussian surrogates at each model's centred null energy give τ=0.67 $[0.38, 0.92]$ (paired difference from the full-energy Gaussian surrogate, 0.69: -0.03 $[-0.31, 0.31]$), and centred null coordinates permuted across images give 0.67. On three models a pre-registered energy scan confirms the path: at no planted content, AS rises with surrogate null energy (Spearman 1; log-log slopes 0.38–0.69, all CIs far from 0).

The surrogates do not settle the question, however. The content excess $X = \text{AS}_{\text{SING}}/\text{AS}_{\text{surr}}$ also tracks the order (τ=0.54 $[0.14, 0.83]$), as does $\text{AS}_{\text{SING}} - \text{AS}_{\text{perm}}$ (0.62), the outcome the pre-registration calls "cannot apportion". And AS does respond to null content at fixed energy: a planted concept raises it by $\times$1.35–1.51 at α=0.3 (ρ_t=0.2) and by $\times$1.14–1.58 at each model's own ρ. Step 2 therefore shows that energy is sufficient to reproduce SING's order, not that it is the operative cause.

Check step	Score	τ with SING's order (all 13)	Status
–	AS_{SING} (SING's score)	0.82 [0.56, 1.00]	pre-registered
–	ρ, uncentred	0.82 [0.56, 1.00]	pre-registered
1	ρ, centred	0.56 [0.11, 0.89]	post hoc
1	AS, offset only	0.56	post hoc
1	AS, offset removed	0.74	post hoc
2	AS, Gaussian surrogate at full energy (AS_{surr})	0.69 [0.39, 0.92]	pre-registered
2	AS, five content-free surrogates	0.49–0.72	pre-registered
2	AS, zero-mean Gaussian at centred energy	0.67 [0.38, 0.92]	post hoc
2	AS, centred null permuted across images	0.67	post hoc
2	content excess $X = AS_{SING}/AS_{surr}$	0.54 [0.14, 0.83]	pre-registered

Table 1: The sanity check on SING's 13 models (Kendall τ, percentile 95% CI over 2000 model resamples where given). Content-free scores reproduce the order about as well as SING's score, and so does the content excess, so the order cannot be apportioned between energy and content. Step 3 (head dependence) is in §4.3.




Figure 1: Ranks (1 = least leakage, ⋆ marks rank 1) under SING Supp. Fig. 12b, ρ alone, AS_{SING} and the size-corrected AS_{fair} (family A, §B.6).

4.3 Step 3: the head

Refitting the head on the same backbone moves ρ and the target-first null share θ_{sem} of §6 by orders of magnitude (ResNet50: released head 0.146 and 0.013, nearest class mean 0.014 and 2.1×10^{-4}, shrinkage LDA 0.930 and 0.930; Table 31). The refit heads are not matched in accuracy: on the same held-out images they are 5–13 points less accurate than the released heads (top-1 0.635–0.779 against 0.762, 0.860 and 0.828 for ResNet50, DINOv2-L and ResNeXt101; the released values were computed post hoc from the cached features and released biases). A null-space leakage number is thus as much a property of the head as of the backbone. The head swap is exploratory and covers three backbones.

4.4 Further analyses in brief

Below we summarise the parts of the full case study (Appendix B) that bear on the check.

- *Equal energy depends on the translator* (Appendix B.2.1, B.2.4). AS per unit null energy loses the agreement with SING's released translators ($\tau = -0.03$ and 0.09 on E12 and S11) and keeps it with retrained ridge translators (0.61 and 0.75). We do not know which translator better reflects null semantics, so neither result decides between the readings.

- *Class-mean permutation* (Appendix B.2.3). Shuffling class means across classes, which preserves null energy exactly, keeps the agreement (τ=0.64 on E12), which leans toward energy, but given ρ the class-aligned part has the stronger partial association (0.81 against 0.22). Our pre-registration allows no stronger claim than these raw numbers.
- *Other null-space scores* (Appendix B.3). A pre-registered energy rule flags none of ViM, ActSub, CORE and conditional $\mathcal{V}$-information as energy-driven (k=0 of 4). Post hoc positive controls show that it also misses SING's AS (released: τ_{EQ}=0.39 and 0.45, median R_B=0.26, mixed) and ρ itself, so the count says nothing about whether the confound is specific to SING.
- *Checkpoint and size correction* (Appendix B.5, B.6). SING's "DinoViT" translator matches a supervised timm ViT-L/16 checkpoint. Size-corrected scores change the order, but none reverses it with confidence.

5 Lessons

Lesson 1: the mean offset can dominate. An uncentred energy share counts the constant mean of the null coordinates as signal. For two of 13 models that mean is most of ρ and produces most of AS (§4.1). Any score built on uncentred null coordinates, or on class means that include the global mean, inherits it. Centring is free and should be reported next to the uncentred value. The offset is not the whole story: after centring, content-free surrogates still reproduce the order (§4.2).

Lesson 2: the readout is part of the measurement. The null space is defined by the head, and the AS readout also passes through a translator. Changing the head on one backbone moves ρ by orders of magnitude (§4.3), and changing the translator flips the equal-energy result (§4.4). A cross-model leakage number should name both, and its conclusion should be checked with a second one.

Lesson 3: calibration criteria can be jointly unsatisfiable. We calibrated eight estimators in semi-synthetic worlds with known null content and none met all three criteria (Appendix B.2.5). As an external reader pointed out, none could. Take any class-level score that depends on the data only through the class-mean null energy, the residual null energy, the row-space energy and a scale-free composition of the null class means. Invariance to rescaling the null part (B) leaves a dependence on the ratio of the two null energies only. World C moves only this ratio, so flatness there (C) removes the dependence over its range. World M also moves only this ratio, so a score that passes B and C cannot rise in world M (M). No score passes all three, not even an oracle that knows the true content. World C also fixes content per unit of *total* energy, so against the row space the class-mean null energy rises $\times$1.81. The calibration result therefore shows that our criteria were inconsistent, not that null content cannot be measured. More generally, state the target first, derive the criteria from it, and check them on an oracle before using them to accept or reject scores.

6 Two pre-registered direct content measures

Interventions on features could not separate energy from content, so we tried to measure null content directly, twice, each time with a pre-registration pushed before any real-model result (details in Appendix B.4 and I). Neither yields a validated content measure. We report them because each failure is informative.

Controlled background edits (ARTEFACT). On the IN-9 Backgrounds Challenge (Xiao et al., 2021), the edit is the null-space difference between a foreground on another class's background and the same foreground on a background of its own class, seen under independent nuisance views. On four models the edit is reproducible (H1 on 4 of 4) and aligned with the inserted class's text (T2 0.0010–0.0017). A control that permutes the background pixels, keeping their colour histogram, is aligned as strongly (0.0009–0.0016), so H2 is ARTEFACT on 4 of 4 and the family statement is NOT SUPPORTED. The registered bootstrap turned out to be invalid for these U-statistics. A post hoc correction changes no verdict. Low-level image statistics can thus align with class text in the null space as strongly as a semantic edit, so any edit-based content test needs an artefact control.

A target stated first (NOT VALIDATED). We fixed the target before the score: the share of a model's text-predictable class signal that lies in $\ker W$, estimated by θ_{sem}, which ignores the null offset and is invariant to global scale and rotation. 6 of its 8 gates pass. The noise gate fails (too few estimable rows, and two small slopes with CIs that exclude 0), and the derangement gate fails on one of 6 cells. θ_{sem} is therefore NOT VALIDATED, and its agreement with SING's order (τ=0.64 [0.19, 0.93] on E12) is reported but not read. Descriptively, the part of the null class means that the row space predicts tracks SING's order (τ=0.76) and the remainder does not (0.21). Given content-free energy, the partial correlation of θ_{sem} with the order is -0.41 $[-0.85, 0.18]$. So removing the offset and the scale is not enough, and a content score must also survive noise and derangement gates derived from its target.

7 Related work

Similar negative controls appear elsewhere: saliency maps that survive randomisation fail as explanations (Adebayo et al., 2018), attention weights need random baselines (Wiegreffe & Pinter, 2019), and emergent abilities can be an artefact of the metric (Schaeffer et al., 2023). Our surrogates are the null-space analogue of the surrogate-data test (Theiler et al., 1992). Cui et al. (2022) regress a confound out of RSA and CKA, and Gröger et al. (2026) find that representational similarity is confounded by model scale and that, after permutation calibration, global convergence largely disappears while local similarity survives, a mixed picture of the same shape as ours. In OOD detection, feature norms confound Mahalanobis scores across models (Müller & Hein, 2025; Park et al., 2023). Recent detectors also score the residual or null part of a feature: k-NNuSA combines nearest-neighbour distance with the residual against the principal subspace (Nguyen et al., 2024), D-KNN separates principal and residual subspaces and recalibrates the residual signal (Peng et al., 2026), and MaRS scores autoencoder residuals with a Mahalanobis distance instead of an ℓ_2 norm (Di Salvo et al., 2026). We did not audit these scores for an energy confound. Wu et al. (2026) audit concept steering across 17 language models and find that an apparent scaling trend comes from raw activation units, the readout metric and the operating point, a measurement confound of the same kind as the one we study. Makelov et al. (2024) show that subspace patching can act through a dormant pathway. Their illusion and our energy path both arise when a component the model ignores still moves a readout. ActSub (Zöngür et al., 2025) and Jacobsen et al. (2019) find useful information in directions a classifier ignores, consistent with informative null content; cross-model scores of it still need an energy-only baseline. Linear erasure (Ravfogel et al., 2020; Belrose et al., 2023) is a stricter notion than projecting out $\ker W$. Linear maps between representations go back to model stitching (Lenc & Vedaldi, 2015; Bansal et al., 2021), and linear translators into CLIP (Moayeri et al., 2023) differ in fidelity across models. XCC is a cross-fitted centred kernel alignment (Cortes et al., 2012; Kornblith et al., 2019). SO_{null} differs from class-separation scores (Kornblith et al., 2021; Papyan et al., 2020). It measures how class structure is arranged relative to the class texts, not how much there is.

8 Discussion

What the SING score is still useful for. SING's code reproduces its 13-model ranking on our pipeline, and its translator view gives readable alignments with class text. Within one model and one head, where the null space is fixed, AS responds to planted concepts at fixed energy, so it carries a content signal there. We did not test within-model comparisons for an energy effect beyond the class-level claims of Appendix C.6. The issue we raise concerns comparisons across models, whose null energies and offsets differ by orders of magnitude. For those, AS needs the energy baseline of §3 next to it. The same holds, as far as we can tell, for any score that reads the null or residual part of a feature across models. We did not show that the confound changes a published conclusion other than the cross-model reading of SING's ranking.

Why does ρ vary? Neural collapse (Papyan et al., 2020) offers a candidate mechanism. Late in training, features concentrate near class means aligned with the classifier rows, so the energy outside the row space shrinks. Models trained further into that regime, or with heads fit differently, would have smaller ρ and hence smaller AS. We have not tested this.

Limitations. The main limits are plain. There are only 13 models, so every cross-model CI is wide, and we ran no equivalence test: "indistinguishable" means that a paired interval covers zero, which also reflects low power. Both direct content measures failed, so energy is shown to suffice, not shown to be the cause. The offset analysis and the centred surrogates are post hoc, and the head swap is exploratory on three backbones. We studied one method on one dataset in depth. SING's order is digitised from a figure. Our retrained translators are ridge maps chosen by us. SING's training recipe may differ, and the equal-energy result depends on this choice. The energy-scan part of the leak-free test covers three models with d_{null}=1048, and the planted strengths stop at α=0.3, below the energy-equivalent strength at each model's own ρ (at ρ_t=0.01, post hoc, content moves AS more than energy does on 2 of the three models). The calibration worlds are semi-synthetic, built on three bases by rescaling class-mean and residual null content; they test whether an estimator can separate the two, not whether real models differ in content. The organisation score's thresholds were set after scratch runs on five models (SO) and three (XCC), two of its bars sit at the scratch values, and its world-C gate was testable on one base only, over ρ=0.005–0.013. The geometric account is consistent with two held-out models and with synthetic data that builds in its gain law; on the 13 models it is exploratory. The true DINO comparison uses our ridge translators, since SING released none for these models. The energy law does not cleanly separate energy from dimension, and its pre-registered flatness part fails. The class-claim CIs reflect image resampling only (class resampling for C6), several claims rely on proxies, and C13 is untestable. The tests of other published scores (Appendix B.3) fit every score on 5 validation images per class instead of the training set, so the four scores are surrogates of the published ones. They use a restricted probe family for $\mathcal{V}$-information and cannot run CANARY's per-class neighbour rule (Shin & Kim, 2026). Their energy rule misses three of its five post hoc positive controls (it flags only SING's IS), and their content tests cannot separate a loss of image-level information from estimator noise. We did not evaluate information-theoretic leakage measures for concept models (Makonnen et al., 2025), which target a different notion of leakage. The background-edit test checks a different construct from SING's, and its corrected CIs were not validated for coverage. The semantic null share's world C$'$ was low-powered by design, and its descriptives (shadow, self-duality, head swap) are exploratory, on 13 models or three bases.

9 Conclusion

Cross-model null-space and residual-energy scores can order models by null energy and a constant offset, with no image or class content involved. On SING's 13 models, the uncentred null-energy fraction reproduces SING's order as well as SING's score; post hoc, a constant offset dominates two models, centring lowers the agreement to τ=0.56, and content-free surrogates at the centred energy still give 0.67. The same backbone gives very different ρ under different heads, and our own calibration criteria could not be met together. Two pre-registered direct content measures did not validate. None of this shows that SING's ranking is wrong. It shows that a cross-model comparison of null semantics needs a baseline: centre the features, compare with content-free surrogates of matched energy, and report the head. The check is cheap, and the script and checklist are meant to make it routine.

Reproducibility. The supplementary material contains the code, pre-registrations, aggregated results and a one-command `make reproduce` that regenerates every table, figure and number in this paper from committed aggregates, and the sanity-check script `sanity_check/null_sanity_check.py`, which runs steps 1 and 2 of §3 on any set of feature files. For review, we provide the code as an anonymised archive, and a public link will be added on acceptance. ImageNet-derived features are not redistributed; checksums, the image list and the extraction scripts are included. A full rerun from features takes about 2 h on 8 CPU cores; feature extraction needs a GPU and ImageNet (Appendix J).

References

Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. In *Advances in Neural Information Processing Systems*, pp. 9525–9536, 2018.

Yamini Bansal, Preetum Nakkiran, and Boaz Barak. Revisiting model stitching to compare neural representations. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. LEACE: Perfect linear concept erasure in closed form. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. arXiv:2306.03819.

Mouïn Ben Ammar, Nacim Belkhir, Sebastian Popescu, Antoine Manzanera, and Gianni Franchi. NECO: NEural collapse based out-of-distribution detection. In *International Conference on Learning Representations (ICLR)*, 2024.

Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 9650–9660, 2021.

Matthew Cook, Alina Zare, and Paul Gader. Outlier detection through null space analysis of neural networks. *arXiv preprint arXiv:2007.01263*, 2020.

Corinna Cortes, Mehryar Mohri, and Afshin Rostamizadeh. Algorithms for learning kernels based on centered alignment. *Journal of Machine Learning Research*, 13(28):795–828, 2012.

Tianyu Cui, Yogesh Kumar, Pekka Marttinen, and Samuel Kaski. Deconfounded representation similarity for comparison of neural networks. In *Advances in Neural Information Processing Systems*, 2022.

MohammadReza Davari, Stefan Horoi, Amine Natik, Guillaume Lajoie, Guy Wolf, and Eugene Belilovsky. Reliability of CKA as a similarity measure in deep learning. In *International Conference on Learning Representations (ICLR)*, 2023.

Francesco Di Salvo, Sebastian Doerrich, and Christian Ledig. MaRS: Robust out-of-distribution detection via Mahalanobis residual scoring. *arXiv preprint arXiv:2606.22649*, 2026.

Jörn Diedrichsen and Nikolaus Kriegeskorte. Representational models: A common framework for understanding encoding, pattern-component, and representational-similarity analysis. *PLoS Computational Biology*, 13(4):e1005508, 2017. doi: 10.1371/journal.pcbi.1005508.

Jörn Diedrichsen, Serge Provost, and Hossein Zareamoghaddam. On the distribution of cross-validated Mahalanobis distances. *arXiv preprint arXiv:1607.01371*, 2016.

Jörn Diedrichsen, Atsushi Yokoi, and Spencer A. Arbuckle. Pattern component modeling: A flexible approach for understanding the representational structure of brain activity patterns. *NeuroImage*, 180:119–133, 2018. doi: 10.1016/j.neuroimage.2017.08.051.

Bradley Efron. Better bootstrap confidence intervals. *Journal of the American Statistical Association*, 82 (397):171–185, 1987.

Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175, 2021.

Yasunori Fujikoshi. A test for additional information in canonical correlation analysis. *Annals of the Institute of Statistical Mathematics*, 34:523–530, 1982. doi: 10.1007/BF02481050.

Fabian Gröger, Shuo Wen, and Maria Brbić. Revisiting the platonic representation hypothesis: An Aristotelian view. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pp. 36724–36766, 2026.

Trevor Hastie, Robert Tibshirani, and Jerome Friedman. *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*. Springer, 2nd edition, 2009.

John Hewitt and Percy Liang. Designing and interpreting probes with control tasks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 2733–2743, 2019.

John Hewitt, Kawin Ethayarajh, Percy Liang, and Christopher D. Manning. Conditional probing: Measuring usable information beyond a baseline. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2021. arXiv:2109.09234.

Daksh Idnani, Vivek Madan, Naman Goyal, David J. Schwab, and Shanmukha Ramakrishna Vedantam. Don't forget the nullspace! Nullspace occupancy as a mechanism for out of distribution failure. In *International Conference on Learning Representations (ICLR)*, 2023. OpenReview id 39z0zPZ0AvB.

Jörn-Henrik Jacobsen, Jens Behrmann, Richard Zemel, and Matthias Bethge. Excessive invariance causes adversarial vulnerability. In *International Conference on Learning Representations (ICLR)*, 2019. arXiv:1811.00401.

Matthew T. Kaufman, Mark M. Churchland, Stephen I. Ryu, and Krishna V. Shenoy. Cortical activity in the null space: permitting preparation without movement. *Nature Neuroscience*, 17(3):440–448, 2014. doi: 10.1038/nn.3643.

Polina Kirichenko, Pavel Izmailov, and Andrew Gordon Wilson. Last layer re-training is sufficient for robustness to spurious correlations. In *International Conference on Learning Representations (ICLR)*, 2023. arXiv:2204.02937.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (BiT): General visual representation learning. In *European Conference on Computer Vision (ECCV)*, pp. 491–507, 2020.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3519–3529, 2019.

Simon Kornblith, Ting Chen, Honglak Lee, and Mohammad Norouzi. Why do better loss functions lead to less transferable features? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 34, 2021.

Nikolaus Kriegeskorte, Marieke Mur, and Peter Bandettini. Representational similarity analysis – connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008. doi: 10.3389/neuro.06.004.2008.

Karel Lenc and Andrea Vedaldi. Understanding image representations by measuring their equivariance and equivalence. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 991–999, 2015.

Xiang Li and Kevin M. Short. Null space properties of neural networks with applications to image steganography. *arXiv preprint arXiv:2401.10262*, 2024.

Aleksandar Makelov, Georg Lange, and Neel Nanda. Is this the subspace you are looking for? An interpretability illusion for subspace activation patching. In *International Conference on Learning Representations*, 2024.

Mikael Makonnen, Moritz Vandenhirtz, Sonia Laguna, and Julia E. Vogt. Measuring leakage in concept-based methods: An information theoretic approach. *arXiv preprint arXiv:2504.09459*, 2025.

Thomas Mensink, Jakob Verbeek, Florent Perronnin, and Gabriela Csurka. Distance-based image classification: Generalizing to new classes at near-zero cost. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(11):2624–2637, 2013. doi: 10.1109/TPAMI.2013.83.

Mazda Moayeri, Keivan Rezaei, Maziar Sanjabi, and Soheil Feizi. Text-to-concept (and back) via cross-model alignment. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202 of *PMLR*, 2023. arXiv:2305.06386.

Maximilian Müller and Matthias Hein. Mahalanobis++: Improving OOD detection via feature normalization. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 45151–45184. PMLR, 2025.

Trang Nguyen, Minh Nguyen Tong, Hung Manh Lu, and Bang Van Le. Out-of-distribution detection via nearest neighbors and null vectors on principal feature space. In *Proceedings of the 15th International Conference on Information and Communication Technology Convergence (ICTC)*, pp. 892–897, 2024. doi: 10.1109/ICTC62082.2024.10826743.

Hamed Nili, Cai Wingfield, Alexander Walther, Li Su, William Marslen-Wilson, and Nikolaus Kriegeskorte. A toolbox for representational similarity analysis. *PLoS Computational Biology*, 10(4):e1003553, 2014. doi: 10.1371/journal.pcbi.1003553.

Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. DINOv2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2024. arXiv:2304.07193.

Vardan Papyan, X. Y. Han, and David L. Donoho. Prevalence of neural collapse during the terminal phase of deep learning training. *Proceedings of the National Academy of Sciences*, 117(40):24652–24663, 2020. arXiv:2008.08186.

Jaewoo Park, Jacky Chen Long Chai, Jaeho Yoon, and Andrew Beng Jin Teoh. Understanding the feature norm for out-of-distribution detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.

Ningkang Peng, Xiaoqian Peng, Yuhao Zhang, Qianfeng Yu, Feng Xing, Peirong Ma, Xichen Yang, Yi Chen, Tingyu Lu, and Yanhui Gu. Breaking semantic hegemony: Decoupling principal and residual subspaces for generalized OOD detection. *arXiv preprint arXiv:2602.05360*, 2026.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning (ICML)*, pp. 8748–8763, 2021.

C. Radhakrishna Rao. Tests with discriminant functions in multivariate analysis. *Sankhyā*, 7(4):407–414, 1946.

C. Radhakrishna Rao. The utilization of multiple measurements in problems of biological classification. *Journal of the Royal Statistical Society, Series B*, 10(2):159–193, 1948. doi: 10.1111/j.2517-6161.1948.tb00008.x.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 7237–7256, 2020.

Hossein Rezaei and Mohammad Sabokrou. Quantifying overfitting: Evaluating neural network performance through analysis of null space. *arXiv preprint arXiv:2305.19424*, 2023.

Rylan Schaeffer, Brando Miranda, and Sanmi Koyejo. Are emergent abilities of large language models a mirage? In *Advances in Neural Information Processing Systems*, 2023.

Wonseok Shin and Songkuk Kim. A canary in the neural mine: Catching an image classifier's silent, confident failures. *arXiv preprint arXiv:2610.33063*, 2026.

Mannat Singh, Laura Gustafson, Aaron Adcock, Vinicius de Freitas Reis, Bugra Gedik, Raj Prateek Kosaraju, Dhruv Mahajan, Ross Girshick, Piotr Dollár, and Laurens van der Maaten. Revisiting weakly supervised pre-training of visual perception models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 804–814, 2022. arXiv:2201.08371.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, 2022.

James Theiler, Stephen Eubank, André Longtin, Bryan Galdrikian, and J. Doyne Farmer. Testing for nonlinearity in time series: The method of surrogate data. *Physica D: Nonlinear Phenomena*, 58(1–4): 77–94, 1992. doi: 10.1016/0167-2789(92)90102-S.

Hugo Touvron, Matthieu Cord, and Hervé Jégou. DeiT III: Revenge of the ViT. In *European Conference on Computer Vision (ECCV)*, pp. 516–533, 2022.

Alexander Walther, Hamed Nili, Naveed Ejaz, Arjen Alink, Nikolaus Kriegeskorte, and Jörn Diedrichsen. Reliability of dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, 137:188–200, 2016. doi: 10.1016/j.neuroimage.2015.12.012.

Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. ViM: Out-of-distribution with virtual-logit matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4921–4930, 2022.

Sarah Wiegreffe and Yuval Pinter. Attention is not not explanation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 11–20, 2019. doi: 10.18653/v1/D19-1002.

Yuqi Wu, Shengming Zhao, and Jie Chen. When is a steerable concept representation real? Measurement confounds in a cross-family audit of neuroscience parallels in LLMs. *arXiv preprint arXiv:2608.08159*, 2026.

Kai Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image backgrounds in object recognition. In *International Conference on Learning Representations (ICLR)*, 2021. arXiv:2006.09994.

Harel Yadid, Meir Yossef Levi, Roy Betser, and Guy Gilboa. Make it SING: Analyzing semantic invariants in classifiers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9911–9920, 2026. arXiv:2603.14610 (v2 supplement cited for Supp. Table 3 and Supp. Fig. 12b).

Jin Mo Yang, Hyung-Sin Kim, and Saewoong Bahk. CORE: Robust out-of-distribution detection via confidence and orthogonal residual scoring. *arXiv preprint arXiv:2603.18290*, 2026.

Barış Zöngür, Robin Hesse, and Stefan Roth. Activation subspaces for out-of-distribution detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. arXiv:2508.21695.

A Pre-registration ledger

Table 2 lists every pre-registered experiment and its outcome. E1 to E9 come from the original plan, R2 from the round-2 pre-registration and R3 from the round-3 one, each written after the previous round's results. Round 4 (R4, R4B and R4C, three files) is in Table 3; the addenda R4B and R4C were written after the R4 results, and each lists the values known when it was written. Round 5 (`PREREG_R5.md`) is in Table 4, round 6 (`PREREG_R6.md`) in Table 5, and rounds 7 and 8 (`r7/PREREG_R7.md`, `r8/PREREG_R8.md`) in Table 6. All times here are IST (UTC+5:30). The round-8 file gives its date, 2026-11-03, in UTC+8; its commit was pushed at 20:56 IST that day (23:26 in UTC+8) and the results at 22:50 IST.

Order of events. The main experiments below were declared in writing before their numbers were computed, over eight rounds. Two round-4 addenda (R4B and R4C) were written after the first round-4 results were known, and R4C also after part of R4B and some exploratory geometry had run; each file lists the values known when it was written. The ledger is in Appendix A. Results marked *post hoc* or *exploratory* were added after seeing data. Because commit times are set by the committer, the repository alone cannot

prove the order of events. The hosting service's push history orders only commits that were pushed separately: the round-3 pre-registration was pushed in a push of its own, in one commit together with its plan (`ROUND3_PLAN.md`) and no code or results, about 68 minutes before the push that carried its results, the round-4 pre-registrations were pushed before theirs, the round-6 pre-registration was pushed together with its code and synthetic unit tests before any real-model result, the round-7 one before any real feature of that round existed, and the round-8 one with its code and tests before any real-model value of its score.

Exp.	Pre-declared criterion (short)	Outcome
Exp 0	null size correlates with SING IS/AS	GO rests on ρ (Spearman +0.94 with the leakage order); d_{null} alone +0.46, p=0.12
Exp 1	r=AS(1048)/AS(24) ≥ 3 on $\geq 3/4$; $\tau_{d=24} \leq 0.5$	GO ($r \approx 10$ on 3/4; BiT 0.06; τ=0.29)
E1	high/low $\geq 3\times$ at fixed d; $\leq 1.5\times$ across d at fixed ρ	MIXED (first part 4/4; second fails)
E2	$\tau(\text{AS}_{\text{fair}}, \text{SING}) \leq 0.5$ or headline claim reverses	PASS as registered; weakened in round 2
E3	$\tau(\text{AS}_{\text{fair}}, \text{planted}) \geq 0.8$, $\tau(\text{AS}_{\text{SING}}, \text{planted}) \leq 0.5$	not passed (0.109 vs 0.386); KILL not met
E8	NCP probe $\tau \geq 0.8$ and flat; KILL if $\tau < 0.6$	KILL (τ=−0.331; flat 0/4)
E9	20-candidate screen, DEV $\tau \geq 0.8$ and flat on $\geq 3/4$	KILL (best M1 τ=0.976, flat 0/4)
R2	KILL-R: drop "disagrees" unless fix 2 and D-weak pass	not fired; "differs from" allowed; D-weak screened at the threshold (5/8)
R2	D-strong: τ CI < 0 under $\geq 5/8$ normalisers	FAIL (0/8 all 13; 1/8 screened)
R2	AS_{fair} removes the ρ trend	FAIL on screened set (-0.79 [$-1.00, -0.23$])
R2	tolerance stability: adjacent $\tau \geq 0.9$	FAIL (AS_{fair} 0.87/0.82; AS_{SING} 0.87); $\rho \geq 0.92$
R2	PC bands $G_{\text{top}}/G_{\text{rand}}$ vs 1 at d=24	"top PCs carry less AS per unit energy" (2/3 screened models)
R2	synthetic oracle passes the flatness rule	FAIL (ratio 3.55): rule ill-posed
R2	DinoViT translator fidelity: used checkpoint best by ≥ 0.05	PASS (0.848 vs 0.677); see D
R3-A	equal-energy A1: ENERGY-ACCOUNTS / PARTIAL / KILL-R3	ENERGY-ACCOUNTS ($\tau = -0.03$ E12, 0.09 S11); no KILL
R3-A	A4 (matched CLIP energy) $\tau < 0.3$ on both sets	yes (-0.15, -0.20); $\kappa - \rho$ CI covers 0
R3-B	N4: AS rises with leak-free null energy, all 3 models	PASS (Spearman 1; slopes 0.38–0.69)
R3-B	B-rank: $\tau(\text{AS}_{\text{surr}}) \geq 0.6$ on all 13 and S11	yes (0.69, 0.64); no claim from X
R3-C	PC bands vs energy law $\rho^{\hat{a}}$	"top PCs carry less AS than energy predicts"; not robust in $\hat{a}$
R3-D	N3: non-matching candidates at chance	PASS ($\lvert\cos - \text{shuffled}\rvert \leq 0.002$)
R3-E	N7: no claim CI excludes its point	FAIL (1 flag: AS_{fair} C6 SD); N6 dedup done
R3-F	N1: paired $\tau(\rho) - \tau(\text{AS}_{\text{SING}})$ CI covers 0	yes $[-0.36, 0.29]$: "indistinguishable"
R3-G	retrained translators: order survives if $\tau \geq 0.6$ on all 13 and S11	survives (0.85, 0.82); A1 with retrained translators 0.61, 0.75 (descriptive)

Table 2: All pre-registered experiments of rounds 1–3 and their outcomes. The pre-registration files are in the repository.

Exp.	Pre-declared criterion (short)	Outcome
R4-S	content-free AS_{perm} and content excess $AS_{SING}-AS_{perm}$ each track SING ($\tau \geq 0.6$ on all 13 and S11, CI > 0); KILL-R4-S if $\tau(AS_{perm}) < 0.3$	both track: cannot apportion (0.69/0.64 and 0.62/0.71); surrogate τ spans 0.49–0.72; no kill
R4-J	KILL-R3 rule applied to retrained A1 (reading only); influence of DinoViT/EVA02	retrained: KILL-R3 level (0.61, 0.75); released S11 without the pair 0.61
R4-J	A4 under ridge translators < 0.3 on both sets	no (0.52, 0.49): holds for released translators only
R4-DN	KILL-DN (feature validity); Q-DN1 (DINO among lowest 4 AS); Q-DN2 (inside energy-law PI)	no kill; Q-DN1 SING-inconsistent (ranks 8, 9 of 15); Q-DN2 mixed
R4-P	energy-equivalent planted strength α^*	$\alpha^* > 0.3$ on all 3 models (outside the tested range)
R4-C6	C6-SD point inside both CIs (class resampling); no flags	PASS
R4-N10	fast holdout < 30 min and within ± 0.03	FAIL (36.3 min; ΔAS_{fair} nl 0.057); not re-timed, see Appendix J
R4B-1	class-mean permutation: CONTENT-CARRIES / ENERGY-CARRIES / UNAPPORTIONED; KILL-R4B-1 on CONTENT-CARRIES	ENERGY-CARRIES under both families (released 0.64/0.64; ridge 0.70/0.67); no kill
R4B-2	semi-synthetic worlds C/M/D: content-diagnostic estimator	none of 8 estimators diagnostic on all 3 bases
R4B-5	NCM_{null}: NCM-CONTENT (≥ 0.6, partial CI $\not\ni 0$) / NCM-NULL (< 0.3)	intermediate (0.45, 0.42); no kill
R4B-3	selectivity R: R-TRACKS (≥ 0.6) / R-NULL (< 0.3); within-model CI $\not\ni 1$ on $\geq 9/12$	R-NULL (0.15, 0.05); within-model 12/12 (4 above, 8 below 1)
R4B-6	DINO inside the E12 PI of Δ_{align} and NCM_{null}; both in the lowest 4	inside both PIs for both; 'least leaking' label not met (it needs both models in the lowest 4); ViT-S/16 alone is in the lowest 4 on both (ranks 3 of 15 and 2 of 14)
R4C-G2	geometry on true DINO: (i) Spearman ≥ 0.9, (ii) oop CI > 0, (iii) closed form $\leq 25\%$; (iv) $\lvert a_{fit}-a_{pred}\rvert \leq 0.1$	PASS on both; exponent predicted; no kill
R4C-G3	synthetic: a_{fit} within ± 0.05 of $(1+s)/2$	PASS (max error 0.027)
R4C-B3	NZS gate (rescaling $\leq 5\%$, planted $\tau \geq 0.6$); energy-free $\lvert\tau(\cdot,\rho)\rvert < 0.3$; SING test	gate pass; not energy-free (0.45, 0.53); SING test inconclusive
R4C-B4	IS energy proxy: $\lvert\tau(\mathrm{IS}, 1-\rho)\rvert \geq 0.6$ on all three sets	no (-0.62, -0.55, -0.49)

Table 3: Round-4 pre-registered tests and outcomes (E12 / S11 unless stated). R4B and R4C rows come from addenda written after the R4 results. No kill fired.

Exp.	Pre-declared criterion (short)	Outcome
R5-cal	world residuals permuted across images (seed 99000); report every changed value	50 of 78 values change; content-diagnostic estimators: none before, none after
R5-G1	exact invariance to $\beta \in \{0.1, 10\}$ and orthogonal maps	SO pass, XCC pass
R5-G2	class-mean derangement: fail on ≤ 2 models	fails: SO 0, XCC 0 (max |mean| 0.002, 0.001)
R5-G3	world S: semantic ≥ 2 SD, arbitrary ≤ 1 SD on $\geq 11/13$	SO 13/13, XCC 13/13
R5-G4	corrected world C: max / min ≤ 1.5; kill if it fails on ≥ 2 bases	SO testable on one base (pass): not testable; XCC testable on two, passes on two
R5-G5	estimable on ≥ 9 of E12 and ≥ 8 of S11	SO 12/11, XCC 12/11; no kill
R5-SO	ORGANISATION-TRACKS ($\tau \geq 0.6$ on E12 and S11) / DOES-NOT-TRACK (< 0.3 on both) / INCONCLUSIVE	INCONCLUSIVE (0.33 [-0.29,0.79], 0.45 [-0.21,0.88])
R5-XCC	same bars, secondary	DOES-NOT-TRACK (-0.12, -0.05)
R5-inh	INHERITED if F1-partial ≤ 0.05 on $\geq 75\%$; plant check ≥ 0.1	NOT INHERITED (7/13, 54%); plant check pass

Table 4: Round-5 pre-registered tests and outcomes (E12 / S11 unless stated). Thresholds were set after scratch runs on five models (SO-type) and three (XCC-type), with plants, worlds and derangements, and a ResNet50 smoke test of the final code. No kill fired.

Test	Criterion	Outcome
G5 estimability	$\mathrm{SD}_{\mathrm{boot}} \leq 0.1\times$ range; verdict needs $\geq$9 E12 and $\geq$8 S11	ViM: 12/11; ActSub $S_{\rightarrow}$: 12/11; CORE S_{mem}: 12/11; $\mathcal{V}$-info (class): 11/10
ViM, energy	ENERGY-DRIVEN if $\tau_{\mathrm{EQ}} < 0.3$ on both sets and median $R_B \geq 0.5$; NOT if ≥ 0.6 and ≤ 0.1	NOT ENERGY-DRIVEN (τ_{EQ} 0.88 / 0.89, R_B 0.06)
ViM, content	RESPONSIVE if $\lvert C_1\rvert \geq 2$ and $\lvert\Delta_{\mathrm{arb}}\rvert \geq 2$ on $\geq$10 of 13; BLIND if both ≤ 1 on $\geq$10	partial (9 / 5 of 13)
ActSub $S_{\rightarrow}$, energy	ENERGY-DRIVEN if $\tau_{\mathrm{EQ}} < 0.3$ on both sets and median $R_B \geq 0.5$; NOT if ≥ 0.6 and ≤ 0.1	MIXED (τ_{EQ} 0.79 / 0.78, R_B 0.14)
ActSub $S_{\rightarrow}$, content	RESPONSIVE if $\lvert C_1\rvert \geq 2$ and $\lvert\Delta_{\mathrm{arb}}\rvert \geq 2$ on $\geq$10 of 13; BLIND if both ≤ 1 on $\geq$10	partial (11 / 8 of 13)
CORE S_{mem}, energy	ENERGY-DRIVEN if $\tau_{\mathrm{EQ}} < 0.3$ on both sets and median $R_B \geq 0.5$; NOT if ≥ 0.6 and ≤ 0.1	MIXED (τ_{EQ} 0.85 / 0.82, R_B 0.11)
CORE S_{mem}, content	RESPONSIVE if $\lvert C_1\rvert \geq 2$ and $\lvert\Delta_{\mathrm{arb}}\rvert \geq 2$ on $\geq$10 of 13; BLIND if both ≤ 1 on $\geq$10	partial (11 / 8 of 13)
$\mathcal{V}$-info (class), energy	ENERGY-DRIVEN if $\tau_{\mathrm{EQ}} < 0.3$ on both sets and median $R_B \geq 0.5$; NOT if ≥ 0.6 and ≤ 0.1	MIXED (τ_{EQ} 0.20 / 0.33, R_B 0.19)
$\mathcal{V}$-info (class), content	RESPONSIVE if $\lvert C_1\rvert \geq 2$ and $\lvert\Delta_{\mathrm{arb}}\rvert \geq 2$ on $\geq$10 of 13; BLIND if both ≤ 1 on $\geq$10	content-responsive (11 / 12 of 13)
Counting rule	GENERAL if $k \geq 3$ (n=4) or $k \geq 2$ (n=3); DESIGN-DEPENDENT if n=4, k=2; SING-SPECIFIC if $k \leq 1$	n=4, k=0: SING-SPECIFIC
Content measurable	$\geq$2 counted scores NOT ENERGY-DRIVEN and RESPONSIVE	no (0)

Table 5: Round-6 pre-registered verdicts (`PREREG_R6.md`, pushed with its code and synthetic unit tests before any real-model number; the content labels are registered outcomes, not readings, see Appendix H). τ_{EQ} on E12 / S11; content counts are $\lvert C_1\rvert \geq 2$ / $\lvert\Delta_{\mathrm{arb}}\rvert \geq 2$ out of 13 models.

Test	Criterion	Outcome
R7 H1, reproducible edit	REPRODUCIBLE if CI lower bound of split-half reliability (null, L2) > 0.10	REPRODUCIBLE, 4/4 (Rel 0.72–0.82)
R7 H2, alignment above controls	ALIGNED if $p < 0.01$ and the CIs of T2(edit)$-$T2(artefact) and T2(edit)$-$nuisance exclude 0 from above; ARTEFACT if $p < 0.01$ but the artefact CI includes 0	ARTEFACT, 4/4 (also with corrected CIs)
R7 H3, noise cancellation	tested only if H2 ALIGNED	NOT TESTED, 4/4
R7 family	SUPPORTED if $\geq$3 of 4 models support cancellation; NOT if $\leq$1	NOT SUPPORTED (0/4)
R7 K0, K1	synthetic stability; no reproducible edit	did not fire
R8 K0	CI method with synthetic coverage in [0.90, 0.99]	did not fire; class bootstrap
R8 G-floor	CI includes 0 in $\geq$90% of 98 surrogate cells and max $\lvert\theta\rvert \leq 0.1\times$ max real	pass
R8 G-noise (world C′)	$\geq$8/12 rows estimable, max/min ≤ 1.5, slope CI includes 0, each base	**fail** (3, 7, 7 of 12 estimable)
R8 invariances, offset world	relative change $\leq 10^{-8}$	pass
R8 G-derange	CI includes 0 and $\lvert\text{mean}\rvert \leq 0.1\times$ max real, 6 cells	**fail** (5/6 cells)
R8 G-S plants	Δ_{sem} CI > 0 and Δ_{arb} CI includes 0, each base	pass
R8 G-B, G-tol, estimability	closed form $\leq 10^{-8}$; $\tau \geq 0.8$ across tolerances; $\geq$11/13 estimable	pass, pass, pass
R8 confirmatory	read only if all gates pass; TRACKS if $\tau \geq 0.6$ and CI > 0 on E12 and S11	NOT VALIDATED; τ 0.64 / 0.64 reported, not read

Table 6: Rounds 7 and 8, pre-registered tests and outcomes. Round 7 was run on four models (ResNet50, EfficientNet-B0, ResNeXt101, DINOv2-L); its corrected CIs are post hoc. Round 8 gates are per base (ResNet50, DINOv2-L, ResNeXt101) or over all 13 models. No kill fired in either round.

B The case study in full

This appendix holds the full analyses of the SING case study that §4–§6 summarise, in the order in which they were run. Analyses are labelled pre-registered, post hoc or exploratory as in the rest of the paper.

B.1 Null energy reproduces SING's order

Reproduction. $\mathrm{AS}_{\mathrm{SING}}$ agrees with SING's order at τ=0.82 (95% CI $[0.56, 1.00]$). The like-for-like comparison, our IS/|AS| ratio against SING's IS/AS ratio, gives τ=0.744 (percentile $[0.33, 1.00]$, BCa $[0.12, 0.94]$). SING's ratios are 0.98–3.35 times ours (Table 11 in Appendix D). The gap is largest for DinoViT (3.35×) and EVA02 (2.5×), both small-ρ models. SING's model comparison uses the same number of images and classes as ours, so the gap is not explained by the subset size. Its likely sources are SING's specific images, its concept set or its checkpoint (§B.5), and we cannot separate them without SING's evaluation lists.

ρ alone reproduces the order. Ranking models by ρ alone gives τ=0.82 $[0.56, 1.00]$, the same as $\mathrm{AS}_{\mathrm{SING}}$ (Fig. 1). On S11 the values are 0.78 for ρ and 0.82 for $\mathrm{AS}_{\mathrm{SING}}$. The paired bootstrap difference $\tau(\rho) - \tau(\mathrm{AS}_{\mathrm{SING}})$ is 0.00 with 95% CI $[-0.36, 0.29]$ (BCa $[-0.37, 0.28]$). Both agreements are far from chance (permutation p=5×10^{-5} for each, the smallest value 20000 permutations can give). ρ and $\mathrm{AS}_{\mathrm{SING}}$ agree with each other at τ=0.69 (Spearman 0.87). Each keeps a partial association with SING's order given the other: partial Kendall τ=0.61 both ways, and partial Spearman 0.63 for $\mathrm{AS}_{\mathrm{SING}}$ given ρ and 0.72 for ρ given $\mathrm{AS}_{\mathrm{SING}}$. The data therefore cannot tell the two predictors apart, and ρ does not make $\mathrm{AS}_{\mathrm{SING}}$ redundant. Null dimension alone is a weak predictor (Spearman +0.46 with the leakage order, p=0.12): DeiT3-L (Touvron et al., 2022) has d_{null}=24 yet the worst ratio. A NuSA-style null norm, $\mathbb{E}_i\|\Pi f_i\|/\|f_i\|$, in the spirit of Cook et al. (2020), is an energy proxy rather than a second leakage score: it orders the models almost as ρ does (τ=0.97) and agrees with SING at τ=0.85.

ρ is uncentred (post hoc). ρ includes the mean of the null coordinates. It splits exactly as $\rho = \rho_{\mathrm{off}} + \rho_{\mathrm{btw}} + \rho_{\mathrm{wit}}$, the energies of the constant per-model null mean, the centred class means and the within-class residuals. The offset is 92% of ρ for DeiT3-L (ρ=0.348, centred 0.029), 85% for ResNet50 (0.146, centred 0.021), 83% for DenseNet121, 33% for ResNeXt101 and at most 9% for the other nine models. Centred $\rho = \rho_{\mathrm{btw}} + \rho_{\mathrm{wit}}$ agrees less with SING's order: τ=0.56 $[0.11, 0.89]$ on all 13, 0.48 $[-0.02, 0.86]$ on E12 and 0.49 $[-0.08, 0.91]$ on S11, against 0.82, 0.79 and 0.78 uncentred (paired difference −0.26 on all 13, percentile $[-0.58, 0.00]$, BCa $[-0.66, -0.03]$). DeiT3-L, which leaks most by SING's order, is 3rd of 13 by uncentred ρ and 8th by centred ρ; ResNet50 moves from 7th to 9th. The components alone give 0.74 (offset), 0.72 (between) and 0.49 (within). The offset carries no image or class content, yet it moves AS. AS with the null part replaced by its mean alone is 4.18° of 5.05° for DeiT3-L and 1.38° of 1.68° for ResNet50 (83% and 83%; AS is an angle, so shares do not add), against 5–25% for nine other models (EVA02-L 55%; DenseNet121 87% of a negligible AS). The broader energy reading does not rest on the offset. Zero-mean Gaussian surrogates at each model's centred null energy, passed through the released translators, give τ=0.67 $[0.38, 0.92]$ on all 13 (0.61 and 0.64 on E12 and S11), close to the full-energy Gaussian surrogate of §B.2.2 (0.69; paired difference −0.03 $[-0.31, 0.31]$), and centred null coordinates permuted across images give 0.67. The order is thus carried by content-free null energy as the translator amplifies it, not by the raw share ρ. Real null content with the offset removed gives 0.74, and the offset alone 0.56. These analyses were run after round 6 and before the round-8 pre-registration, which lists them as known. They change no pre-registered verdict.

The rank plot for this section is Fig. 1 in the main text.

Within a model, AS grows with removed energy. On ResNet50, ResNeXt101, BiT-R50x1 (Kolesnikov et al., 2020) and DINOv2-L (Oquab et al., 2024), all with d_{null}=1048, removing random d-dimensional subspaces of the null space with $d \in \{24, \ldots, 1048\}$ raises AS about tenfold from d=24 to d=1048 on three of four models (Table 20, Fig. 3 in Appendix E). For random subspaces, removed energy is close to linear in d, so this experiment cannot separate energy from dimension. A second experiment mixes high- and low-variance null PCs to vary energy at fixed d and dimension at fixed energy. It fits $\log|\mathrm{AS}| = a\log\rho + b\log d + c_{\mathrm{model}}$ over 76 cells on five models with a=0.431 (cell bootstrap $[0.388, 0.485]$, model-clustered bootstrap $[0.382, 0.464]$, leave-one-model-out 0.408–0.452; the clustered CI rests on five clusters, one with a single cell, so it is not more reliable for being narrower) and a dimension term b=0.010 whose CI covers 0 (Appendix E). A first-order calculation gives a=0.5: if the translator maps the removed component linearly and the residual is small, the angle changes in proportion to $\|\Pi f\| \propto \sqrt{\rho}$. The pre-registered flatness part of this experiment failed (max/min across d at fixed ρ up to 2.29 against a 1.5 bar), so we claim only $a \approx 0.4$–0.5.

Score	all 13	E12	S11
ρ (null energy fraction)	0.82 [0.56, 1.00]	0.79 [0.49, 0.97]	0.78 [0.44, 1.00]
$\mathrm{AS}_{\mathrm{SING}}$ (released translators)	0.82 [0.56, 1.00]	0.79 [0.51, 1.00]	0.82 [0.51, 1.00]
κ (CLIP-space null energy)	0.72 [0.44, 0.95]	0.67 [0.37, 0.93]	0.67 [0.35, 0.96]
NuSA-style null norm	0.85 [0.64, 1.00]	0.82 [0.57, 0.97]	0.82 [0.53, 1.00]
$\gamma = \kappa/\rho$ (translator null gain)	−0.10 [−0.56, 0.43]	−0.06 [−0.59, 0.54]	0.05 [−0.51, 0.74]
Leak-free surrogate $\mathrm{AS}_{\mathrm{surr}}$	0.69 [0.39, 0.92]	–	0.64 [0.27, 0.92]
Equal-energy interventions (released translators)			
A1: remove $\beta\Pi f$, $\beta^2\rho = 0.005$	–	−0.03 [−0.54, 0.61]	0.09 [−0.45, 0.78]
A1′: same, $\rho_0 = 0.001$	–	−0.03 [−0.54, 0.61]	0.09 [−0.45, 0.78]
A2: top null PCs, energy ρ_0	–	0.03 [−0.54, 0.54]	0.13 [−0.43, 0.67]
A3: random null rotation, energy ρ_0	–	0.03 [−0.47, 0.67]	0.16 [−0.50, 0.84]
A4: matched CLIP-space energy κ_0	–	−0.15 [−0.68, 0.44]	−0.20 [−0.74, 0.46]
Retrained ridge translators (test half)			
$\mathrm{AS}_{\mathrm{SING}}$	0.85 [0.61, 1.00]	0.82 [0.57, 1.00]	0.82 [0.51, 1.00]
A1	–	0.61 [0.15, 0.94]	0.75 [0.32, 1.00]
A1, λ on extended grid†	0.49 [−0.10, 0.91]	0.39 [−0.21, 0.86]	0.53 [−0.06, 1.00]

Table 7: Kendall τ against SING's order (percentile 95% CI, 2000 model resamples). E12 drops DenseNet ($\rho < \rho_0$); S11 also drops BiT. A1′ gives the same order as A1 because, for each model, AS is monotone in the removed fraction. †Post hoc: ridge penalty chosen on an extended grid $10^{3..6}$, since the pre-registered grid put every model at its upper edge.

BiT is the exception. Its full-null AS collapses (r=0.06) while its partial subspaces give large AS (9–13°), because the translator's null blocks nearly cancel (top singular value of AV_n 284, against 5.6 for ResNet50). This is also why BiT fails the screen.

B.2 Energy or content? Interventions

Agreement between ρ and SING's order does not show that energy drives AS across models. Energy could instead *mediate* genuine leakage, if models with more null energy also hold more class content there. We ran four interventions in round 3 and further tests in round 4, pre-registered unless marked post hoc or exploratory (Tables 7 and 8, Fig. 2 in Appendix D). None of them separates the two readings. They do show that AS has a content-free path from null energy to the score. They also show that the data cannot apportion SING's order between null energy and null content. We read a τ of 0.6 or more as tracking and $|\tau| < 0.3$ as not reproducing the order; with 13 models, most CIs are wide, so we treat point estimates between the bars as inconclusive. In round 3 we applied the bars unevenly. $\mathrm{AS}_{\mathrm{surr}}$ was read on its point $\tau \geq 0.6$, but X needed its whole CI above 0.6.

B.2.1 Equal null energy (released translators)

Design. In *A1* we remove $\beta\Pi f$ with $\beta = \sqrt{\rho_0/\rho}$, ρ_0=0.005, so every model loses the same fraction of its feature energy, taken from its own null space in its own proportions. *A2* removes the same energy from the top-variance null PCs, and *A3* removes it from a random rotation of the null basis. *A4* matches energy in CLIP space instead: with $\kappa = \mathbb{E}\|A\Pi f\|^2/\mathbb{E}\|Tf\|^2$, we remove $\beta'\Pi f$ with $\beta'^2\kappa = \kappa_0$=0.0023. The pre-registered outcome was ENERGY-ACCOUNTS if τ(A1) < 0.3 and the paired CI of $\tau(\mathrm{AS}_{\mathrm{SING}}) - \tau$(A1) is above 0 on both E12 and S11, and a kill of the energy reading if τ(A1) $\geq$ 0.6 on both.

What A1 measures. For a small removal, the translated shift is close to linear in the removed component, so A1 $\approx \beta\,\mathrm{AS}_{\mathrm{SING}} = \mathrm{AS}_{\mathrm{SING}}\sqrt{\rho_0/\rho}$: A1 is, to first order, AS per unit null amplitude. The data agree: A1 and $\mathrm{AS}_{\mathrm{SING}}/\sqrt{\rho}$ give nearly the same order (τ=0.79 on E12 and 0.82 on S11; Spearman 0.92 and 0.93), and A1 and $\mathrm{AS}_{\mathrm{SING}}/\rho^{\hat{a}}$ give τ=0.73 and 0.75. The first-order ratio A1/($\beta\mathrm{AS}_{\mathrm{SING}}$) runs from 0.36 (DeiT3-L) to 1.00 (DinoViT). The question A1 answers is therefore whether AS *per unit null energy* tracks SING's order. Whether energy causes AS is a separate question.

Result. With the released translators, AS per unit energy does not track SING: τ=−0.03 [−0.54, 0.61] on E12 and 0.09 [−0.45, 0.78] on S11. The paired drop from $\mathrm{AS}_{\mathrm{SING}}$ has CI [0.23, 1.39] (BCa [0.25, 1.41]) on E12 and [0.08, 1.30] on S11, which meets the pre-registered ENERGY-ACCOUNTS criterion. Taking the energy from top PCs (0.03) or random directions (0.03) gives the same picture. The result rests on few models. Delete-one jackknife values of τ(A1) span [−0.16, 0.13] on E12 and [−0.02, 0.29] on S11, but dropping DinoViT and EVA02 together gives 0.38 on E12 and 0.61 on S11. The S11 value reaches the level (≥ 0.6) that our round-3 kill rule set for the energy reading, and no other of the 55 leave-two-out subsets of S11 does. Matching CLIP-space energy instead (A4: −0.15 and −0.20) gives the same result, but only with the released translators. With our ridge translators A4 gives 0.52 and 0.49 (§B.2.4). We therefore do not use A1 or A4 as evidence about the cause of the order. The A1 scores still differ across models by a factor of six (Table 12), so equalising energy changes their order without making them equal.

Translator gain. CLIP-space energy κ tracks SING's order slightly less well than ρ (τ=0.67 on E12; paired difference CI [−0.41, 0.28]), and the null gain $\gamma = \kappa/\rho$ does not (τ=−0.06), although gain shapes the A1 values (§B.2.4).

B.2.2 Leak-free null content

Design. We replace each image's null coordinates $c_i = V_n^\top f_i$ with a draw $\tilde{c}_i \sim \mathcal{N}(\mu, \Sigma)$, where μ and Σ are the mean and covariance of c over the 10k images (5 draws). The row-space part, and so every logit, is unchanged. The surrogate carries no image-specific and thus no class-specific content. On ResNet50, ResNeXt101 and DINOv2-L we scale the surrogate to null energy fractions $\rho_t \in \{0.01, 0.05, 0.2, 0.45\}$. We then optionally plant a concept direction with strength $\alpha \in \{0, 0.1, 0.3\}$, using the generator of our holdout test (Appendix F; concepts water, green, thin, knitted). The pre-registered test required that, at α=0, AS rise with ρ_t with Spearman $\geq$0.8 and that the log-log slope CI exclude 0, on all three models.

Result. The test passes on all three models (Spearman 1; slopes 0.38–0.69, all CIs far from 0; Table 13 in Appendix D). AS therefore grows with null energy that carries no image-specific content, which gives it a content-free path from null energy to the score.

Planted content. Planted content raises AS at fixed energy, by ×1.04–1.09 at α=0.1 and ×1.35–1.51 at α=0.3 (ρ_t=0.2), and by ×1.14–1.58 at α=0.3 when each model keeps its own ρ (Table 17 in Appendix D; DINOv2-L ×1.17). Across the interquartile range of ρ over the 12 models (0.038 to 0.341), the energy law moves AS by r_E=2.4–5.4× on these three models. The planted strength that would move AS as much, α^*, is therefore above 0.3, the largest strength we tested, on all three models. So AS does respond to null content at fixed energy. At ρ_t=0.2 and at each model's own ρ, though, content moves it less than the observed spread of energy does. This does not hold at the lowest energy (post hoc, from the same sweep). At ρ_t=0.01, α=0.3 moves AS by ×2.70 (ResNet50), ×3.47 (ResNeXt101) and ×5.26 (DINOv2-L), above r_E (2.39, 5.37 and 4.92) on 2 of the three models.

Leak-free scores and the content excess. On all 13 models, replacing each model's null content with its own leak-free surrogate, at its own energy and covariance, gives $\mathrm{AS}_{\mathrm{surr}}$ with τ=0.69 [0.39, 0.92] against SING (0.64 on S11) and Spearman 0.96 with $\mathrm{AS}_{\mathrm{SING}}$. In round 4 we pre-registered both halves of this decomposition and five more surrogates (Table 16 in Appendix D).

- *Content-free half.* AS with surrogate null content tracks SING ($\tau \geq 0.6$) for three of the five content-free surrogates. Its value depends on the surrogate: point τ on all 13 models runs from 0.49 (isotropic and mean-only) to 0.72 (zero-mean Gaussian), and $\mathrm{AS}_{\mathrm{surr}}$ with the same Gaussian tracks CLIP-space null energy κ (τ=0.92). Real null coordinates permuted across images ($\mathrm{AS}_{\mathrm{perm}}$) give 0.69 [0.39, 0.92] on all 13 and 0.64 on S11.
- *Content half.* The excess $X = \mathrm{AS}_{\mathrm{SING}}/\mathrm{AS}_{\mathrm{surr}}$ has τ=0.54 [0.14, 0.83] on all 13 and 0.60 [0.24, 0.91] on S11, and $\mathrm{AS}_{\mathrm{SING}} - \mathrm{AS}_{\mathrm{perm}}$ has 0.62 [0.15, 0.92] and 0.71 [0.28, 1.00]. Given ρ, the partial Spearman of X with the order is 0.79 [0.02, 0.97] on S11, against 0.52 for $\mathrm{AS}_{\mathrm{perm}}$.

Both halves track the order, the outcome the pre-registration calls "cannot apportion". The data cannot apportion SING's order between null energy and image-specific null content.

B.2.3 Class-mean permutation

Design. Write each image's null coordinates as $z_i = \mu_{y_i} + r_i$, with μ_c the class mean over its 10 images and r_i the within-class residual. We draw a derangement π of the 1000 classes (5 draws) and set $z'_i = \mu_{\pi(y_i)} + r_i$. The logits are unchanged, and because every class has 10 images, the total null energy and the uncentred null second-moment matrix are preserved exactly (largest relative error 2×10^{-16}). Only the alignment between an image's class and its class-mean null content is broken. $\mathrm{AS}_{\mathrm{cperm}}$ is the mean AS over draws, $\Delta_{\mathrm{align}} = \mathrm{AS}_{\mathrm{SING}} - \mathrm{AS}_{\mathrm{cperm}}$ and the share is $\Delta_{\mathrm{align}}/\mathrm{AS}_{\mathrm{SING}}$.

Result. With the released translators, $\mathrm{AS}_{\mathrm{cperm}}$ still tracks SING (τ=0.69 $[0.34, 0.94]$ on all 13, 0.64 on E12, 0.64 on S11), and the median share is 0.10 (E12) and 0.14 (S11). With our ridge translators the pattern is the same ($\mathrm{AS}_{\mathrm{cperm}}$ 0.70 and 0.67; median share -0.04). This is the pre-registered outcome ENERGY-CARRIES under both translator families. Since both surrogates preserve null energy, this outcome was largely foreseeable once we knew that $\mathrm{AS}_{\mathrm{perm}}$ tracks the order. Δ_{align} itself tracks the order with the released translators (0.64, 0.64) but not with ours (0.09, 0.13).

Reading. We take this as evidence leaning toward energy, not as a demonstration, for two reasons. First, given ρ, the class-aligned part keeps the stronger association with the order: with the released translators the partial Spearman is 0.22 (all 13), 0.22 (E12) and 0.35 (S11) for $\mathrm{AS}_{\mathrm{cperm}}$, against 0.76, 0.81 and 0.88 for Δ_{align}. Second, Δ_{align} fails the calibration of §B.2.5: at fixed class content it falls as energy rises (τ=-1.00 in world C on all three bases). Our pre-registration allows no stronger claim from this test than its raw numbers.

B.2.4 Retrained translators

SING's translators were fit by its authors, and AS depends on them. We fit our own ridge translators (Hastie et al., 2009, §3.4) $f \mapsto$ CLIP image embedding on half of the 10k images (5000; penalty chosen on a held-out split of that half) and evaluate on the other half. Test fidelity (mean cosine) is 0.79–0.84, against 0.81–0.87 for the released translators on the same images. SING does not list the images its translators were fit on, so on our subset their fidelity may be partly in-sample; ours is measured out of sample. With retrained translators, $\mathrm{AS}_{\mathrm{SING}}$ still agrees with SING (τ=0.85 $[0.61, 1.00]$; 0.82 on S11; τ=0.72 against released-translator AS). The AS order is thus not specific to the released translators.

The equal-energy result is. With retrained translators, A1 gives τ=0.61 $[0.15, 0.94]$ on E12 and 0.75 $[0.32, 1.00]$ on S11. Read against the round-3 rule (a kill of the energy reading if $\tau(\mathrm{A1}) \geq 0.6$ on both E12 and S11), this is at the kill level. The rule was registered for the released translators, so we apply it as a reading, not as a registered outcome. The paired CI of $\tau(\mathrm{AS}_{\mathrm{SING}}) - \tau(\mathrm{A1})$ covers 0 ($[-0.20, 0.65]$ on E12, $[-0.32, 0.49]$ on S11). Leaving out any two models keeps it at 0.42 or more on E12 and 0.61 or more on S11. Released and retrained A1 order the models almost independently (τ=0.06 on E12). Retrained A1 spans a narrow range (0.048–0.091°, against 0.049–0.302° released) and follows ρ (τ=0.58 and 0.67). Given ρ, its partial Spearman with the order is 0.15 (E12) and 0.41 (S11). With these translators, matched CLIP-space energy (A4) gives 0.52 $[-0.10, 0.97]$ and 0.49, between our bars, and κ itself tracks the order (0.76, 0.75). The pre-registered penalty grid put every model at its upper edge. On a post hoc extended grid (10^3–10^6; interior choices 10^4 for VGG16, VGG19 and DenseNet, 10^3 otherwise) A1 gives 0.39 $[-0.21, 0.86]$ on E12 and 0.53 on S11; the drop comes from the two VGG models alone, and forcing 10^6 on every model gives about 0.79. Whether AS per unit energy tracks SING's order therefore depends on how the translator is fit. It does not with the released translators, and it does with ours. We do not know which translator better reflects null semantics, so neither result decides between the two readings.

B.2.5 Calibration and translator-free scores

Semi-synthetic worlds. To check whether any estimator can tell null content from null energy, we built three worlds on each of three bases (ResNet50, ResNeXt101 and DINOv2-L, each with its released translator) by rescaling the class-mean part μ_y and the residual r of the null coordinates, with the 12 E12 values of ρ as targets. Before rescaling, we permute the residual across images. An earlier version used each image's own residual. Within a class those residuals sum to zero, so class means estimated on disjoint subsets of the class's images come out anti-correlated. The correction changes 50 of the 78 entries of Table 18 (earlier values in Table 25), but not the verdict. We measure content by L, the class-mean null energy as a share of total feature energy. In world C, L is fixed while ρ varies; in world M the residual is fixed, so L rises with ρ; in world D, ρ is fixed and L varies. An estimator is *content-diagnostic* if, on all three bases, $|\tau(\cdot, \rho)| \leq 0.2$ in world C, $\tau(\cdot, L) \geq 0.8$ in world M and $\tau(\cdot, L) \geq 0.6$ in world D. Across the eight estimators we tested (ρ, AS, A1, $\mathrm{AS}_{\mathrm{gauss}}$, X, Δ_{align}, $\mathrm{NCM}_{\mathrm{null}}$ and the selectivity R), none meets all three criteria (Table 18 in Appendix D), and below we explain why none can. The bar is strict. In world C, where L is fixed and ρ grows (the absolute class-mean null energy rises $\times 1.81$, since the row-space energy is held fixed), the class-mean share of null energy falls from 50% to 0.6%, and a score that responds to that share fails world C by construction. $\mathrm{NCM}_{\mathrm{null}}$ tracks L in world D (0.99–1.00) and rises with it in world M (0.44–0.88, meeting the criterion on two bases), and Δ_{align} and X track it in world D (0.91–1.00 for Δ_{align}); all three fail world C (X meets the world-C criterion on one base only). AS follows ρ at fixed content (world C, $\tau \geq 0.97$ on all bases). The energy exponents in worlds C and M run from 0.31 to 0.59, against $\hat{a}=0.431$ from the energy law and 0.53 $[0.24, 0.82]$ across models.

The criteria cannot all be met (post hoc). An external reader pointed out that the criteria we gathered over several rounds contradict each other. Take any class-level score that depends on the data only through the class-mean null energy E_b, the residual null energy E_r, the row-space energy E_{row} and a scale-free composition κ of the null class means (for example, their share aligned with the class texts). Invariance to rescaling the null part (round-5 G1, round-6 $R_B \leq 0.1$) leaves a dependence on E_b/E_r only, given κ and E_{row}. World C moves only this ratio, so flatness there removes the dependence over the range it covers. World M also moves only this ratio, so a score that passes the first two criteria cannot rise in world M over the shared range. No score passes all three, not even an oracle that knows the true content. Arrangement scores such as $\mathrm{SO}_{\mathrm{null}}$ escape only by dropping the world-M requirement, and they cannot say how much content leaks. The reader also noted the yardstick problem above: world C fixes L per unit of *total* feature energy, so against the row space, which a null-space intervention leaves alone, the class-mean null energy rises $\times 1.81$, and a score of null content measured against the row space must fail world C. Like ρ, L also counts the null offset as content. The calibration result therefore shows that our criteria were inconsistent, not that null content cannot be measured. Round 8 (§B.4) fixed a target first and derived its gates from it.

Further analyses (Appendix C). Three translator-free or energy-free scores (null decodability $\mathrm{NCM}_{\mathrm{null}}$, null zero-shot accuracy NZS and a selectivity ratio R) do not track SING's order (τ=0.45, 0.30 and 0.15 on E12). None is both energy-free and fully calibrated (Appendix C.2). A pre-registered round-5 score of how the null class means are arranged relative to the class texts, $\mathrm{SO}_{\mathrm{null}}$, is exactly invariant to rescaling the null part. It passes its invariance, derangement and planted-code gates. Its world-C energy gate could be tested on only one base. Its agreement with SING's order is inconclusive (τ=0.33 and 0.45; Appendix C.3). Top-variance null PCs are not clearly more semantic per unit energy than random null subspaces; the label flips with the energy exponent (Appendix C.1). A geometric decomposition shows how AS grows with energy without regard to the class text. The out-of-plane part of the removed translated component changes the angle at second order, whatever its direction. The pre-registered checks of this account pass on two held-out models but are not a strong test (Appendix C.4). SING's IS also rises with null energy and tracks SING's order (τ=0.74 on all 13).

B.2.6 What the interventions show

Energy and SING's score cannot be separated by their agreement with SING's order (§B.1). AS has a content-free energy path. It grows with surrogate null content that has no image-specific content, and the out-of-plane mechanism explains how. Content-free surrogates at each model's energy reproduce the order,

and so does the content excess. The data cannot apportion the order between the two. AS per unit energy loses the agreement with the released translators and keeps it with ours. Shuffling class means keeps the agreement (τ=0.64 on E12), which leans toward energy, but given ρ the class-aligned part has the stronger association (0.81 against 0.22), and our pre-registration allows no stronger claim than these raw numbers. No estimator we tested meets all three calibration criteria, and none could (§B.2.5), so this cannot settle the question. AS responds to planted content at fixed energy, so these results do not show that AS carries no leakage signal.

B.3 Do other null-space scores share the energy confound?

If null energy drives SING's order, it might also drive other published scores that read the null or residual part of a feature. In round 6 we pre-registered two energy statistics and applied them to ViM (Wang et al., 2022), the insignificant-subspace score $S_{\rightarrow}$ of ActSub (Zöngür et al., 2025), the membership score S_{mem} of CORE (Yang et al., 2026) and the conditional $\mathcal{V}$-information that the null part adds to the logits (Hewitt et al., 2021), with a NuSA-style null share (Cook et al., 2020) as an uncounted reference. `PREREG_R6.md` was pushed together with its code and synthetic unit tests before any real-model number was computed. E1 rescales every model's null part to ρ=0.005, and τ_{EQ} is Kendall τ between a score's cross-model values after and before. E2 sweeps each model through the 12 E12 values of ρ, and R_B is the range over the sweep divided by the range across the 13 models. The rule calls a score ENERGY-DRIVEN if $\tau_{\text{EQ}}<0.3$ on E12 and S11 and the median $R_B \geq 0.5$. Only Πf changes, so the logits do not. We have no training features, so each score is fitted on 5 validation images per class and is a surrogate of the published one (Appendix H).

Positive controls (post hoc). The rule flags none of the four scores (k=0 of 4). Run through the identical code (Table 26 in Appendix H), it flags SING's IS with both translators but misses SING's AS (released: τ_{EQ}=0.39 and 0.45, median R_B=0.26, mixed), ρ itself and the NuSA share. The count is therefore uninformative, and we do not use it to decide whether the confound is specific to SING. Released AS retains only 0.11 of its cross-model range after E1, so the thresholds, not weak energy dependence, cause the miss.

What the statistics show (descriptive). ViM, ActSub and CORE keep their order under E1 largely because they are scale-normalised by construction. With ViM's α frozen, E1 moves ResNet50's score from 0.876 to 2.5×10^{-4}. The retained cross-model range after E1 is 0.11 for SING's AS, 0.29 for $\mathcal{V}$-information, 0.78 for ActSub, 0.90 for ViM and 0.92 for CORE, a descriptive comparison rather than a validity gate. None of the four tracks SING's order, and we do not read the content tests (Appendix H).

B.4 Measuring null content directly

Rounds 3–6 inferred content from interventions on features. Rounds 7 and 8 tried to measure it (details in Appendix I).

Round 7: controlled background edits. On the IN-9 Backgrounds Challenge (Xiao et al., 2021) (900 foregrounds), the edit is the null-space difference between a foreground on the next class's background and the same foreground on a background of its own class, seen under four independent nuisance views at each of three strengths. The artefact control permutes the background pixels, which keeps their colour histogram and destroys layout and meaning. The primary statistic T2 is an unbiased HSIC alignment between the edit's null-space Gram matrix and the CLIP text embedding of the inserted class. `r7/PREREG_R7.md` was pushed before any real feature existed. On ResNet50, EfficientNet-B0, ResNeXt101 and DINOv2-L the edit is reproducible (H1 on 4 of 4; split-half reliability 0.72–0.82) and aligned with the text (T2 0.0010–0.0017, permutation p=0.001, the floor). The artefact control is aligned as strongly (0.0009–0.0016; the CIs of the difference include 0 at every level on every model), so H2 is ARTEFACT on 4 of 4, H3 (noise cancellation) was not tested, and the family statement is NOT SUPPORTED (0 of 4). After the analysis we found that the registered bootstrap is invalid for these U-statistics: resampling with replacement turns duplicated images into off-diagonal pairs (ResNet50: point T2 0.0017, bootstrap CI 0.012–0.016). A post hoc half-sampling correction, not validated for coverage, changes no verdict. A background edit also tests a different construct

from SING's. It asks whether the null space carries the meaning of an inserted context, not how much of a model's own class signal its head leaves unused.

Round 8: a target stated first. Following the external reader, round 8 fixed the target before the score: T1, the share of a model's text-predictable class signal that lies in $\ker W$. With Z and R the centred null and row-space class means and $S(\cdot)$ the class-mean energy predicted from the CLIP class texts by a ridge map cross-fitted over two 500-class folds, $\theta_{\text{sem}} = S(Z)/(S(Z) + S(R))$. It ignores the null offset and is invariant to global scale and rotation. Its eight gates follow from T1 (Table 6). One asks for flatness in a world C′ that fixes the class-mean null energy against the row space while the null noise grows. `r8/PREREG_R8.md` was pushed with its code and synthetic tests before any real-model value. 6 of the 8 gates pass. G-noise fails: only 3, 7 and 7 of 12 C′ rows are estimable on ResNet50, DINOv2-L and ResNeXt101 (8 needed), and two of the slopes are small but have CIs that exclude 0. G-derange fails on one of 6 cells, by a tiny but significant mean. θ_{sem} is therefore NOT VALIDATED, and its agreement with SING's order (τ=0.64 $[0.19, 0.93]$ on E12, 0.64 $[0.13, 0.96]$ on S11) is reported but not read. The C′ design was weak. At its fixed content (half the smallest real ρ), θ_{sem} lies between -0.0008 and 0.0016, against real values up to 0.40, so most noisy rows fall below the estimability bar. We did not foresee this, and we do not redesign the gate after the fact.

Round 8 descriptives (no verdicts). θ_{sem} factors into composition (the text-predictable fraction of the null class-mean energy) and amount. DeiT3-L's top value (0.40) comes from composition (0.70, the highest of 13) with little centred class-mean energy (ρ_{btw}=0.022), whereas ResNeXt101 and DINOv2-L have large amounts and low composition (0.11 and 0.06; Table 30 in Appendix I). Split the null coordinates z into the shadow Hs, their linear prediction from the row-space coordinates s, and the innovation $u = z - Hs$. The shadow's θ_{sem} tracks SING's order (τ=0.76 $[0.40, 1.00]$ on E12) and the innovation's does not (0.21 $[-0.29, 0.67]$). Given content-free energy ($\rho_{\text{off}} + \rho_{\text{wit}}$), the partial correlation of θ_{sem} with the order is -0.41 $[-0.85, 0.18]$ (no positive association beyond energy, although the CI includes 0). The head's self-duality, the mean cosine between the rows of W and the centred class means in the full space (cf. NC3 in Papyan et al., 2020), is anti-correlated with the order ($\tau = -0.64$ $[-1.00, -0.22]$ on E12). Refitting the head on the same backbone moves ρ and θ_{sem} by orders of magnitude (ResNet50: released head 0.146 and 0.013, nearest class mean 0.014 and 2.1×10^{-4}, shrinkage LDA 0.930 and 0.930; Table 31). The refit heads are not matched in accuracy: on the same held-out images they are 5–13 points less accurate than the released heads (top-1 0.635–0.779 against 0.762, 0.860 and 0.828 for ResNet50, DINOv2-L and ResNeXt101; the released values were computed post hoc from the cached features and released biases). A null-space leakage number is thus as much a property of the head as of the backbone. None of this mathematics is new. The ρ split is a plug-in variance identity; θ_{sem} uses held-out-condition encoding models and cross-validated inner products (Diedrichsen & Kriegeskorte, 2017; Diedrichsen et al., 2016; 2018; Walther et al., 2016); the shadow/innovation split is Rao's additional information in discriminant analysis and its canonical-correlation form (Rao, 1946; 1948; Fujikoshi, 1982), and the Fisher innovation score J_{inn} is a Gaussian form of conditional usable information (Hewitt et al., 2021); the null/row split mirrors output-null subspaces in motor cortex (Kaufman et al., 2014); and NCM heads (Mensink et al., 2013), last-layer retraining (Kirichenko et al., 2023) and head–class-mean duality (Papyan et al., 2020) are standard. Neither round yields a validated content measure. The descriptives associate SING's order with row-space-predictable null signal and head geometry. These observations fit the energy reading without testing it.

B.5 The DinoViT checkpoint

SING reports its "DinoViT" at 84.0% top-1 and itself describes the model as pretrained beyond ImageNet. Its released configuration loads a timm AugReg ViT-L/16. We evaluated five public ViT-L/16 checkpoints on the full 50k validation set: torchvision IMAGENET1K_V1 (79.67%), timm AugReg (85.85%), SWAG linear (Singh et al., 2022) (85.14%), SWAG end-to-end (88.07%) and `google/vit-large-patch16-224` (81.98%) (Fig. 7, Appendix E). None falls within 84.0 ± 0.3. SING's evaluation protocol is not specified, so the 84.0% versus 85.85% gap is unexplained.

With SING's `dinovit1` translator on 1000 images, the timm AugReg features give mean cosine 0.848 to the CLIP image embeddings. Their shuffled-pair floor is 0.575, centred cosine is 0.674 and retrieval top-1 is 78.8%. Every other candidate, re-extracted with its native transform, is at its own shuffled floor (largest gap

0.002) with retrieval top-1 at most 0.2%. SING's translator was thus fit on this supervised timm checkpoint, while the other candidates are at chance. DINO never released a ViT-L with a 1000-way head (Caron et al., 2021). Conclusions about self-supervision should therefore not rest on this model.

True DINO backbones. The two DINO backbones released with a linear ImageNet head, ViT-B/16 and ViT-S/16 (Caron et al., 2021), rank 8 and 9 of 15 by raw AS under our ridge translators (pre-registered outcome "SING-inconsistent"), but their null energy is above the median, and against the energy law the evidence is mixed (Appendix C.5).

B.6 Size-corrected scores and SING's claims

Dividing AS by the AS of an energy-matched random removal, $\mathrm{AS}_{\mathrm{fair}}$, over three families of controls gives point τ against SING of -0.18, -0.41 and -0.13 on all 13 models, all below the pre-registered 0.3 bar. Over eight normalisers, the pre-registered reversal criterion (CI entirely below 0 under at least 5 of 8) fails (0/8 on all 13; on S11 only family B, which is not logit-preserving, meets it). Family-A $\mathrm{AS}_{\mathrm{fair}}$ over-corrects (Spearman with ρ -0.79 on S11). Size-corrected rankings therefore *differ* from SING's. The direction depends on the normaliser, and we make no reversal claim. For SING's testable class-level claims under $\mathrm{AS}_{\mathrm{SING}}$, 7 hold, 3 reverse (one borderline) and 1 is contradicted. These differences may reflect protocol differences and are not caused by size correction (Appendix C.6, Table 10).

B.7 Summary of the case-study findings

What we can and cannot conclude. SING's cross-model ranking is indistinguishable from the ranking by null energy. AS responds to null energy through a path that carries no image-specific content, and we can describe that path geometrically. The data cannot separate null energy from real null content as the source of SING's order: content-free surrogates and the content excess both reproduce it, AS per unit energy tracks the order with one translator family and not the other, the class-mean permutation leans toward energy without settling it (its raw numbers are all our pre-registration supports), no estimator we tried meets all three calibration criteria, and a pre-registered score of null class organisation is inconclusive against the order. Post hoc, part of the agreement of uncentred ρ comes from a constant null offset (centred τ=0.56). Content-free surrogates at the centred energy still reproduce the order (0.67). Our calibration criteria could not be met by any score, and two direct content tests (§B.4) gave no validated content measure. We do not conclude that SING's ranking is wrong, or that AS carries no semantic signal. AS responds to planted concepts at fixed energy. The claim we support is narrower: a cross-model AS comparison cannot be read as a comparison of null semantics, because energy and content are not separated by any control we have. Whether the confound extends to other null-space scores is open. The round-6 energy rule flags SING's IS but not its AS or a pure energy score (§B.3). Its verdicts on ViM, ActSub, CORE and $\mathcal{V}$-information therefore cannot settle the question. Three of those scores keep their order when null energy is equalised largely because they normalise scale by construction. Those scores were built for OOD detection rather than for comparing null semantics across models. None of them tracks SING's order (ActSub and CORE are inconclusive).

Recommendations.

1. Report d_{null}, ρ (centred and uncentred, with the null offset) and the null tolerance next to any null-space score, and check rank stability across tolerances and heads.
2. Compare every cross-model AS-type score (a score that measures how far a readout moves when the null component is removed) with the ranking by ρ alone, as a control in the sense of Hewitt & Liang (2019), and with content-free surrogates of matched energy. Report the surrogate used, since the result depends on it.
3. Check conclusions with a second, independently fit translator, and calibrate any content estimator on worlds with known content before using it across models.

4. Name the exact checkpoint and its measured accuracy, and check translator fidelity against a shuffled floor.
5. Flag translator conditioning when full-null and partial-null AS disagree (BiT).
6. Before reading a null-space score across models, rescale the null part to equal energy and sweep it through the observed range (E1 and E2 of §B.3). Check the statistics on positive controls (ρ, an AS-type score, and the score with any built-in normalisation frozen), and report the retained cross-model range after equalisation as a descriptive comparison. Both tests are cheap and leave the logits unchanged.
7. State the target first, derive the criteria from it, and check on a synthetic oracle that the criteria can be met together before using them to accept or reject scores (Appendix F, §B.2.5).

Summary in the order of the analyses. Using SING's code and released translators, we reproduce its 13-model ranking. The uncentred null energy fraction ρ performs equally well. Post hoc, centring ρ lowers its agreement to τ=0.56 because a constant null offset dominates two models. Content-free surrogates at the centred energy still reproduce the order (0.67). A content-free path connects null energy to AS, and image-independent null content with each model's own energy reproduces the order. The content excess reproduces it too, and AS per unit energy tracks the order with retrained translators but not with the released ones, so the data cannot separate null energy from real null content as the source of the order. SING's "DinoViT" translator matches a supervised timm checkpoint. Under our ridge translators, true DINO backbones fall mid-table by raw AS, and the evidence is mixed once energy is accounted for. Size-corrected scores change the order without reversing it with confidence. Our pre-registered energy rule for other null-space scores flags SING's IS but not its AS or a pure energy score, so it cannot say whether the confound extends to them. Our earlier calibration criteria cannot be met together by any score. Two direct content tests gave no validated measure. Background edits are matched by a low-level artefact control, and a semantic null share defined from a stated target failed two of eight gates. Cross-model AS-type null-space comparisons should report ρ, an energy-only baseline and content-free surrogates of matched energy next to the score.

C Details of further analyses

This appendix holds analyses summarised in the main text, unchanged.

Round-4 scores. Table 8 lists the round-4 scores against SING's order.

C.1 Are high-energy null directions more semantic?

If the high-variance null directions were the semantic ones, energy would partly *be* the signal. At matched d, we compare the top-variance null PCs with random null subspaces. In round 2 we used $G = \mathrm{AS}/\sqrt{\rho}$. The pre-registered round-2 label was "top PCs carry less AS per unit energy" on 2 of the 3 screened models at d=24: $G_{\mathrm{top}}/G_{\mathrm{rand}}$ was 0.60 for ResNeXt101 and 0.87 for DINOv2-L, with CIs below 1, against 1.16 for ResNet50. At d=100 the ratios were 1.01 (ResNet50), 0.85 (ResNeXt101), 0.83 (DINOv2-L) and 0.011 (BiT, not counted). But $\sqrt{\rho}$ is not the fitted law. In round 3 we compare against $\rho^{\hat{a}}$, $H = (\mathrm{AS}_{\mathrm{top}}/\rho^{\hat{a}}_{\mathrm{top}})/(\mathrm{AS}_{\mathrm{rand}}/\rho^{\hat{a}}_{\mathrm{rand}})$. At $\hat{a}$=0.431 and d=24, H is 1.50 (ResNet50), 0.74 (ResNeXt101) and 0.98 [0.97, 0.99] (DINOv2-L), which gives the pre-registered label "top PCs carry less AS than energy predicts" (2/3). DINOv2-L's H differs from 1 by 2%, a negligible effect even though its CI excludes 1. At the low end of the CI for a (0.388), the label flips to "more", so it is *not robust* (Table 14 in Appendix D). High-energy null directions are not clearly more semantic per unit energy. The result varies across models and with the exponent, so this test does not decide between the readings.

C.2 Translator-free and energy-free scores

- *Null decodability* $\mathrm{NCM}_{\mathrm{null}}$: leave-one-out nearest-class-mean accuracy on the normalised null coordinates, minus a shuffled-label control. It needs no translator. It ranges from 5.2 to 80.9 points and gives τ=0.45 $[-0.11, 0.90]$ on E12 and 0.42 on S11, between our bars. It follows ρ (0.48, 0.42), and its partial association given ρ is about zero (-0.05, -0.01).

Score	E12	S11
A1 and its influence (released)		
A1, all models	-0.03 $[-0.54, 0.61]$	0.09 $[-0.45, 0.78]$
A1 without DinoViT and EVA02	0.38	0.61
Retrained ridge translators		
A1	0.61 $[0.15, 0.94]$	0.75 $[0.32, 1.00]$
A4 (matched CLIP-space energy)	0.52 $[-0.10, 0.97]$	0.49 $[-0.17, 1.00]$
κ	0.76 $[0.40, 0.97]$	0.75 $[0.32, 1.00]$
Class-mean permutation (idea 1)		
$\mathrm{AS}_{\mathrm{cperm}}$, released	0.64 $[0.28, 0.90]$	0.64 $[0.22, 0.92]$
Δ_{align}, released	0.64 $[0.28, 0.90]$	0.64 $[0.24, 0.91]$
$\mathrm{AS}_{\mathrm{cperm}}$, ridge	0.70 $[0.33, 0.94]$	0.67 $[0.24, 1.00]$
Δ_{align}, ridge	0.09 $[-0.57, 0.61]$	0.13 $[-0.58, 0.63]$
Translator-free and energy-free scores		
$\mathrm{NCM}_{\mathrm{null}}$ (idea 5)	0.45 $[-0.11, 0.90]$	0.42 $[-0.22, 0.92]$
null zero-shot NZS (B3)	0.30 $[-0.31, 0.89]$	0.38 $[-0.28, 0.96]$
selectivity R, k=20 (idea 3)	0.15 $[-0.44, 0.59]$	0.05 $[-0.59, 0.63]$
Geometry (exploratory)		
$\mathrm{AS}_{\mathrm{oop}}$ (out-of-plane only)	0.67 $[0.37, 0.93]$	0.67 $[0.35, 0.96]$
$\mathrm{AS}_{\mathrm{in}}$ (in-plane only)	0.67 $[0.33, 0.93]$	0.67 $[0.29, 1.00]$
SING's IS (B4)		
IS against row-space energy $1-\rho$	-0.55 $[-0.83, -0.10]$	-0.49 $[-0.84, 0.02]$

Table 8: Round-4 scores against SING's order (Kendall τ, percentile 95% CI, 2000 model resamples). A1: AS after removing $\sqrt{\rho_0/\rho}\,\Pi f$ (§B.2.1); ridge: our retrained translators on the test half (§B.2.4); $\mathrm{AS}_{\mathrm{cperm}}$ and Δ_{align}: §B.2.3; $\mathrm{NCM}_{\mathrm{null}}$, NZS and R: §B.2.5; geometry and IS: §C.4.

- *Null zero-shot accuracy* NZS: zero-shot classification from the translated null part alone, minus a permuted control. It passes its validity gate (no change under rescaling of Πf; τ=1 with planted content on all three bases), but it is not energy-free ($\tau(\cdot, \rho)$=0.45 and 0.53), and against SING it gives 0.30 $[-0.31, 0.89]$ (E12) and 0.38 (S11): inconclusive. Given ρ, its partial association with the order has negative point estimates, but every CI includes 0 (-0.60 $[-0.89, 0.50]$, -0.63 $[-0.92, 0.47]$ and -0.54 $[-0.93, 0.86]$ on all 13, E12 and S11).
- *Selectivity R*: AS after removing the top-20 between-class null directions (estimated on held-out images) over AS after removing the same energy at random. Within each model R differs from 1 (CI excludes 1 on 12 of 12 models), but in both directions (4 above 1, 8 below). Across models it does not reproduce the order (τ=0.15 and 0.05; k=5 and 50 give the same).

None of these scores tracks SING's order, and none is both energy-free and fully calibrated.

C.3 Organisation score (round 5, pre-registered)

The scores above measure how much class information the null part carries, which rises with its energy. $\mathrm{SO}_{\mathrm{null}}$ instead asks whether the null class means are *arranged* like the class texts. It is the Spearman correlation between a cross-validated (crossnobis) class-dissimilarity matrix of the null coordinates (Walther et al., 2016) and the dissimilarity matrix of SING's class-text embeddings, both double-centred, in the manner of representational similarity analysis (Kriegeskorte et al., 2008; Nili et al., 2014), divided by the square root of its split-half reliability. It needs no translator and is exactly invariant to rescaling the null part. A secondary score, XCC_{24}, is a cross-fitted alignment of the null and text class Gram matrices in random 24-dimensional frames. Both scores pass the pre-registered invariance, derangement and planted-code gates on all 13 models: exact invariance to scale and rotation, no signal after class means are deranged across classes, and a response to a semantic but not to an arbitrary planted class code. Both are estimable on 12 of E12 and 11 of S11.[1] After double-centring, the derangement gate is close to satisfied by construction. The semantic plant is built to raise a text-alignment score. These two gates are therefore sanity checks rather than evidence of validity (Appendix G). The corrected world C could not test $\mathrm{SO}_{\mathrm{null}}$: as ρ grows at

[1]Because $\mathrm{SO}_{\mathrm{null}}$ is scale-free, it is defined even where the null energy is negligible: DenseNet121 (ρ=1.8 $\times$ 10^{-8}) has $\mathrm{SO}_{\mathrm{null}}$=0.115. DenseNet121 is in neither E12 nor S11.

fixed L, its reliability falls below the floor of 0.10, so only one base has three estimable rows, and by the pre-registered rule this is not a kill. In worlds M and D both scores stay flat as L varies (within a factor 1.07 and 1.06). Against SING's order $\mathrm{SO}_{\mathrm{null}}$ gives τ=0.33 $[-0.29, 0.79]$ on E12 and 0.45 $[-0.21, 0.88]$ on S11: INCONCLUSIVE. It also follows ρ (0.42, 0.53), and given ρ its partial association is 0.03 and 0.23, with CIs that include 0. Without the reliability correction, raw SO gives 0.48 and 0.64 against SING and follows ρ more closely (0.58, 0.71; post hoc). XCC_{24}, averaged over random 24-dimensional frames, gives -0.12 and -0.05 (DOES-NOT-TRACK for this variant), although across all 13 models it agrees with $\mathrm{SO}_{\mathrm{null}}$ (τ=0.49). In post-hoc checks the full-null XCC gives 0.33 and 0.42 against SING, so at n=13 the organisation result depends on the method. The other pre-registered descriptives are in Appendix G. $\mathrm{SO}_{\mathrm{null}}$ is nearly unrelated to the between-class share η^2 (τ=0.03, 0.05). With the row-space class Gram projected out, the full-null XCC is at or below 0.05 on 7 of 13 models and above it on 6 (up to 0.43). This is below the pre-registered 75% bar for INHERITED. The plant check passed narrowly (minimum 0.109 against a bar of 0.10), so the pre-registered statement is NOT INHERITED. On about half of the models the congruence is therefore largely explained by the row-space class geometry, and we do not claim that null congruence is in general independent of it. The thresholds were set after scratch runs on five models for SO-type and three for XCC-type scores, which the pre-registration discloses. Appendix G reports how each label depends on its bar.

C.4 How AS grows with energy

Decomposition. Split the removed translated null component $\delta = A\Pi f$ into its part in the plane of $T(f)$ and the class text t and the orthogonal, out-of-plane part. The out-of-plane part changes the angle to t only at second order, by $\frac{1}{2}\cot\theta\,\|\delta_{\mathrm{oop}}\|^2/\|T(f)\|^2$. It does so whatever direction δ_{oop} has, so it is blind to the class text. If the translator's squared gain per null PC scales with the PC's variance as λ^s, a first-order argument predicts the energy exponent $a_{\mathrm{pred}} = (1+s)/2$.

Pre-registered tests. On a synthetic model with a known gain slope $s \in \{-0.4, \ldots, 0.2\}$ the fitted exponent is within 0.027 of $(1+s)/2$ (G3, pass). On the two true DINO backbones of §B.5, which were not used to design the test, the pre-registered checks pass on both: the Gaussian closed form orders the surrogate AS perfectly (Spearman 1), the out-of-plane-only removal shifts the angle ($[0.265, 0.269]$ and $[0.516, 0.523]$ degrees), the closed form is within 0.033 and 0.066 of the measured out-of-plane shift, and a_{pred} is within 0.1 of a_{fit} (0.603 against 0.669; 0.569 against 0.580; Table 19 in Appendix D). The out-of-plane share of AS is 0.52 and 0.80. These results are consistent with the account, but they are not a strong test of it. The Spearman check in G2 uses only four ρ_t points, and the G3 generator builds in the gain law. This gives a mechanism by which AS responds to null energy without regard to the class text. It does not show that the null space holds no semantics.

Exploratory, 13 models (post hoc). With the released translators the out-of-plane share of AS runs from 0.20 to 0.98, and the in-plane and out-of-plane parts track SING equally (τ=0.67 and 0.67 on E12). a_{pred} is within 0.1 of a_{fit} on 6 of the 8 models where both can be computed; it misses on BiT (0.08 against 0.40) and on DINOv2-L (0.29 against 0.39).

SING's IS. SING's invariant-space shift IS is not a proxy for row-space energy: $\tau(\mathrm{IS}, 1-\rho)$ is -0.62, -0.55 and -0.49 on the three sets, short of the pre-registered 0.6 on two. IS does, however, rise with null energy (CIs $[-0.89, -0.21]$, $[-0.83, -0.10]$ and $[-0.84, 0.02]$, excluding 0 on two sets), and it tracks SING's order (τ=0.74, 0.70 and 0.71).

C.5 True DINO backbones

In round 4 we evaluated the two DINO backbones that were released with a linear ImageNet head, ViT-B/16 and ViT-S/16 (Caron et al., 2021), together with a supervised timm AugReg ViT-B/16 as a control (Table 9). Their 50k top-1 is 78.06%, 76.91% and 84.54% (the DINO values are within 0.2 points of the published linear-evaluation accuracies), and the pre-registered feature checks pass. Each DINO head leaves a null space of dimension 536 (ρ=0.189 and 0.437); the AugReg head has none. There is no released SING

Model	top-1 (50k)	d_{null}	ρ	fidelity	AS (ridge) [rank/15]	95% PI from E12 law	NCM_{null}
DINO ViT-B/16	78.06	536	0.189	0.819	0.514 [8]	$[0.380, 0.884]$	56.9
DINO ViT-S/16	76.91	536	0.437	0.816	0.652 [9]	$[0.661, 1.573]$ (below)	53.4
AugReg ViT-B/16	84.54	0	0	–	–	–	–

Table 9: True DINO backbones with their released linear heads (§B.5), ridge translators on the test half. Rank among 15 models (1 = least leakage); prediction interval from the E12 energy law $\log \text{AS} \sim \log \rho$. AugReg ViT-B/16: supervised control with an empty null space.

translator for these models, so we use ridge translators fit as in §B.2.4 (fidelity 0.819 and 0.816) and compare with the 13 models under their ridge translators. AS is 0.514° (ViT-B/16) and 0.652° (ViT-S/16), ranks 8 and 9 of 15 (median of the 13: 0.399°). The pre-registered raw-AS question (Q-DN1) asks whether both DINO models rank among the four lowest. Its outcome is "SING-inconsistent", since both lie above the median of the 13. Raw ridge AS is not SING's own measure, however. It also tracks null energy, which for both models is above the median of the 13 (ρ=0.189 and 0.437). Post hoc, we therefore put more weight on the energy-adjusted reading (Q-DN2). Against the energy law fitted on E12, ViT-B/16 lies inside the 95% prediction interval ($[0.38, 0.88]$, predicted 0.58) and ViT-S/16 lies just below it ($[0.66, 1.57]$, predicted 1.02). ViT-S/16 thus has less AS than its energy predicts. That leans toward SING's account for that model, and the pre-registered outcome is mixed. For Δ_{align} and NCM_{null}, both models fall inside the prediction intervals from ρ. The pre-registered "least leaking" label, which needs both models among the four lowest, holds for neither score. ViT-S/16 alone is among the four lowest on both (Δ_{align} rank 3 of 15, NCM_{null} rank 2 of 14), while ViT-B/16 ranks 13 and 6. Both DINO heads are linear probes on frozen, concatenated block features, a different regime from the supervised heads of the 13 models, so this comparison is indicative only.

C.6 Size-corrected scores and class-level claims

Size-corrected scores. $\text{AS}_{\text{fair}} = \text{AS}_{\text{null}}/\text{AS}_{\text{rand}}$ divides AS by the AS of an energy-matched random removal. We used three families of controls, and name the family each time. In *family A*, the random subspace is Haar over the full feature space and changes the logits. *Family B* draws from the lowest-σ row-space directions of W. It is not logit-preserving either: it moves the logits by up to 14–74 logit SDs on models with a large span (VGG, ResNeXt; Table 12). *Family C* compares a 24-dimensional null subspace with a family-B control of matched energy. Point τ against SING on all 13 models is -0.18 (A), -0.41 (B) and -0.13 (C), and on S11 it is -0.56, -0.60 and -0.27. All fall below the pre-registered 0.3 bar.

Over eight normalisers (AS/ρ^a for $a \in \{0.25, 0.43, 0.5, 1\}$, $\text{AS}/d_{\text{null}}$, families A–C), the 95% CI excludes AS_{SING}'s 0.82 for 7 of 8 normalisers on all 13 models. On S11 it does so for exactly 5 of 8, so the weak "differs from" criterion passes at the threshold (5/8). The pre-registered reversal criterion (CI entirely below 0 under at least 5 of 8 normalisers) fails. It fails on all 13 models (0/8), and on S11 only family B meets it ($[-0.89, -0.23]$). That single pass comes from a control that is not logit-preserving. Normalising by the fitted exponent leaves a positive τ ($\rho^{0.43}$: +0.33 $[-0.15, 0.77]$; $\sqrt{\rho}$: +0.26), and family-A AS_{fair} over-corrects: its Spearman correlation with ρ is -0.79 $[-1, -0.23]$ on S11 (Fig. 5, Appendix E). Size-corrected rankings therefore *differ* from SING's, but the direction depends on the normaliser, and we make no reversal claim. Model ranks from AS_{SING} and AS_{fair} also shift with the null tolerance. Adjacent-tolerance τ falls to 0.87 and 0.82, below the pre-registered 0.9, while ρ stays at or above 0.92.

Class-level claims. For each of SING's testable claims we define a signed effect (positive = SING's direction) and bootstrap images within class (1000×, BCa intervals; Table 10). A claim *holds* if the CI is above 0, is *reversed* (rev.) if below, and is *not confirmed* (n.c.) if it covers 0. Rows that share a computation are merged. Under AS_{SING}, 7 claims hold, 3 reverse (one borderline) and 1 is contradicted. The reversed claims are C4 (DinoViT does not have the lowest class AS; ConvNeXt and DenseNet are lower), C8 (ResNet's porcupine and sports-car classes are not in its top decile) and C10 (jellyfish ≫ camel; effect -0.107, BCa $[-0.210, -0.006]$). C10 is borderline: its percentile interval $[-0.206, 7.9\times10^{-4}]$ covers 0. C9 ("no correlation" between ResNet and DinoViT class AS) is contradicted by a small correlation (-0.033, BCa CI excludes 0).

ID	Claim (short)	Effect AS_{SING} [BCa 95% CI]	AS_{SING}	AS_{fair}
C1/C11	DinoViT best ratio / least steerable (proxy)	$0.149\ [0.142, 0.156]$	holds	opp.
C2	ResNeXt worst ratio (proxy)	$0.323\ [0.303, 0.343]$	holds	opp.
C3/C6m	ResNet > DinoViT (class mean)	$1.383\ [1.372, 1.394]$	holds	opp.
C4	DinoViT least leakage	$-0.293\ [-0.298, -0.289]$	**rev.**	opp.*
C5	ResNeXt top-2 of 5	$1.442\ [1.424, 1.462]$	holds	opp.
C6 sd	ResNet class SD > DinoViT	$0.744\ [0.711, 0.785]$	holds	opp.
C7	DinoViT per-class $\lvert AS\rvert < 1°$	$0.500\ [0.499, 0.500]$	holds	n/a
C8 porcupine	Porcupine ≥90th pct (ResNet)	$-5.2\ [-8.4, -1.9]$	**rev.**	opp.
C8 sports car	Sports car ≥90th pct (ResNet)	$-29.0\ [-34.1, -23.9]$	**rev.**	opp.
C9 spearman	No ResNet–DinoViT class corr.	$-0.033\ [-0.074, -0.012]$	contra.	contra.
C10	Jellyfish ≫ camel	$-0.107\ [-0.210, -0.006]$	**rev.**†	opp.
C12	Supp. Fig. 12b order (τ)	$0.821\ [0.56, 1.00]$‡	holds	n.c.‡
C13	EVA02 target-space order	–	untestable	untestable

Table 10: SING's class-level claims under AS_{SING} (BCa 95% CI, images resampled within class, so the CIs are conditional on the 13 fitted translators) and family-A AS_{fair}. rev. = CI on the opposite side of 0; n.c. = not confirmed; opp. = opposite side under AS_{fair}, a diagnostic since AS_{fair} over-corrects; contra. = a nonzero correlation where SING reports none. C1/C11 and C3/C6 mean are one computation each. C1/C2/C11 use $|AS|$ proxies for SING's ratio and steerability. *Under AS_{fair}, C4 coincides numerically with C1/C11 (same model attains the minimum) and is counted once. C6 SD: classes resampled. †Borderline: the percentile interval covers 0. ‡Model bootstrap; under AS_{fair}, $\tau = -0.18\ [-0.78, 0.35]$, not confirmed. C7 has no AS_{fair} analogue.

These differences may reflect protocol differences (for C10, SING used about 30 concepts and 1300 images). They are not caused by size correction. Under AS_{fair} (family A) the other testable effects fall on the opposite side (opp.). Because AS_{fair} over-corrects, we treat these as diagnostics, not reversals. The image-bootstrap CIs ignore uncertainty from the choice of models and normaliser, so they are narrow. For C6 (class SD) the bootstrap now resamples classes, since the effect is a spread over classes; the point estimate lies inside both the BCa and the percentile interval under both scores (AS_{SING}: $0.744\ [0.711, 0.785]$). Under AS_{fair} the effect is $-0.203\ [-0.243, -0.166]$, but correcting the SDs for within-class sampling noise shrinks it to -0.025 (AS_{SING}: 0.752), so the AS_{fair} diagnostic for C6 is fragile.

D Additional tables

Model	ρ	ours IS/|AS|	SING IS/AS	SING/ours
VGG16	0.350	17.75	24.26	1.37
VGG19	0.339	15.56	19.89	1.28
DenseNet121	1.8×10^{-8}	41.48	70.71	1.70
ResNet50	0.146	17.40	24.81	1.43
"DinoViT"	0.005	20.95	70.16	3.35
EffNet-B0	0.130	22.15	36.28	1.64
BiT-R50x1	0.046	24.93	47.21	1.89
ResNeXt101	0.451	12.60	13.88	1.10
ConvNeXt-B	0.013	32.86	37.38	1.14
Swin-L	0.274	21.21	29.18	1.38
DINOv2-L	0.322	15.49	16.61	1.07
DeiT3-L	0.348	9.73	9.51	0.98
EVA02-L	0.009	21.64	54.32	2.51

Table 11: Like-for-like reproduction. Our IS/|AS| on the 10k subset against SING's IS/AS (digitised Supp. Fig. 12b). $\tau(\text{ours}, \text{SING}) = 0.744\ [0.33, 1.00]$.




Figure 2: Agreement with SING's order under the energy controls and interventions of §B.2 (95% percentile CIs). Dotted line: τ=0.3; dashed: τ=0.6, the pre-registered bars.

Model	d_{null}	ρ	κ	γ	AS_{SING}	A1	AS_{surr}	fair A	fair B	B max Δlogit/SD
VGG16	3096	0.350	0.119	0.34	1.088	0.084	0.922	0.708	0.867	14.4
VGG19	3096	0.339	0.123	0.36	1.256	0.094	0.879	0.716	1.087	13.7
DenseNet121*	27	1.8×10^{-8}	2.5×10^{-8}	1.36	2.5×10^{-4}	–	2.4×10^{-4}	0.152	0.671	1.5×10^{-8}
ResNet50	1048	0.146	0.281	1.93	1.676	0.160	1.176	0.855	0.989	0.3
"DinoViT"	24	0.005	0.013	2.46	0.294	0.284	0.296	1.632	1.220	5.0×10^{-3}
EffNet-B0	280	0.130	0.030	0.23	0.443	0.076	0.378	0.889	1.267	0.8
BiT-R50x1*	1048	0.046	0.061	1.31	0.557	0.153	0.589	0.042	1.142	9.3×10^{-2}
ResNeXt101	1048	0.451	0.219	0.49	1.999	0.112	1.476	0.707	0.591	74.4
ConvNeXt-B	24	0.013	0.002	0.17	0.080	0.049	0.085	0.974	0.961	4.1×10^{-2}
Swin-L	536	0.274	0.151	0.55	1.019	0.105	1.170	0.829	1.130	7.5
DINOv2-L	1048	0.322	0.165	0.51	1.499	0.104	0.960	0.712	0.961	6.0
DeiT3-L	24	0.348	1.085	3.11	5.048	0.215	3.364	1.065	0.776	16.4
EVA02-L	24	0.009	0.031	3.47	0.417	0.302	0.411	2.612	1.306	2.3×10^{-2}

Table 12: Per-model scores on the 10k subset at tolerance 10^{-5}. κ: CLIP-space null energy; $\gamma = \kappa/\rho$; A1: AS after removing $\sqrt{\rho_0/\rho}\,\Pi f$; AS_{surr}: AS with leak-free surrogate null content; fair A/B: AS_{fair} families; last column: largest logit change of the family-B control in logit SDs (family B is not logit-preserving). *Excluded by the screen. Family C: Table 15.

	AS at α=0, ρ_t =					AS(α)/AS(0), ρ_t=0.2	
Model	0.01	0.05	0.2	0.45	slope [95% CI]	α=0.1	α=0.3
ResNet50	0.371	0.665	0.817	1.935	0.377 [0.375, 0.379]	1.088	1.508
ResNeXt101	0.074	0.175	0.453	1.105	0.690 [0.689, 0.692]	1.040	1.353
DINOv2-L	0.082	0.192	0.485	1.151	0.677 [0.676, 0.678]	1.049	1.363

Table 13: Leak-free null content (§B.2.2). AS at α=0 against the surrogate's null energy ρ_t; OLS slope of logAS on $\log \rho_t$ with 1000× image bootstrap; AS response to a planted concept at ρ_t=0.2.

Model	d=24, $\hat{a}$ = 0.431	d=24, $\hat{a}$ = 0.388	d=24, $\hat{a}$ = 0.485	d=100, $\hat{a}$ = 0.431	d=100, $\hat{a}$ = 0.388	d=100, $\hat{a}$ = 0.485
ResNet50	1.50 [1.48, 1.51]	1.75 [1.73, 1.77]	1.23 [1.21, 1.24]	1.18 [1.17, 1.19]	1.30 [1.28, 1.31]	1.05 [1.03, 1.06]
ResNeXt101	0.74 [0.73, 0.76]	0.85 [0.83, 0.87]	0.63 [0.61, 0.64]	0.97 [0.96, 0.99]	1.06 [1.04, 1.07]	0.87 [0.86, 0.89]
DINOv2-L	0.98 [0.97, 0.99]	1.06 [1.04, 1.07]	0.89 [0.88, 0.90]	0.91 [0.89, 0.92]	0.96 [0.95, 0.97]	0.85 [0.83, 0.86]
BiT-R50x1*	0.009 [0.009, 0.009]	0.010 [0.010, 0.010]	0.008 [0.008, 0.008]	0.012 [0.012, 0.012]	0.013 [0.013, 0.013]	0.011 [0.011, 0.011]

Table 14: PC bands against the fitted energy law (§C.1): H with 1000× image-bootstrap CIs at three values of $\hat{a}$ (E1 point estimate and CI ends). $H < 1$: top PCs carry less AS than energy predicts. *BiT is reported but not counted.

	VGG16	VGG19	Dense	RN50	DinoViT	Eff	BiT	RNX	ConvNeXt	Swin	DINOv2	DeiT3	EVA02
fair C	1.32	1.35	0.71	1.14	1.20	1.44	135.6	1.04	0.97	1.08	1.00	0.79	1.33

Table 15: Family-C $\mathrm{AS}_{\mathrm{fair}}$ per model (`r2/results/fix2_models.csv`).

Kind	Null content	all 13	E12	S11	partial r given ρ (S11)
content-free	$\mathcal{N}(\mu, \Sigma)$ (round 3, $\mathrm{AS}_{\mathrm{surr}}$)	0.69 [0.39, 0.92]	0.64 [0.31, 0.90]	0.64 [0.27, 0.92]	0.52 [−0.07, 0.94]
content-free	$\mathcal{N}(0, \Sigma)$	0.72 [0.43, 0.94]	0.67 [0.38, 0.93]	0.67 [0.35, 0.96]	–
content-free	isotropic $\mathcal{N}(0, I)$	0.49 [0.04, 0.89]	0.39 [−0.04, 0.87]	0.60 [0.16, 0.96]	–
content-free	mean only (μ)	0.49 [0.07, 0.83]	0.39 [−0.05, 0.74]	0.38 [−0.16, 0.79]	–
content-free	real c permuted across images, $\mathrm{AS}_{\mathrm{perm}}$	0.69 [0.39, 0.92]	0.64 [0.31, 0.90]	0.64 [0.27, 0.92]	0.52 [−0.07, 0.94]
class content	real c permuted within class	0.79 [0.50, 1.00]	0.76 [0.46, 0.97]	0.78 [0.44, 1.00]	–
excess	$X = \mathrm{AS}_{\mathrm{SING}}/\mathrm{AS}_{\mathrm{surr}}$	0.54 [0.14, 0.83]	0.58 [0.21, 0.86]	0.60 [0.24, 0.91]	0.79 [0.02, 0.97]
excess	$\mathrm{AS}_{\mathrm{SING}} - \mathrm{AS}_{\mathrm{surr}}$	0.59 [0.15, 0.89]	0.64 [0.24, 0.90]	0.67 [0.27, 0.96]	0.81 [0.02, 0.98]
excess	$\mathrm{AS}_{\mathrm{SING}} - \mathrm{AS}_{\mathrm{perm}}$	0.62 [0.15, 0.92]	0.67 [0.25, 0.96]	0.71 [0.28, 1.00]	0.77 [0.04, 1.00]
excess	within-class/across-image	0.41 [0.00, 0.69]	0.45 [0.12, 0.74]	0.45 [0.09, 0.75]	0.57 [−0.48, 0.93]
–	real ($\mathrm{AS}_{\mathrm{SING}}$)	0.82 [0.56, 1.00]	0.79 [0.51, 1.00]	0.82 [0.51, 1.00]	0.78

Table 16: Surrogate null content (§B.2.2): Kendall τ against SING [percentile 95% CI], released translators, 3 draws per surrogate (5 for the Gaussian), each rescaled to the model's own null energy. Last column: partial Spearman given ρ on S11 with its CI.

Model	own ρ	AS(α)/AS(0), ρ_t=0.2 α=0.1	AS(α)/AS(0), ρ_t=0.2 α=0.3	AS(α)/AS(0), own ρ α=0.1	AS(α)/AS(0), own ρ α=0.3	AS (°) own ρ, α=0/0.3	r_E
ResNet50	0.146	1.088	1.508	1.099	1.581	0.768/1.214	2.39
ResNeXt101	0.451	1.040	1.353	1.018	1.137	1.107/1.259	5.37
DINOv2-L	0.322	1.049	1.363	1.019	1.169	0.762/0.891	4.92

Table 17: Planted content (§B.2.2): AS response to a planted concept at the surrogate energy ρ_t=0.2 and at each model's own ρ, absolute AS at its own ρ, and $r_E = \mathrm{AS}(\rho_{75})/\mathrm{AS}(\rho_{25})$, the AS change the energy law gives across the interquartile range of ρ.

Estimator	World C: $\lvert\tau(\cdot,\rho)\rvert \le 0.2$ RN50	RNX	DINOv2	World M: $\tau(\cdot,L) \ge 0.8$ RN50	RNX	DINOv2	World D: $\tau(\cdot,L) \ge 0.6$ RN50	RNX	DINOv2	diagnostic
ρ	1.00	1.00	1.00	1.00	1.00	1.00	$-0.03^{\dagger}$	$0.00^{\dagger}$	$0.06^{\dagger}$	no
AS	0.97	1.00	1.00	0.33	1.00	1.00	0.12	1.00	1.00	no
A1	0.73	0.64	0.48	0.52	−0.76	−0.79	−1.00	0.70	0.61	no
$\mathrm{AS}_{\mathrm{gauss}}$	1.00	1.00	1.00	0.94	1.00	1.00	−0.52	−1.00	−0.76	no
X	−0.03	−0.88	−0.52	−0.45	−0.73	−0.76	0.91	1.00	1.00	no
Δ_{align}	−1.00	−1.00	−1.00	−0.21	0.58	0.12	0.91	1.00	1.00	no
$\mathrm{NCM}_{\mathrm{null}}$	−0.72	−0.99	−0.99	0.81	0.88	0.44	1.00	1.00	0.99	no
selectivity R	−0.91	−0.21	−0.15	−0.06	−0.79	0.70	−0.33	−0.94	−0.33	no
exponent a	0.59	0.47	0.43	0.31	0.53	0.47		–		

Table 18: Calibration worlds (§B.2.5): Kendall τ against ρ in world C and against L (class-mean null energy as a share of total feature energy) in worlds M and D, on three bases. Criteria in the header; "diagnostic" requires all nine. †In world D, ρ is fixed by design and varies only through the small cross term between class means and permuted residuals, so its τ with L is ≈ 0 (near-ties) and carries no information. Last row: fitted energy exponent.

Model	AS	$\mathrm{AS}_{\mathrm{in}}$	$\mathrm{AS}_{\mathrm{oop}}$	oop share	oop closed-form err.	$a_{\mathrm{pred}} = (1+s)/2$	a_{fit}
Exploratory (post hoc): 13 models, released translators							
VGG16	1.088	0.786	0.667	0.61	0.086	0.42	0.36
VGG19	1.256	0.857	0.678	0.54	0.086	0.42	0.36
ResNet50	1.676	0.938	1.645	0.98	0.160	0.40	0.44
"DinoViT"	0.294	0.291	0.096	0.33	0.016	0.33	–
EffNet-B0	0.443	0.395	0.201	0.45	0.024	0.69	0.67
BiT-R50x1	0.557	0.502	0.405	0.73	0.052	0.08	0.40
ResNeXt101	1.999	1.169	1.287	0.64	0.116	0.44	0.45
ConvNeXt-B	0.080	0.081	0.016	0.20	0.002	0.79	–
Swin-L	1.019	0.938	0.849	0.83	0.096	0.41	0.45
DINOv2-L	1.499	0.857	1.096	0.73	0.124	0.29	0.39
DeiT3-L	5.048	1.926	4.626	0.92	0.185	0.37	–
EVA02-L	0.417	0.393	0.229	0.55	0.044	−0.03	–
Confirmatory (pre-registered G2): true DINO, ridge translators							
DINO ViT-B/16	0.514	0.384	0.267	0.52	0.033	0.60	0.67
DINO ViT-S/16	0.652	0.630	0.519	0.80	0.066	0.57	0.58
Synthetic calibration (G3): known gain slope s							
s	−0.4, −0.2, 0.0, 0.2				$a_{\mathrm{fit}} - (1+s)/2$:	−0.002, −0.004, 0.006, 0.027	

Table 19: Geometric decomposition of AS (§C.4), degrees. oop: out-of-plane; closed-form error: relative error of $\frac{1}{2}\cot\theta\|\delta_{\mathrm{oop}}\|^2/\|T(f)\|^2$ among images with $\|\delta_{\mathrm{oop}}\|/\|T(f)\| < 0.5$; a_{fit}: energy exponent fitted on matched-d cells (– where the cell fit is not available). DenseNet omitted ($\rho \approx 0$).

E Energy law, Exp 1 and checkpoint accuracy

Model	r	2σ band	R^2 (vs $d \equiv$ vs ρ_d)
ResNet50	10.15	[5.83, 14.48]	0.983
ResNeXt101	11.44	[6.93, 15.95]	0.977
DINOv2-L	10.48	[8.85, 12.10]	0.974
BiT-R50x1	0.060	[0.057, 0.063]	0.512

Table 20: Exp 1: $r = \mathrm{AS}(d{=}1048)/\mathrm{AS}(d{=}24)$ over random null subspaces (20 seeds). For random subspaces ρ_d is linear in d, so the two R^2 coincide. At matched $d{=}24$ across 8 models, τ against SING is 0.29 ($p{=}0.40$).




Figure 3: Exp 1: mean |AS| against subspace size d (a) and removed energy ρ_d (b). BiT collapses at the full null (translator cancellation). Full-null anchors: ResNet50 1.682°, ResNeXt101 1.999°, BiT 0.556°, DINOv2-L 1.499°.




Figure 4: Energy law: |AS| against ρ over 76 cells on five models (ResNet50, ResNeXt101, DINOv2-L, VGG16, EVA02-L) at fixed $d \in \{24, 100, 280\}$ and fixed $\rho \in \{0.5\%, 2\%, 8\%\}$. Solid: pooled fit ($a$=0.431); dashed: $\sqrt{\rho}$. At fixed d the high/low-energy ratio exceeds 3× on all 4 evaluable models; at fixed ρ the max/min across d exceeds 1.5 in several cells (up to 2.29), so the pre-registered rating is *mixed*.




Figure 5: (a) AS_{SING} rises with ρ. (b) Family-A AS_{fair} falls with ρ: it over-corrects. $\times$: models excluded by the screen.




Figure 6: τ against SING for each normaliser and for ρ alone (2000× model bootstrap), on all 13 models and on S11. Dotted line: the τ=0.3 bar.




Figure 7: Top-1 on ImageNet-val (native evaluation transform) of the five public ViT-L/16 candidates. None matches SING's reported 84.0%.

F Planted leakage, score search and the flatness rule

Planted leakage (E3). We planted a CLIP concept direction (`red`, `striped`, `water`) into the null spaces of 8 models at log-uniform $\alpha \in [0.01, 1]$ over 50 trials, with logits unchanged (max $|\Delta\text{logit}| \leq 2.3\times10^{-5}$). Kendall τ against the planted ranking, averaged over concepts, is 0.386 $[0.324, 0.448]$ for AS_{SING} and 0.109 $[0.046, 0.171]$ for AS_{fair} (both α=0-subtracted). The pre-registered target ($\text{AS}_{\text{fair}} \geq 0.8$, $\text{AS}_{\text{SING}} \leq 0.5$) was not met. Neither score recovers planted strength well across models.

E8 (pre-registered; killed). A probe-based null-content score (ridge-probe R^2 on null coordinates, z-scored against energy-matched random subspaces) gave τ=-0.331 $[-0.392, -0.273]$ on the planted task and was flat on 0/4 models. Three implementation caveats apply: the z-score saturates, λ was chosen by approximate leave-one-out rather than the pre-registered exact cross-validation, and λ sat at the grid floor in 18 of 96 fits.

E9 (pre-registered; killed). We screened 20 candidate scores on two development concepts. The rule required $\tau \geq 0.8$ and flatness (max / min ≤ 1.5 across nested null subspaces) on at least 3 of 4 models at $\alpha \in \{0.1, 1\}$. No candidate passed. The best was M1, a debiased null-leakage estimate $\hat{L}^2 = (\|\sum_i Pf_i s_i\|^2 - \sum_i \|Pf_i\|^2 s_i^2)/(n(n-1)\mathbb{E}\|f\|^2)$ with standardised concept scores s_i, scored as $\sqrt{\max(\hat{L}^2, 0)}$. It reached τ=0.976 $[0.963, 0.988]$ but was flat on 0/4 models.

The flatness rule is ill-posed. We tested the rule on synthetic Gaussian features with a known head (m=400, d_{null}=300). Our exact oracle is the planted amplitude inside the removed subspace. It fails the rule with max / min 3.55 and 3.48 ($\approx \sqrt{300/24}$), because a larger removed subspace contains more of the plant. A revised rule (max / min of score/oracle ≤ 1.5, post hoc) is passed by M1 (ratios 1.00–1.03). Under the revised rule M1 is flat on 4/4 models, and E8's score on 0/4. E8 and E9 remain killed as registered.

Holdout (post hoc). We ran the E9 holdout on four held-out concepts (water, green, thin, knitted; 50 trials at seed 1; linear and nonlinear plants) for the six candidates declared in the round-2 pre-registration plus AS_{SING} and AS_{fair}, with the E9 pass rule (Table 21). Only M1 meets both τ thresholds. Under the registered flatness rule no candidate passes; that rule also fails for the oracle (above). Under the revised rule, M1 passes. Paired over trials (1000×, seed 0), τ(M1)$-\tau(\text{AS}_{\text{fair}})$ is 0.77 [0.71, 0.82] for the linear plant and 1.01 [0.96, 1.06] for the nonlinear plant, so M1 tracks the planted leakage better than AS_{fair} under both

Score	lin. τ [95% CI]	nl. τ	flat	rev. flat	pass
M1	0.93 [0.91, 0.95]	0.97	0/0	4/4	rev.
M2	0.44 [0.39, 0.48]	0.46	0/0	0/0	no
S9	0.45 [0.40, 0.51]	0.44	0/1	2/0	no
S10	0.37 [0.33, 0.42]	0.52	3/4	0/0	no
M5 ($AS/\sqrt{\rho}$)	0.22 [0.18, 0.27]	0.15	0/0	0/0	no
S4 (AS/ρ)	−0.08 [−0.15, −0.01]	−0.14	0/0	0/0	no
AS_{SING} (raw)	0.33 [0.27, 0.40]	0.36	0/0	0/0	no
AS_{fair} (sub.)	0.17 [0.11, 0.22]	−0.04	0/0	0/0	no

Table 21: E9 holdout (post hoc; AS_{fair} is α=0-subtracted; water, green, thin, knitted; 50 trials, seed 1; 8 models). Flat = number of the 4 large-null models flat at α=0.1/1 under the registered rule; rev. flat = under the revised score/oracle rule. Pass: lin. $\tau \geq 0.8$, CI lower ≥ 0.7, nl. $\tau \geq 0.6$, flat on $\geq 3/4$ at both α (yes = registered rule, rev. = only with the revised rule).

plants. The revised rule also changes which candidate counts as flat: S10, the only candidate flat under the registered rule (3/4 and 4/4 models at α=0.1/1), is flat on 0/4 and 0/4 under the revised one. The plant is written along the null projection that M1 itself measures, and M1, unlike the AS-family scores, is given the concept score that defines the plant. This comparison therefore favours M1 by construction. One of the four held-out concepts, water, was also an E3 plant concept whose results we had seen before choosing the holdout set; its inclusion was pre-registered, but the set is not fully unseen. M1 was picked after the DEV results and the flatness rule was revised after the oracle test, so this holdout is post hoc. E9 stays a KILL as registered, and M1 is a candidate for a future pre-registered test, not a validated score.A reduced-draw mode (5 instead of 20 random draws for AS_{fair}, 2 instead of 5 nested bases, S9 omitted), declared before it was run, gives the same M1 and AS_{SING} values and the same flatness verdicts. AS_{fair} moves by +0.02 (linear) and +0.06 (nonlinear; 0.057), and the run takes 36 min on 8 CPU cores. It fails both targets we set ($\pm$0.03, under 30 min), so the full run (1.95 h) is the reference (Appendix J).

M1 on the 13 models (post hoc, descriptive). At α=0 on the full null, averaged over SING's 173 concepts, M1 gives τ=0.667 $[0.29, 0.94]$ against SING, an interval that includes AS_{SING}'s value. M1 orders the models much as ρ does (τ=0.79), as expected for a score scaled by total feature energy. Its holdout validation favours it by construction (the plant is written along the projection it measures), so this agreement is not independent evidence about energy. We treat M1 as a candidate for a future pre-registered test, not as a validated score.

G Round 5: calibration fix and organisation score

Calibration fix. Round 4 built the worlds of §B.2.5 from each image's own residual $r = c - \mu_y$. Within a class these residuals sum to zero, so a class mean estimated on one subset of images is the negative of the residual mean of the rest. This biases any estimator that compares class means across disjoint images. Round 5 permutes r across all images (seed 99000) before rescaling, and keeps the round-4 results file. The fix was coded and run, and the corrected world τ values for ResNet50 were seen, before `PREREG_R5.md` was pushed; the pre-registration states this. Permuting r across images keeps the class means, the pooled residual distribution and the total residual energy, but not class-specific residual covariance or the image-level coupling between row-space content and the null residual, so the worlds are cleaner than real features. 50 of 78 entries change (Table 18 against Table 25). By $|\Delta\tau|$ the largest changes (0.48 each) are X in world C on ResNet50 ($-0.52 \to -0.03$); A1 in world C on DINOv2-L ($0.00 \to 0.48$); X in world C on DINOv2-L ($-1.00 \to -0.52$). The most consequential is NCM_{null} in world M on DINOv2-L (from 0.80 to 0.44, so it now misses the world-M criterion on that base). In the corrected world C, NCM_{null} falls as energy grows at fixed content (τ from −0.99 to −0.72). In round 4 the world-M range of that score was 0.80–0.92. The content-diagnostic verdict is unchanged (none before, none after). In world D, ρ is no longer exactly constant, because the cross term between class means and permuted residuals is not exactly zero. Its τ with L is therefore now defined, and it is close to 0.

Scores. For $\mathrm{SO}_{\mathrm{null}}$, the images are split into four class-stratified folds (seed 99200). Crossnobis distances between class means are computed from folds $\{0, 1\}$ and from folds $\{2, 3\}$ (Walther et al., 2016). Each distance matrix and the text dissimilarity $1 - \cos$ are double-centred. $\mathrm{SO}_{\mathrm{null}}$ is the mean Spearman correlation of the two halves with the text matrix, divided by the square root of their reliability r_{rel} (Spearman between halves), and is estimable if $r_{\mathrm{rel}} \geq 0.10$. We added double-centring after the scratch run. Without it, a class-mean derangement left SO near its real value on ResNet50 (disclosed in the pre-registration). XCC_{24} takes centred half-means from two image halves per class and forms their off-diagonal cross Gram, normalised against the centred text Gram and averaged over 50 Haar 24-frames (seeds 99100+s). It is estimable if its self-term $z \geq 5$ (10 class folds, seed 99600). Permutation nulls use 200 joint class permutations (seed 99300).

Gates and outcomes. G1 (exact invariance to $\beta \in \{0.1, 10\}$ and an orthogonal map, seed 99500): SO pass, XCC pass. G2 (class-mean derangement, seeds 94000+r): no failures; the largest mean derangement score is 0.002 (SO) and 0.001 (XCC). G3 (world S, seed 99400): on all 13 models, the semantic plant at α=0.3 raises SO by at least 13 null SDs, and the arbitrary plant changes it by at most -5.0 (it lowers it). G4: SO testable on one base, XCC on two (both pass where testable); not a kill. G5: estimable on all 13. No kill fired. Inheritance: F1-partial ≤ 0.05 on 7 of 13 models (54%, below the 75% bar), with the plant check passed (minimum 0.109), so the pre-registered statement is NOT INHERITED.

What the gates show. G2 is close to satisfied by construction once both matrices are double-centred. Deranging class means permutes the rows and columns of the class dissimilarity matrix, so the gate mainly guards against per-class residual spread, which is the problem the scratch run exposed. G3 plants a random projection of the text geometry. That plant is built to raise a text-alignment score, so this gate is a sensitivity check, not evidence of validity. The arbitrary plant lowers SO because it adds class structure unrelated to the texts. SO therefore measures how the null class means are arranged relative to the texts (relative alignment), not how much class information the null part holds.

Centring correction (post hoc). The committed double-centring subtracts the off-diagonal row means of each hollow (zero-diagonal) dissimilarity matrix. For an additive class effect a_i+a_j this leaves a residual of $(a_i+a_j-2\bar{a})/(N-1)$, and the row sums of the output are not centred, so it does not remove additive per-class effects exactly. In a synthetic test with no content and large class offsets correlated with the text marginal, this version gives a spurious, estimable $\mathrm{SO}_{\mathrm{null}}$. We reran $\mathrm{SO}_{\mathrm{null}}$ with an exact hollow double-centring (`r5/so_exact_r5.py`; same features, folds, text, permutation null and gates; the original code path reproduces the committed values to 2×10^{-16}). This is a separately labelled post-hoc rerun. The registered values and verdict are unchanged in the record. Per model, $\mathrm{SO}_{\mathrm{null}}$ changes by at most 0.0012. The order of the 13 models is unchanged (τ=1.00), 13 of 13 models stay estimable, G2 passes on 13 and G3 on 13, τ with SING's order is 0.38 on all 13 models (0.33/0.45 on E12/S11), and the outcome is still INCONCLUSIVE.

Sensitivity to the bars (post hoc). Two bars sit at the scratch values: the inheritance bar of 0.05 (scratch maximum 0.040) and the plant-check bar of 0.10 (scratch minimum 0.103, final minimum 0.109). The reliability floor of 0.10 was set after the scratch run showed ResNet50's world-C rows falling below it. With a plant bar of 0.11, the inheritance statement becomes UNINFORMATIVE. Raising the inheritance bar to 0.12 gives INHERITED (10 of 13 models). Across reliability floors from 0.005 to 0.4, SO keeps its label (INCONCLUSIVE), and no kill fires. With α=0.1 in G3, SO passes on 12 and XCC on 13 of 13 models. At floors of 0.005–0.05, G4 is testable for SO on two bases and passes on both (max/min ratio at most 1.04). On DINOv2-L, the base testable at the pre-registered floor, the rows cover only ρ=0.005–0.013. The row-space analogues give $\mathrm{SO}_{\mathrm{row}}$ 0.30 and 0.35 and $\mathrm{XCC}_{\mathrm{row}}$ 0.27 and 0.35 against SING. All numbers in this paragraph come from `r5/posthoc_r5.py`.

Model	ρ	η^2	SO_{null}	rel	XCC_{24}	z	G2 SO / XCC	G3 SO sem / arb	F1-partial
VGG16	0.35	0.24	0.310	0.41	0.098	21.7	1.1×10^{-4} / 4.6×10^{-4}	196 / −14.1	0.052
VGG19	0.34	0.26	0.288	0.44	0.090	23.1	−0.002 / 2.3×10^{-4}	202 / −13.3	0.029
DenseNet121	1.8×10^{-8}	0.21	0.115	0.26	0.123	21.8	-1.7×10^{-5} / 2.6×10^{-4}	170 / −36.2	−0.051
ResNet50	0.15	0.19	0.312	0.25	0.169	18.2	−0.002 / 8.3×10^{-4}	267 / −53.4	0.040
"DinoViT"	5.4×10^{-3}	0.13	0.114	0.14	0.122	30.7	-7.4×10^{-4} / 9.6×10^{-4}	29 / −12.6	0.031
EffNet-B0	0.13	0.25	0.202	0.36	0.120	27.9	0.002 / 0.001	148 / −20.3	0.162
BiT-R50x1	0.05	0.24	0.347	0.44	0.219	26.6	7.9×10^{-4} / 0.001	115 / −7.6	0.098
ResNeXt101	0.45	0.63	0.276	0.67	0.077	10.0	0.002 / 2.0×10^{-4}	146 / −15.9	0.002
ConvNeXt-B	0.01	0.42	0.160	0.57	0.167	45.2	-2.8×10^{-4} / -3.1×10^{-4}	52 / −18.9	0.119
Swin-L	0.27	0.30	0.488	0.63	0.218	28.5	7.9×10^{-4} / 2.1×10^{-4}	90 / −24.8	0.426
DINOv2-L	0.32	0.37	0.209	0.49	0.051	27.6	5.0×10^{-4} / 3.0×10^{-4}	225 / −17.8	0.001
DeiT3-L	0.35	0.76	0.523	0.90	0.559	18.7	-4.2×10^{-4} / 0.001	13 / −67.0	0.429
EVA02-L	8.9×10^{-3}	0.38	0.039	0.49	0.046	36.9	-5.5×10^{-5} / -1.0×10^{-4}	49 / −5.0	0.036
True DINO (values only)									
DINO ViT-B/16	0.19	0.29	0.302	0.42	0.163	31.7	–	–	−0.040
DINO ViT-S/16	0.44	0.31	0.440	0.53	0.275	31.8	–	–	−0.002

Table 22: Round-5 scores and gates per model. rel: split-half reliability of SO_{null}; z: XCC self-term; G2: mean over 5 class-mean derangements; G3: change at α=0.3 in null-SD units for the semantic / arbitrary plant; F1-partial: full-null XCC with the row-space class Gram projected out. True DINO models are values only.

Base	Score	G4: estimable rows, max / min	World B range	World M range	World D range
ResNet50	SO_{null}	0/12, not estimable	0.312–0.312 (12)	0.223–0.236 (11)	0.230–0.236 (4)
ResNet50	XCC_{24}	1/12, not estimable	0.169–0.169 (12)	0.122–0.128 (12)	0.122–0.127 (6)
ResNeXt101	SO_{null}	2/12, not estimable	0.276–0.276 (12)	0.248–0.265 (12)	0.252–0.265 (9)
ResNeXt101	XCC_{24}	3/12, 1.009 (pass)	0.077–0.077 (12)	0.072–0.073 (12)	0.072–0.074 (11)
DINOv2-L	SO_{null}	3/12, 1.009 (pass)	0.209–0.209 (12)	0.179–0.181 (12)	0.179–0.183 (11)
DINOv2-L	XCC_{24}	6/12, 1.066 (pass)	0.051–0.051 (12)	0.043–0.044 (12)	0.041–0.044 (12)

Table 23: Round-5 scores in the corrected worlds. G4 uses world C; worlds B (whole null part rescaled; truth: flat), M and D are descriptive. Ranges over estimable rows, count in parentheses.

Score	Set	n	τ vs SING [95% CI]	$\tau(\cdot,\rho)$	partial r given ρ
SO_{null}	E12	12	0.33 $[-0.29, 0.79]$	0.42	0.03 $[-0.67, 0.74]$
SO_{null}	S11	11	0.45 $[-0.21, 0.88]$	0.53	0.23 $[-0.41, 0.82]$
SO_{null}	all13	13	0.38 $[-0.11, 0.75]$	0.46	0.04 $[-0.62, 0.68]$
XCC_{24}	E12	12	−0.12 $[-0.77, 0.44]$	−0.03	0.09 $[-0.75, 0.75]$
XCC_{24}	S11	11	−0.05 $[-0.73, 0.54]$	0.02	0.14 $[-0.75, 0.79]$
XCC_{24}	all13	13	−0.13 $[-0.69, 0.39]$	−0.05	0.11 $[-0.65, 0.69]$

Table 24: Round-5 confirmatory test: Kendall τ with SING's order (model bootstrap, percentile 95% CI), τ with ρ, and the partial Spearman given ρ. Labels: SO_{null} INCONCLUSIVE, XCC_{24} DOES-NOT-TRACK.

	World C			World M			World D		
Estimator	RN50	RNX	DINOv2	RN50	RNX	DINOv2	RN50	RNX	DINOv2
ρ	1.00	1.00	1.00	1.00	1.00	1.00	–	–	–
AS	1.00	1.00	1.00	0.33	1.00	1.00	0.24	0.97	0.94
A1	0.70	0.55	0.00	0.45	−0.76	−0.85	−1.00	0.48	0.94
$\mathrm{AS}_{\mathrm{gauss}}$	1.00	1.00	1.00	0.94	1.00	1.00	−0.55	−1.00	−0.94
X	−0.52	−1.00	−1.00	−0.67	−0.76	−0.88	0.97	1.00	0.97
Δ_{align}	−1.00	−1.00	−1.00	−0.15	0.61	0.18	0.94	1.00	0.94
$\mathrm{NCM}_{\mathrm{null}}$	−0.32	−1.00	−1.00	0.92	0.88	0.80	0.93	1.00	1.00
selectivity R	−0.88	−0.45	−0.30	−0.06	−0.85	0.79	−0.73	−0.88	−0.48
exponent a	0.55	0.49	0.30	0.28	0.52	0.42		–	

Table 25: Round-4 calibration worlds with in-sample residuals, superseded by Table 18; kept for comparison.

H Round 6: energy statistics for published null-space and residual scores

Reading of the positive controls (post hoc). We ran scores that the rule should flag through the identical code (Table 26; `r6/POSTHOC_R6.md`). It flags SING's IS with both translators (τ_{EQ}=0.12 and 0.24, median R_B 0.57 released and 0.79 retrained). It misses the other three controls. The NuSA share moves fully with the sweep (R_B=0.89) but keeps part of its order after E1 (τ_{EQ}=0.27 and 0.31), because the per-image null share keeps a model-specific spread when the mean energy is equalised. ρ itself has no order left after E1, so τ_{EQ} is undefined and the rule returns mixed. SING's AS with the released translators gives τ_{EQ}=0.39 and 0.45 and median R_B=0.26 (mixed), and with the retrained translators 0.85, 0.85 and 0.67 (mixed). Because the rule misses SING's AS and a pure energy score, it cannot show that other scores are free of the confound. The pre-registered count (k=0 of 4 scores energy-driven) is therefore uninformative, and we do not use it to decide whether the confound is specific to SING. Yet the retained cross-model range of released AS after equalising energy is only 0.11 (below). The miss therefore comes from the thresholds, not from weak energy dependence. The τ part of the rule also says little by itself. If the order after E1 were unrelated to the order before, τ_{EQ}<0.3 would hold with probability 0.90 for 12 models.

Score	τ_{EQ} E12	τ_{EQ} S11	med. R_B	retained range after E1	rule output
Positive controls (energy scores or SING's own score; post hoc except NuSA)					
NuSA share	0.27	0.31	0.89	5.4×10^{-3}	mixed
ρ itself	–	–	0.99	0	mixed
SING AS, released	0.39	0.45	0.26	0.11	mixed
SING AS, retrained	0.85	0.85	0.67	0.15	mixed
SING IS, released	0.12	0.24	0.57	0.11	energy-driven
SING IS, retrained	0.12	0.24	0.79	0.05	energy-driven
Audited scores (pre-registered; frozen-α ViM post hoc)					
ViM	0.88	0.89	0.06	0.90	not energy-driven
ViM, α frozen†	-0.52	-0.49	1.33	1.93	energy-driven
ActSub $S_{\rightarrow}$	0.79	0.78	0.14	0.78	mixed
CORE S_{mem}	0.85	0.82	0.11	0.92	mixed
$\mathcal{V}$-information	0.20	0.33	0.19	0.29	mixed

Table 26: Round-6 energy statistics with post hoc positive controls (§B.3). τ_{EQ}: Kendall τ between a score after equalising null energy (E1) and before, on the estimable models. Median R_B: range over the energy sweep E2 relative to the range across models. Retained range: the retained cross-model range, range(E1)/range(real) over the estimable E12 models (post hoc). It is a descriptive comparison, not a validity gate and not the fraction of confounding removed: frozen-α ViM retains 1.93 of its range yet is energy-driven. Rule output: ENERGY-DRIVEN needs $\tau_{\mathrm{EQ}}<0.3$ on both sets and median $R_B\geq0.5$; NOT ENERGY-DRIVEN needs $\tau_{\mathrm{EQ}}\geq0.6$ and $R_B\leq0.1$; anything else is mixed. For ρ, τ_{EQ} is undefined because all E1 values are equal. †ViM with α frozen at its real-data value of each fit half. Pre-registered content counts and labels: Table 27 (Appendix H).

Scores. ViM (Wang et al., 2022): origin $u=-W^{+}b$, uncentred covariance of $f-u$, residual space after the top D eigenvectors (D=1000 for $d\geq2048$ and 512 otherwise, as in the official code), α from the fit half; model-level score is the mean virtual-logit probability (descriptive: mean of the official score s). ActSub $S_{\rightarrow}$ (Zöngür et al., 2025): full SVD of W, split index from the official rule, a random 10% reference set of the fit half, 10 nearest cosine neighbours, $S_{\rightarrow}=-\log(1-\bar{c})$. CORE S_{mem} (Yang et al., 2026): cosine between the residual of z with respect to the predicted class's weight and that class's normalised mean residual on the fit half (descriptive: the same on Πf). Conditional $\mathcal{V}$-information (Hewitt et al., 2021): held-out NLL gain of a softmax probe on [a scaled copy of the logits; the top 64 principal coordinates of Πf] over the logits alone, with an ℓ_2 penalty chosen once per model by inner cross-validation and then frozen (descriptive: top-1 correctness as target). The NuSA-style reference is the mean of $\|\Pi f\|/\|f\|$. Every image is scored by quantities fitted on the other half. We checked ViM's residual dimension and ActSub's split rule and neighbour count against the official code. The main deviation is that we have no training features, so every fitted quantity uses 5 validation images per class from the other half of a class-stratified split. The scores are therefore surrogates of the published ones, with three known fidelity limits: CORE's per-class mean residuals rest on 5 images, fewer than the about 13 per class it needs; ActSub's reference set is 10% of this fit half, not of a training set; and $\mathcal{V}$-information uses a restricted probe family, since a full map of the 1000 logits is not identifiable from 5 images per class. We did not run CANARY (Shin & Kim, 2026), whose per-class k=100 neighbour rule needs more references per class, nor NECO (Ben Ammar et al., 2024) or the nearest-neighbour score of Sun et al. (2022).

Pre-registered verdicts. Table 27 gives the registered outcomes. All four scores are estimable on enough models ($\mathcal{V}$-information on 11 of E12 and 10 of S11), so n=4. ViM is NOT ENERGY-DRIVEN (τ_{EQ}=0.88 and 0.89, median R_B=0.06). ActSub and CORE keep their order (0.79/0.78 and 0.85/0.82) with median R_B 0.14 and 0.11, just above the 0.1 bar, so both are MIXED. $\mathcal{V}$-information (τ_{EQ}=0.20 and 0.33, R_B=0.19) is MIXED. The counting rule gives k=0 of n=4, for which the pre-registration states that the confound is largely specific to SING. We withdraw that statement. The post hoc positive controls of §B.3 show that the rule does not flag SING's own AS, so k carries no information about other scores, and we do not generalise from it. The registered content labels (PARTIAL for ViM, ActSub and CORE; CONTENT-RESPONSIVE for $\mathcal{V}$-information) are listed in Table 27 and the ledger as registered outcomes only. We do not use them as

readings, for the reasons below. The registered statement that null content is measurable needs two scores that are both not energy-driven and content-responsive, and it is not made.

Content tests and the C2 flag. C1 permutes Πf across images, and C3 adds an arbitrary class code (α=0.3), both in image-bootstrap SDs. The within-class permutation C2 moves every score by more than 1 SD on more than 3 models (ViM 8, ActSub 11, CORE 9, $\mathcal{V}$-information 12 of 13), so the pre-registered ESTIMATOR-NOISY flag is set for every score. That flag assumed that C2 preserves the content a score measures. It need not. In the synthetic check of `r6/tests/test_posthoc_r6.py` (post hoc), the null part carries the image-level noise of the logits, so logits and null part together identify the class. The conditional $\mathcal{V}$-information gain is 1.18 nats. After a within-class permutation, which leaves every class's null distribution exactly unchanged, it is -9.7×10^{-3}. The C2 flag therefore cannot separate a real loss of within-class or image-level information from estimator noise. Permuting Πf across images in C1 also breaks the coupling between row-space and null parts, and the bootstrap SDs over 10 000 images are small, so C1 and C3 effects mix content with that coupling (the NuSA share passes C1 on 9 models). For $\mathcal{V}$-information, |C2| exceeds |C1| on 11 of 13 models. The semantic class code (descriptive) moves the scores in the same direction as the arbitrary code on most models. None of the four scores refers to class text.

Positive controls (post hoc). `r6/controls_r6.py` runs SING's AS and IS (class-text target) through the round-6 interventions with the same seeds, with the released translator on all 10k images and with the round-3 ridge translator (refit on the fixed training half with its recorded penalty, scored on the other 5000 images), and `r6/posthoc_r6.py` passes them through the unchanged verdict code. AS, released: estimable on 12 of E12 and 11 of S11, τ_{EQ} 0.39/0.45, median R_B 0.26 (0.25 over E12), mixed. AS, retrained: 0.85/0.85, 0.67 (0.70), mixed. IS, released: 0.12/0.24, 0.57, energy-driven; retrained: 0.12/0.24, 0.79, energy-driven. Both IS controls are therefore flagged, and both AS controls are not. The NuSA share is MIXED (Table 27). ρ is equal on every model after E1, so τ_{EQ} is undefined and the conjunctive rule returns mixed. Under independence of the orders before and after E1, $P(\tau_{\mathrm{EQ}}<0.3)$ is 0.90 for 12 models and 0.89 for 11 (20 000 permutations). The τ part of the rule therefore says little by itself.

Built-in normalisation (post hoc). ViM's α is refitted after each intervention and scales inversely with the null norm, so the refit score is close to invariant to E1. With α frozen at the real-data value of each fit half, E1 moves the score from 0.876 to 2.5×10^{-4} for ResNet50, from 0.843 to 8.5×10^{-5} for DINOv2-L and from 0.876 to 3.1×10^{-5} for VGG16; refitting multiplies α by 4.9, 6.4 and 8.5 on these models (0.8–8.5 over the 13). Frozen-α ViM gives τ_{EQ} $-0.52/-0.49$ and median R_B 1.33 (energy-driven), and its retained cross-model range is 1.93. CORE on Πf and the cosine parts of ActSub and CORE do not depend on the scale of the null part. The retained cross-model range after E1 (E12, estimable models) is 5.4×10^{-3} (NuSA share), 0.11 and 0.15 (AS, released and retrained), 0.11 (IS, released), 0.29 ($\mathcal{V}$-information), 0.78 (ActSub), 0.90 (ViM), 0.92 (CORE), 1.00 (CORE on Πf) and 0.75 (ViM score s).

$\mathcal{V}$-information (post hoc). Its range across the 13 models is 0.0600 nats, and DenseNet121 alone contributes 86% of it. DenseNet121's null part is tiny ($\rho=1.8\times10^{-8}$) and is scaled up by up to 7×10^{3} in the sweep. Without DenseNet121 the range is 0.0123. Re-applying the estimability rule to this range leaves 7 of E12 and 7 of S11 estimable, against the 9 and 8 that a verdict needs (verdict possible: no). The median R_B over the 12 models is then 0.94, and τ_{EQ} on the estimable models is 0.52/0.52. Of the 13 gains, four are zero to four decimals or negative (VGG16 1.1×10^{-5}, BiT-R50x1 -0.0032, ResNeXt101 -0.0086, DINOv2-L -0.0053), and 4 are within 2 bootstrap SDs of zero. The penalty chosen by inner cross-validation was the largest grid value in 15 of 26 fits, so the probe is heavily shrunk. An independent rerun on ResNet50 gave 0.00103 instead of the audit's 0.00158. This suggested that the chosen penalty flips between runs. We could not reproduce a flip: in 2 reruns with the registered inner cross-validation seed, the penalty chosen for the two halves was λ_A/λ_B=1/0.1 (relative to the default), as in the audit, and the value was 0.00158. The value does depend on the penalty. Over the four combinations of $\{0.1, 1\}$ for the two halves it is 0.00098, 0.00087, 0.00158 and 0.00147 (A/B = 0.1/0.1, 0.1/1, 1/0.1, 1/1), a range of almost a factor of two that contains the value of the independent rerun, and the cross-validated gains that pick λ_B differ by less than 10^{-3} nats (`r6/vinfo_repro_r6.py`). A different BLAS or thread count could therefore change the choice. We treat the ResNet50 value as known only to this range.

Cross-model and synthetic worlds (descriptive). Table 28 gives τ with SING's order, τ with ρ and the partial association given ρ. None of the four primary scores tracks SING's order. ViM and $\mathcal{V}$-information do not, and ActSub and CORE are inconclusive (τ on E12/S11: ViM 0.03/0.05, ActSub 0.36/0.49, CORE 0.33/0.42, $\mathcal{V}$-information $-0.09/-0.20$). The NuSA share does (0.82/0.82). Table 29 gives each score in the corrected calibration worlds of §B.2.5: the world-C ratio of the content-free excess (pass if at most 1.5 with all values positive) and τ with ρ in world C and with L in worlds M and D. CORE on Πf is exactly invariant to rescaling the null part (R_B=0), responds to both content tests on all 13 models. With SING's order it gives τ=0.45 and 0.38 (partial given ρ 0.57 and 0.48). It was pre-registered as descriptive, so it is not counted, and we do not interpret it further here. In the worlds, only CORE passes the world-C bar, and on one base (DINOv2-L). ActSub, CORE and $\mathcal{V}$-information fall as ρ grows at fixed content in world C ($\tau_\rho \leq -0.73$) and rise with content in worlds M and D ($\tau_L \geq 0.88$), whereas ViM rises with ρ in world C and moves against L in worlds M and D, and the NuSA share rises with ρ in world C on all three bases. These worlds are semi-synthetic and do not enter the verdicts.

What the statistics show (descriptive, from the main text). ViM, ActSub and CORE keep their order under E1 (τ_{EQ} 0.78–0.89). All three, however, are scale-normalised by construction. ViM refits α, the ratio of mean maximum logit to mean residual norm, on every fit, so rescaling the null part rescales α inversely. With α frozen at its real-data value, E1 moves ResNet50's ViM score from 0.876 to 2.5×10^{-4} (refitting multiplies α by 0.8 to 8.5 across models). ActSub's cosine neighbours and CORE's cosine scores do not depend on scale. The retained cross-model range (post hoc), range(E1)/range(real) over the E12 models, is 5.4×10^{-3} for the NuSA share, 0.11 for SING's AS (released), 0.29 for $\mathcal{V}$-information, 0.78 for ActSub, 0.90 for ViM (1.93 with α frozen) and 0.92 for CORE. This is a descriptive comparison, not a validity gate and not the fraction of confounding removed: frozen-α ViM retains 1.93 of its range, yet the rule labels it energy-driven. In the semi-synthetic worlds of §B.2.5, ActSub, CORE and $\mathcal{V}$-information fall as ρ grows at fixed content (world C, τ_ρ from -0.73 to -1.00 on all three bases), ViM rises with it ($+1.00$), and ViM moves against content in worlds M and D (τ_L down to -1.00; Table 29). $\mathcal{V}$-information depends most on energy of the four, but 86% of its cross-model range comes from DenseNet121, four of its 13 gains are zero to four decimals or negative, and its penalty sat at the top of the grid in 15 of 26 fits (Appendix H). None of the four tracks SING's order (Table 28). We do not read the content tests. Their within-class permutation moves every score by more than 1 SD on several models, and a synthetic check shows that this permutation can remove real image-level conditional information while keeping each class's null distribution (a gain of 1.18 nats falls to -9.7×10^{-3}). The flag therefore cannot separate a real loss of within-class or image-level information from estimator noise.

Deviations. Every test changes only Πf, so the logits are unchanged up to 1.3×10^{-5} (DenseNet121, whose null part is scaled up by factors of about 5×10^2 to 7×10^3 to reach the E1 and E2 targets). On every other model the change is below 10^{-12}. The pre-registration's 10^{-8} tolerance referred to the synthetic unit tests. No other deviation from `PREREG_R6.md` occurred. Everything in this appendix marked post hoc is listed in `r6/POSTHOC_R6.md`.

Score	estimable E12	estimable S11	τ_{EQ} E12	τ_{EQ} S11	med. R_B	$\lvert C_1\rvert \geq 2$ / $\lvert\Delta_{\text{arb}}\rvert \geq 2$	verdict energy	verdict content
ViM	12	11	0.88	0.89	0.06	9 / 5	not energy-driven	partial
ActSub $S_{\rightarrow}$	12	11	0.79	0.78	0.14	11 / 8	mixed	partial
CORE S_{mem}	12	11	0.85	0.82	0.11	11 / 8	mixed	partial
$\mathcal{V}$-info (class)	11	10	0.20	0.33	0.19	11 / 12	mixed	responsive
Descriptive, not counted								
ViM score s	12	11	1.00	1.00	0.03	4 / 6	not energy-driven	partial
CORE on Πf	12	11	1.00	1.00	$1.6{\times}10^{-16}$	13 / 13	not energy-driven	responsive
$\mathcal{V}$-info (correct)	9	9	0.28	0.28	0.13	7 / 0	mixed	partial
NuSA share	12	11	0.27	0.31	0.89	9 / 7	mixed	partial

Table 27: Round 6, pre-registered outcomes (`PREREG_R6.md`). Estimable: models passing the estimability rule in E12 and S11. τ_{EQ}: Kendall τ between the score after equalising null energy and before. Median R_B: range over the energy sweep relative to the range across models. Counts out of 13 models of $\lvert C_1\rvert \geq 2$ (across-image permutation of Πf) and $\lvert\Delta_{\text{arb}}\rvert \geq 2$ (arbitrary class code, α=0.3), in bootstrap SDs. The content labels are registered outcomes that we do not use as readings, because the C2 flag fires for every score and cannot separate a real loss of information from noise (Appendix H). Counting rule: k=0 of n=4; uninformative given the positive controls of Table 26.

Score	τ E12	τ S11	τ all 13	τ with ρ (E12 / S11)	partial given ρ (E12 / S11)
ViM	0.03 $[-0.44, 0.47]$	0.05 $[-0.47, 0.54]$	0.10 $[-0.36, 0.55]$	0.18 / 0.20	-0.34 / -0.25
ActSub $S_{\rightarrow}$	0.36 $[-0.25, 0.83]$	0.49 $[-0.12, 0.92]$	0.21 $[-0.39, 0.72]$	0.33 / 0.42	0.19 / 0.33
CORE S_{mem}	0.33 $[-0.25, 0.80]$	0.42 $[-0.19, 0.88]$	0.23 $[-0.32, 0.71]$	0.18 / 0.20	0.42 / 0.52
$\mathcal{V}$-info (class)	-0.09 $[-0.69, 0.51]$	-0.20 $[-0.79, 0.48]$	-0.24 $[-0.77, 0.35]$	-0.16 / -0.24	0.21 / 0.08
ViM score s	-0.33 $[-0.84, 0.20]$	-0.35 $[-0.91, 0.25]$	-0.31 $[-0.77, 0.22]$	-0.42 / -0.42	0.37 / 0.35
CORE on Πf	0.45 $[-0.03, 0.86]$	0.38 $[-0.18, 0.83]$	0.28 $[-0.26, 0.77]$	0.24 / 0.16	0.57 / 0.48
$\mathcal{V}$-info (correct)	0.17 $[-0.38, 0.82]$	0.17 $[-0.38, 0.82]$	0.16 $[-0.40, 0.71]$	0.00 / 0.00	0.50 / 0.50
NuSA share	0.82 $[0.57, 0.97]$	0.82 $[0.53, 1.00]$	0.85 $[0.64, 1.00]$	0.97 / 0.96	0.76 / 0.80

Table 28: Round 6, descriptive: Kendall τ of each score with SING's order (percentile 95% CI over 2000 model resamples), τ with ρ, and the partial Spearman correlation with SING's order given ρ, over the estimable models.

Score	DINOv2-L C ratio	DINOv2-L C τ_ρ	DINOv2-L M τ_L	DINOv2-L D τ_L	ResNet50 C ratio	ResNet50 C τ_ρ	ResNet50 M τ_L	ResNet50 D τ_L	ResNeXt101 C ratio	ResNeXt101 C τ_ρ	ResNeXt101 M τ_L	ResNeXt101 D τ_L
ViM	∞	1.00	-1.00	-1.00	∞	1.00	-0.12	-1.00	∞	1.00	-0.24	-1.00
ActSub $S_{\rightarrow}$	∞	-1.00	0.97	1.00	∞	-1.00	1.00	1.00	∞	-1.00	1.00	1.00
CORE S_{mem}	1.34	-1.00	1.00	1.00	3.57*	-1.00	1.00	1.00	1.85*	-1.00	1.00	1.00
$\mathcal{V}$-info (class)	2.14*	-0.94	0.97	1.00	∞	-0.73	0.88	0.97	∞	-0.94	1.00	1.00
ViM score s	∞	-1.00	-0.91	1.00	∞	-1.00	-0.15	1.00	∞	-1.00	-0.06	1.00
CORE on Πf	39.22*	-1.00	1.00	1.00	8.06*	-1.00	1.00	1.00	21.49*	-1.00	1.00	1.00
$\mathcal{V}$-info (correct)	2.99*	-1.00	-1.00	-0.42	2.78*	-0.97	0.67	0.97	∞	-1.00	-0.82	0.97
NuSA share	∞	1.00	1.00	0.39	∞	1.00	1.00	0.73	∞	1.00	1.00	0.94

Table 29: Round 6, descriptive: scores in the corrected calibration worlds (residuals permuted across images, seed 100500). C ratio: max/min over the 12 world-C rows of the score minus its content-free floor (one across-image permutation); * fails the pre-stated 1.5 bar or has a non-positive excess; ∞ marks a non-positive minimum. τ_ρ: τ with ρ in world C; τ_L: τ with L in worlds M and D.

I Rounds 7 and 8: details

Round 7. The edit is `mixed_next` against `mixed_same` of IN-9 (Xiao et al., 2021), with the null space of each released head. The nuisance views are random resized crops, flips, photometric jitter, blur and JPEG

compression at three strengths, applied identically to the edit, its reference and the two artefact images. The automated verdict file also prints an ALIGNED line for the secondary statistic T. The pre-registration makes T descriptive, so that line is not a verdict. Reliability and T2 in the main text are at the medium level. The row-space analogue of the edit gives T2 0.0014–0.0027. The post hoc correction uses 500 within-group half-samples without replacement (seed 100750); H2 stays ARTEFACT on 4 of 4. The nuisance levels also change content. The edit's cross-view energy falls by 37–49% from the weakest to the strongest level, so they were not a clean world-C analogue either. Per-model numbers are in `r7/README.md`.

Round 8. Where C′ rows are estimable, θ_{sem} is nearly flat (max/min 1.01, 1.12 and 1.25), but the log-log slope CIs on DINOv2-L ($[-0.041, -0.004]$) and ResNeXt101 ($[0.036, 0.067]$) exclude 0 (ResNet50 $[-0.092, 0.063]$). The failing G-derange cell is ResNet50 on real data (mean 1.1×10^{-4}, CI $[3.5\times10^{-5}, 1.9\times10^{-4}]$; the size bar holds). In world M θ_{sem} rises ×219–279, in world D ×19–29, and in the old world C, whose content rises against the row space, ×1.6 and ×2.3 on two bases. On S11 the shadow gives 0.78 $[0.39, 1.00]$, the innovation 0.24 $[-0.27, 0.70]$, self-duality -0.60 $[-0.96, -0.12]$ and the partial correlation -0.43 $[-0.88, 0.41]$; J_{inn} gives 0.36 $[-0.26, 0.83]$ and 0.45. Table 30 lists the per-model quantities and Table 31 the head swap. A second class-fold split (seed 100801) gives the same τ (0.64 and 0.64). The class bootstrap had synthetic coverage 0.97 (signal) and 0.99 (no content), so K0 did not fire. The zero floor passes: the largest surrogate $|\theta_{\text{sem}}|$ over 98 cells is 0.0026, against a bar of 0.040. The invariances hold to 4×10^{-16}. The semantic plants raise θ_{sem} by 0.37, 0.35 and 0.29 on the three bases. Descriptive τ with SING's order: θ_{cls} (the null share of class-mean energy, without the text map) 0.70 $[0.36, 1.00]$ and 0.71; $\tau(\theta_{\text{sem}}, \rho)$ 0.73 and 0.71; $\tau(\theta_{\text{sem}}, \rho_{\text{btw}})$ 0.61 and 0.53 (E12 and S11).

Model	θ_{sem}	θ_{cls}	comp.	ρ	ρ_{off}	shadow	innov.	self-dual.
DeiT3-L	0.401	0.129	0.70	0.348	0.320	0.208	0.176	0.64
ResNeXt101	0.212	0.346	0.11	0.451	0.149	0.179	0.005	0.42
DINOv2-L	0.093	0.266	0.06	0.322	0.012	0.094	0.054	0.46
VGG19	0.109	0.225	0.16	0.339	0.028	0.085	−0.001	0.55
VGG16	0.113	0.226	0.17	0.350	0.029	0.088	−0.001	0.54
ResNet50	0.013	0.020	0.25	0.146	0.124	0.011	9.4×10^{-4}	0.74
Swin-L	0.287	0.209	0.23	0.274	0.022	0.112	0.188	0.60
EfficientNet	0.092	0.103	0.19	0.130	8.9×10^{-4}	0.055	0.028	0.57
ConvNeXt	0.015	0.011	0.19	0.013	4.6×10^{-4}	0.007	0.005	0.66
BiT-R50	0.033	0.041	0.26	0.046	0.002	0.024	0.006	0.72
EVA02-L	0.004	0.005	0.07	0.009	7.6×10^{-4}	0.002	0.003	0.78
DinoViT	5.9×10^{-4}	0.001	0.16	0.005	1.4×10^{-4}	4.7×10^{-4}	4.5×10^{-4}	0.79
DenseNet121	2.5×10^{-9}	3.4×10^{-9}	0.29	1.8×10^{-8}	1.5×10^{-8}	2.4×10^{-9}	9.2×10^{-11}	0.70

Table 30: Round 8, per model in SING's order (most leakage first). comp.: composition $S(Z)/\hat{E}_b(Z)$. Shadow and innovation: θ_{sem} of Hs and u. Self-dual.: mean cosine between the rows of W and the centred class means. ρ and ρ_{off} are plug-in.

Base	Head	ρ	AS (°)	top-1	θ_{sem}
ResNet50	released	0.146	1.68	–	0.013
	NCM	0.014	0.34	0.652	2.1×10^{-4}
	LDA	0.930	2.56	0.635	0.930
DINOv2-L	released	0.322	1.50	–	0.093
	NCM	0.107	0.48	0.745	0.001
	LDA	0.436	1.42	0.752	0.377
ResNeXt101	released	0.451	2.00	–	0.212
	NCM	0.036	0.38	0.773	2.2×10^{-4}
	LDA	0.662	2.46	0.779	0.676

Table 31: Round 8, head swap on three backbones: heads fit on images 0–4 of each class, top-1 on images 5–9; every head leaves d_{null}=1048. AS uses the released translator. Released-head top-1 on images 5–9 (post hoc, not in the table): ResNet50 0.762, DINOv2-L 0.860, ResNeXt101 0.828.

J Reproducibility and compute

`make reproduce` regenerates every table, figure and number in this paper from committed aggregates in under a minute. This checks consistency, not the feature-level computation. `make reproduce-full` reruns the feature-level analyses from the private ImageNet features: about 2 h wall on 8 CPU cores, most of it the holdout. `make holdout-fast` runs the reduced holdout (36 min on 8 cores). It fails its pre-registered accuracy target on a deterministic quantity, so a faster machine cannot make it pass. We did not re-time it. The timing itself may be affected by contention. The machine is shared, an earlier attempt was aborted because other jobs were running, the load average was not recorded for the timed run, and the job used about 7.3 of the 8 cores. The round-4 analyses (`r4/`) run on CPU from the same private features (`make reproduce-r4`); extracting the true DINO features needs a GPU. The round-5 analyses (`r5/`, `make reproduce-r5`) take about 20 min for the corrected calibration worlds on 4 cores and 9 min for the organisation-score gates on 4 cores, on a shared machine. The round-6 audit (`r6/`, `make reproduce-r6`) took 3–74 min per model and about 1 h per calibration base with 2 threads per process, four processes in parallel on the shared 8-core machine. The 4096-dimensional VGG models take longest. The post hoc round-6 controls (`make reproduce-r6-posthoc`) took from about a minute per model to about 40 min for each VGG model, and the $\mathcal{V}$-information penalty rerun about 16 min, on 2 threads of a heavily loaded 2-core machine. The post hoc round-5 $\mathrm{SO}_{\mathrm{null}}$ rerun (`r5/so_exact_r5.py`) takes about 3 min. Round 7 needs the IN-9 images; its features were extracted on CPU (ResNet50, EfficientNet-B0) and on a GPU (ResNeXt101, DINOv2-L). Round 8 (`r8/run_r8.py`) and the post hoc offset analyses (`r8/posthoc/`) run on CPU from the cached features. Feature extraction (13 models on the 10k subset, the Exp 1 features and the five ViT-L/16 candidates on the 50k validation set) needs ImageNet and a GPU. Two jobs were timed: the Exp 1 extraction (1.4 GPU-hours on one cloud GPU) and the re-extraction of the five ViT-L/16 candidates for the translator check (1.9 h on two T4 GPUs, about 3.8 GPU-hours including weight downloads). The other extraction jobs were not timed; we estimate under 10 GPU-hours for all extraction.

Seeds. Family A random draws $10000{+}r$ ($r < 20$); family B $50000{+}r$; family C subspaces $30000{+}j$ and controls $60000{+}j$; Exp 1 20 seeds per d; E3 plants seed 0, bootstrap $10000\times$ seed 1; model bootstrap $2000\times$ seed 0; claim bootstrap $1000\times$ seed 0; E9 and holdout α seed 1; flatness bases $20000{+}j$; PC-band draws $40000{+}j$; A3 rotations $80000{+}j$; leak-free surrogates $70000{+}r$; translator split permutation seed 0. Round 4: surrogates $92000{+}r$ (zero-mean, isotropic, permuted) and $93000{+}r$ (within-class permutation); class-mean derangements $94000{+}r$; NCM shuffled labels 95000; selectivity random rotations $96000{+}j$; NZS control 97000; synthetic geometry model 98000; geometry random subspaces $1000d{+}r$; selectivity and geometry image bootstraps seed 0. Round 5: calibration residual permutation 99000; XCC Haar frames $99100{+}s$; SO folds 99200; permutation nulls 99300; world-S plants 99400 and inheritance plant 99401; G1 rotation 99500; XCC self-term folds 99600; class-mean derangements $94000{+}r$. Round 6: halves 100100; ActSub reference subsets 100150/100151; across-image permutations $100200{+}r$; within-class permutations $100250{+}r$; class-code plants 100400; world residual permutation 100500; image bootstrap 100600; $\mathcal{V}$-information inner CV 100700. Round 7: image selection 100701; background permutation 100710; nuisance views from 100700; permutation tests $100720{+}L$; bootstrap 100730; synthetic study 100740; post hoc half-sampling 100750. Round 8: class folds 100800 (sensitivity 100801); offset direction 100802; rotations 100803; derangements 100804; plants 100805; resampling 100806; Gaussian and permutation surrogates 100807 and 100808; J draws 100809; K0 $100820000{+}i$ and $100830000{+}i$; world residual permutation 99000.