

Classification: Decision Tree

Classification: Definition

- Given a collection of records (training set)
 - Each record is by characterized by a tuple (x,y) , where x is the attribute set and y is the class label
 - ◆ x : attribute, predictor, independent variable, input
 - ◆ y : class, response, dependent variable, output
- Task:
 - Learn a model that maps each attribute set x into one of the predefined class labels y


General Approach for Building Classification Model

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set

Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?

Test Set



Classification Techniques


- Base Classifiers
 - Decision Tree based Methods
 - Rule-based Methods
 - Nearest-neighbor
 - Neural Networks
 - Deep Learning
 - Naïve Bayes and Bayesian Belief Networks
 - Support Vector Machines
- Ensemble Classifiers
 - Boosting, Bagging, Random Forests

Example of a Decision Tree

categorical
categorical
continuous
class

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes


Training Data



Model: Decision Tree

Apply Model to Test Data

Start from the root of tree.




Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?

Apply Model to Test Data

Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?



Assign Defaulted to
"No"


Decision Tree Classification Task

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set

Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?

Test Set




Decision Tree Induction

- Many Algorithms:
 - Hunt's Algorithm (one of the earliest)
 - CART
 - ID3, C4.5
 - SLIQ, SPRINT

General Structure of Hunt's Algorithm

- | Let D_t be the set of training records that reach a node t
- | General Procedure:
 - If D_t contains records that belong the same class y_t , then t is a leaf node labeled as y_t
 - If D_t contains records that belong to more than one class, use an attribute test to split the data into smaller subsets. Recursively apply the procedure to each subset.

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



Hunt's Algorithm

Defaulted = No

(7,3)

(a)


ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Hunt's Algorithm

Defaulted = No

(7,3)


(a)




(b)

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Hunt's Algorithm




(a)



(b)


ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



(c)


Hunt's Algorithm

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes




(7,3)


(a)



(b)



(d)



(c)

Design Issues of Decision Tree Induction

- | How should training records be split?
 - Method for specifying test condition
 - ◆ depending on attribute types
 - Measure for evaluating the goodness of a test condition
- | How should the splitting procedure stop?
 - Stop splitting if all the records belong to the same class or have identical attribute values
 - Early termination


Methods for Expressing Test Conditions

- | Depends on attribute types
 - Binary
 - Nominal
 - Ordinal
 - Continuous
- | Depends on number of ways to split
 - 2-way split
 - Multi-way split

Test Condition for Nominal Attributes


- **Multi-way split:**

- Use as many partitions as distinct values.



- **Binary split:**


- Divides values into two subsets



Test Condition for Ordinal Attributes



| Multi-way split:

- Use as many partitions as distinct values




| Binary split:

- Divides values into two subsets
- Preserve order property among attribute values




This grouping violates order property

Test Condition for Continuous Attributes



(i) Binary split



(ii) Multi-way split

Splitting Based on Continuous Attributes

- Different ways of handling
 - **Discretization** to form an ordinal categorical attribute

Ranges can be found by equal interval bucketing, equal frequency bucketing (percentiles), or clustering.

 - ◆ Static – discretize once at the beginning
 - ◆ Dynamic – repeat at each node
 - **Binary Decision**: $(A < v)$ or $(A \geq v)$
 - ◆ consider all possible splits and finds the best cut
 - ◆ can be more compute intensive

How to determine the Best Split

- | Greedy approach:
 - Nodes with **pur**er class distribution are preferred
- | Need a measure of node impurity:

C0: 5
C1: 5

High degree of impurity

C0: 9
C1: 1

Low degree of impurity

Measures of Node Impurity

| Gini Index

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

| Entropy

$$Entropy(t) = -\sum_j p(j | t) \log p(j | t)$$

| Misclassification error

$$Error(t) = 1 - \max_i P(i | t)$$

Finding the Best Split

1. Compute impurity measure (P) before splitting
2. Compute impurity measure (M) after splitting
 - | Compute impurity measure of each child node
 - | M is the weighted impurity of children
3. Choose the attribute test condition that produces the highest gain

$$\text{Gain} = P - M$$

or equivalently, lowest impurity measure after splitting (M)

Finding the Best Split

Before Splitting:

C0	N00
C1	N01

→ **P**

A?

Yes

No

Node N1

Node N2

C0 **N10**

C1 **N11**

C0 **N20**

C1 **N21**



M11



M12



M1

B?

Yes

No

Node N3

Node N4

C0 **N30**

C1 **N31**

C0 **N40**

C1 **N41**



M21



M22



M2

Gain = P – M1 vs P – M2

Measure of Impurity: GINI

- Gini Index for a given node t :

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

(NOTE: $p(j | t)$ is the relative frequency of class j at node t).

- Maximum $(1 - 1/n_c)$ when records are equally distributed among all classes, implying least interesting information
- Minimum (0.0) when all records belong to one class, implying most interesting information

Measure of Impurity: GINI

- Gini Index for a given node t :

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

(NOTE: $p(j | t)$ is the relative frequency of class j at node t).

- For 2-class problem ($p, 1 - p$):

- ◆ $GINI = 1 - p^2 - (1 - p)^2 = 2p(1-p)$

C1	0
C2	6
Gini=0.000	

C1	1
C2	5
Gini=0.278	

C1	2
C2	4
Gini=0.444	

C1	3
C2	3
Gini=0.500	

Computing Gini Index of a Single Node

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Gini = 1 - P(C1)^2 - P(C2)^2 = 1 - 0 - 1 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Gini = 1 - (1/6)^2 - (5/6)^2 = 0.278$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Gini = 1 - (2/6)^2 - (4/6)^2 = 0.444$$

Computing Gini Index for a Collection of Nodes

- | When a node p is split into k partitions (children)


$$GINI_{split} = \sum_{i=1}^k \frac{n_i}{n} GINI(i)$$

where, n_i = number of records at child i ,
 n = number of records at parent node p .

- | Choose the attribute that minimizes weighted average Gini index of the children
- | Gini index is used in decision tree algorithms such as CART, SLIQ, SPRINT

Binary Attributes: Computing GINI Index

- Splits into two partitions
- Effect of Weighing partitions:
 - Larger and Purer Partitions are sought for.



	Parent
C1	7
C2	5
Gini = 0.486	

Gini(N1)

$$= 1 - (5/6)^2 - (1/6)^2$$
$$= 0.278$$

Gini(N2)

$$= 1 - (2/6)^2 - (4/6)^2$$
$$= 0.444$$

	N1	N2
C1	5	2
C2	1	4
Gini=0.361		

Weighted Gini of N1 N2

$$= 6/12 * 0.278 +$$
$$6/12 * 0.444$$
$$= 0.361$$

$$\text{Gain} = 0.486 - 0.361 = 0.125$$

Categorical Attributes: Computing Gini Index

- | For each distinct value, gather counts for each class in the dataset
- | Use the count matrix to make decisions

Multi-way split

	CarType		
	Family	Sports	Luxury
C1	1	8	1
C2	3	0	7
Gini	0.163		

Two-way split
(find best partition of values)

	CarType	
	{Sports, Luxury}	{Family}
C1	9	1
C2	7	3
Gini	0.468	

	CarType	
	{Sports}	{Family, Luxury}
C1	8	2
C2	0	10
Gini	0.167	

Which of these is the best?

Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
 - Sort the attribute on values
 - Linearly scan these values, each time updating the count matrix and computing gini index
 - Choose the split position that has the least gini index

Sorted Values	<div>Cheat</div>	No	No	No	Yes	Yes	Yes	No	No	No	No
	Annual Income										
	60	70	75	85	90	95	100	120	125	220	

Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
 - Sort the attribute on values
 - Linearly scan these values, each time updating the count matrix and computing gini index
 - Choose the split position that has the least gini index

Sorted Values Split Positions	Cheat	No		No		No		Yes		Yes		Yes		No		No		No		No		
	Annual Income																					
	60		70		75		85		90		95		100		120		125		220			
	55		65		72		80		87		92		97		110		122		172		230	
	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>
Yes	0	3	0	3	0	3	0	3	1	2	2	1	3	0	3	0	3	0	3	0	3	0
No	0	7	1	6	2	5	3	4	3	4	3	4	3	4	4	3	5	2	6	1	7	0
Gini	0.420		0.400		0.375		0.343		0.417		0.400		<u>0.300</u>		0.343		0.375		0.400		0.420	

Measure of Impurity: Entropy

- I Entropy at a given node t:

$$Entropy(t) = -\sum_j p(j | t) \log p(j | t)$$

(NOTE: $p(j | t)$ is the relative frequency of class j at node t).

- ◆ Maximum ($\log n_c$) when records are equally distributed among all classes implying least information
 - ◆ Minimum (0.0) when all records belong to one class, implying most information
-
- Entropy based computations are quite similar to the GINI index computations

Computing Entropy of a Single Node

$$Entropy(t) = -\sum_j p(j | t) \log_2 p(j | t)$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Entropy = -0 \log 0 - 1 \log 1 = -0 - 0 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Entropy = - (1/6) \log_2 (1/6) - (5/6) \log_2 (1/6) = 0.65$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Entropy = - (2/6) \log_2 (2/6) - (4/6) \log_2 (4/6) = 0.92$$

Computing Information Gain After Splitting

I Information Gain:

$$GAIN_{split} = Entropy(p) - \left(\sum_{i=1}^k \frac{n_i}{n} Entropy(i) \right)$$


Parent Node, p is split into k partitions;

n_i is number of records in partition i

- Choose the split that achieves most reduction (maximizes GAIN)
- Used in the ID3 and C4.5 decision tree algorithms

Problem with large number of partitions

- Node impurity measures tend to prefer splits that result in large number of partitions, each being small but pure



- Customer ID has highest information gain because entropy for all the children is zero

Gain Ratio

I Gain Ratio:

$$GainRATIO_{split} = \frac{GAIN_{Split}}{SplitINFO} \quad SplitINFO = -\sum_{i=1}^k \frac{n_i}{n} \log \frac{n_i}{n}$$

Parent Node, p is split into k partitions

n_i is the number of records in partition i

- Adjusts Information Gain by the entropy of the partitioning (SplitINFO).
 - ◆ Higher entropy partitioning (large number of small partitions) is penalized!
- Used in C4.5 algorithm
- Designed to overcome the disadvantage of Information Gain

Gain Ratio

| Gain Ratio:

$$GainRATIO_{split} = \frac{GAIN_{Split}}{SplitINFO} \quad SplitINFO = -\sum_{i=1}^k \frac{n_i}{n} \log \frac{n_i}{n}$$

Parent Node, p is split into k partitions

n_i is the number of records in partition i

	CarType		
	Family	Sports	Luxury
C1	1	8	1
C2	3	0	7
Gini	0.163		

SplitINFO = 1.52

	CarType	
	{Sports, Luxury}	{Family}
C1	9	1
C2	7	3
Gini	0.468	

SplitINFO = 0.72

	CarType	
	{Sports}	{Family, Luxury}
C1	8	2
C2	0	10
Gini	0.167	

SplitINFO = 0.97

Measure of Impurity: Classification Error

- | Classification error at a node t :

$$Error(t) = 1 - \max_i P(i | t)$$

- Maximum ($1 - 1/n_c$) when records are equally distributed among all classes, implying least interesting information
- Minimum (0) when all records belong to one class, implying most interesting information

Computing Error of a Single Node

$$Error(t) = 1 - \max_i P(i | t)$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Error = 1 - \max(0, 1) = 1 - 1 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Error = 1 - \max(1/6, 5/6) = 1 - 5/6 = 1/6$$


C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Error = 1 - \max(2/6, 4/6) = 1 - 4/6 = 1/3$$

Comparison among Impurity Measures

For a 2-class problem:



Decision Tree Based Classification


| Advantages:

- Inexpensive to construct
- Extremely fast at classifying unknown records
- Easy to interpret for small-sized trees
- Robust to noise (especially when methods to avoid overfitting are employed)
- Can easily handle redundant or irrelevant attributes (unless the attributes are interacting)

| Disadvantages:

- Space of possible decision trees is exponentially large. Greedy approaches are often unable to find the best tree.
- Does not take into account interactions between attributes
- Each decision boundary involves only a single attribute

Limitations of single attribute-based decision boundaries



Both **positive (+)** and **negative (o)** classes generated from skewed Gaussians with centers at (8,8) and (12,12) respectively.