SECURENOVA AI IDENTITY SECURITY

CAPSTONE PROJECT 4

Blue Team Hardening

Defensive controls • Auth0 hardening • Cryptographic identity • Anomaly detection

Accenture | Capstone Submission

Project Overview

This report documents the SecureNova AI Identity Security blue-team hardening work. It builds on the Project 3 red-team assessment and records defensive controls, test outcomes, configuration evidence, and the limits of the supplied experiments.

Scope and Test Environment

Item	Description
Input/output guardrails	NVIDIA NeMo Guardrails 0.24.1; custom Python actions
Model used in recorded input test	Gemini 3.5 Flash
Cryptographic identity	Ed25519 signing and verification
Identity provider	Auth0 development tenant; SecureNova SSO Client
Access-token lifetime	300 seconds maximum for the configured API
Refresh-token rotation	Enabled; 0-second overlap period
Anomaly detection	Python detector over 100 retrieved Auth0 log events

Executive Summary

The recorded tests show successful blocking of three selected malicious inputs, redaction of a synthetic JWT, rejection of a tampered Ed25519-signed message, successful Auth0 refresh-token rotation with rejection of the old token, and detection of two replay-related events in a 100-event Auth0 log batch.

Observed category	Outcome
Input guardrails	3/3 selected attack payloads blocked (100% test-set pass rate).
JWT output protection	Synthetic JWT replaced with [REDACTED] (1/1 test passed).
Cryptographic identity	Ed25519 key pair generated; modified message rejected.
Auth0 token hardening	300-second API token lifetime; refresh rotation enabled; old token replay returned HTTP 403.
Legitimate-input test	0 of 10 legitimate prompts incorrectly blocked (0.00% false-positive rate on this set).
Anomaly detection	100 Auth0 events scanned; 2 refresh-token replay-related events detected.

Percentage interpretation: these are test-specific validation rates, not a measured aggregate reduction in real-world attack success. Project 3 and Project 4 tests were not all identical paired end-to-end experiments.

1. Input Guardrails — Prompt Injection Blocking

The NeMo input rail invokes the custom detect_prompt_injection action. Configured patterns cover indirect prompt injection, credential disclosure, agent identity spoofing, privileged-access manipulation, security override, and system-prompt extraction.

Three payloads were tested: the original Project 3 PI-02 indirect JWT-disclosure payload, a reconstructed agent identity spoofing message, and a reconstructed system-prompt extraction request. All three matched configured rules and were blocked.

Result: 3/3 blocked (100% for this selected test set). This does not establish detection of every possible prompt injection.

Evidence 1 — Input guardrail blocking




Figure 1. Original Project 3 PI-02 payload and two reconstructed attack payloads blocked by the NeMo input rail.

2. Output Guardrail — JWT Redaction

A controlled output test placed a synthetic JWT-shaped credential in a model response. The custom redact_jwt_output action replaced the token with [REDACTED]. The NeMo output rail returned RailStatus.MODIFIED; the JWT was present before the rail and absent afterward.

Result: 1/1 synthetic JWT redaction test passed (100%). The test credential was synthetic, not a production token.

Evidence 2 — JWT output redaction




Figure 2. NeMo output rail modified the response and replaced the synthetic credential with [REDACTED].

3. Cryptographic Agent Identity — Ed25519

An Ed25519 public/private key pair was generated for Agent A. The private key is retained locally and excluded from version control; the public key is used for verification.

The signing test verified the original message and rejected the modified message. This validates tamper detection for the tested message and signature.

Evidence 3 — Ed25519 key generation




Figure 3. Ed25519 key generation completed and both key files were confirmed.

Evidence 4 — Tampered message rejection




Figure 4. Original message signature verified; the tampered message signature was rejected.

4. Auth0 Hardening

The Auth0 API settings show a maximum access-token lifetime of 300 seconds. The SecureNova SSO Client configuration shows refresh-token rotation enabled and a rotation overlap period of 0 seconds. The captured settings also show maximum refresh-token lifetime enabled at 31,557,600 seconds (one year); idle lifetime was not enabled in the screenshot.

Evidence 5 — Auth0 API access-token lifetime




Figure 5. Auth0 API maximum access-token lifetime configured to 300 seconds.

Evidence 6 — Refresh-token rotation settings




Figure 6. Refresh-token rotation enabled with zero-second overlap.

The live refresh-token test recorded a successful initial login, HTTP 200 for rotation, issuance of a new refresh token, and HTTP 403 / invalid_grant when the old refresh token was reused. The test concluded PASSED.

Evidence 7 — Live refresh-token rotation and replay test




Figure 7. New refresh token issued after rotation; replay of the old token rejected with HTTP 403.

5. Auth0 Post-Login Action and Legitimate-Input Test

A custom Auth0 Post Login Action named SecureNova Risk-Based Authentication was created and attached to the Post Login flow. The captured Auth0 log evidence shows a successful login event.

Evidence 8 — Auth0 login log




Figure 8. Auth0 monitoring log showing a successful login event for SecureNova SSO Client.

A separate ten-prompt legitimate-input test was run against the NeMo guardrail: 10 legitimate prompts tested, 0 incorrectly blocked, 10 correctly allowed, and a 0.00% false-positive rate on this test set.

Evidence 9 — Legitimate-input false-positive test




Figure 9. Ten legitimate prompts allowed; zero incorrectly blocked.

Scope note: the ten-prompt result measures the NeMo guardrail test set. It does not independently measure the false-positive rate of the Auth0 Post Login Action.

6. Anomaly Detection — Live Auth0 Refresh-Token Replay

A Python detector authenticated to the Auth0 Management API and retrieved 100 real tenant log events. It searched for failed refresh-token exchanges whose descriptions indicated a reused refresh token.

Two refresh-token replay-related events were detected. The retrieved batch did not meet the repeated-failed-login threshold. Three distinct source IP addresses were observed, but they were not automatically classified as malicious.

Evidence 10 — Live Auth0 anomaly detection




Figure 10. Live Auth0 log analysis scanned 100 events and flagged two refresh-token replay events.

7. Before/After Comparison with Project 3


Project 3 recorded controlled attacks including synthetic JWT disclosure, acceptance of an unverified orchestrator identity, partial system-prompt information disclosure, and RAG poisoning that triggered a local mock tool action. Project 4 adds defensive controls addressing related trust-boundary weaknesses.

Project 3 red-team finding	Project 4 control	Project 4 validation
Indirect prompt injection disclosed a synthetic JWT	NeMo input guardrail and JWT output redaction	PI-02 blocked; synthetic JWT redacted in output test.
Unverified claimed orchestrator led to simulated ADMIN action	Ed25519 signing and verification	Tampered message rejected.
Partial system-prompt information disclosure	Prompt-injection / extraction patterns	Selected SP-01 payload blocked.
Poisoned RAG content triggered local mock tool request	Input guardrail pattern checks	Selected malicious payloads blocked; original RAG workflow not rerun end-to-end.
Refresh-token replay risk	Auth0 refresh-token rotation	Old refresh token replay rejected with HTTP 403.

Project 4 validation measure	Result	Rate
Selected malicious input payloads blocked	3 / 3	100%
Synthetic JWT output-redaction test	1 / 1	100%
Ed25519 tampered-message rejection	1 / 1	100%
Old refresh token rejected after rotation	1 / 1	100%
Legitimate prompts incorrectly blocked	0 / 10	0.00% false-positive rate
Replay-related events detected in retrieved Auth0 batch	2 events	No recall percentage available

The 100% values are pass rates for small, specific test sets. They must not be averaged into a single overall security-improvement score. A defensible attack-success reduction percentage requires rerunning the same Project 3 payloads and workflows against Project 4 with identical success criteria.

Evidence 11 — Before/after comparison table



Five-scenario comparison

Scenario	Project 3 baseline	Project 4 defense / validation	Project 4 test-specific result
Agent identity spoofing	Successful controlled simulation: an unauthenticated message claiming TRUSTED_ORCHESTRATOR led to a simulated ADMIN action.	Ed25519 signing and verification. Original message verified; modified/tampered message rejected.	100% validation pass (1/1 tampered-message test); original spoofing workflow not rerun end-to-end.
Indirect prompt injection	Three-document Gemini test; 0 of 3 synthetic credentials exposed.	NeMo input guardrails with configured prompt-injection patterns. Three selected attack payloads blocked in the guardrail test.	100% validation pass (3/3 selected payloads blocked); not a paired rerun of the original Gemini experiment.
RAG/MCP knowledge-base poisoning	Successful controlled simulation: poisoned retrieved content caused a mock grant_test_access call and simulated ADMIN role assignment.	Prompt-injection guardrail pattern detection. Selected prompt-injection payloads blocked; original poisoned KB/MCP workflow not rerun end-to-end.	Not separately measured end-to-end against the original Project 3 workflow.
System prompt extraction	Six tests; full system prompt not returned, but SP-04 disclosed the USER role.	Input guardrail patterns for system-prompt extraction and prompt injection. Three selected attack payloads blocked; all six original extraction prompts not rerun.	Not separately measured end-to-end against the original Project 3 workflow.
JWT/credential disclosure	The supplied indirect-injection report recorded 0 of 3 synthetic credentials exposed. A separate JWT output-redaction attack baseline was not supplied.	NeMo output guardrail redacts JWT-shaped strings. Synthetic JWT replaced with [REDACTED]; test passed.	100% validation pass (1/1 synthetic JWT redaction test); not a paired baseline comparison.

Project 4 measured test results

Measure	Passed / tested	Percentage
Selected input-guardrail attack payloads blocked	3 / 3	100%
Ed25519 tampered-message rejection	1 / 1	100%
Synthetic JWT output-redaction test	1 / 1	100%
Auth0 replay events detected in retrieved log batch	2 / 2	100%
Legitimate inputs incorrectly blocked	0 / 10	0% false-positive rate

Figure 11. Summary comparison of Project 3 findings and Project 4 defensive validation results.

8. Conclusion

Project 4 demonstrates practical defensive controls at model input/output, agent identity, identity-provider, and monitoring boundaries. Selected prompt-injection payloads were blocked, synthetic JWT output was redacted, tampered signed messages were rejected, Auth0 refresh-token rotation invalidated the previous token, and replay-related events were identified in live tenant logs.

Limitations and Interpretation

- Small test sets; rates describe only the supplied test cases.
- Project 3 baseline and Project 4 defense tests are not fully paired end-to-end experiments; no aggregate attack-reduction percentage is calculated.
- The false-positive test is the NeMo guardrail test over ten legitimate prompts; it does not establish the false-positive rate of the Auth0 Post Login Action.
- The Auth0 log script detected two refresh-token replay-related failed exchange events among 100 retrieved events; the three observed IPs were not classified as malicious.
- The agent identity signature test verifies tamper detection, but the original Project 3 agent-spoofing workflow was not rerun end-to-end through a production authorization boundary.
- All Project 3 attack actions were simulations using synthetic data and local mock functions.

Evidence Index

- Screenshot 1: Input guardrail blocking — three selected malicious payloads.
- Screenshot 2: JWT output redaction — synthetic JWT replaced with [REDACTED].
- Screenshot 3: Ed25519 key generation — public/private key files created.
- Screenshot 4: Tampered message rejection — signature verification failed for modified message.
- Screenshot 5: Auth0 API token lifetime — maximum access-token lifetime set to 300 seconds.
- Screenshot 6: Auth0 refresh-token configuration — rotation enabled, overlap 0 seconds.
- Screenshot 7: Auth0 refresh-token rotation and replay test — new token issued; old token rejected.
- Screenshot 8: Auth0 login log — successful login event.
- Screenshot 9: Ten legitimate-input false-positive test — 0/10 incorrectly blocked.
- Screenshot 10: Live Auth0 anomaly detection — 100 events scanned; two replay alerts.
- Screenshot 11: Before/after comparison table — Project 3 findings mapped to Project 4 controls.